Thứ
Ngày No.

Tên: Nguyễn Ngọc Nam Giang
Lớp: 13-ĐH-CNTT5.
MSSV: 1350080064.

1

```
interface Mail
{
  void sendMail();
  void log();
}
class MailImpl implements Mail
{
  @Override
  public void sendMail()
  {
    System.out.println("Gui mail");
  }

  @Override
  public void log()
  {
    System.out.println("In mail");
  }

  public static void Main()
```


Thứ
Ngày No.

```
  MailImpl mail = new MailImpl();
  mail.SendMail();
  mail.log();
}
}
```

2.

```
interface Shape
{
  void draw()
}

class Rectangle implements Shape
{
  void draw()
  {
    System.out.println("Ve Rectangle");
  }
}

class Circle implements Shape
{
  void draw()
  {
    System.out.println("Ve Circle");
  }
```

```
{
    System.out.println("May bay bat dau");
}
void tang toc()
{
    System.out.println("may bay tang toc");
}
void day lai()
{
    System.out.println("may bay day lai");
}

double layVanToc()
{
    return 999.00f;
}
void catcanh()
{
    System.out.println("May bay cat canh");
}
void haCanh()
{
    System.out.println("May bay ha canh");
}
}
```

```
public static void Main()
{
    Rectangle rec = new Rectangle();
    rec.draw();
    Circle cir = new Circle();
    cir.draw();
}
}
3
interface PhuongTienDiChuyen
{
    String layTenHangSanXuat();
    void batdau();
    void tangtoc();
    void daylai();
    double layVanToc();
}
class MayBay implements MayBay
{
    String loaidonlen;
public String layTenHangSanXuat()
{
    return "TenSanXuatMayBay";
}
public void batdau()
```

```
class XeOto implements PhuongTienDiChuyen
{   String loaiNhienLieu = "Diesel";
    public String layTenHangSanXuat () {
    {
      return "Hay San Xuat Oto";
    }
    public void bardau()
    {
      System.out.println("Oto bardau");
    }
    public void taytoc () {
      System.out.println("Oto taytoc");
    }
    public void dunglai () {
      System.out.println("Oto dung lai");
    }
    public double layVanToc () {
      return 60.0f;
    }
} }.
class XeDap implements PhuongTienDiChuyen
{
    public String layTenHangSanXuat ()
    {
      return "Hay San Xuat XeDap";
    }
    public void bardau()
    {
      System.out.println("Xe dap bardau");
    }
    public void taytoc ()
    {
      System.out.println("Xedap taytoc");
    }
    public void dunglai ()
    {
      System.out.println("Xedap dung lai");
    }
    public double layVanToc () {
      return 12f;
    }
}
```

Bài 1:

```
interface Car
{
    String getColor();
    double getSpeed();
}
```

```
Class
~~public~~ BMW implements Car
{
    public String getColor() {
        return "Color of BMW"
    }

    public double getSpeed () {
        return 60.0f ;
    }

    public void accelerate ()
    {
        System.out.println("accelerate : " + getSpeed());
    }

    public String toString()
    {
        return "Color : " + getColor() + " Speed : " + getSpeed()
    }

class Civic implements Car
{
    public String getColor(){
        return " Color of Civic ";
    }

    public double getSpeed(){
        return 40f ;
    }
}
```

```
} ~~public~~

interface Movable
{
    void moveUp();
    void moveDown();
    void moveLeft();
    void moveRight();
}
~~class MovableCircle implements Movable~~
~~{~~
    ~~int radius;~~
class MovablePoint implements Movable {
    int x;
    int y;
int xSpeed;
    int ySpeed;
    public MovablePoint ( int x, int y, int xSpeed , int ySpeed)
    {
        this.x = x;
        this.y = y;
        this.xSpeed = xSpeed;
        this.ySpeed = ySpeed;
    }.
```

```
public void moveUp() {
}

public void moveDown() {
}
public void moveLeft() {
}
public void moveRight() {
}
}
class MovableCircle implements Moveable {
  int radius;
  MovablePoint center;
public MovableCircle (MovablePoint movablePoint, int radius)
  {
    this.center = movablePoint;
    this.radius = radius;
  }
  public void moveUp() {

  }
public void moveDown() {

}
public void moveLeft() {

}
public void moveRight() {

}
}
class Program() {
  public static void Main()
  {
    MovablePoint movePoint = new MovablePoint(10,10,5,5);
    movePoint.moveUP();
    movePoint.moveDown();
    movePoint.moveLeft();
    movePoint.moveRight();

    MovableCircle circlePoint = new MovableCircle(movePoint,5)
    circlePoint.moveUp();
    circlePoint.moveDown();
    circlePoint.moveLeft();
    circlePoint.moveRight();
  }
}
```

```
interface IEmployee {
    int calculateSalary();
    String getName();
}.
class Employee implements IEmployee {
    String name;
    int paymentPerHour;
public Employee ( String name , int payment )
{
    this.name = name;
    this.paymentPerHour = payment;
}
public void setName ( String name ) {
    this.name = name;
}
public String getName () {
    return this.name ;
}
public void setPaymentPerHour ( int payment )
{
    this.paymentPerHour = payment;
}
public int getPaymentPerHour ()
{
    return this.paymentPerHour;
}
}.
```

```
class PartTimeEmployee implements Employee
{
    int workingHours;
    public PartTimeEmployee ( String name , int paymentPerHour, int workingHours
    {
        super ( name , paymentPerHour );
        this.workingHours = workingHours;
    }
    public int calculateSalary()
    {
        return this.workingHours * this.paymentPerHour;
    }
}.
class FullTimeEmployee implements Employee
{
    public FullTimeEmployee ( String name , int paymentPerHour )
    {
        super ( name , paymentPerHour );
    }
    public int calculateSalary()
    {
        return this.paymentPerHour * 16 * 2;
    }
}
```