

# restful-booker

API documentation for the playground API restful-booker. [Click here to go back to Home \[/\]](#)

---

## Auth

### Auth - CreateToken

Creates a new auth token to use for access to the PUT and DELETE /booking

POST

```
https://restful-booker.herokuapp.com/auth
```

- Example 1: [#examples-Auth-CreateToken-1\_0\_0-0]

```
curl -X POST \  
  https://restful-booker.herokuapp.com/auth \  
  -H 'Content-Type: application/json' \  
  -d '{  
    "username" : "admin",  
    "password" : "password123"  
  }'
```

#### Header

| Field        | Type   | Description                                                                       |
|--------------|--------|-----------------------------------------------------------------------------------|
| Content-Type | string | Sets the format of payload you are sending<br><br>Default value: application/json |

#### Request body

| Field    | Type   | Description                                               |
|----------|--------|-----------------------------------------------------------|
| username | String | Username for authentication<br>Default value: admin       |
| password | String | Password for authentication<br>Default value: password123 |

## Success 200

| Field | Type   | Description                     |
|-------|--------|---------------------------------|
| token | String | Token to use in future requests |

- Response: [#success-examples-Auth-CreateToken-1\_0\_0-0]

```
HTTP/1.1 200 OK
```

```
{  
  "token": "abc123"  
}
```

# Booking

## Booking - GetBookingIds

Returns the ids of all the bookings that exist within the API. Can take optional query strings to search and return a subset of booking ids.

GET

```
https://restful-booker.herokuapp.com/booking
```

- Example 1 (All IDs): [#examples-Booking-GetBookings-1\_0\_0-0]
- Example 2 (Filter by name): [#examples-Booking-GetBookings-1\_0\_0-1]
- Example 3 (Filter by checkin/checkout date): [#examples-Booking-GetBookings-1\_0\_0-2]

```
curl -i https://restful-booker.herokuapp.com/booking
```

```
curl -i https://restful-booker.herokuapp.com/booking?firstname=sally&lastname=
```

```
curl -i https://restful-booker.herokuapp.com/booking?checkin=2014-03-13&checko
```

## Parameter

| Field     |          | Type   | Description                                                                                                         |
|-----------|----------|--------|---------------------------------------------------------------------------------------------------------------------|
| firstname | optional | String | Return bookings with a specific firstname                                                                           |
| lastname  | optional | String | Return bookings with a specific lastname                                                                            |
| checkin   | optional | date   | Return bookings that have a checkin date greater than or equal to the set checkin date. Format must be CCYY-MM-DD   |
| checkout  | optional | date   | Return bookings that have a checkout date greater than or equal to the set checkout date. Format must be CCYY-MM-DD |

## Success 200

| Field     | Type     | Description                                           |
|-----------|----------|-------------------------------------------------------|
| object    | object[] | Array of objects that contain unique booking IDs      |
| bookingid | number   | ID of a specific booking that matches search criteria |

- Response: [#success-examples-Booking-GetBookings-1\_0\_0-0]

```
HTTP/1.1 200 OK
```

```
[
  {
    "bookingid": 1
  },
  {
```

```
    "bookingid": 2
  },
  {
    "bookingid": 3
  },
  {
    "bookingid": 4
  }
]
```

## Booking - GetBooking

Returns a specific booking based upon the booking id provided

GET

```
https://restful-booker.herokuapp.com/booking/:id
```

- Example 1 (Get booking): [#examples-Booking-GetBooking-1\_0\_0-0]

```
curl -i https://restful-booker.herokuapp.com/booking/1
```

### Header

| Field  | Type   | Description                                                                                                                          |
|--------|--------|--------------------------------------------------------------------------------------------------------------------------------------|
| Accept | string | Sets what format the response body is returned in. Can be application/json or application/xml<br><br>Default value: application/json |

### Url Parameter

| Field | Type   | Description                                      |
|-------|--------|--------------------------------------------------|
| id    | String | The id of the booking you would like to retrieve |

### Success 200

| Field     | Type   | Description                                  |
|-----------|--------|----------------------------------------------|
| firstname | String | Firstname for the guest who made the booking |

| Field           | Type    | Description                                             |
|-----------------|---------|---------------------------------------------------------|
| lastname        | String  | Lastname for the guest who made the booking             |
| totalprice      | Number  | The total price for the booking                         |
| depositpaid     | Boolean | Whether the deposit has been paid or not                |
| bookingdates    | Object  | Sub-object that contains the checkin and checkout dates |
| checkin         | Date    | Date the guest is checking in                           |
| checkout        | Date    | Date the guest is checking out                          |
| additionalneeds | String  | Any other needs the guest has                           |

- JSON Response: [#success-examples-Booking-GetBooking-1\_0\_0-0]
- XML Response: [#success-examples-Booking-GetBooking-1\_0\_0-1]
- URL Response: [#success-examples-Booking-GetBooking-1\_0\_0-2]

HTTP/1.1 200 OK

```
{
  "firstname": "Sally",
  "lastname": "Brown",
  "totalprice": 111,
  "depositpaid": true,
  "bookingdates": {
    "checkin": "2013-02-23",
    "checkout": "2014-10-23"
  },
  "additionalneeds": "Breakfast"
}
```

HTTP/1.1 200 OK

```
<booking>
  <firstname>Sally</firstname>
```

```
<lastname>Brown</lastname>
<totalprice>111</totalprice>
<depositpaid>true</depositpaid>
<bookingdates>
  <checkin>2013-02-23</checkin>
  <checkout>2014-10-23</checkout>
</bookingdates>
<additionalneeds>Breakfast</additionalneeds>
</booking>
```

HTTP/1.1 200 OK

firstname=Jim&lastname=Brown&totalprice=111&depositpaid=true&bookingdates%5Bch

## Booking - CreateBooking

Creates a new booking in the API

POST

<https://restful-booker.herokuapp.com/booking>

- JSON example usage: [#examples-Booking-CreateBooking-1\_0\_0-0]
- XML example usage: [#examples-Booking-CreateBooking-1\_0\_0-1]
- URLEncoded example usage: [#examples-Booking-CreateBooking-1\_0\_0-2]

```
curl -X POST \
  https://restful-booker.herokuapp.com/booking \
  -H 'Content-Type: application/json' \
  -d '{
    "firstname" : "Jim",
    "lastname" : "Brown",
    "totalprice" : 111,
    "depositpaid" : true,
    "bookingdates" : {
      "checkin" : "2018-01-01",
      "checkout" : "2019-01-01"
    },
    "additionalneeds" : "Breakfast"
  }'
```

```
curl -X POST \
  https://restful-booker.herokuapp.com/booking \
  -H 'Content-Type: text/xml' \
  -d '<booking>
    <firstname>Jim</firstname>
    <lastname>Brown</lastname>
    <totalprice>111</totalprice>
    <depositpaid>true</depositpaid>
    <bookingdates>
      <checkin>2018-01-01</checkin>
      <checkout>2019-01-01</checkout>
    </bookingdates>
    <additionalneeds>Breakfast</additionalneeds>
  </booking>'
```

```
curl -X POST \
  https://restful-booker.herokuapp.com/booking \
  -H 'Content-Type: application/x-www-form-urlencoded' \
  -d 'firstname=Jim&lastname=Brown&totalprice=111&depositpaid=true&bookingdate'
```

## Header

| Field        | Type   | Description                                                                                                                          |
|--------------|--------|--------------------------------------------------------------------------------------------------------------------------------------|
| Content-Type | string | Sets the format of payload you are sending. Can be application/json or text/xml<br><br>Default value: application/json               |
| Accept       | string | Sets what format the response body is returned in. Can be application/json or application/xml<br><br>Default value: application/json |

## Request body

| Field     | Type   | Description                                  |
|-----------|--------|----------------------------------------------|
| firstname | String | Firstname for the guest who made the booking |
| lastname  | String | Lastname for the guest who made the booking  |

| Field           | Type    | Description                              |
|-----------------|---------|------------------------------------------|
| totalprice      | Number  | The total price for the booking          |
| depositpaid     | Boolean | Whether the deposit has been paid or not |
| checkin         | Date    | Date the guest is checking in            |
| checkout        | Date    | Date the guest is checking out           |
| additionalneeds | String  | Any other needs the guest has            |

## Success 200

| Field        | Type    | Description                                             |
|--------------|---------|---------------------------------------------------------|
| bookingid    | Number  | ID for newly created booking                            |
| booking      | Object  | Object that contains                                    |
| firstname    | String  | Firstname for the guest who made the booking            |
| lastname     | String  | Lastname for the guest who made the booking             |
| totalprice   | Number  | The total price for the booking                         |
| depositpaid  | Boolean | Whether the deposit has been paid or not                |
| bookingdates | Object  | Sub-object that contains the checkin and checkout dates |
| checkin      | Date    | Date the guest is checking in                           |
| checkout     | Date    | Date the guest is checking out                          |



| Field           | Type   | Description                   |
|-----------------|--------|-------------------------------|
| additionalneeds | String | Any other needs the guest has |

- JSON Response: [#success-examples-Booking-CreateBooking-1\_0\_0-0]
- XML Response: [#success-examples-Booking-CreateBooking-1\_0\_0-1]
- URL Response: [#success-examples-Booking-CreateBooking-1\_0\_0-2]

HTTP/1.1 200 OK

```
{
  "bookingid": 1,
  "booking": {
    "firstname": "Jim",
    "lastname": "Brown",
    "totalprice": 111,
    "depositpaid": true,
    "bookingdates": {
      "checkin": "2018-01-01",
      "checkout": "2019-01-01"
    },
    "additionalneeds": "Breakfast"
  }
}
```

HTTP/1.1 200 OK

```
<?xml version='1.0'?>
<created-booking>
  <bookingid>1</bookingid>
  <booking>
    <firstname>Jim</firstname>
    <lastname>Brown</lastname>
    <totalprice>111</totalprice>
    <depositpaid>true</depositpaid>
    <bookingdates>
      <checkin>2018-01-01</checkin>
      <checkout>2019-01-01</checkout>
    </bookingdates>
    <additionalneeds>Breakfast</additionalneeds>
  </booking>
</created-booking>
```

```
</booking>
</created-booking>
```

HTTP/1.1 200 OK

bookingid=1&booking%5Bfirstname%5D=Jim&booking%5Blastname%5D=Brown&booking%5Bt

## Booking - UpdateBooking

Updates a current booking

PUT

<https://restful-booker.herokuapp.com/booking/:id>

- JSON example usage: [#examples-Booking-UpdateBooking-1\_0\_0-0]
- XML example usage: [#examples-Booking-UpdateBooking-1\_0\_0-1]
- URLEncoded example usage: [#examples-Booking-UpdateBooking-1\_0\_0-2]

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json' \
  -H 'Cookie: token=abc123' \
  -d '{
    "firstname" : "James",
    "lastname" : "Brown",
    "totalprice" : 111,
    "depositpaid" : true,
    "bookingdates" : {
      "checkin" : "2018-01-01",
      "checkout" : "2019-01-01"
    },
    "additionalneeds" : "Breakfast"
  }'
```

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: text/xml' \
  -H 'Accept: application/xml' \
```

```
-H 'Authorization: Basic YWRtaW46cGFzc3dvcmQxMjM=' \
-d '<booking>
  <firstname>James</firstname>
  <lastname>Brown</lastname>
  <totalprice>111</totalprice>
  <depositpaid>true</depositpaid>
  <bookingdates>
    <checkin>2018-01-01</checkin>
    <checkout>2019-01-01</checkout>
  </bookingdates>
  <additionalneeds>Breakfast</additionalneeds>
</booking>'
```

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: application/x-www-form-urlencoded' \
  -H 'Accept: application/x-www-form-urlencoded' \
  -H 'Authorization: Basic YWRtaW46cGFzc3dvcmQxMjM=' \
  -d 'firstname=Jim&lastname=Brown&totalprice=111&depositpaid=true&bookingdate'
```

## Header

| Field                  | Type   | Description                                                                                                                                          |
|------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Content-Type           | string | Sets the format of payload you are sending. Can be application/json or text/xml<br><br>Default value: application/json                               |
| Accept                 | string | Sets what format the response body is returned in. Can be application/json or application/xml<br><br>Default value: application/json                 |
| Cookie optional        | string | Sets an authorization token to access the PUT endpoint, can be used as an alternative to the Authorization<br><br>Default value: token=<token_value> |
| Authorization optional | string | YWRtaW46cGFzc3dvcmQxMjM=] Basic authorization header to access the PUT endpoint, can be used as an alternative to the Cookie header                  |

| Field | Type | Description          |
|-------|------|----------------------|
|       |      | Default value: Basic |

## Url Parameter

| Field | Type   | Description                           |
|-------|--------|---------------------------------------|
| id    | Number | ID for the booking you want to update |

## Request body

| Field           | Type    | Description                                  |
|-----------------|---------|----------------------------------------------|
| firstname       | String  | Firstname for the guest who made the booking |
| lastname        | String  | Lastname for the guest who made the booking  |
| totalprice      | Number  | The total price for the booking              |
| depositpaid     | Boolean | Whether the deposit has been paid or not     |
| checkin         | Date    | Date the guest is checking in                |
| checkout        | Date    | Date the guest is checking out               |
| additionalneeds | String  | Any other needs the guest has                |

## Success 200

| Field      | Type   | Description                                  |
|------------|--------|----------------------------------------------|
| firstname  | String | Firstname for the guest who made the booking |
| lastname   | String | Lastname for the guest who made the booking  |
| totalprice | Number | The total price for the booking              |

| Field           | Type    | Description                                             |
|-----------------|---------|---------------------------------------------------------|
| depositpaid     | Boolean | Whether the deposit has been paid or not                |
| bookingdates    | Object  | Sub-object that contains the checkin and checkout dates |
| checkin         | Date    | Date the guest is checking in                           |
| checkout        | Date    | Date the guest is checking out                          |
| additionalneeds | String  | Any other needs the guest has                           |

- JSON Response: [#success-examples-Booking-UpdateBooking-1\_0\_0-0]
- XML Response: [#success-examples-Booking-UpdateBooking-1\_0\_0-1]
- URL Response: [#success-examples-Booking-UpdateBooking-1\_0\_0-2]

HTTP/1.1 200 OK

```
{
  "firstname" : "James",
  "lastname" : "Brown",
  "totalprice" : 111,
  "depositpaid" : true,
  "bookingdates" : {
    "checkin" : "2018-01-01",
    "checkout" : "2019-01-01"
  },
  "additionalneeds" : "Breakfast"
}
```

HTTP/1.1 200 OK

```
<booking>
  <firstname>James</firstname>
  <lastname>Brown</lastname>
  <totalprice>111</totalprice>
  <depositpaid>true</depositpaid>
  <bookingdates>
    <checkin>2018-01-01</checkin>
    <checkout>2019-01-01</checkout>
```

```
</bookingdates>
<additionalneeds>Breakfast</additionalneeds>
</booking>
```

HTTP/1.1 200 OK

firstname=Jim&lastname=Brown&totalprice=111&depositpaid=true&bookingdates%5Bch

## Booking - PartialUpdateBooking

Updates a current booking with a partial payload

PATCH

<https://restful-booker.herokuapp.com/booking/:id>

- JSON example usage: [#examples-Booking-PartialUpdateBooking-1\_0\_0-0]
- XML example usage: [#examples-Booking-PartialUpdateBooking-1\_0\_0-1]
- URLEncoded example usage: [#examples-Booking-PartialUpdateBooking-1\_0\_0-2]

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json' \
  -H 'Cookie: token=abc123' \
  -d '{
    "firstname" : "James",
    "lastname" : "Brown"
  }'
```

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: text/xml' \
  -H 'Accept: application/xml' \
  -H 'Authorization: Basic YWRtaW46cGFzc3dvcmQxMjM=' \
  -d '<booking>
    <firstname>James</firstname>
    <lastname>Brown</lastname>
  </booking>'
```

```
curl -X PUT \
  https://restful-booker.herokuapp.com/booking/1 \
  -H 'Content-Type: application/x-www-form-urlencoded' \
  -H 'Accept: application/x-www-form-urlencoded' \
  -H 'Authorization: Basic YWRtaW46cGFzc3dvcmQxMjM=' \
  -d 'firstname=Jim&lastname=Brown'
```

## Header

| Field                  | Type   | Description                                                                                                                                                     |
|------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Content-Type           | string | Sets the format of payload you are sending. Can be application/json or text/xml<br><br>Default value: application/json                                          |
| Accept                 | string | Sets what format the response body is returned in. Can be application/json or application/xml<br><br>Default value: application/json                            |
| Cookie optional        | string | Sets an authorization token to access the PUT endpoint, can be used as an alternative to the Authorization<br><br>Default value: token=<token_value>            |
| Authorization optional | string | YWRtaW46cGFzc3dvcmQxMjM=] Basic authorization header to access the PUT endpoint, can be used as an alternative to the Cookie header<br><br>Default value: Basic |

## Url Parameter

| Field | Type   | Description                           |
|-------|--------|---------------------------------------|
| id    | Number | ID for the booking you want to update |

## Request body

| Field              | Type   | Description                                  |
|--------------------|--------|----------------------------------------------|
| firstname optional | String | Firstname for the guest who made the booking |

| Field           |          | Type    | Description                                 |
|-----------------|----------|---------|---------------------------------------------|
| lastname        | optional | String  | Lastname for the guest who made the booking |
| totalprice      | optional | Number  | The total price for the booking             |
| depositpaid     | optional | Boolean | Whether the deposit has been paid or not    |
| checkin         | optional | Date    | Date the guest is checking in               |
| checkout        | optional | Date    | Date the guest is checking out              |
| additionalneeds | optional | String  | Any other needs the guest has               |

## Success 200

| Field           |  | Type    | Description                                             |
|-----------------|--|---------|---------------------------------------------------------|
| firstname       |  | String  | Firstname for the guest who made the booking            |
| lastname        |  | String  | Lastname for the guest who made the booking             |
| totalprice      |  | Number  | The total price for the booking                         |
| depositpaid     |  | Boolean | Whether the deposit has been paid or not                |
| bookingdates    |  | Object  | Sub-object that contains the checkin and checkout dates |
| checkin         |  | Date    | Date the guest is checking in                           |
| checkout        |  | Date    | Date the guest is checking out                          |
| additionalneeds |  | String  | Any other needs the guest has                           |

- JSON Response: [#success-examples-Booking-PartialUpdateBooking-1\_0\_0-0]



- XML Response: [#success-examples-Booking-PartialUpdateBooking-1\_0\_0-1]
- URL Response: [#success-examples-Booking-PartialUpdateBooking-1\_0\_0-2]

HTTP/1.1 200 OK

```
{
  "firstname" : "James",
  "lastname" : "Brown",
  "totalprice" : 111,
  "depositpaid" : true,
  "bookingdates" : {
    "checkin" : "2018-01-01",
    "checkout" : "2019-01-01"
  },
  "additionalneeds" : "Breakfast"
}
```

HTTP/1.1 200 OK

```
<booking>
  <firstname>James</firstname>
  <lastname>Brown</lastname>
  <totalprice>111</totalprice>
  <depositpaid>true</depositpaid>
  <bookingdates>
    <checkin>2018-01-01</checkin>
    <checkout>2019-01-01</checkout>
  </bookingdates>
  <additionalneeds>Breakfast</additionalneeds>
</booking>
```

HTTP/1.1 200 OK

firstname=Jim&lastname=Brown&totalprice=111&depositpaid=true&bookingdates%5Bch

## Booking - DeleteBooking

Deletes a booking from the API. Requires an authorization token to be set in the header or a Basic auth header.

## DELETE

```
https://restful-booker.herokuapp.com/booking/1
```

- Example 1 (Cookie): [#examples-Booking-DeleteBooking-1\_0\_0-0]
- Example 2 (Basic auth): [#examples-Booking-DeleteBooking-1\_0\_0-1]

```
curl -X DELETE \  
https://restful-booker.herokuapp.com/booking/1 \  
-H 'Content-Type: application/json' \  
-H 'Cookie: token=abc123'
```

```
curl -X DELETE \  
https://restful-booker.herokuapp.com/booking/1 \  
-H 'Content-Type: application/json' \  
-H 'Authorization: Basic YWRtaW46cGFzc3dvcmQxMjM='
```

## Header

| Field                  | Type   | Description                                                                                                                                                        |
|------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cookie optional        | string | Sets an authorization token to access the DELETE endpoint, can be used as an alternative to the Authorization<br><br>Default value: token=<token_value>            |
| Authorization optional | string | YWRtaW46cGFzc3dvcmQxMjM=] Basic authorization header to access the DELETE endpoint, can be used as an alternative to the Cookie header<br><br>Default value: Basic |

## Url Parameter

| Field | Type   | Description                           |
|-------|--------|---------------------------------------|
| id    | Number | ID for the booking you want to update |

## Success 200

| Field | Type   | Description               |
|-------|--------|---------------------------|
| OK    | String | Default HTTP 201 response |

- Response: [#success-examples-Booking-DeleteBooking-1\_0\_0-0]

```
HTTP/1.1 201 Created
```

# Ping

## Ping - HealthCheck

A simple health check endpoint to confirm whether the API is up and running.

GET

```
https://restful-booker.herokuapp.com/ping
```

- Ping server: [#examples-Ping-Ping-1\_0\_0-0]

```
curl -i https://restful-booker.herokuapp.com/ping
```

### Success 200

| Field | Type   | Description               |
|-------|--------|---------------------------|
| OK    | String | Default HTTP 201 response |

- Response: [#success-examples-Ping-Ping-1\_0\_0-0]

```
HTTP/1.1 201 Created
```

Generated with apidoc [<https://apidocjs.com>] 0.25.0 - 2025-06-11T20:24:26.733Z