

CS 361 Machine Learning Exam 1 (January-May Session, 2021)

Total No.: 20
30 Minutes

Attempt all questions

Time:

...

Points: 14/20

1

Which of the following sentence is FALSE regarding regression?
(1/1 Point)

- ☐ It relates inputs to outputs
- ☐ It is used for prediction
- ☐ It may be used for interpretation
- ☒ It discovers causal relationships ✓

2

In the case of supervised learning, which statement(s) is/are NOT TRUE?
(1/1 Point)

- ☐ It prefer the simplest hypothesis consistent with data
- ☐ Given a collection of examples of f , return a function h that approximates f .

- ☒ Feature space is always same as input space ✓
- ☐ Can be called as Inductive Learning

3

Which of the following is/are true about Maximum Likelihood Estimate (MLE)?
(1/1 Point)

- ☒ MLE does not necessarily exist. ✓
- ☐ MLE always exists
- ☒ If exists/exist, it/they may not be unique ✓
- ☐ If exists/exist, it/they must be unique

✗

4

102.9	16.7
109.9	18.7
116.1	20.7
121.7	22.9
127	25.3
132.2	28.1
137.5	31.4
140	32.2
147	37
153	40.9
160	47
166	52.6

Consider the given figure that shows a sample data consisting of two features X1 and X2, and a class label Y. Assume that k-NN is used for memorizing this data and performing classification on some test points. But observing the data and labels, there could be some problems if k-NN memorizes this given data. What operations can be done so that k-NN can generally work well with such data too?
(0/1 Point)

- ☐ Transform the data by column-wise subtracting the mean and dividing by the standard deviation ✓
- ☐ Multiply class of each of the K neighbors by a weight proportional to the inverse of the distance from that training point to the given test point ✓
- ☒ Plotting a graph of validation error-rate vs. k-value and get the best value of k
- ☒ Checking different distance metrics and deciding which performs the best



5

In the context of "Curse of Dimensionality", which of the following statement(s) is/are TRUE?

(0/1 Point)

- ☒ The distance between two randomly drawn data points increases drastically with their dimensionality. ✓
- ☒ One possible solution is to increase the number of training samples, n , until the nearest neighbors are truly close to the test point.
- ☒ In d dimensions, $d-1$ dimensions will be orthogonal to the normal of any given hyper-plane. ✓
- ☒ The true dimensionality of the data may be much lower than its ambient space. ✓

6

Assertion (P): The path taken by Stochastic Gradient Descent (SGD) towards the minima has high variance and convergence is complicated.
Reason (R): In each iteration of SGD, random samples are picked based on which derivatives are calculated.

(1/1 Point)

- ☒ Both P and R are true and R is the correct explanation of P ✓
- ☐ Both P and R are true but R is not the correct explanation of P
- ☐ Both P and R are false
- ☐ P is false but R is true

☐ P is true but R is false

✗

7

MLE can be considered as minimizing the dissimilarities between p_{data} and p_{model} , where the dissimilarity is measured by using
(0/1 Point)

- ☐ MAP of p_{data} and p_{model}
- ☒ Argmax of gaussian distribution estimators
- ☒ KL Divergence ✓
- ☒ Log-likelihood of Bayes error between p_{data} , and p_{model}

8

In the given figure, for a sample data distribution, X-axis and Y-axis denote the independent and dependent variables respectively. Which of the following are true if we try to model this distribution?
(1/1 Point)



- ☐ Simple linear regression will have low bias and high variance
- ☒ Learning a quadratic fit will have low bias and low variance. ✓

- ☒ Learning a polynomial fit of degree 3 will tend to overfit ✓
- ☐ Simple Linear regression will have high bias and high variance

9

In the context of regularization, which of the following is/are true?
(1/1 Point)

- ☐ Weights and biases are regularized using the same lambda
- ☐ Only the weights related to affine transformations are regularized in addition to biases
- ☒ Biases are not regularized as un-regularized biases do not impose high variance ✓
- ☐ Weights and biases are regularized using the different lambda

✗

10

What is the use of a regularization parameter while performing a regularized linear regression?
(0/1 Point)

- ☒ Controls the trade-off between the need for the model to fit the training set well and also have a large number of model parameters
- ☐ It reduces the bias in the model and hence reduces overfitting
- ☒ Until some point, increasing it reduces the variance of the model significantly without significant addition of bias to the model ✓
- ☐ None of the above

✗

11

Which of the following statement(s) is/are TRUE?
(0/1 Point)

- ☒ If the samples are drawn i.i.d. from the same distribution P , then the testing loss is an unbiased estimator of the true generalization loss. ✓
- ☐ We are trying to find a hypothesis h which would have performed well on the past/known data ✓
- ☒ We evaluate our classifier on the testing loss ✓
- ☐ None of the above

12

Which of the following statement is/are NOT true for stochastic gradient descent?

(1/1 Point)

- ☐ In SGD, a few samples are selected randomly instead of the whole data set for each iteration
- ☒ SGD is slower than Batch Gradient Descent ✓
- ☐ For SGD, path for reaching global/local minima is more randomized.
- ☒ Normal gradient descent is less expensive (computation cost) than SGD. ✓

✗

13

Which of the following are true with respect to the Naive Bayes classifier?

(0/1 Point)

- ☐ Assumption of independent predictor variables ✓
- ☐ Should only be used when we have categorical input variables
- ☒ It will make the correct MAP decision rule classification as long as the correct class is more probable than any other class ✓
- ☒ We can consider Naive Bayes to be a log linear model ✓

14

Large values of the log-likelihood statistic indicate that
(1/1 Point)

- ☐ the statistical model fits the data well
- ☐ as the predictor variable increases, the likelihood of the outcome occurring decreases
- ☐ there are a greater number of explained vs. unexplained observations
- ☒ statistical model is a poor fit of the data ✓

15

Consider a univariate linear regression model. Which of the following are true?
(1/1 Point)

- ☐ Changing the input variable by 1 unit always affects the output by 1 unit too
- ☐ Considering Mean Squared Error to compute the loss is a good idea as it reduces the effect of outliers
- ☐ Since it is univariate, we need to estimate one coefficient for modelling the data
- ☐ The decision boundary is a property of the data set given to us
- ☒ None of the above ✓

16

If the cost function of Linear Regression is used for Logistic regression
(1/1 Point)

- ☐ Regularization for logistic regression may be hampered.
- ☐ Hypothesis function becomes intractable
- ☒ Cost function will be non convex in nature ✓

- ☐ Cost function becomes logarithmic in nature

17

Which of the following about kNN classifiers are true?
(1/1 Point)

- ☐ Considering more neighbors for assessment of class votes improves classification accuracy.
- ☒ There is no explicit training phase ✓
- ☐ Decision boundary is smoother with smaller values of k
- ☒ Can be used for both classification and regression ✓

18

K-fold cross-validation is
(1/1 Point)

- ☒ Linear in K ✓
- ☐ Quadratic in K
- ☐ Cubic in K
- ☐ Exponential in K

19

Bayesian networks allow the compact specification of
(1/1 Point)

- ☐ Conditional independence
- ☐ Belief
- ☒ Joint probability distributions ✓
- ☐ Propositional logic statements

20

$$\frac{1}{2N} \sum_{i=1}^N (y_i - \beta_0)^2$$

For the one-parameter model, mean-Square error (MSE) is defined as given. We have a half-term in the front because,
(1/1 Point)

- ☐ scaling MSE by half makes gradient descent converge faster
- ☐ presence of half makes it easy to do grid search
- ☒ it does not matter whether half is there or not ✓
- ☐ none of the above

This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Powered by Microsoft Forms | [Privacy and cookies](#) | [Terms of use](#)