122COM: Databases

David Croft

Coventry University

david.croft@coventry.ac.uk

2015

Overview

SQL

Database *(*noun) - a collection of information that is organized so that it can easily be accessed, managed, and updated.

- Pronounced S-Q-L or Sequel.
  - Structured Query Language.
- 4th generation language.
- Used to query relational databases.
- Doesn't matter what underlying database is.
  - MS SQL Server, Oracle, PostgreSQL, MySQL, SQLite.
  - In reality, minor variations.

Relational Databases

C

Built around tables.

- Can be imagined like a spreadsheet.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

Row/record →

↑ Column/attribute

C

Many types of query.

- SELECT - Get information from the database.
- INSERT - Add information to the database.
- DELETE - Remove information.

Also used for database administration.

- CREATE - Create a whole new table/schema/function.
- ALTER - Modify a table/schema/function.
- DROP - Delete a whole table/schema/function.

SELECT C

Used to retrieve information from the database.

SELECT C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

SELECT

C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT * FROM staff;
```

SELECT C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT * FROM staff;
```

#	id	forename	surname	job
1	0	Malcolm	Reynolds	Captain
2	4	Zoe	Washburne	Co-captain
3	11	Hoban	Washburne	Pilot
4	23	Kaywinnet	Frye	Mechanic

SELECT C

Used to retrieve information from the database.

SELECT C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

SELECT C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT * FROM staff WHERE surname = 'Washburne';
```

SELECT C

Used to retrieve information from the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT * FROM staff WHERE surname = 'Washburne';
```

#	id	forename	surname	job
1	4	Zoe	Washburne	Co-captain
2	11	Hoban	Washburne	Pilot

count()

What if we want to now how many records there are?

- count() function.
- More efficient.
  - Minimum amount of data.

count()

What if we want to now how many records there are?

- count() function.
- More efficient.
  - Minimum amount of data.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

count()

What if we want to now how many records there are?

- count() function.
- More efficient.
  - Minimum amount of data.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT count(*) FROM staff;
```

count()

What if we want to now how many records there are?

- count() function.
- More efficient.
  - Minimum amount of data.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
SELECT count(*) FROM staff;
```

#	count(*)
1	4

INSERT I

Used to add information to the database.

INSERT

Used to add information to the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

INSERT

I

Used to add information to the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
INSERT INTO staff VALUES (42, 'Simon', 'Tam', 'Doctor');
```

INSERT

Used to add information to the database.

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic

```
INSERT INTO staff VALUES (42, 'Simon', 'Tam', 'Doctor');
```

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic
42	Simon	Tam	Doctor

INSERT I

Used to add information to the database.

INSERT

Used to add information to the database.

```
INSERT INTO staff (forename, id, surname)
    VALUES ('River', 43, 'Tam');
```

INSERT

Used to add information to the database.

```
INSERT INTO staff (forename, id, surname)
    VALUES ('River', 43, 'Tam');
```

id	forename	surname	job
0	Malcolm	Reynolds	Captain
4	Zoe	Washburne	Co-captain
11	Hoban	Washburne	Pilot
23	Kaywinnet	Frye	Mechanic
42	Simon	Tam	Doctor
43	River	Tam	

Databases

C

Why use databases at all?

- Databases...
  - have structure.
  - scale.
  - multi-user.
  - fault tolerant.
- Can include SQL queries in other languages.

SQLite

Using SQLite3 in labs.

- Not really a database.
  - Behaves like one.
  - SQL.
- Good for small/non-urgent databases.
  - $\leq$ gigabytes of data.
- Efficient
  - Don’t need to waste resources on a ’real’ database.
- Convenient.
  - Don’t need to install, configure, managed a ’real’ database.
  - Portable, 1 file.
- No network.
  - Single user only.

How to use SQL queries in Python?

```
import sqlite3 as sql

con = sql.connect('firefly.sqlite')
cur = con.cursor()

cur.execute('''SELECT * FROM staff;''')
for row in cur:
    print(row)

con.close()
```

lec_select.py

```
(0, 'Malcolm', 'Reynolds', 'Captain')
(4, 'Zoe', 'Washburne', 'Co-captain')
(11, 'Hoban', 'Washburne', 'Pilot')
(23, 'Kaywinnet', 'Frye', 'Mechanic')
```

Multiple queries.

```
import sqlite3 as sql

con = sql.connect('firefly.sqlite')
cur = con.cursor()

cur.execute('SELECT count(*) FROM staff;')
print(cur.fetchone()[0])

cur.execute('SELECT * FROM staff;')
for row in cur:
    pass

con.close()
```

lec_multi.py

```
4
```

Static queries

So far looked at static queries.

- Same query is run every time.
- Real power is in dynamic queries.
  - Code creates new queries to ask new questions.

Dynamic queries


```
import sqlite3 as sql

con = sql.connect('firefly.sqlite')
cur = con.cursor()

question = input('Who is the...')

cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))

for row in cur:
    print('%s %s' % row)
```

lec_dynamic.py

```
Who is the...Captain
Malcolm Reynolds
```

Bad dynamic queries


```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))
```

```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = "%s";''' % question )
```

- User could input anything.
  - `Captain"; DROP TABLE staff; --`
- Sanitise inputs.

Bad dynamic queries


```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))
```

```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = "%s";''' % question )
```

- User could input anything.
  - `Captain"; DROP TABLE staff; --`
- Sanitise inputs.
- Always use placeholders.

Bad dynamic queries


```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))
```

```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = "%s";''' % question )
```

- User could input anything.
  - `Captain"; DROP TABLE staff; --`
- Sanitise inputs.
- Always use placeholders.
  - No exceptions.

Bad dynamic queries


```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))
```

```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = "%s";''' % question )
```

- User could input anything.
  - `Captain"; DROP TABLE staff; --`
- Sanitise inputs.
- Always use placeholders.
  - No exceptions.
  - NO EXCEPTIONS!

Bad dynamic queries


```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = ?;''', (question,))
```

```
cur.execute('''SELECT forename, surname FROM staff
               WHERE job = '%s';''' % question)
```

- User should input anything.
- Contains DROP TABLE staff;
- Sanitise inputs
- Always use placeholders.
  - No exceptions.
  - NO EXCEPTIONS!

NO EXCEPTIONS!

SQL injection

A

Around since at least 1998.

Notable SQL injection attacks.

- 2015 TalkTalk - 160,000 customers' details.
- 2014 Hold security - found 420,000 vulnerable websites.
- 2012 Yahoo - 450,000 logins.
- 2011 MySql - mysql.com compromised.
- 2008 Heartland Payment - 134,000,000 credit cards.

Many, many more.



https://xkcd.com/327/

Efficient inserting

A

```
con = sql.connect('firefly.sqlite')
cur = con.cursor()

cur.execute('''INSERT INTO staff (forename, surname)
               VALUES (?,?)''', ('River', 'Tam'))
con.commit()
con.close()
```

lec_single_insert.py

`commit()` command.

- Have modified database.
- Tell database to save changes.
- `revert()` command to undo everything done since `commit()`.

Multiple inserts

A

What is you want to insert a lot of records?

- Could run multiple small INSERT statements.
  - Slow.
- Could run one big INSERT statement.
  - Fast.

```
con = sql.connect('firefly.sqlite')
cur = con.cursor()

people = [('Simon','Tam','Doctor'), ('River','Tam',None)]

cur.executemany('''INSERT INTO staff (forename, surname, job)
                   VALUES (?,?,?)''', people)

cur.commit()
con.close()
```

lec_multi_insert.py

Quiz

Recap

- SQL used to query databases.
- Databases are...
  - fault tolerant.
  - multi user.
  - scalable.
- Always use place holders in dynamic queries.
  - Say no to SQL injection!
- Inserting data
  - Avoid small inserts.
  - Use big inserts.

The End