


Examples



Lecture 20 (Graphs 1)

Graphs and Traversals

CS61B, Fall 2025 @ UC Berkeley

Slides credit: Josh Hug

Tree Definition

Lecture 20, CS61B, Fall 2025

Trees

- **Tree Definition**
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals

- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals


Challenge: Invent Breadth First Search

Tree Definition (Reminder)

A tree consists of:

- A set of nodes.
- A set of edges that connect those nodes.
 - Constraint: There is exactly one path between any two nodes.

Green structures below are trees. Pink ones are not.



Rooted Trees Definition (Reminder)



A rooted tree is a tree where we've chosen one node as the "root".

- Every node N except the root has exactly one parent, defined as the first node on the path from N to the root.
- A node with no child is called a leaf.







For each of these:

- A is the root.
- B is a child of A. (and C of B)
- A is a parent of B. (and B of C)






We've seen trees as nodes in a specific data structure implementation: Search Trees, Tries, Heaps, Disjoint Sets, etc.



Trees are a more general concept.

- Organization charts.
- Family lineages* including phylogenetic trees.
- MOH Training Manual for Management of Malaria.



*: Not all family lineages are trees!

Tree Traversals

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- **Tree Traversals**
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals


- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals

Challenge: Invent Breadth First Search

Example: File System Tree


Sometimes you want to iterate over a tree. For example, suppose you want to find the total size of all files in a folder called 61b.

- What one might call “tree iteration” is actually called “tree traversal.”
- Unlike lists, there are many orders in which we might **visit** the nodes.
 - Each ordering is useful in different ways.



Level Order

- Visit top-to-bottom, left-to-right (like reading in English): DBFACEG




Level Order

- Visit top-to-bottom, left-to-right (like reading in English): DBFACEG

Depth First Traversals

- 3 types: Preorder, Inorder, Postorder
- Basic (rough) idea: Traverse “deep nodes” (e.g. A) before shallow ones (e.g. F).
- Note: Traversing a node is different than “visiting” a node. See next slide.




Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children:

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:
preOrder(D)




Demo: Preorder Depth-First Tree Traversal

Preorder: “Visit” a node, then traverse its children: D

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:
preOrder(D)




Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: D

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:
preOrder(D)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: D

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DB

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DB

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)



Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: DB


```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)

preOrder(A)



Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: DBA


```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)

preOrder(A)



Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: DBA


```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)

preOrder(A)



Skipping over the steps of
preOrder(null) for brevity.

Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: DBA


```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)

preOrder(A)



Skipping over the steps of
preOrder(null) for brevity.

Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBA

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBAC

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(B)




Skipping over the steps of preOrder(C) for brevity.

Demo: Preorder Depth-First Tree Traversal

Preorder: "Visit" a node, then traverse its children: DBAC

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:
preOrder(D)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBAC

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(F)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBACF

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(F)



Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBACFE

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(F)



Skipping over the steps of preOrder(E) for brevity.

Demo: Preorder Depth-First Tree Traversal


Preorder: "Visit" a node, then traverse its children: DBACFEG

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

Call stack:

preOrder(D)

preOrder(F)



Skipping over the steps of preOrder(G) for brevity.


Preorder traversal: "Visit" a node, then traverse its children: DBACFEG

Inorder traversal: Traverse left child, visit, then traverse right child:

ABCDEF G

```
preOrder(BSTNode x) {  
    if (x == null) return;  
    print(x.key)  
    preOrder(x.left)  
    preOrder(x.right)  
}
```

```
inOrder(BSTNode x) {  
    if (x == null) return;  
    inOrder(x.left)  
    print(x.key)  
    inOrder(x.right)  
}
```




Preorder traversal: "Visit" a node, then traverse its children: DBACFEG

Inorder traversal: Traverse left child, visit, traverse right child: ABCDEFG

Postorder traversal: Traverse left, traverse right, then visit: ???????

1. DBACEFG
2. GFEDCBA
3. GEFCABD
4. ACBEGFD
5. ACBFEGD
6. Other

```
postOrder(BSTNode x) {  
    if (x == null) return;  
    postOrder(x.left)  
    postOrder(x.right)  
    print(x.key)  
}
```




Depth First Traversals

Preorder traversal: "Visit" a node, then traverse its children: DBACFEG

Inorder traversal: Traverse left child, visit, traverse right child: ABCDEFG

Postorder traversal: Traverse left, traverse right, then visit: ACBEGFD

1. DBACEFG
2. GFEDCBA
3. GEFCABD
4. **ACBEGFD**
5. ACBFEGD
6. Other




```
postOrder(BSTNode x) {  
    if (x == null) return;  
    postOrder(x.left)  
    postOrder(x.right)  
    print(x.key)  
}
```

A Useful Visual Trick (for Humans, Not Algorithms)

- Preorder traversal: We trace a path around the graph, from the top going counter-clockwise. “Visit” every time we pass the LEFT of a node.
- Inorder traversal: “Visit” when you cross the bottom of a node.
- Postorder traversal: “Visit” when you cross the right of a node.

Example: Post-Order Traversal

- 4 7 8 5 2 9 6 3 1



Usefulness of Tree Traversals

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- **Usefulness of Tree Traversals**

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals


- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals

Challenge: Invent Breadth First Search

What Good Are All These Traversals?

Example: Preorder Traversal for printing directory listing:


```
sc2APM/  
  directOverlay/  
    directIO/  
      DXHookD3D11.cs  
      Injector.cs  
    directO.suo  
    directO.sln  
  notes  
  python/  
    printAPM.py
```



What Good Are All These Traversals?

Example: Postorder Traversal for gathering file sizes.


```
postOrder(BSTNode x) {  
    if (x == null) return 0;  
    int total = 0;  
    for (BSTNode c : x.children())  
        total += postOrder(c)  
    total += x.fileSize();  
    return total;  
}
```



What Good Are All These Traversals?

Example: Postorder Traversal for gathering file sizes.

```
postOrder(BSTNode x) {  
    if (x == null) return 0;  
    int total = 0;  
    for (BSTNode c : x.children())  
        total += postOrder(c)  
    total += x.fileSize();  
    return total;  
}
```



Graph Definition

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- **Graph Definition**
- Some Famous Graph Problems

Graph Traversals

- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals

Challenge: Invent Breadth First Search

Trees are fantastic for representing strict hierarchical relationships.


- But not every relationship is hierarchical.
- Example: Paris Metro map.

Introduction to **Network Visualization** with Gephi – Martin Grandjean

Examples

This is not a tree: Contains cycles!

- More than one way to get from A to B.







Tree Definition (Revisited)

A tree consists of:

- A set of nodes.
- A set of edges that connect those nodes.
 - Constraint: There is exactly one path between any two nodes.

Green structures on slide are trees. Pink ones are not.







Graph Definition

A graph consists of:

- A set of nodes.
- A set of zero or more edges, each of which connects two nodes.

Green structures below are graphs.


- Note, all trees are graphs!



Graph Example: BART

Is the BART graph a tree?

- No, has one cycle.
 - San Bruno
 - SFO
 - Millbrae






Graph Definition

A simple graph is a graph with:

- No edges that connect a vertex to itself, i.e. no “length 1 loops”.
- No two edges that connect the same vertices, i.e. no “parallel edges”.

Green graph below is simple, pink graphs are not.



A simple graph is a graph with:

- No edges that connect a vertex to itself, i.e. no “loops”.
- No two edges that connect the same vertices, i.e. no “parallel edges”.



In 61B, **unless otherwise explicitly stated, all graphs will be simple.**

- In other words, when we say “graph”, we mean “simple graph.”



Directed

Undirected


Acyclic:



Cyclic:



With Edge Labels



- Graph:
 - Set of **vertices**, a.k.a. **nodes**.
 - Set of **edges**: Pairs of vertices.
 - Vertices with an edge between are **adjacent**.
 - Optional: Vertices or edges may have **labels** (or **weights**).
- A **path** is a sequence of vertices connected by edges.
 - A **simple path** is a path without repeated vertices.
- A **cycle** is a path whose first and last vertices are the same.
 - A graph with a cycle is 'cyclic'.
- Two vertices are **connected** if there is a path between them. If all vertices are connected, we say the graph is connected.




Figure from Algorithms 4th Edition


Graph Example: The Paris Metro

This schematic map of the Paris Metro is a graph:

- Undirected
- Connected
- Cyclic (not a tree!)
- Vertex-labeled (each has a color).

Introduction to **Network Visualization** with GEPHI – Martin Grandjean


Examples



Directed Graph Example

Not a tree!

- Two paths from group_action to event.



Edge captures 'is-a-type-of' relationship. Example: descent is-a-type-of movement.

Some Famous Graph Problems

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- **Some Famous Graph Problems**

Graph Traversals

- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals


Challenge: Invent Breadth First Search

There are lots of interesting questions we can ask about a graph:

- What is the shortest route from S to T? What is the longest without cycles?
- Are there cycles?
- Is there a tour you can take that only uses each node (station) exactly once?
- Is there a tour that uses each edge exactly once?

Introduction to **Network Visualization** with GEPHI – Martin Grandjean

Examples



Some well known graph problems and their common names:

- **s-t Path.** Is there a path between vertices s and t ?
- **Connectivity.** Is the graph connected, i.e. is there a path between all vertices?
- **Biconnectivity.** Is there a vertex whose removal disconnects the graph?
- **Shortest s-t Path.** What is the shortest path between vertices s and t ?
- **Cycle Detection.** Does the graph contain any cycles?
- **Euler Tour.** Is there a cycle that uses every edge exactly once?
- **Hamilton Tour.** Is there a cycle that uses every vertex exactly once?
- **Planarity.** Can you draw the graph on paper with no crossing edges?
- **Isomorphism.** Are two graphs isomorphic (the same graph in disguise)?

Often can't tell how difficult a graph problem is without very deep consideration.

Some well known graph problems:

- **Euler Tour.** Is there a cycle that uses every edge exactly once?
- **Hamilton Tour.** Is there a cycle that uses every vertex exactly once?

Difficulty can be deceiving.

- An efficient Euler tour algorithm $O(\# \text{ edges})$ was found as early as 1873 [[Link](#)].
- Despite decades of intense study, no efficient algorithm for a Hamilton tour exists. Best algorithms are exponential time.

Graph problems are among the most mathematically rich areas of CS theory.

Motivation for Graph Traversals: s-t Connectivity

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals


- **Motivation: s-t Connectivity**
- Depth First Search
- Tree vs. Graph Traversals

Challenge: Invent Breadth First Search

Let's solve a classic graph problem called the s-t connectivity problem.

- Given source vertex s and a target vertex t , is there a path between s and t ?

Requires us to traverse the graph somehow.




Let's solve a classic graph problem called the s-t connectivity problem.

- Given source vertex s and a target vertex t , is there a path between s and t ?

Requires us to traverse the graph somehow.


- Try to come up with an algorithm for $\text{connected}(s, t)$.



One possible recursive algorithm for $\text{connected}(s, t)$.

- Does $s == t$? If so, return true.
- Otherwise, if $\text{connected}(v, t)$ for any neighbor v of s , return true.
- Return false.


What is wrong with the algorithm above?



One possible recursive algorithm for `connected(s, t)`.

- Does `s == t`? If so, return true.
- Otherwise, if `connected(v, t)` for any neighbor `v` of `s`, return true.
- Return false.

What is wrong with the algorithm above?




One possible recursive algorithm for `connected(s, t)`.

- Does `s == t`? If so, return true.
- Otherwise, if `connected(v, t)` for any neighbor `v` of `s`, return true.
- Return false.

What is wrong with it? Can get caught in an infinite loop. Example:

- `connected(0, 7)`:
 - Does `0 == 7`? No, so...
 - if (`connected(1, 7)`) return true;
- `connected(1, 7)`:
 - Does `1 == 7`? No, so...
 - If (`connected(0, 7)`) ... ← Infinite loop.




One possible recursive algorithm for `connected(s, t)`.

- Does `s == t`? If so, return true.
- Otherwise, if `connected(v, t)` for any neighbor `v` of `s`, return true.
- Return false.

What is wrong with it? Can get caught in an infinite loop.

- How do we fix it?



Depth First Search

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals

- Motivation: s-t Connectivity
- **Depth First Search**
- Tree vs. Graph Traversals


Challenge: Invent Breadth First Search

One possible recursive algorithm for $\text{connected}(s, t)$.

- Mark s .
- Does $s == t$? If so, return true.
- Otherwise, if $\text{connected}(v, t)$ for any unmarked neighbor v of s , return true.
- Return false.


Basic idea is same as before, but visit each vertex at most once.

- Marking nodes prevents multiple visits.



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.


Call stack: 0

mark(0).

Is $0 == 7$? No.

isMarked(1)? No.

- Check connected(1, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1$


mark(1).

Is $1 == 7$? No.

isMarked(0)? Yes.

isMarked(2)?

- Check connected(2, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2$


mark(2).

Is $2 == 7$? No.

isMarked(1)? Yes.

isMarked(5)?

- Check connected(5, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5$


mark(5).

Is $5 == 7$? No.

isMarked(2)? Yes.

isMarked(4)?

- Check connected(4, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 4$


mark(4).

Is $4 == 7$? No.

isMarked(1)? Yes.

isMarked(3)? No.

- Check connected(3, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.


Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 4 \rightarrow 3$

mark(3).

Is $3 == 7$? No.

isMarked(4)? Yes.

No more neighbors! Return false.



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 4$

mark(4).

Is $4 == 7$? No.


isMarked(1)? Yes.

isMarked(3)? No.

- Check connected(3, 7). Answer was false.

isMarked(5)? Yes.

No more neighbors, so return false.



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5$

mark(5).

Is $5 == 7$? No.


isMarked(2)? Yes.

isMarked(4)?

- Check connected(4, 7). Answer was false, so keep checking neighbors.

isMarked(6)?

- Check connected(6, 7).



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 6$


mark(6).

Is $6 == 7$? No.

isMarked(5)? Yes.

isMarked(7)? No.

- Check connected(7, 7).




connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 6 \rightarrow 7$

mark(7).

Is $7 == 7$? Yes. Return true!



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5 \rightarrow 6$


mark(6).

Is $6 == 7$? No.

isMarked(5)? Yes.

isMarked(7)? No.

- Check connected(7, 7). Answer was true, so return true.



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2 \rightarrow 5$

mark(5).

Is $5 == 7$? No.

isMarked(2)? Yes.


isMarked(4)?

- Check connected(4, 7). Answer was false, so keep checking neighbors.

isMarked(5)? Yes.

isMarked(6)?

- Check connected(6, 7): Return true!



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1 \rightarrow 2$


mark(2).

Is $2 == 7$? No.

isMarked(1)? Yes.

isMarked(5)?

- Check connected(5, 7). Answer was true, so return true!



connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

Call stack: $0 \rightarrow 1$


mark(1).

Is $1 == 7$? No.

isMarked(0)? Yes.

isMarked(2)?

- Check connected(2, 7). Answer was true, so return true!



Demo: s-t Connectivity

connected(s, t):

- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.


Call stack: 0

mark(0).

Is $0 == 7$? No.

isMarked(1)? No.

- Check connected(1, 7). Answer was true, so return true!



Demo: s-t Connectivity

connected(s, t): **T**


- Mark s.
- Does $s == t$? If so, return true.
- Otherwise, if connected(v, t) for any unmarked neighbor v of s, return true.
- Return false.

mark(0).

Is $0 == 7$? No.

isMarked(1)? No.


- Check connected(1, 7). Answer was true, so return true!



Depth First Traversal

This idea of exploring a neighbor's entire subgraph before moving on to the next neighbor is known as Depth First Traversal or Depth First Search.


- Example: Explore 1's subgraph completely before using the edge 0-3.
- Called "depth first" because you go as deep as possible.



Depth First Traversal


This idea of exploring a neighbor's entire subgraph before moving on to the next neighbor is known as Depth First Traversal.

- Example: Explore 1's subgraph completely before using the edge 0-3.
- Called "depth first" because you go as deep as possible.



Entirely possible for 1's subgraph to include 3!

- It's still depth first, since we're not using the edge 0-3 until the subgraph is explored.



From: <https://xkcd.com/761/>

I REALLY NEED TO STOP USING DEPTH-FIRST SEARCHES.

DFS is a very powerful technique that can be used for many types of graph problems.

Another example:


- Let's discuss an algorithm that computes a path to every vertex.
- Let's call this algorithm `DepthFirstPaths`.
- Goal: Find a path from s to every other reachable vertex, visiting each vertex at most once.

dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0)

Order of dfs calls: 0



Order of dfs returns:

#	marked	edgeTo	Start by calling dfs(0).
0	F	-	
1	F	-	
2	F	-	
3	F	-	
4	F	-	
5	F	-	
6	F	-	
7	F	-	
8	F	-	


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

#	marked	edgeTo	dfs(0):
0	T	-	mark(0).
1	F	0	
2	F	-	isMarked(1)? No.
3	F	-	• edgeTo[1] = 0. dfs(1).
4	F	-	
5	F	-	
6	F	-	
7	F	-	
8	F	-	

Call stack:
dfs(0)

Order of dfs calls: 01



Order of dfs returns:


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1)

Order of dfs calls: 012

#	marked	edgeTo	dfs(1):
0	T	-	mark(1).
1	T	0	
2	F	1	isMarked(0)? Yes.
3	F	-	isMarked(2)? No.
4	F	-	• edgeTo[2] = 1. dfs(2).
5	F	-	
6	F	-	
7	F	-	
8	F	-	



Order of dfs returns:


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1) → dfs(2)

Order of dfs calls: 0125

#	marked	edgeTo	dfs(2):
0	T	-	mark(2).
1	T	0	
2	T	1	isMarked(1)? Yes.
3	F	-	isMarked(5)? No.
4	F	-	• edgeTo[5] = 2. dfs(5).
5	F	2	
6	F	-	
7	F	-	
8	F	-	



Order of dfs returns:

Demo: DepthFirstPaths

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

#	marked	edgeTo	dfs(5):
0	T	-	mark(5).
1	T	0	
2	T	1	isMarked(2)? Yes.
3	F	-	isMarked(4)? No.
4	F	5	• edgeTo[4] = 5. dfs(4).
5	T	2	
6	F	-	
7	F	-	
8	F	-	

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5)

Order of dfs calls: 01254



Order of dfs returns:

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(4)

Order of dfs calls: 012543

#	marked	edgeTo	dfs(4):
0	T	-	mark(4).
1	T	0	
2	T	1	isMarked(1)? Yes.
3	F	4	isMarked(3)? No.
4	T	5	• edgeTo[3] = 4. dfs(3).
5	T	2	
6	F	-	
7	F	-	
8	F	-	



Order of dfs returns:

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

#	marked	edgeTo	dfs(3):
0	T	-	mark(3).
1	T	0	
2	T	1	isMarked(4)? Yes.
3	T	4	
4	T	5	No more children, so return.
5	T	2	
6	F	-	
7	F	-	
8	F	-	

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(4) → dfs(3)

Order of dfs calls: 012543



Order of dfs returns: 3

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(4)

Order of dfs calls: 012543

#	marked	edgeTo	dfs(4):
0	T	-	mark(4).
1	T	0	
2	T	1	isMarked(3)? No.
3	T	4	• edgeTo[3] = 4. dfs(3).
4	T	5	
5	T	2	No more children, so return.
6	F	-	
7	F	-	
8	F	-	



Order of dfs returns: 34


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1) → dfs(2) →
dfs(5)

Order of dfs calls: 0125436

#	marked	edgeTo	dfs(5):
0	T	-	mark(5).
1	T	0	
2	T	1	isMarked(2)? Yes.
3	T	4	isMarked(4)? No.
4	T	5	• edgeTo[3] = 4. dfs(4).
5	T	2	isMarked(6)? No.
6	F	5	• edgeTo[6] = 5. dfs(6).
7	F	-	
8	F	-	



Order of dfs returns: 34

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

#	marked	edgeTo	dfs(6):
0	T	-	mark(6).
1	T	0	
2	T	1	isMarked(5)? Yes.
3	T	4	isMarked(7)? No.
4	T	5	• edgeTo[7] = 6. dfs(7).
5	T	2	
6	T	5	
7	F	6	
8	F	-	

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(6)

Order of dfs calls: 01254367



Order of dfs returns: 34

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(6) → dfs(7)

Order of dfs calls: 01254367

#	marked	edgeTo	dfs(7):
0	T	-	mark(7).
1	T	0	
2	T	1	isMarked(6)? Yes.
3	T	4	
4	T	5	No more children, so return.
5	T	2	
6	T	5	
7	T	6	
8	F	-	



Order of dfs returns: 347

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(6)

Order of dfs calls: 01254367

#	marked	edgeTo	dfs(6):
0	T	-	mark(6).
1	T	0	
2	T	1	isMarked(5)? Yes.
3	T	4	isMarked(7)? No.
4	T	5	• edgeTo[7] = 6. dfs(7).
5	T	2	
6	T	5	No more children, so return.
7	T	6	
8	F	-	



Order of dfs returns: 3476


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1) → dfs(2) →
dfs(5)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(5):
0	T	-	mark(5).
1	T	0	
2	T	1	isMarked(2)? Yes.
3	T	4	isMarked(4)? No.
4	T	5	• edgeTo[3] = 4. dfs(4).
5	T	2	isMarked(6)? No.
6	T	5	• edgeTo[6] = 5. dfs(6).
7	T	6	isMarked(8)? No.
8	F	5	• edgeTo[8] = 5. dfs(8).



Order of dfs returns: 3476

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:

dfs(0) → dfs(1) → dfs(2) →
dfs(5) → dfs(8)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(8):
0	T	-	mark(8)
1	T	0	
2	T	1	isMarked(5)? Yes.
3	T	4	
4	T	5	No more children, so return.
5	T	2	
6	T	5	
7	T	6	
8	T	5	



Order of dfs returns: 34768

dfs(v):


- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1) → dfs(2) →
dfs(5)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(5):
0	T	-	mark(5).
1	T	0	
2	T	1	isMarked(2)? Yes.
3	T	4	isMarked(4)? No.
4	T	5	• edgeTo[3] = 4. dfs(4).
5	T	2	isMarked(6)? No.
6	T	5	• edgeTo[6] = 5. dfs(6).
7	T	6	isMarked(8)? No.
8	T	5	• edgeTo[8] = 5. dfs(8)

No more children, so return.



Order of dfs returns: 347685


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1) → dfs(2)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(2):
0	T	-	mark(2).
1	T	0	
2	T	1	isMarked(1)? Yes.
3	T	4	isMarked(5)? No.
4	T	5	• edgeTo[5] = 2. dfs(5).
5	T	2	
6	T	5	No more children, so return.
7	T	6	
8	T	5	



Order of dfs returns: 3476852


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0) → dfs(1)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(1):
0	T	-	mark(1).
1	T	0	
2	T	1	isMarked(0)? Yes.
3	T	4	isMarked(2)? No.
4	T	5	• edgeTo[2] = 1. dfs(2).
5	T	2	isMarked(4)? Yes.
6	T	5	
7	T	6	
8	T	5	No more children, so return.



Order of dfs returns: 34768521


dfs(v):

- Mark v.
- For each unmarked adjacent vertex w:
 - set edgeTo[w] = v.
 - dfs(w)

Call stack:
dfs(0)

Order of dfs calls: 012543678

#	marked	edgeTo	dfs(0):
0	T	-	mark(0).
1	T	0	
2	T	1	isMarked(1)? No.
3	T	4	● edgeTo[1] = 0. dfs(1).
4	T	5	
5	T	2	No more children, so return.
6	T	5	
7	T	6	
8	T	5	



Order of dfs returns: 347685210

Tree vs. Graph Traversals

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs

- Graph Definition
- Some Famous Graph Problems

Graph Traversals


- Motivation: s-t Connectivity
- Depth First Search
- **Tree vs. Graph Traversals**

Challenge: Invent Breadth First Search

Tree Traversals


There are many tree traversals:

- Preorder: DBACFEG
- Inorder: ABCDEFG
- Postorder: ACBEGFD
- Level order: DBFACEG




There are many tree traversals:

- Preorder: DBACFEG
- Inorder: ABCDEFG
- Postorder: ACBEGFD
- Level order: DBFACEG




What we just did in DepthFirstPaths is called “**DFS Preorder**.”

- **DFS Preorder: Action** is **before DFS** calls to neighbors.
 - Our action was setting edgeTo.
 - Example: edgeTo[1] was set before DFS calls to neighbors 2 and 4.
- One valid DFS preorder for this graph: 012543678
 - Equivalent to the order of dfs calls.




There are many tree traversals:

- Preorder: DBACFEG
- Inorder: ABCDEFG
- Postorder: ACBEGFD
- Level order: DBFACEG




Could also do actions in **DFS Postorder**.

- **DFS Postorder: Action** is **after** DFS calls to neighbors.
- Example: `dfs(s)`:
 - `mark(s)`
 - For each unmarked neighbor `n` of `s`, `dfs(n)`
 - `print(s)`
- Results for `dfs(0)` would be: 347685210
- Equivalent to the order of `dfs` returns.




Just as there are many tree traversals:

- Preorder: DBACFEG
- Inorder: ABCDEFG
- Postorder: ACBEGFD
- Level order: DBFACEG




So too are there many graph traversals, given some source:

- DFS Preorder: 012543678 (dfs calls).
- DFS Postorder: 347685210 (dfs returns).




Just as there are many tree traversals:

- Preorder: DBACFEG
- Inorder: ABCDEFG
- Postorder: ACBEGFD
- Level order: DBFACEG



So too are there many graph traversals, given some source:

- DFS Preorder: 012543678 (dfs calls).
- DFS Postorder: 347685210 (dfs returns).
- BFS order: Act in order of distance from s.
 - BFS stands for “breadth first search”.
 - Analogous to “level order”. Search is wide, not deep.
 - 0 1 24 53 68 7



Challenge: Invent Breadth First Search

Lecture 20, CS61B, Fall 2025

Trees

- Tree Definition
- Tree Traversals
- Usefulness of Tree Traversals

Graphs


- Graph Definition
- Some Famous Graph Problems

Graph Traversals

- Motivation: s-t Connectivity
- Depth First Search
- Tree vs. Graph Traversals

Challenge: Invent Breadth First Search

Shortest Paths Challenge Before Next Lecture



Goal: Given the graph above, find the length of the shortest path from s to all other vertices.

- Give a general algorithm.
- Hint: You'll need to somehow visit vertices in BFS order.
- Hint #2: You'll need to use some kind of data structure.

Will discuss a solution in the next lecture.

Graphs are a more general idea than a tree.

- A tree is a graph where there are no cycles and every vertex is connected.
- Key graph terms: Directed, Undirected, Cyclic, Acyclic, Path, Cycle.

Graph problems vary widely in difficulty.

- Common tool for solving almost all graph problems is traversal.
- A traversal is an order in which you visit / act upon vertices.
- Tree traversals:
 - Preorder, inorder, postorder, level order.
- Graph traversals:
 - DFS preorder, DFS postorder, BFS.
- By performing actions / setting instance variables during a graph (or tree) traversal, you can solve problems like s-t connectivity or path finding.

Project 4A (Ngrams) due today.

HW10: LLRB Set due Friday.

Then the rest of the month is all project 4B/4C/4D.

- First of two really big design projects.

