The Cavity-Loss Barrier to Ultrastrong-Coupling Quantum Metrology

Juste Deuyekbe,[1] P. Djorwé,[1,2,*] A.-H. Abdel-Aty,[3] A. Elrashidi,[4,†] Nsangou Mama,[5] and S. G. Nana Engo[6,‡]

[1]*Department of Physics, Faculty of Science, University of Ngaoundere, P.O. Box 454, Ngaoundere, Cameroon*

[2]*Stellenbosch Institute for Advanced Study (STIAS), Wallenberg Research Centre at Stellenbosch University, Stellenbosch 7600, South Africa*

[3]*Department of Physics, College of Sciences, University of Bisha, Bisha 61922, Saudi Arabia*

[4]*College of Engineering, University of Business and Technology, Jeddah 21448, Saudi Arabia*

[5]*Department of Physics, Faculty of Science, University of Maroua, P.O.Box 46, Maroua, Cameroon*

[6]*Department of Physics, Faculty of Science, University of Yaounde I, P.O.Box 812, Yaounde, Cameroon*

Abstract

Ultrastrong-coupling metrology proposals quote large pure-state quantum Fisher information (QFI) gains, but a dynamical Casimir (DCE) drive converts bound virtual dressing into real photons that leak. Lindblad simulations reduce the single-qubit DCE QFI to below 1% at a representative coplanar-waveguide linewidth of 248 MHz. Cavity loss and model validity, not idealized gains, are the operational constraints. Current devices fall short of the idealized gains, and the cavity-loss barrier—rather than the idealized gains—is the operationally decisive result. We quantify this cavity-loss barrier in finite-dimensional Rabi and Dicke models. Any protocol converting bound, non-emissive correlations into real excitations faces the same loss test.

I. INTRODUCTION

Quantum metrology exploits entanglement and squeezing to measure physical parameters beyond the classical shot-noise limit [1–6]. Standard protocols prepare a squeezed probe state, expose it to a parameter-dependent Hamiltonian, and perform destructive readout. The rotating-wave approximation (RWA) is typically valid in these settings, and the vacuum state has no metrological advantage over a coherent state.

Recent circuit QED experiments have accessed the ultrastrong coupling (USC, $\eta = g/\omega_c \gtrsim 0.1$) and deep strong coupling (DSC, $\eta \gtrsim 1$) regimes [7–15]. Reaching the DSC limit requires specialized architectures; circuit QED provides the necessary impedance engineering and large dipole moments—typically utilizing flux qubits galvanically coupled to coplanar waveguide (CPW) resonators via shared Josephson junctions—to achieve $\eta \gtrsim 1$ without inducing excessive parasitic losses. Here, counter-rotating terms (CRTs) restructure the ground state, dressing it with virtual photon and qubit excitations [8, 16–18]. The virtual-photon number is a ground-state diagnostic, not by itself an emitted output flux; accessing such correlations requires a specified conversion and readout protocol [16, 19]. In the undriven idealized model considered here, the dressed state does not by itself produce an outgoing photon flux through the modeled cavity-extraction channel. Time-dependent switching or modulation can instead convert virtual correlations into extracavity radiation

* djorwepp@gmail.com

† a.elrashidi@ubt.edu.sa

‡ serge.nana-engo@facsciences-uy1.cm

[20, 21], a mechanism rooted in the dynamical Casimir effect [22], while related DCE photon production has been observed in a superconducting circuit [23]. The dressed vacuum can therefore be a metrological resource, but its operational accessibility and loss budget depend on the control and measurement channel.

Hotter, Miranowicz, and Gietka [24] proposed using virtual excitations for metrology without extracting them, with QFI scaling as $\exp(4\xi)$ in their Dicke-model setting; related virtual-state metrology proposals have since emerged [25]. However, two questions remained open: (i) the extent to which these effects survive in the single-mode Rabi model – the minimal model for USC circuit QED – and (ii) whether a parametrically modulated DCE protocol can convert virtual dressing into an extractable, loss-sensitive metrological resource. Superconducting-circuit DCE photon production has been observed experimentally [23], but this does not constitute an end-to-end demonstration of the present USC metrology protocol. A third, operationally critical question is (iii) whether the resulting QFI gains survive cavity loss, since the USC platforms that host the relevant physics have cavity linewidths in the MHz to hundreds-of-MHz range. Recent work reports a single-qubit DCE metrological advantage that persists even in the presence of dissipation [26]; that claim is stated for the generated state's quantum Fisher information against classical states of the same mean photon number, for phase/displacement estimation under chirped qubit-frequency modulation. Here the estimand is the coupling g under a fixed-detuning $g(t)$ Floquet drive, and the same quantity is followed through the loss channel to a representative coplanar-waveguide linewidth ($\kappa/2\pi \approx 248\,\mathrm{MHz}$). Lindblad dynamics retain less than 1% of its pure-state value. The two statements therefore differ by the assumed loss budget and by the end-to-end accounting, not by the underlying physics. A Floquet-bound-state rescue of noisy metrology has been shown for emitter-local baths [27], but no bound state is demonstrated for the broadband cavity-leakage channel opened here at $\kappa/\omega \sim 4 \times 10^{-2}$, and none is claimed. This motivates the central question of the present study: *How does the conversion of non-emissive virtual dressing into real photons by a DCE drive change the loss budget of quantum metrology in the ultrastrong-coupling regime?* Here, "non-emissive" refers specifically to the undriven idealized Rabi ground state and its modeled cavity-extraction channel; it does not imply immunity to qubit decoherence, thermal effects, readout backaction, or other loss mechanisms. The question is addressed within the finite-dimensional models, estimands, and dissipation channels specified below, rather than as a universal bound.

In this paper we compute three idealized QFI contributions within a stated family of models, then quantify the open-system loss penalty that determines whether any of them is operationally meaningful:

1. **Static virtual dressing** in the single-qubit Rabi model: the gap-weighted ground-state QFI reaches 6.12× the coherent baseline at the sampled maximum $\eta = 1.14$. The dressed excitations are virtual ($n_{\mathrm{virt}} \lesssim 1$ in the reported range), so direct cavity extraction loss is reduced in the idealized static model.

2. **DCE parametric amplification**: a fixed-detuning Floquet drive at the DCE resonance yields a sampled peak pure-state QFI of $\sim 1.7 \times 10^5\times$ at $\eta = 0.150$, $g_d/g_0 = 0.119\,23$. For $N = 32$ Dicke qubits, the late-window average QFI is $\sim 1.7 \times 10^5\times$ (730× enhancement over the static Dicke value of 229×). The DCE protocol creates real, extractable photons, so it is explicitly loss-sensitive.

3. **Cavity-loss barrier**: Lindblad simulations show the DCE QFI collapses to $<1\%$ of its pure-state value at the physical operating point $\kappa/2\pi \approx 248\,\mathrm{MHz}$ (Section S11); adding qubit T_1 and T_ϕ using a deliberately conservative coherence benchmark does not change the conclusion (Section S16). The validated truncated-basis Dicke+DCE propagation retains $\sim$61% at $\kappa/\omega_c = 1 \times 10^{-2}$ and $\sim$16% at the physical κ over the $N_{\mathrm{cav}} = 6$ basis; intermediate truncations at $N_{\mathrm{cav}} = 10$ ($\sim 12\%$) and 12 ($\sim 7\%$) confirm the trend is truncation-dependent (Table S15); the truncation-extension basis $N_{\mathrm{cav}} \in \{16, 20, 24\}$ is partial-or-inconclusive (two of six truncation comparisons meet the 5% tolerance: $N_{\mathrm{cav}} = 16$ vs 24 at $\kappa/\omega_c = 1 \times 10^{-2}$ and $N_{\mathrm{cav}} = 20$ vs 24 at the physical κ) and gives a further reduced retention of $\sim 3\%$ at the physical κ (Section S15); its boundary peak is in fact a still-rising artifact, not a converged local maximum (Section S17). Resource-normalized benchmarks at matched intracavity photon budget are provided in Section S13, and a comparison with adaptive coherent-state protocols is provided in Section S14.

The operational message is therefore conditional: in the sampled single-qubit sweep, the first point at or above 80% peak-QFI retention is $\kappa/2\pi = 0.6\,\mathrm{MHz}$, with 80.6% retention; the low-loss rows are not strictly monotonic, so no continuous threshold is inferred. This sampled low-linewidth point is compatible with some 3D microwave cavities but not with

the cited CPW linewidth. We frame the loss barrier as the central physical result, report the pure-state QFI gains as upper bounds within their stated scans, and identify the loss-scaling crossover as the metric that future work should target. This accounting is not specific to circuit QED: any protocol that proposes to extract information from bound, non-emissive correlations by converting them into real excitations — photonic, phononic, or magnonic — faces the same test between idealized information gain and the loss channel opened by that conversion.

II. METHODS

Figure 1 shows the schematic circuit realization: a superconducting CPW resonator coupled to a flux qubit via a SQUID-mediated tunable coupler, whose time-modulated coupling $g(t)$ implements both the static ($g_d = 0$) and driven ($g_d \neq 0$) protocols analyzed below, at the operating parameters listed in Table II.




FIG. 1. Schematic of the experimental setup. A superconducting CPW resonator coupled to a flux qubit via a SQUID-mediated tunable coupler [8, 10, 12, 13]. The time-modulated coupling $g(t) = g_0 + g_d \cos(\omega_d t)$ enables DCE amplification.

The Hamiltonian for the quantum Rabi model and the Dicke model, the QFI formulas, and the Non-Markovian TWA framework [28] are provided in the Section S1. We set $\hbar = 1$ throughout. Because the interaction is time dependent in the DCE protocol, the effective control convention is part of the model specification: strongly nonadiabatic time-dependent USC interactions can yield gauge-dependent predictions if the control Hamiltonian is not transformed consistently [29]. We therefore interpret the following results within the stated

effective coupling modulation and do not claim gauge-independent device predictions. A related but distinct SI analysis (Section S20) verifies that our QFI predictions are unchanged under a controlled finite-dimensional similarity transformation of the Hamiltonian, state, control interaction, and observables; this establishes internal representation consistency within the truncated Hilbert space but does not resolve the physical gauge ambiguity identified by [29], which would require independently specified laboratory control fields in each gauge. For the static Rabi ground state, an eigenstate family, the QFI with respect to the coupling is the gap-weighted sum $F_Q = 4\sum_{k\neq 0} |\langle\Psi_k|\hat{\sigma}_x(\hat{a}+\hat{a}^\dagger)|\Psi_G\rangle|^2/(E_k - E_0)^2$ (Section S2), normalized to the coherent-state baseline $F_Q^{\mathrm{coh}} = 1$; the naive variance form $F_Q = 4\,\mathrm{Var}(\hat{\sigma}_x(\hat{a}+\hat{a}^\dagger))$ holds only for unitary-encoding families and would overestimate the static QFI by 3.4× at the peak (Section S2 S2.2). The variance form weights all excitations equally, while the gap-weighted form suppresses high-energy contributions through the $1/(E_k - E_0)^2$ denominator. For the driven DCE protocol the state is not stationary, so we use the equivalent fidelity-based QFI $F_Q \approx 8\,[1 - |\langle\Psi_\eta(t)|\Psi_{\eta+\delta}(t)\rangle|]/\delta^2$ (Section S2); all DCE QFI values quoted in this work are this fidelity-based QFI. To control the approximation used for the Non-Markovian TWA dynamics, we replace the Floquet-Magnus expansion with a Duhamel formulation [30], whose stated error estimate grows linearly in time under its assumptions. We restrict dynamically evaluated metrics to the declared Lyapunov window $t < \tau_L = 1/\lambda_{\max}$; this limits, rather than eliminates, the effect of trajectory separation. Within this window the TWA is used as an approximation for the CRT-containing USC dynamics and is cross-checked against exact calculations where available. However, its semiclassical approximation begins to break down for $\eta > 0.150$ due to the accumulation of quantum fluctuations in the Wigner trajectories. Consequently, for static observables in the deep strong coupling (DSC) regime ($\eta > 0.150$), we employ Exact Diagonalization (ED) to ensure rigorous evaluation. Full convergence analysis and bounds on the TWA validity are given in the Section S3.

A. Static enhancement from virtual dressing

Table I shows the static Rabi ground-state QFI as a function of η. The QFI remains close to unity for $\eta \ll 0.1$, then increases monotonically, reaching 5.75× at $\eta = 1.0$ (onset of DSC) and a sampled maximum of 6.12× at $\eta = 1.14$. Beyond this, the QFI decreases

slowly as the ground state enters the deep strong coupling regime.

This enhancement is purely a virtual effect: the photon number $n_{\text{virt}} = \langle a^\dagger a \rangle$ remains modest (0.69 at $\eta = 1.0$), and no real photons are created. The virtual squeezing parameter $\xi = \frac{1}{2}\ln(1+2\eta^2)$ captures the dressing strength, and the QFI scales as $F_Q \propto e^{4\xi}$ as predicted by Hotter, Miranowicz, and Gietka [24].

TABLE I. Rabi ground-state QFI as a function of normalized coupling η.

η	n_{virt}	QFI	Baseline-relative QFI
0.10	0.0025	1.03	1.03×
0.80	0.3282	4.11	4.11×
1.00	0.6814	5.75	5.75×
1.14	1.0339	6.12	6.12× (sampled max)
1.30	1.5084	5.67	5.67×

B. Dynamical Casimir amplification

When we modulate the coupling near the DCE resonance, parametric amplification populates the cavity with photons drawn from the vacuum [22, 23, 31, 32]. Unlike the static case, these photons are real and extractable. Table II shows the DCE-enhanced QFI for a range of η and modulation amplitudes g_d.

III. QUANTUM FISHER INFORMATION SCALING AND BOUNDS

As shown in Fig. 2, the static Rabi ground-state QFI exceeds both the coherent baseline and the stated squeezed-state reference e^{2r} for $\eta > 0.3$. This is a comparison of idealized state families, not a matched-pump or open-system sensing benchmark. The QFI grows from the small-coupling asymptote $F_Q - 1 \approx 3\eta^2$ (effective coefficient 3.0 as $\eta \to 0$, rising to ≈ 3.8 at $\eta = 0.5$; Section S2 S2.2) to $F_Q \approx 6.1$ in the DSC regime ($\eta \approx 1.1$). Beyond the sampled maximum at $\eta = 1.14$, the QFI decreases as the ground state asymptotes to the degenerate DSC limit.

TABLE II. DCE-enhanced QFI at the two-dimensional fixed-detuning scan maximum (single qubit, $N = 1$). The peak QFI is a pure-state Cramér-Rao bound within the stated scan; it is not a pump-power-normalized experimental gain.

Quantity	**Value**
Peak QFI (scan maximum)	$\sim 1.7 \times 10^5\times$
Last-window mean (scan)	$\sim 1.3 \times 10^5\times$
Full-window mean (scan)	$\sim 4.7 \times 10^4\times$
Peak photon number n_{peak}	9.3

Operating point: $\eta = 0.150$, $g_d/g_0 = 0.119\,23$, $\omega_q/\omega_c = 1.027$, $\omega_d/\omega_c = 2.077$.

Exact unrounded scan maximum: $170\,903\times$.




FIG. 2. Quantum Fisher Information scaling for the static Rabi ground state. The QFI increases monotonically with η, reaching $6.12\times$ the coherent baseline at the sampled maximum $\eta = 1.14$ (exact value $6.1160\times$). The squeezed-state baseline e^{2r} (where $r = 0.5\sinh^{-1}\eta$) lies below the computed Rabi QFI for $\eta > 0.3$; this comparison is conditional on the stated baseline and does not constitute a resource-normalized experimental advantage.

The model-dependent operating screens are shown in Fig. 3. In the adopted phenomenological thermal model, QFI retention decreases as the thermal occupancy $n_{th} = (e^{\hbar\omega_c/k_BT} - 1)^{-1}$ grows; the displayed temperature scale is conditional on that model. The flux-noise value $5\times10^{-7}\,\Phi_0/\sqrt{\text{Hz}}$ is an adopted screening input, not an independently validated threshold, because no time-domain flux-noise simulation is included in the canonical data artifacts. In this idealized comparison, cavity extraction has little direct effect on the static virtual-state calculation, whereas it affects the DCE protocol where real photons are present [33–35].




FIG. 3. Model-dependent operating screens. (a) Baseline-relative QFI retention in (η, T) space under the stated thermal model. (b) The corresponding (η, κ) screen; the static result is less sensitive to cavity extraction in this idealized model because the dressed excitations are virtual. These panels are not device-level robustness certifications.

IV. DCE-DRIVEN METROLOGICAL ENHANCEMENT




FIG. 4. DCE-enhanced metrology. (a) Static Rabi QFI vs coupling strength η, showing the USC threshold ($\eta = 0.1$), DSC onset ($\eta = 1.0$), and sampled optimum ($\eta = 1.14$, QFI=6.12). The symlog scale reveals the monotonic increase from 1.0× at $\eta = 0.01$ to the peak. (b) Noise robustness: the fixed-detuning DCE scan (peak $\sim 1.7 \times 10^5\times$ at $\eta = 0.15$, $g_d/g_0 = 0.119\,23$, $\omega_q/\omega_c = 1.027$, $\omega_d/\omega_c = 2.077$) vs extraction loss γ. The panel shows the adopted phenomenological loss screen; it is not an open-system DCE simulation or a device-level validation.

The DCE enhancement mechanism is shown in Fig. 4. The parametric drive at the near-resonant modulation couples the vacuum to the first excited manifold of the Rabi




FIG. 5. Two-dimensional fixed-detuning DCE scan. (a) Color map of DCE-enhanced QFI in the $(\eta, g_d/g_0)$ plane at $\omega_q/\omega_c = 1.027$ and $\omega_d/\omega_c = 2.077$. The maximum $\sim 1.7 \times 10^5\times$ (exact value $170\,903\times$) occurs at $\eta = 0.150$, $g_d/g_0 = 0.119\,23$. (b) Line cuts at fixed g_d/g_0, showing the resonance structure driving the scan maximum.

model, creating a resonant amplification channel; this is a specific instance of the Floquet modulation of the Rabi coupling recently studied in the USC regime [36]. Unlike the static protocol, which is limited by the ground-state curvature, the DCE protocol accesses higher-lying states with larger parameter sensitivity.

Figure 5 maps the two-dimensional parameter space $(\eta, g_d/g_0)$ at fixed normalized frequencies $\omega_q/\omega_c = 1.027$ and $\omega_d/\omega_c = 2.077$. The scan maximum lies at a balance in which η is approximately 0.15 and g_d/g_0 is approximately $0.119\,23$. The peak QFI of $\sim 1.7 \times 10^5\times$ (exact value $170\,903\times$) is a ratio of idealized pure-state QFI values from the fixed-detuning scan; relative to the separately evaluated static Rabi value at the same coupling ($1.07\times$ at $\eta = 0.15$), the driven-to-static ratio is $\sim 1.6 \times 10^5\times$. This is not a pump-power-normalized experimental gain.

We note that this peak QFI is computed for a pure state undergoing unitary evolution, representing the ultimate coherent Cramér-Rao bound. In a realistic driven-dissipative setup, the generated real photons ($n_{\text{peak}} \approx 9.3$) will leak out of the cavity. To quantify this, we performed Lindblad master-equation simulations of the mixed-state QFI under single-photon cavity loss at the published operating point (Section S11). The peak QFI retains $\sim 80.6\%$ of the pure-state value at the first sampled row meeting the 80% target, $\kappa/\omega_c = 1 \times 10^{-4}$ ($\kappa/2\pi = 0.6\,\text{MHz}$). The lower-loss rows are not strictly monotonic (78.3%

at 10^{-5} and 78.8% at 5×10^{-5}), so no interpolated threshold is claimed. Retention degrades to $\sim 48\%$ at $\kappa/\omega_c = 1 \times 10^{-3}$ ($\kappa/2\pi \approx 6\,\mathrm{MHz}$) and $\sim 1\%$ at the simulated physical point $\kappa/\omega_c \approx 4.1 \times 10^{-2}$ ($\kappa/2\pi \approx 246\,\mathrm{MHz}$; the cited CPW value is approximately 248 MHz). The degradation exceeds the simple exponential envelope $\exp(-\kappa t)$ because the Lindblad dynamics modify the entire state evolution, not just the peak amplitude. To approach the theoretical coherent limits reported here, measurements must be executed on timescales much faster than the cavity decay rate (κ^{-1}), placing a premium on high-coherence platforms with $\kappa/2\pi \lesssim 1\,\mathrm{MHz}$. Figure 6 shows the corresponding pure-state (lossless) time trace at the rounded operating point.




FIG. 6. Rounded-point DCE time trace ($\eta = 0.150$, $g_d/g_0 = 0.119$, $\omega_q/\omega_c = 1.027$, $\omega_d/\omega_c = 2.077$). The independent trace gives a peak QFI of approximately 170 492× and a last-window mean of approximately 123 638×. (b) The photon population follows the same cycle. These values are distinct from the fixed-detuning scan maximum listed in Table II.

V. COLLECTIVE ENHANCEMENT: THE DICKE MODEL

The single-qubit Rabi model is fundamentally limited by qubit saturation: the two-level structure caps the maximum QFI at $\sim 6\times$. To access higher metrological gain, we extend to the collective Dicke model with N qubits coupled to a single cavity mode [37]:

$$\hat{H}_{\mathrm{Dicke}} = \omega_c \hat{a}^\dagger \hat{a} + \omega_q \hat{J}_z + \frac{g}{\sqrt{N}} \hat{J}_x (\hat{a} + \hat{a}^\dagger), \tag{1}$$




FIG. 7. Dicke-model collective enhancement in the finite-size calculation. (a) Static QFI versus N at $\eta = 1.15$ ($\omega_q/\omega_c = 1.005$), from the extended exact-diagonalization grid: growth is super-linear over $N \leq 18$ (fit $\alpha = 2.216 \pm 0.034$, $R^2 = 0.9988$), slows markedly beyond $N \approx 21$, and continues up to $N = 64$ ($\approx 350\times$; Section S28) with no tested single-plateau form describing the data, which does not preclude saturation beyond the window. (b) Static QFI versus η for $N = 4, 8, 16, 32$ ($\omega_q/\omega_c = 1.005$), with the thermodynamic critical coupling marked at $\eta_c = 0.5$. The sampled maximum shifts with N (≈ 1.40 at $N = 4$, ≈ 1.15 at $N = 16$, ≈ 1.10 at $N = 32$); squares mark the fixed $\eta = 1.15$ operating point of the finite-size grid. The exponent characterizes the $N \leq 18$ super-linear regime and does not extrapolate to the thermodynamic limit.

where $\hat{J}_{x,z}$ are collective spin operators for N qubits (see Section S1 for the full numerical implementation). The $1/\sqrt{N}$ normalization ensures a well-defined thermodynamic limit and gives rise to a superradiant phase transition at $\eta_c = \sqrt{\omega_q/\omega_c}/2 = 0.5$ for $\omega_q = \omega_c$ [37].

Figure 7 shows the static QFI of the Dicke model as a function of N and η (Table III tabulates the $\eta = 1.15$ values). In the superradiant regime ($\eta \approx 1.15$), the QFI exhibits collective enhancement. Fitted on the $N \leq 18$ data at fixed $\eta = 1.15$ and $\omega_q/\omega_c = 1.005$ (where the data are monotonic and not visibly saturating), the power law $F_Q \propto N^\alpha$ gives $\alpha = 2.216 \pm 0.034$ ($R^2 = 0.9988$, 95% CI: $[2.150, 2.282]$); the super-linear scaling exceeds the linear expectation for independent qubits. Growth slows strongly at larger N: $F_Q(N = 27) = 229\times$ and $F_Q(N = 33) = 238\times$ (only $\sim 4\%$ increase over a 22% increase in N), and the local growth exponent falls below unity beyond $N \approx 21$. The growth nevertheless continues over the tested window rather than saturating into a tested form: an extended grid (method in Section S28) up to $N = 64$ gives $F_Q \approx 350\times$, which single-plateau forms

do not describe. Saturation beyond the window is not excluded. The reported exponent therefore characterizes the $N \leq 18$ super-linear regime and does not extrapolate to the thermodynamic limit.

At $\eta = 1.15$, the system is in the superradiant regime of the finite Dicke calculation; the finite-size spectrum retains the parity structure associated with the thermodynamic transition, rather than realizing a thermodynamic phase transition literally. At finite temperature, thermal mixing of these macroscopically distinct vacua would reduce the QFI. A symmetry-breaking preparation or readout protocol would therefore be needed to select one minimum; the present pure-state calculation assumes that selection and does not model the bias field or its experimental cost.

TABLE III. Dicke-model static QFI in the superradiant regime of the finite-size calculation.

N	η	QFI
4	1.15	6.4×
8	1.15	28.4×
16	1.15	134.2×
32	1.15	229×

All entries at $\eta = 1.15$. The sampled static-QFI maximum shifts with N (≈ 1.40 at $N = 4$, ≈ 1.15 at $N = 16$, ≈ 1.10 at $N = 32$), so $\eta = 1.15$ is a fixed operating point rather than the optimum for every N; the super-linear N^{α} scaling with $\alpha \approx 2.22$ is measured on $N \leq 18$; growth slows strongly beyond $N \approx 21$ and continues, without a plateau, up to $N = 64$ (Section S28).

A. Dicke + DCE: Beyond $10^4\times$

Adding a Floquet DCE drive to the Dicke model further amplifies the QFI. Table IV shows the time-averaged and peak QFI for $N = 32$ qubits with DCE modulation at $\omega_d = \omega_c + \omega_q$.

The modeled late-window average QFI of the Dicke+DCE protocol reaches 167 271× ($\sim 1.7 \times 10^5\times$, a 730× enhancement over the static Dicke QFI of 229×) at $g_d/g_0 = 0.15$ with $\omega_q/\omega_c = 1.0$ and $\omega_d/\omega_c = 2.0$. A boundary value of 251 557× ($\sim 2.5 \times 10^5\times$, a 1098× enhancement) is reached at the last stored time point (period 40). *The boundary peak is not*

TABLE IV. Dicke + DCE enhancement ($N = 32$, $\eta = 1.15$, $\omega_q/\omega_c = 1.0$, $\omega_d/\omega_c = 2.0$). The late-window average value is the operationally meaningful figure; the peak at the simulation boundary ($\sim 2.5 \times 10^5\times$ at period 40) is a still-rising artifact, not a converged local maximum (Section S17).

g_d/g_0	Late-window avg Enhancement	
0.15	$\sim 1.7 \times 10^5\times$	730×

a converged local maximum. Convergence tests in Section S17 show the Dicke+DCE QFI grows monotonically with simulation window: at period 60 the peak is 7.0× higher than at period 20, with no sign of saturation. The published $2.5 \times 10^5\times$ is therefore an arbitrary boundary value, not a physical number. We report both ratios but lead with the late-window average enhancement as the operationally meaningful figure. Relative to the static Dicke QFI (229×), the peak-to-static ratio at period 40 is 1098× and the late-window average-to-static ratio is 730×. The values reported here correspond to a 2D optimum at fixed detunings ($\omega_q/\omega_c = 1.0$, $\omega_d/\omega_c = 2.0$); a full 4D optimization over (g_d/g_0, ω_q/ω_c, ω_d/ω_c, η) was not performed, so no further improvement is inferred. The collective mechanism differs from the single-qubit DCE: the drive amplifies the cooperative cavity response of all N qubits and produces real photons whose information content must be assessed together with drive power, loss, and readout.

Figure 8 shows the time-dependent QFI dynamics for the Dicke+DCE protocol. Unlike the single-qubit case where QFI oscillates with a $\sim$ 34-period cycle, the collective system reaches a late-window average after $\sim$ 25 drive periods. The late-window average QFI is 167 271× relative to the stated coherent baseline. The last stored time point at period 40 gives 251 557×, but this is a still-rising boundary value, not a converged local maximum (Section S17); we therefore report both the late-window average value (730× enhancement over the static Dicke QFI of 229×) and the boundary peak (1098×) but the former is the operationally meaningful figure. These are pure-state model values; their open-system interpretation requires an explicit loss, drive-power, and readout analysis.




FIG. 8. Dicke+DCE time dynamics at $N = 32$, $\eta = 1.15$, $g_d/g_0 = 0.15$. (a) QFI builds up over ~ 25 drive periods and continues rising through the end of the simulation window, reaching $\sim 2.5 \times 10^5\times$ (exact value 251 557×) at the last stored point (period 40); the late-window average is $\sim 1.7 \times 10^5\times$ (exact value 167 271×) — a 730× enhancement over the static Dicke QFI (229×). *The peak value is not a converged local maximum*; Section S17 shows the peak continues to grow with the simulation window (7× higher at period 60 than at period 20). (b) The intracavity photon population grows from the bare vacuum to $n_{\text{peak}} \approx 10.9$ and an average of $n_{\text{avg}} \approx 9.3$ over the simulation window, consistent with collective parametric amplification and real-photon production. The smoother saturation profile compared to the single-qubit case suppresses relaxation oscillations.

B. Robustness of collective enhancement

Figure 9 reports a model-dependent robustness screen against thermal dephasing and cavity loss. The assumed $1/\sqrt{N}$ collective-noise suppression gives the displayed retention within this phenomenological model, but it does not include all qubit-qubit interactions, inhomogeneous couplings, drive noise, or a full mixed-state QFI calculation. These curves therefore delimit a simulation assumption rather than establish experimental practicality.

VI. OPERATING POINTS WITHIN THE NUMERICAL SCANS

The principal sampled operating points across the four protocols are summarized in Table V. The table records maxima or representative points within the declared scans; it is




FIG. 9. Model-dependent robustness screen for the Dicke calculation. (a) The plotted QFI-retention curves compare the stated thermal-dephasing model for collective and single-qubit readout. (b) The cavity-loss scan reports the phenomenological decay model used here, with a 50% degradation scale near $\kappa/2\pi \approx 248\,\mathrm{MHz}$. The full Lindblad simulation in Section S11 shows the actual degradation at this κ is $\sim 99\%$ (retaining $\sim 1\%$ of the pure-state QFI), because the dissipation modifies the entire state evolution rather than merely attenuating the peak. These curves are not an open-system validation or a device-level guarantee.

not a global optimization or device-level operating prescription. Full parameter sweeps and sensitivity analyses are provided in the Section S9.

TABLE V. Principal sampled operating points. Values labeled as maxima are maxima within the stated numerical scans, not global or experimentally optimized parameters. The Dicke+DCE row reports the late-window average value as the operationally meaningful figure; the boundary peak ($2.5 \times 10^5\times$) is an arbitrary boundary value, not a converged local maximum (Section S17), and is not reproduced here.

Protocol	N	η	g_d/g_0	Baseline ratio	Cavity-loss sensitivity
Static (sampled maximum)	1	1.14	0.0	6.12×	Reduced in idealized model
DCE (single-qubit, scan max)	1	0.150	0.119 23	$\sim 1.7 \times 10^5\times$	Partial
Dicke static	32	1.15	0.0	229×	Partial
Dicke + DCE (late-window average)	32	1.15	0.15	$\sim 1.7 \times 10^5\times$	Partial

VII. DISCUSSION

a. From bound dressing to accessible radiation. The central question — how the conversion of non-emissive virtual dressing into real photons changes the loss budget, i.e. whether the resulting QFI gains survive cavity loss — separates two physically different resources. In the static calculation, n_{virt} characterizes correlations within an undriven dressed ground state; it is not an emitted flux or a directly measured photon stream. Theory has shown that a specified switching or conversion protocol can release virtual correlations as extracavity radiation, and superconducting-circuit experiments have observed DCE photon production, but neither result supplies the conversion efficiency, output measurement, or resource accounting for the present QFI protocol [19–21, 23]. In our model, the DCE drive is therefore the operation that makes the information-bearing field extractable, while cavity loss and readout determine how much of that information remains accessible. The comparison is operational rather than universal: it contrasts a state-sensitive, non-emissive idealization with a driven output-field protocol under the specified finite-dimensional models.

b. The loss barrier is the central operational result. The Lindblad simulations in Section S11 and Section S15 show that the DCE QFI collapses under cavity loss well before reaching the physical operating point of the USC platforms that motivate this study. At the physical cavity linewidth of the cited CPW experiments ($\kappa/2\pi \approx 248\,\mathrm{MHz}$), the single-qubit DCE QFI retains $< 1\%$ of its pure-state value. The validated truncated-basis Dicke+DCE propagation ($N_{\mathrm{cav}} = 6$, $T_{\max} = 10$ periods, pure-state reference $2962\times$, i.e. $85\times$ below the full $N_{\mathrm{cav}} = 28$ calculation) retains $\sim 61\%$ at $\kappa/\omega_c = 1 \times 10^{-2}$ and $\sim 16\%$ at the physical κ; intermediate truncations at $N_{\mathrm{cav}} = 10$ and 12 (newly recomputed, Table S15) give $\sim 12\%$ and $\sim 7\%$ retention at the physical κ, and the truncation extension to $N_{\mathrm{cav}} \in \{16, 20, 24\}$ is not truncation-converged and reports retention of $\sim 3\%$ at the physical κ (4.4% at $N_{\mathrm{cav}} = 16$, 2.7% at $N_{\mathrm{cav}} = 20$, 2.6% at $N_{\mathrm{cav}} = 24$), so the reduced-model values are not truncation-converged (Section S15). The operationally meaningful number is therefore: the $\sim 1.7\times10^5\times$ pure-state QFI is a coherent-Cramér-Rao upper bound that the protocol cannot reach on a CPW platform. The $6.12\times$ static virtual-dressing gain is not a device-level loss claim: it concerns parameter sensitivity of an un-driven dressed ground state, whereas the effect of a concrete conversion/readout channel, qubit decoherence, and readout backaction requires a separate analysis. In particular, the modeled virtual-photon population should not be

interpreted as a directly available output resource without such a channel. Adding qubit $T_1 = 30\,\mu s$ and $T_\phi = 5\,\mu s$ — a deliberately conservative benchmark, chosen as a conservative benchmark rather than a record-device parameter — retains 78.6% and 79.1%, respectively, of the pure-state QFI when cavity loss is absent; including both channels retains 79.1%. At the combined physical operating point ($\kappa/2\pi = 248\,\mathrm{MHz}$ plus qubit decoherence), the QFI retains 0.959%, essentially identical to cavity loss alone, so cavity loss remains the dominant channel. Because this benchmark is conservative rather than representative of the best demonstrated coherence, the true qubit-decoherence contribution on a state-of-the-art device would be smaller still, making the cavity-loss-dominated conclusion, if anything, more robust than this estimate suggests. We therefore frame the loss scaling, not the pure-state QFI, as the result the community should anchor on. This is a single-platform Lindblad case study at one representative linewidth, not a universal noisy-metrology bound (cf. the correlated-noise bounds framework [38]); nor is it a critical-metrology claim, which combines quench-beyond-critical-point enhancement with a different scaling program [39].

c. Cavity-channel model comparison. The retention numbers above rely on treating cavity decay as Markovian (the $\sqrt{\kappa}\,\hat{a}$ Lindblad collapse operator). A dedicated cavity-mode HEOM calculation (Section S27) that couples the cavity mode itself to a structured Drude–Lorentz bath, rather than the qubit as in Sections S22 and S25, confirms excellent Markovian agreement at low linewidth ($\kappa/\omega_c = 10^{-4}$: mean fidelity errors of approximately 9.2×10^{-5}–3.7×10^{-4}) but finds mean fidelity discrepancies of approximately 4.8%–24% at the physical linewidth $\kappa/\omega_c = 4.1 \times 10^{-2}$, depending on the assumed bath cutoff and time window. This is a tested model-comparison range, not a propagated statistical uncertainty interval and not a validation of the full Dicke+DCE QFI calculation; the headline retention values should therefore be interpreted as first-order Markovian estimates whose sensitivity to cavity-bath memory remains model-dependent.

d. Loss-dependent interrogation window. The additional mixed-state interrogation analysis provides a qualified answer to the information–entropy part of the central question. At the fixed single-qubit DCE operating point, the fidelity-based QFI and the declared information-rate objective $R_Q(t) = F_Q(t)/t$ remain boundary-limited at 40 drive periods for $\kappa/\omega_c \leq 1 \times 10^{-3}$. At larger loss, the information-rate maximum moves earlier, from 18.08 periods at $\kappa/\omega_c = 0.005$ to 6.96 periods at $\kappa/\omega_c = 0.041$, while the QFI at those rate maxima falls from 10 449 to 1242 (Section S18). The accompanying von Neumann entropies are

nonzero, but the stored entropy derivative is only a finite-difference mixedness diagnostic, not a thermodynamic entropy-production rate. Thus the simulation supports a model-specific loss-dependent information-rate crossover, not a universal or thermodynamically derived τ_{opt}.

e. Resource-normalized comparison. At matched intracavity photon budget $n = 9.01$ (the DCE peak), the pure-state DCE QFI is 4742× the coherent-state shot-noise reference $F_Q = 4n$ and 249× the stated squeezed-state reference $F_Q = 4n(1+2n)$ (Section S13). This is a model comparison at matched intracavity population, not a fair device benchmark. Pump power, bandwidth, state-preparation cost, loss, readout, and measurement time are not matched. A fully resource-normalized comparison would additionally require matching the external pump power needed to reach that intracavity population, the total interrogation bandwidth, the state-preparation and readout duration, and the loss accrued over that duration for each competing protocol. The pump-proxy scaling reported in Section S13 (g_d^2, the time-averaged modulation energy) bounds only the first of these costs and is not sufficient on its own to establish such a comparison. The loss collapse above prevents interpreting the ratio as an operational advantage. The adaptive-protocol comparison is retained in the SI only as a formal reference with different estimands and is not used as a device-performance claim.

Our calculations separate three idealized contributions to the model QFI:

f. Static virtual dressing ($\lesssim 6.1\ \times$). The ground state of the Rabi Hamiltonian is dressed by CRTs, producing a virtual squeezing parameter ξ that grows with η. The gap-weighted ground-state QFI defined in the Supplemental Material reaches 6.12× at the sampled maximum $\eta = 1.14$, while the variance expression is not the correct QFI for this eigenstate family. The state contains virtual photons ($n_{\mathrm{virt}} \lesssim 1$ in the reported range), so direct cavity extraction loss is reduced in the idealized static model; this does not establish immunity to qubit decoherence, dispersive-readout backaction, or thermal noise.

g. DCE parametric amplification ($\lesssim 1.7 \times 10^5 \times$ single-qubit, $\lesssim 1.7 \times 10^5 \times$ collective late-window average). A Floquet modulation at the near-DCE modulation condition $\omega_d \approx \omega_c + \omega_q$ drives parametric amplification of the vacuum state. For a single qubit, this creates real photons ($n_{\mathrm{avg}} > 1$) that carry enhanced parameter information, boosting the sampled peak QFI to $\sim 1.7 \times 10^5\times$ at $\eta = 0.150$, $g_d/g_0 = 0.119\,23$. For $N = 32$ qubits in the Dicke model, the collective enhancement in the superradiant regime ($\eta = 1.15$) combined with

DCE drive yields a late-window average QFI of $\sim 1.7 \times 10^5\times$ (730× enhancement over the static 229×). The last-window value at the end of the simulation window is $\sim 2.5 \times 10^5\times$ (1098× enhancement), but this is a still-rising boundary, not a converged value (Section S17). The DCE protocol is loss-sensitive; the quoted factors are baseline-relative pure-state model values and do not by themselves establish suitability for a device.

A. Comparison with Hotter, Miranowicz, and Gietka (2025)

Hotter, Miranowicz, and Gietka [24] predicted quadratic QFI scaling $F_Q \propto e^{4\xi}$ in the Dicke model using virtual-state observables. Our calculations are consistent with that scaling over the stated finite-size numerical range, while extending the comparison to the Rabi model and to a driven DCE protocol:

1. **Quantitative validation**: At $\eta = 1.15$, $N = 32$, we find $F_Q = 229\times$ in the finite-size superradiant regime. The effective squeezing parameter $\xi_{\text{eff}} = \frac{1}{4}\ln(F_Q) = 1.36$ is numerically consistent with the predicted $e^{4\xi}$ trend over this finite-size range.

2. **DCE amplification**: Adding a Floquet drive at the DCE resonance provides a 730× late-window average enhancement (static 229× → DCE 167 271×); the last-window boundary value at period 40 is 251 557× (1098× enhancement) but is a still-rising artifact (Section S17), not a converged local maximum. This mechanism was not considered in Ref. [24].

3. **Collective scaling**: The QFI scales as $\propto N^{2.216\pm0.034}$ (OLS restricted to $N \leq 18$ at $\eta = 1.15$, $R^2 = 0.9988$), super-linear, exceeding the linear scaling expected from independent qubits. Growth slows markedly beyond $N \approx 21$ and continues up to $N = 64$ with no tested single-plateau form fitting the window (Section S28), so this power law characterizes the small-N super-linear regime and does not extrapolate to the thermodynamic limit.

4. **Floquet context**: The DCE modulation used here is closely related to Floquet engineering of the Rabi model in the USC regime [36]; our work shows that a specific Floquet protocol—parametric amplification at the DCE resonance—converts virtual dressing into a metrological resource.

B. Experimental feasibility

Experimental feasibility details, including platform-specific implementation schematics and the staged experimental roadmap, are provided in the Section S10.

C. Limitations of the present analysis

Our approach has several limitations. First, the Dicke model assumes identical qubit-cavity coupling for all N qubits ($g_i = g$), which requires uniform SQUID-mediated coupling in experiment. Inhomogeneous coupling would reduce the collective enhancement factor. Second, we neglect qubit-qubit interactions ($\hat{\sigma}_+^{(i)}\hat{\sigma}_-^{(j)}$), which may arise from virtual photon exchange and could modify the superradiant phase transition. Third, the time-dependent DCE simulations assume perfect Floquet modulation without amplitude noise or pulse shaping. Fourth, the TWA validity bounds enforce $\eta \leq 0.150$ for reliable long-time integration; beyond this boundary, exact quantum dynamics (or Master Equation approaches) are required. Fifth, the quoted DCE QFI values are pure-state upper bounds; open-system effects such as cavity loss, qubit relaxation (T_1), and dephasing (T_2) reduce the achievable information. Sixth, the multilevel-emitter screen (Section S24) shows that at the canonical and strong drive amplitudes used to obtain the headline DCE-QFI enhancements, all driven configurations with $d_e \geq 3$ exceed the 1% leakage threshold (best case: fluxonium-like at 2.99%), so the two-level approximation used throughout is a model choice, not a validated assumption at that operating point. A staged drive-amplitude sweep (Section S26) shows that platform-specific operating windows satisfying the 1% criterion do exist at reduced drive (fluxonium-like up to $g_d = 0.06$, flux-qubit-like up to $g_d = 0.04$, transmon-like up to $g_d = 0.02$, all at the physical loss point). The corresponding QFI enhancement at those points (54–86×) is orders of magnitude below the canonical $\sim 1.7 \times 10^5\times$ headline value. No tested drive amplitude simultaneously satisfies the leakage criterion and reproduces the headline enhancement; the trade-off is monotonic across all three platforms. In addition, the time-dependent USC description is an effective control model: gauge consistency and the physical implementation of the modulation must be checked before interpreting its output field as a device-level observable [29]. The Lindblad simulations in Section S11 (single-qubit) and Section S15 (Dicke) quantify this degradation under cavity loss, showing $< 1\%$ retention at the physical

operating point $\kappa/\omega_c \approx 4.1 \times 10^{-2}$ for the single-qubit protocol and a reduced-model $\sim 3\,\%$–$16\,\%$ retention range (over $N_{\mathrm{cav}} = 6$–20, with the $N_{\mathrm{cav}} = 16$ and 20 rows sourced from the truncation-extension artifact of status `partial_or_inconclusive`) for the truncated-basis Dicke+DCE protocol; the combined cavity + qubit analysis in Section S16 confirms cavity loss is the dominant channel over the simulation window. The $1/\sqrt{N}$ collective-noise suppression assumed in the phenomenological thermal-dephasing model (Eq. (S12)) does *not* apply to cavity loss in the Lindblad treatment: Table S14 shows the Dicke+DCE QFI is degraded by more than an order of magnitude at physical κ with no detectable collective-noise suppression on the tested window, and the residual retention is truncation-dependent rather than a converged value. The energy-budget consistency check of the Supplemental Material (Section S2 S2.2) explains why these mechanisms are hierarchical rather than independent: the static single-qubit ceiling ($F_Q \lesssim 6.1$) is set by the two-level saturation of the qubit, i.e. by the limited virtual population it can host, and the DCE and collective routes overcome precisely that ceiling—the former by converting virtual dressing into real, extractable photons, the latter by distributing the same dressing over N qubits with a super-linear $N^{2.22}$ cooperative gain on the small-N side.

D. Experimental roadmap

The calculations above show that the Dicke+DCE QFI continues to grow over the tested pure-state windows (still rising at period 60) while its validated reduced-truncation Lindblad propagation retains only $\sim 16\,\%$ at $N_{\mathrm{cav}} = 6$, decreasing through $\sim 12\,\%$ at $N_{\mathrm{cav}} = 10$ and $\sim 7\,\%$ at $N_{\mathrm{cav}} = 12$ to $\sim 2.6\,\%$ at $N_{\mathrm{cav}} = 24$, with intermediate values at $N_{\mathrm{cav}} \in \{16, 20\}$ (artifact status `partial_or_inconclusive`) at the physical $\kappa/\omega_c = 4.1 \times 10^{-2}$ (Section S15). An independent confirmatory run at $N_{\mathrm{cav}} = 20$ reproduces 2.69% retention, consistent with the artifact value. The staged experimental program below is calibrated to these two facts: pure-state gains are uninformative without a matched open-system benchmark, and the loss barrier is the gating constraint.

1. **Stage** 1 ($N = 1$, single qubit, flux-based CPW or 3D cavity): the first milestone is the matched open-system benchmark, not the pure-state QFI. Quantitative gate: measure the cavity-loss-augmented QFI at the published operating point and compare it with the first sampled reference row, 80.6% retention at $\kappa/2\pi = 0.6\,\mathrm{MHz}$. Because

the low-loss sweep is not strictly monotonic, this is a reference point rather than a continuous threshold; the comparison tolerance is 20 % (set as a calibration margin for this program). A 3D cavity at $\omega_c/2\pi = 6\,\mathrm{GHz}$ is a candidate platform for testing the loss scaling; a CPW platform with $\kappa/2\pi = 248\,\mathrm{MHz}$ is outside the modeled 80%-retention regime and is not the platform used for that calibration.

2. **Stage** 2 ($N = 4$ to 8, small array): the second milestone is the collective scaling exponent at the loss-controlled regime. Quantitative gate: measure the Dicke static QFI at the published $\eta = 1.15$ and verify that the $N^{2.22}$ super-linear scaling on $N \leq 18$ holds, with the same $< 20\,\%$ tolerance as Stage 1. At this stage the DCE modulation is not yet engaged; the test is for collective dressing, not amplification. These gates are model-calibration checkpoints, not advantage claims.

3. **Stage** 3 ($N = 16$ to 32, full Dicke+DCE): the third milestone is the simultaneous demonstration of (i) collective dressing, (ii) DCE modulation, and (iii) the loss barrier. Quantitative gate: measured Dicke+DCE QFI at the published operating point must be compared against the loss curve at explicitly matched linewidth, truncation, window, and resource settings; the single-qubit 80.6% row is not a Dicke threshold; the boundary-peak ($2.5 \times 10^5\times$) is not a meaningful target because the Dicke+DCE QFI is still rising at the tested pure-state window boundary. The simultaneous uniform coupling of $N = 32$ qubits at $\eta = 1.15$ and the corresponding DCE modulation fidelity remain open experimental questions; a 3D-cavity-based array is a candidate platform for the required low linewidth, but whether it can also provide the required collective coupling uniformity remains an open experimental question; demonstrated USC experiments on 3D cavities are at the single-qubit level.

Within the literature comparison made here, we did not identify an end-to-end demonstration of all these stages (Section S10); the table in Section S7 records the current state-of-the-art at each parameter. The QFI ceiling that the staged program should target is not the published $\sim 1.7 \times 10^5\times$ — that is a pure-state upper bound that is not, by itself, informative on a lossy platform. The informative target is the late-window average value at the loss-controlled operating point, which the published single-qubit loss analysis (Section S11) samples at 80.6% for $\kappa/2\pi = 0.6\,\mathrm{MHz}$. The nonmonotonic low-loss rows do not support a continuous threshold or a transfer of that reference to the Dicke model.

VIII. CONCLUSION

The cavity-loss barrier, not the idealized QFI values that motivate probing it, is the central result of this work: Lindblad simulations show the DCE QFI collapsing to $< 1\%$ of its pure-state value at the physical CPW cavity linewidth ($\kappa/2\pi \approx 248\,\mathrm{MHz}$), while the validated truncated-basis Dicke+DCE propagation retains only $\sim 16\,\%$ at $N_{\mathrm{cav}} = 6$, decreasing through $\sim 12\,\%$ at $N_{\mathrm{cav}} = 10$ and $\sim 7\,\%$ at $N_{\mathrm{cav}} = 12$ to $\sim 2.6\,\%$ at $N_{\mathrm{cav}} = 24$, with intermediate values at $N_{\mathrm{cav}} \in \{16, 20\}$ (artifact status `partial_or_inconclusive`) at the same κ (Section S15). This Markovian cavity-loss treatment itself carries a 4.8%–24% model-comparison range at the physical linewidth, as confirmed by a dedicated cavity-mode HEOM cross-check (Section S27). We computed three idealized QFI contributions within the stated models to establish how large the erased gains are: static virtual dressing in the single-qubit Rabi model (6.12× relative to the coherent baseline), DCE-driven amplification ($\sim 1.7 \times 10^5\times$ single-qubit sampled peak; $\sim 1.7 \times 10^5\times$ collective late-window average), and finite-size collective enhancement in the Dicke model (229× static at $N = 32$), all pure-state upper bounds erased to the retentions above at the physical κ. The collective Dicke+DCE QFI is monotonically increasing with simulation window and not converged at the published boundary; the headline $2.5 \times 10^5\times$ value is an arbitrary cutoff, not a physical saturation. The late-window average value is the operationally meaningful figure for both the single-qubit DCE and the Dicke+DCE protocols.

The finite-size Dicke calculation shows a superradiant-regime scaling $\propto N^{2.216\pm0.034}$ restricted to $N \leq 18$ ($R^2 = 0.9988$); growth slows markedly at larger N and continues up to $N = 64$ in the extended screen, with no tested single-plateau saturation form fitting the window and none excluded beyond it. The DCE drive further amplifies the modeled pure-state QFI while producing real photons, so the corresponding open-system performance depends on cavity loss, qubit decoherence, drive power, and readout, as already quantified above. The local HEOM comparison supports the bath-model check only within its stored short-time Spin–Boson scope (Section S22); it does not validate the high-QFI DCE traces. Adding conservative transmon qubit dissipation ($T_1 = 30\,\mu\mathrm{s}$, $T_\phi = 5\,\mu\mathrm{s}$, well chosen as a conservative benchmark rather than a record-device parameter) retains 78.6%–79.1% without cavity loss and 0.959% at the physical CPW point when combined with cavity loss; the SI-consistent calculation therefore confirms that cavity decay is the dominant decoherence channel over

the simulation window. The multilevel-emitter screen further shows that the two-level approximation itself, used throughout this analysis, is not validated at the drive amplitudes needed to reach the headline enhancements, though platform-specific safe operating windows exist at substantially reduced drive and reduced QFI enhancement (Sections S24 and S26).

The operational message is conditional: the single-qubit sweep first samples 80.6% peak-QFI retention at $\kappa/2\pi = 0.6\,\mathrm{MHz}$, but its low-loss rows are not strictly monotonic and do not define a continuous threshold. This sampled reference is compatible with some 3D-cavity implementations but not with the cited CPW linewidth. The matched-intracavity-population comparisons in the Supplemental Information are formal, lossless references with unmeasured pump, bandwidth, readout, and time costs; they do not establish a device-level metrological advantage.

DATA AVAILABILITY

The data and code supporting this study are publicly archived at https://github.com/NanaEngo/Floquet-virtual-state-metrology-dce. The archived package includes the manuscript sources, Supplemental Information, figures, deterministic analysis scripts, environment specification, and JSON data artifacts backing the reported tables and claims. Historical internal audits, generated build files, and local scheduler logs are excluded from the shared package. A pump- and readout-resource-normalized device comparison at the loss-controlled operating point remains the open follow-up.

AI USE DISCLOSURE

Artificial-intelligence tools assisted with manuscript editing, package organization, and consistency checks during preparation. All authors remain responsible for the accuracy, originality, interpretation, and final wording of this manuscript.

---

[1] C. M. Caves, Phys. Rev. D **23**, 1693 (1981).

[2] V. Giovannetti, S. Lloyd, and L. Maccone, Science **306**, 1330 (2004).

[3] V. Giovannetti, S. Lloyd, and L. Maccone, Nat. Photon. **5**, 222 (2011).

[4] M. G. A. Paris, Int. J. Quantum Inf. **7**, 125 (2009).

[5] L. Pezzè, A. Smerzi, M. K. Oberthaler, R. Schmied, and P. Treutlein, Rev. Mod. Phys. **90**, 035005 (2018).

[6] S. L. Braunstein and C. M. Caves, Phys. Rev. Lett. **72**, 3439 (1994).

[7] C. Ciuti, G. Bastard, and I. Carusotto, Phys. Rev. B **72**, 115303 (2005).

[8] A. F. Kockum, A. Miranowicz, S. De Liberato, S. Savasta, and F. Nori, Nat. Rev. Phys. **1**, 19 (2019).

[9] A. F. Kockum, *Quantum optics with artificial atoms*, Ph.D. thesis, Chalmers University of Technology (2014).

[10] P. Forn-Díaz, J. J. García-Ripoll, B. Peropadre, J.-L. Orgiazzi, M. A. Yurtalan, R. Belyansky, C. M. Wilson, and A. Lupascu, Phys. Rev. Lett. **118**, 197001 (2017).

[11] P. Forn-Díaz, L. Lamata, E. Rico, J. Kono, and E. Solano, Rev. Mod. Phys. **91**, 025005 (2019).

[12] T. Niemczyk, F. Deppe, H. Huebl, E. P. Menzel, F. Hoi, A. Marx, R. Gross, M. J. Fink, M. J. Schwarz, M. Goppl, G. Romero, E. Solano, and S. Filipp, Nat. Phys. **6**, 772 (2010).

[13] F. Yoshihara, K. Furuya, S. Ashhab, F. Nori, and K. Semba, Nat. Phys. **13**, 44 (2017).

[14] J. Q. You and F. Nori, Nature **474**, 589 (2011).

[15] S. M. Girvin, in *Current Trends in Atomic Physics* (Oxford University Press, 2019).

[16] S. De Liberato, Nat. Commun. **8**, 1465 (2017).

[17] P. Bertet, in *Strong Light-Matter Coupling* (World Scientific, 2014).

[18] N. Didier, J. Bourassa, and A. Blais, Phys. Rev. Lett. **113**, 203601 (2014).

[19] L. Giannelli, E. Paladino, M. Grajcar, G. S. Paraoanu, and G. Falci, Phys. Rev. Research **6**, 013008 (2024).

[20] R. Stassi, A. Ridolfo, O. Di Stefano, M. J. Hartmann, and S. Savasta, Phys. Rev. Lett. **110**, 243601 (2013).

[21] L. Garziano, A. Ridolfo, R. Stassi, O. Di Stefano, and S. Savasta, Phys. Rev. A **88**, 063829 (2013).

[22] P. D. Nation, M. P. Blencowe, and F. Nori, Rev. Mod. Phys. **84**, 1 (2012).

[23] C. M. Wilson, G. Johansson, A. Pourkabirian, M. Simoen, J. R. Johansson, T. Duty, F. Nori, and P. Delsing, Nature **479**, 376 (2011).

[24] C. Hotter, A. Miranowicz, and K. Gietka, Phys. Rev. Lett. **135**, 100802 (2025).

[25] X. Lin and H. Yuan, Communications Physics **8**, 481 (2025).

[26] H. R. Schelb, A. P. Costa, and A. V. Dodonov, Physics Letters A **566**, 131163 (2026).

[27] S.-Y. Bai and J.-H. An, Phys. Rev. Lett. **131**, 050801 (2023).

[28] A. Polkovnikov, Ann. Phys. **325**, 1790 (2010).

[29] A. Stokes and A. Nazir, Phys. Rev. Research **3**, 013116 (2021).

[30] J. Larson, J. Opt. Soc. Am. B **41**, C235 (2024).

[31] V. Macrì, A. Ridolfo, O. Di Stefano, A. F. Kockum, F. Nori, and S. Savasta, Phys. Rev. X **8**, 011031 (2018).

[32] H. Seok, L. F. Buchmann, E. M. Wright, and P. Meystre, Phys. Rev. A **88**, 063850 (2013).

[33] A. A. Clerk, M. H. Devoret, S. M. Girvin, F. Marquardt, and R. J. Schoelkopf, Rev. Mod. Phys. **82**, 1155 (2010).

[34] S. Putz, *Circuit Cavity QED with Macroscopic Solid-State Spin Ensembles*, Springer Theses (Springer, 2017).

[35] S. Putz, Conclusion and outlook, in *Circuit Cavity QED with Macroscopic Solid-State Spin Ensembles*, Springer Theses (Springer, 2017) Chap. 10.

[36] K. Akbari, F. Nori, and S. Hughes, Phys. Rev. Lett. **134**, 063602 (2025).

[37] R. Gilmore, Phys. Lett. A **55**, 459 (1976).

[38] S. Kurdzialek, F. Albarelli, and R. Demkowicz-Dobrzanski, Phys. Rev. Lett. **135**, 130801 (2025).

[39] C. Hotter, H. Ritsch, and K. Gietka, Phys. Rev. Lett. **132**, 060801 (2024).