

From African-Natural-Product Chemical Space to Resistance-Resilience Hypotheses: An Integrated Computational Study of Antimalarial Polypharmacology

Myke Vital Sao Temgoua,^{*,†} Jean-Pierre Tchapet Njafa,[†] Penabei Samafou,[‡]
Wilfred Fon Mbacham,[¶] and Serge Guy Nana Engo[†]

[†]*Department of Physics, Faculty of Science, University of Yaoundé I, P.O. Box 812,
Yaoundé, Cameroon*

[‡]*Department of Medical Imaging and Radiation Sciences, Faculty of Medicine and Health
Sciences, Université de Sherbrooke, Sherbrooke, QC J1H 5N4, Canada*


[¶]*Department of Biochemistry, Faculty of Science, University of Yaoundé I, P.O. Box 812,
Yaoundé, Cameroon*

E-mail: myke-vital.sao@facsciences-uy1.cm

Abstract

Polypharmacology could make antimalarial discovery less vulnerable to single-target resistance, but computational prioritization often conflates multi-target docking, mutation tolerance, and biological activity. Docking is sensitive to receptor and scoring-function choices, so cross-target profiles should be treated as structured hypotheses rather than calibrated measurements.^{1,2} We developed an integrated, evidence-bounded workflow that connects an African-natural-product-inspired chemical-space

funnel to target-anchored docking and a mutation-aware resistance-resilience score (RRS). A hybrid library of 65 856 molecules, generated from 396 African natural products and 454 synthetic antimalarial compounds, yielded 19 913 computationally prioritized synthesizable leads after variational-autoencoder clustering, multi-parameter optimization, and scaffold expansion. A locked 17-member polypharmacology-oriented cohort was then evaluated by AutoDock Vina against PfDHFR, PfCRT, PfClpP, and PfATP4 using target-specific anchors. All 68 candidate-target pairs passed an automated predeclared geometric gate, with scores ranging from $-7.91 \text{ kcal mol}^{-1}$ to $-4.63 \text{ kcal mol}^{-1}$; the raw poses remain subject to independent structural review. Separately, corrected per-target RRS was derived from the distinct declared wild-type and mutant docking panel in `docking_mutants.csv` for PfDHFR (N51I, C59R, S108N, I164L) and PfCRT (K76T, K76A), excluding non-binding wild-type targets from the RRS denominator. The 17-member cohort comprised six A*, five B, five C, and one D RRS profiles, with RRS values spanning 68.2 to 111.7. Cross-metric associations were exploratory: PNS-RRS $\rho = -0.559$, ACSI-RRS $\rho = -0.132$, and RRS-wild-type score $\rho = -0.433$; none survived the prespecified Bonferroni threshold. The study yields computational hypotheses about multi-target and mutation-resilient chemotypes, not measured potency, confirmed target engagement, or demonstrated resistance circumvention.



Keywords: African natural products; antimalarial discovery; polypharmacology; resistance resilience; molecular docking; chemical space; PfDHFR; PfCRT

1 Introduction

Antimalarial resistance is a systems problem.³⁻⁵ A compound that depends on one protein–ligand interaction may lose activity after a single parasite mutation,⁶ whereas a chemotype that engages several resistance-relevant processes could provide a broader mechanistic starting point.^{7,8} This rationale does not imply that every computationally predicted multi-target profile is biologically useful: target breadth, mutation tolerance, physicochemical tractability, and experimental activity are distinct properties that must be measured separately.

African natural products provide a chemically rich but incompletely explored starting point for such studies.^{2,9-11} Their ring systems and stereochemical complexity can complement synthetic antimalarial chemistry, while computational expansion can generate tractable analogues around privileged scaffolds. The challenge is to connect this chemical-space exploration to a target-level analysis without allowing the prioritization score to become a surrogate for activity.

We therefore assembled an integrated workflow with three deliberately separated layers. First, a chemical-space funnel combines African natural products and synthetic antimalarials, expands the library, and prioritizes synthesizable candidates. Second, target-anchored docking evaluates a locked polypharmacology-oriented cohort against four proteins with unequal structural evidence. Third, a mutation-aware RRS summarizes changes in docking estimates for declared computational PfDHFR and PfCRT mutant panels. Polypharmacology is read from the four-target docking profile; RRS is read from target-specific mutant comparisons. The two layers are joined by canonical molecular identity for exploratory interpretation, not by assuming that multi-target docking proves mutation resilience.

The central question was: can this separation produce a coherent computational map from chemical-space novelty to multi-target and mutation-resilience hypotheses? We predeclared three safeguards: candidate sets would remain distinct, non-binding wild-type targets would not inflate RRS denominators, and all activity-like language would be restricted to computational predictions.

2 Materials and Methods

2.1 Chemical-space funnel

The upstream library combined 396 African natural products with 454 synthetic antimalarial compounds. Similarity-based expansion and SELFIES perturbation^{12,13} were followed by structure validation, deduplication, and PAINS filtering,¹⁴ producing 65 856 unique molecules. A SMILES variational autoencoder¹⁵ was used to obtain latent representations. K-means clustering of the selected 64-dimensional representation yielded 484 centroids. Multi-parameter optimization combined docking-derived scores, DiffDock confidence,¹⁶ QED,¹⁷ an ADMET composite, and a Lipinski penalty.¹⁸ The 76 centroids above the optimization threshold mapped to 53 clusters and expanded to 40 481 molecules; 19 913 molecules remained after synthetic-accessibility and MPO filtering.

Novelty was evaluated with Morgan fingerprints¹⁹ (radius 2, 2 048 bits). In a 5 000-molecule sample, 92.6 % had maximum whole-molecule Tanimoto similarity below 0.4 to the African-NP seed set, while scaffold recovery was 69.3 % (70/101 annotated seed scaffolds). The candidate sets were locked before the target-anchored docking analysis.

2.2 Candidate-set identity

Set A comprised the MPO top-20 candidates, Set B comprised the parent-study MD top-20 candidates, and Set C comprised the 17-member P2 polypharmacology-oriented cohort. The integrated analysis used Set C. Canonical SMILES, candidate identifiers, source hashes, and cohort labels were checked row-wise across the target-panel, P2, and integrated manifests. The four parent-study MD systems (201-PfDHFR, 438-PfATP4, the 164-labelled PfClpR cohort, and 214-PfCRT) were not treated as MD validation of Set C.

2.3 Target-anchored docking

The target panel comprised PfDHFR (7F3Y; methotrexate copy A702), PfCRT (6UKJ; Y01 A501 cavity), PfClpP (2F6I; chain-A Ser252/His223/Asp219 catalytic triad), and PfATP4 (9N10; D451 phosphorylation-loop region and DPPR hinge). The PfClpP identity correction is material: 4GM2 is PfClpR and was excluded from PfClpP claims. Y01 is treated as a membrane/cavity proxy, and the PfATP4 region is mechanism-motivated because no small-molecule inhibitor is co-crystallized.

Ligands were standardized with Open Babel²⁰ and converted to PDBQT with Meeko.²¹ AutoDock Vina was run with fixed target-specific boxes following established docking protocols;²² scores were interpreted with the usual caveats attached to empirical scoring functions.²³ The geometric gate required a rank-1 centroid inside the box, at least one atom within 10 Å of the target anchor, and at least 90 % of ligand atoms inside the padded box. The gate is a pose-quality and provenance criterion, not evidence of binding. Vina values are reported in kcal mol⁻¹ and were not converted to experimental free energies.

2.4 Resistance-resilience score

RRS was computed separately for each target and candidate. For mutation m and target t ,

$$\text{RRS}_{i,m,t} = 100 \times \frac{|S_{\text{Vina},i,m,t}|}{|S_{\text{Vina},i,WT,t}|}. \quad (1)$$

Here S_{Vina} denotes the AutoDock Vina scoring-function output; it is not an experimental free energy. RRS eligibility was evaluated from the separate WT/mutant panel in `docking_mutants.csv`, not from the four-target V5 wild-type matrix. Only targets satisfying the declared genuine-binding wild-type criterion ($|S_{\text{Vina},i,WT,t}| \geq 5 \text{ kcal mol}^{-1}$) contributed to a candidate’s mean. Non-binding targets were excluded rather than assigned a zero score or used as a denominator. PfDHFR mutations were N51I, C59R, S108N, and I164L; PfCRT mutations were K76T and K76A. RRS classes were assigned using the pre-

specified P2 rules: A* required the maximum absolute eligible WT score in the mutant panel to be at least 7 kcal mol⁻¹ and all available RRS values to be at least 80 %; A required all available values to be at least 80 % without the A* WT-anchor criterion; B required all values to be at least 70 % but not all to be at least 80 %; C required at least one value to be at least 80 % without meeting A/A* or B; and D was assigned when no available mutant RRS reached 80 %. These classes summarize ratios of docking-score magnitudes, not ratios of binding free energies.

2.5 Polypharmacology, PNS, and ACSI

Polypharmacology was treated as a target-profile hypothesis derived from the four-target Vina matrix, not as confirmed simultaneous engagement and not from RRS. No cross-target arithmetic composite was used because Vina scores are not calibrated across different pocket architectures. PNS was retained as a network-based descriptor and ACSI as a chemical-space descriptor. Their associations with RRS and wild-type Vina score were evaluated with Spearman correlation on the 17-member cohort. Three exploratory correlations were corrected with Bonferroni $\alpha = 0.017$. No association was interpreted as causal, and no non-significant association was interpreted as equivalence.

2.6 Evidence boundary and reproducibility

All raw poses, receptor and ligand files, configurations, candidate manifests, and analysis scripts are archived in the project repository. Automated checks verify file integrity, schema, candidate identity, and row counts. These reproducibility controls do not substitute for structural or experimental validation; the manuscript therefore reports the computational evidence together with its uncertainty and scope.

3 Results

3.1 Chemical-space expansion preserved scaffolds while diversifying molecules

The hybrid library contained 65 856 unique structures. Whole-molecule novelty and scaffold recovery were simultaneously high: 92.6% of the evaluated sample was below the whole-molecule Tanimoto threshold of 0.4, whereas 70 of 101 annotated seed scaffolds were recovered. Scaffold-only similarity exceeded whole-molecule similarity (mean 0.379 versus 0.206), consistent with preservation of ring systems and diversification of peripheral substituents. The funnel produced 19 913 computationally prioritized molecules predicted to be synthesizable; this is a prioritization output, not a synthesis result.

3.2 The locked cohort spans four computational target profiles

Set C contained 17 candidates selected for a polypharmacology-oriented analysis. Target-anchored docking generated 68/68 pairs that passed the automated geometric gate. Score ranges were $-6.35 \text{ kcal mol}^{-1}$ to $-4.86 \text{ kcal mol}^{-1}$ for PfDHFR, $-7.91 \text{ kcal mol}^{-1}$ to $-5.12 \text{ kcal mol}^{-1}$ for PfCRT, $-7.03 \text{ kcal mol}^{-1}$ to $-5.05 \text{ kcal mol}^{-1}$ for PfClpP, and $-7.57 \text{ kcal mol}^{-1}$ to $-4.63 \text{ kcal mol}^{-1}$ for PfATP4. This 68-pair result is raw computational evidence from an automated pose-quality screen; the gate is not independent structural review and does not constitute biological validation. The most favorable within-target estimates included PP-06 in the PfCRT cavity (-7.91) and PP-13 in the PfATP4 machinery region (-7.57). These are target-specific, within-panel observations rather than calibrated potency rankings; no cross-target arithmetic composite was used.

3.3 Per-target RRS separates mutation tolerance from target breadth

Corrected RRS analysis classified the 17-member cohort as six A*, five B, five C, and one D profiles. RRS values ranged from 68.2 to 111.7. Five candidates were classified on PfCRT alone because their PfDHFR WT estimates in the separate mutant docking panel did not meet the genuine-binding threshold; this statement does not refer to the distinct V5 four-target wild-type matrix. This target-specific missingness is scientifically informative: it prevents a near-zero wild-type denominator from producing an artificial resistance-resilience score.

The previously described PP-11 PfDHFR C59R knockout pattern was not retained as a design rule. PP-11’s PfDHFR WT estimate in the separate mutant panel was non-binding under the declared threshold, whereas its PfCRT mutant profile was evaluated on the PfCRT denominator; the four-target V5 matrix is not used to define this RRS eligibility decision. The corrected analysis therefore supports a target-specific rather than a mixed-target interpretation of resilience. The complete per-mutant profile is listed in Table 1 and visualized in Figure 1; cross-metric relationships are displayed in Figure 2. These derived figures and tables are reproducible computational outputs; they should not be interpreted as independent structural validation or experimental evidence.

3.4 Cross-metric associations were exploratory and mostly null

On the 17-member cohort, PNS and RRS showed a negative trend ($\rho = -0.559$), but the nominal result did not survive Bonferroni correction. ACSI and RRS were weakly associated ($\rho = -0.132$), and RRS versus wild-type Vina score showed $\rho = -0.433$; neither was significant under the prespecified threshold. PNS versus wild-type Vina score was positive ($\rho = 0.389$), illustrating that network and docking descriptors need not be interchangeable. These results do not establish a general relationship between natural-product character, target breadth, and mutation tolerance.

Table 1: Per-target resistance-resilience scores (RRS, Equation 1) for the 17-member cohort. Values are percentages of the corresponding wild-type Vina score magnitude; — marks wild-type non-binders ($|S_{\text{Vina},i,WT,t}| < 5 \text{ kcal mol}^{-1}$), excluded from the denominator. RRS_{mean} is the candidate mean over all eligible target-mutant ratios. Classes are the operational categories defined in Table S2, not biological resistance phenotypes.

Candidate	Class	RRS _{PfDHFR} (%)				RRS _{PfCRT} (%)		RRS _{mean} (%)
		N51I	C59R	S108N	I164L	K76T	K76A	
PP-01	A*	86.4	85.5	87.6	83.9	92.5	90.9	87.8
PP-02	A*	—	—	—	—	87.9	94.6	91.3
PP-03	C	68.1	68.3	65.8	69.0	80.0	81.4	72.1
PP-04	C	68.8	66.9	68.8	73.5	105.3	103.6	81.1
PP-05	B	—	—	—	—	77.1	79.3	78.2
PP-06	A*	—	—	—	—	90.6	94.1	92.4
PP-07	B	71.8	71.8	72.4	72.2	84.2	77.6	75.0
PP-08	C	62.1	62.1	67.2	66.3	83.9	83.1	70.8
PP-09	B	70.6	73.0	75.8	76.5	75.8	73.5	74.2
PP-10	B	76.0	76.4	75.7	75.8	89.4	89.6	80.5
PP-11	A*	—	—	—	—	82.7	82.5	82.6
PP-12	C	75.2	66.1	62.9	72.5	70.4	87.2	72.4
PP-13	A*	—	—	—	—	110.2	99.4	104.8
PP-14	D	62.2	65.5	68.0	64.9	78.8	77.7	69.5
PP-15	A*	123.2	112.7	125.9	131.8	86.2	90.1	111.7
PP-16	B	72.9	74.7	73.7	75.9	80.1	80.6	76.3
PP-17	C	59.3	61.2	59.5	58.9	76.8	93.4	68.2





Figure 1: Exploratory per-target RRS mutation profiles for the 17-member source-panel cohort. Values are ratios of Vina-score magnitudes relative to the declared wild-type denominator; blank cells indicate excluded non-binding wild-type targets. The classes are computational operational categories, not biological resistance phenotypes.

Exploratory cross-metric relationships



Associations are descriptive and do not establish biological activity, causality, or resistance protection.

Figure 2: Exploratory relationships between RRS and PNS or ACSI. Points are colored by the operational RRS class. These associations are descriptive source-panel analyses and do not establish causality, biological activity, or resistance protection.

4 Discussion

The principal contribution of this study is an evidence architecture rather than a claim of confirmed multi-target activity. In particular, the workflow makes target-specific evidence classes explicit and prevents an uncalibrated cross-target score average from disguising differences in pocket quality. The chemical-space funnel provides structurally diverse, computationally tractable hypotheses; target-anchored docking provides a standardized pose layer; and per-target RRS provides a mutation-aware comparison that avoids target mixing. Keeping these layers separate makes the resulting hypotheses more falsifiable.

The four-target profile and the RRS profile answer different questions. A candidate can have favorable docking estimates across several targets without being resilient to a specific mutation. Conversely, a candidate can show high RRS on one target while lacking evidence for a second target. Because raw Vina scores are not calibrated across unlike receptors, target breadth is represented by the pattern of target-specific evidence, not by averaging scores across targets. The use of a 17-member locked cohort and canonical-SMILES joins

prevents these distinctions from being hidden by row order or by a single composite score.

The null and corrected findings are important. The absence of a Bonferroni-significant cross-metric association means that chemical-space relatedness and network position cannot be used as substitutes for target-specific mutation analysis. The retraction of the PP-11 C59R interpretation further demonstrates why non-binding wild-type baselines must be excluded before calculating ratios. In this setting, a narrower and more conditional RRS claim is stronger than an apparently larger pooled-target effect.

Reading the two layers together is more informative than either alone. PP-06 is the only candidate in the top quartile of within-target scores for all four proteins and is simultaneously classified A* on its PfCRT mutant panel (mean RRS 92.4%), and PP-11, top-quartile on three targets, is likewise A* (82.6%), whereas PP-13 combines a Pareto-front position in the four-target profile with the second-highest mean RRS (104.8%). These three candidates therefore represent the workflow’s most economical combined multi-target and mutation-resilience hypotheses and its most defensible first choices for biochemical, mutant-panel, and molecular-dynamics follow-up. The other A* assignments are either PfCRT-only (PP-02, PP-06, PP-11, PP-13) or pair a moderate four-target profile with PfDHFR resilience (PP-01, PP-15); none of these operational assignments should be read as confirmed activity.

The study has substantial limitations. Docking scores are approximate scoring-function outputs and do not establish affinity, kinetics, or cellular activity. PfCRT is represented by a proxy cavity, and PfATP4 by conserved catalytic machinery without a co-crystallized inhibitor. RRS covers PfDHFR and PfCRT but not PfClpP or PfATP4, and the cohort is small and purposefully enriched for predicted polypharmacology. The parent MD systems are separate from Set C and cannot validate the Set C RRS profile. No new IC₅₀/EC₅₀ measurements were available. Finally, independent structural assessment remains necessary before the raw target panel can support stronger structural conclusions. The next experiments should combine biochemical or cellular potency measurements, resistance-mutant assays, orthogonal binding methods, and candidate-specific molecular dynamics.

5 Conclusion

An African-natural-product-inspired chemical-space funnel was connected to a four-target, target-anchored docking panel and a corrected per-target RRS analysis. The workflow identified a 17-member cohort with reproducible computational pose profiles and heterogeneous mutation-resilience classes, while retaining null findings and target-specific missingness. Its value is hypothesis generation: it proposes which chemotypes and target-mutation combinations should be tested next, without claiming that docking, RRS, or polypharmacology estimates are experimental evidence.

Supporting Information

The Supporting Information contains the candidate manifest, target-anchor evidence, complete 17-by-4 docking matrix, RRS definitions and table, PNS/ACSI values, cross-metric statistics, provenance fields, and reproducibility instructions.

Author Contributions

M.V.S.T. and S.G.N.E. designed the integrated study. M.V.S.T. and J.-P.T.N. developed the chemical-space and docking analyses. P.S. and W.F.M. contributed to target biology and resistance interpretation. All authors reviewed and approved the manuscript scope.

Notes

The authors declare no competing financial interest. This is a computational, hypothesis-generating study; no experimental potency is claimed.

Data Availability

Data and code are available at https://github.com/NanaEngo/Malaria_codesV2. Integrated manifests and derived figures are in `Project1_Chem_space_antimalarial_V6_CorrectedGrid/`; source RRS data are in `Project2_Polypharmacology_MD_ValidationV2607/results/`; raw Vina data are in `Project1_Chem_space_antimalarial_V5_CorrectedGrid/results/`.

References

- (1) Kitchen, D. B.; Decornez, H.; Furr, J. R.; Bajorath, J. Docking and scoring in virtual screening for drug discovery: methods and applications. *Nature Reviews Drug Discovery* **2004**, *3*, 935–949.
- (2) Simoben, C. V.; Babiaka, S. B.; Moumbock, A. F. A.; Namba-Nzanguim, C. T.; Eni, D. B.; Medina-Franco, J. L.; Günther, S.; Ntie-Kang, F.; Sippl, W. Challenges in natural product-based drug discovery assisted within silico-based methods. *13*, 31578–31594.
- (3) World Health Organization *World Malaria Report 2024*; 2024; Accessed 2025-03-03.
- (4) Ariey, F. et al. A molecular marker of artemisinin-resistant *Plasmodium falciparum* malaria. *Nature* **2014**, *505*, 50–55.
- (5) Ashley, E. A.; Pyae Phyo, A.; Woodrow, C. J. Malaria. *391*, 1608–1621.
- (6) Fidock, D. A.; Nomura, T.; Talley, A. K.; Cooper, R. A.; Dzekunov, S. M.; Kirkman, L. A.; Weber, J. L.; Su, X.; Wellems, T. E.; Martin, S. K. Mutations in the *P. falciparum* Digestive Vacuole Transmembrane Protein PfCRT and Evidence for Their Role in Chloroquine Resistance. *Science* **2000**, *293*, 861–871.
- (7) Wells, T. N. C.; van Huijsduijnen, R. H.; Voorhis, W. C. V. Malaria medicines: a glass half full? *Nat. Rev. Drug Discovery* **2015**, *14*, 424–442.

- (8) Siqueira-Neto, J. L.; Wicht, K. J.; Chibale, K.; Burrows, J. N.; Fidock, D. A.; Winzeler, E. A. Antimalarial drug discovery: progress and approaches. *Nat. Rev. Drug Discovery* **2023**, *22*, 807–826.
- (9) Newman, D. J.; Cragg, G. M. Natural Products as Sources of New Drugs over the Last 25 Years. *Journal of Natural Products* **2007**, *70*, 461–477.
- (10) Ntie-Kang, F.; Onguéné, P. A.; Lifongo, L. L.; Mbaze, L. M.; Sippl, W.; Günther, S. In silico analyses of bioactive natural products from african medicinal plants for drug-discovery. *BMC Complementary and Alternative Medicine* **2018**, *18*, 106.
- (11) Cheuka, P. M.; Dziwornu, G.; Okombo, J.; Chibale, K. Plasmepsin Inhibitors in Anti-malarial Drug Discovery: Medicinal Chemistry and Target Validation (2000 to Present). *63*, 4445–4467.
- (12) Nigam, A.; Pollice, R.; Krenn, M.; Gomes, G. d. P.; Aspuru-Guzik, A. Beyond generative models: superfast traversal, optimization, novelty, exploration and discovery (STONED) algorithm for molecules using SELFIES. *Chem. Sci.* **2021**, *12*, 7079–7090.
- (13) Krenn, M.; Häse, F.; Nigam, A.; Friederich, P.; Aspuru-Guzik, A. Self-referencing embedded strings (SELFIES): A 100.
- (14) Baell, J. B.; Holloway, G. A. New Substructure Filters for Removal of Pan Assay Interference Compounds (PAINS) from Screening Libraries and for Their Exclusion in Bioassays. *J. Med. Chem.* **2010**, *53*, 2719–2740.
- (15) Kingma, D. P.; Welling, M. Auto-Encoding Variational Bayes. **2013**,
- (16) Corso, G.; Stärk, H.; Jing, B.; Barzilay, R.; Jaakkola, T. DiffDock: Diffusion Steps, Twists, and Turns for Molecular Docking. International Conference on Learning Representations (ICLR). 2023.

- (17) Bickerton, G. R.; Paolini, G. V.; Besnard, J.; Muresan, S.; Hopkins, A. L. Quantifying the chemical beauty of drugs. *Nature Chemistry* **2012**, *4*, 90–98.
- (18) Lipinski, C. A. Lead- and drug-like compounds: the rule-of-five revolution. *Adv. Drug Delivery Rev.* **2004**, *1*, 337–341.
- (19) Rogers, D.; Hahn, M. Extended-Connectivity Fingerprints. *50*, 742–754, PMID: 20426451.
- (20) O’Boyle, N. M.; Banck, M.; James, C. A.; Morley, C.; Vandermeersch, T.; Hutchison, G. R. Open Babel: An open chemical toolbox. *Journal of Cheminformatics* **2011**, *3*.
- (21) Eberhardt, J.; Santos-Martins, D.; Tillack, A. F.; Forli, S. AutoDock Vina 1.2.0: New Docking Methods, Expanded Force Field, and Python Bindings. *Journal of Chemical Information and Modeling* **2021**, *61*, 3891–3898.
- (22) Trott, O.; Olson, A. J. AutoDock Vina: Improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *Journal of Computational Chemistry* **2009**, *31*, 455–461.
- (23) Quiroga, R.; Villarreal, M. A. Vinardo: A Scoring Function Based on Autodock Vina Improves Scoring, Docking, and Virtual Screening. *PLOS ONE* **2016**, *11*, e0155183.