



CS201 DISCRETE MATHEMATICS FOR COMPUTER SCIENCE

Dr. QI WANG

Department of Computer Science and Engineering

Office: Room903, Nanshan iPark A7 Building

Email: wangqi@sustech.edu.cn

Properties of Relations

■ **Reflexive Relation:** A relation R on a set A is called *reflexive* if $(a, a) \in R$ for **every** element $a \in A$.

Irreflexive Relation: A relation R on a set A is called *irreflexive* if $(a, a) \notin R$ for **every** element $a \in A$.

Symmetric Relation: A relation R on a set A is called *symmetric* if $(b, a) \in R$ whenever $(a, b) \in R$ for **all** $a, b \in A$.

Antisymmetric Relation: A relation R on a set A is called *antisymmetric* if $(b, a) \in R$ and $(a, b) \in R$ implies $a = b$ for **all** $a, b \in A$.

Transitive Relation: A relation R on a set A is called *transitive* if $(a, b) \in R$ and $(b, c) \in R$ implies $(a, c) \in R$ for **all** $a, b, c \in A$.



Connectivity

- **Lemma:** Let A be a set with n elements, and R a relation on A . If there is a path from a to b with $a \neq b$, then there exists a path of length $\leq n - 1$.

$$R^* = \bigcup_{k=1}^n R^k$$



Connectivity

- **Lemma:** Let A be a set with n elements, and R a relation on A . If there is a path from a to b with $a \neq b$, then there exists a path of length $\leq n - 1$.

$$R^* = \bigcup_{k=1}^n R^k$$

Theorem: The transitive closure of a relation R equals the connectivity relation R^* .



Connectivity

- **Lemma:** Let A be a set with n elements, and R a relation on A . If there is a path from a to b with $a \neq b$, then there exists a path of length $\leq n - 1$.

$$R^* = \bigcup_{k=1}^n R^k$$

Theorem: The transitive closure of a relation R equals the connectivity relation R^* .

Recall Finding a transitive closure corresponds to finding all pairs of elements that are connected with a directed path



Equivalence Relation

- **Definition** A relation R on a set A is called an *equivalence relation* if it is *reflexive*, *symmetric*, and *transitive*.
- **Definition** Let R be an *equivalence relation* on a set A . The *set of all elements* that are related to an element a of A is called the *equivalence class* of a , denoted by $[a]_R$. When only one relation is considered, we use the notation $[a]$.

$$[a]_R = \{b : (a, b) \in R\}$$



Equivalence Classes and Partitions

- **Theorem** Let R be an equivalence relation on a set A . Then union of all the equivalence classes of R is A :

$$A = \bigcup_{a \in A} [a]_R$$



Equivalence Classes and Partitions

- **Theorem** Let R be an equivalence relation on a set A . Then union of all the equivalence classes of R is A :

$$A = \bigcup_{a \in A} [a]_R$$

Theorem The equivalence classes form a partition of A .



Equivalence Classes and Partitions

- **Theorem** Let R be an equivalence relation on a set A . Then union of all the equivalence classes of R is A :

$$A = \bigcup_{a \in A} [a]_R$$

Theorem The equivalence classes form a partition of A .

Theorem Let $\{A_1, A_2, \dots, A_i, \dots\}$ be a partition of S . Then there is an equivalence relation R on S , that has the sets A_i as its equivalence classes.



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*?



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*? Yes



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*? Yes

Is R *antisymmetric*?



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*? Yes

Is R *antisymmetric*? Yes



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*? Yes

Is R *antisymmetric*? Yes

Is R *transitive*?



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R *reflexive*? Yes

Is R *antisymmetric*? Yes

Is R *transitive*? Yes



Partial Ordering

- **Definition** A relation R on a set S is called a *partial ordering*, or *partial order*, if it is *reflexive*, *antisymmetric*, and *transitive*. A set S together with a partial ordering R is called a *partially ordered set*, or *poset*, denoted by (S, R) . Members of S are called *elements of the poset*.

Example:

$S = \{1, 2, 3, 4, 5\}$, R denotes the “ \geq ” relation

Is R reflexive? Yes

Is R antisymmetric? Yes

Is R transitive? Yes

R is a partial ordering



Partial Ordering

- **Example:**

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “|” relation



Partial Ordering

■ Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “|” relation

Is R reflexive? Yes

Is R antisymmetric? Yes

Is R transitive? Yes



Partial Ordering

■ Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “|” relation

Is R reflexive? Yes

Is R antisymmetric? Yes

Is R transitive? Yes

R is a partial ordering



Comparability

- **Definition** The elements a and b of a poset (S, \preceq) are *comparable* if either $a \preceq b$ or $b \preceq a$. Otherwise, a and b are called *incomparable*.



Comparability

- **Definition** The elements a and b of a poset (S, \preceq) are *comparable* if either $a \preceq b$ or $b \preceq a$. Otherwise, a and b are called *incomparable*.

Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “|” relation



Comparability

- **Definition** The elements a and b of a poset (S, \preceq) are *comparable* if either $a \preceq b$ or $b \preceq a$. Otherwise, a and b are called *incomparable*.

Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “|” relation

2, 4 are comparable, 3, 5 are incomparable.



Total Ordering

- **Definition** If (S, \preccurlyeq) is a poset and every two elements of S are comparable, S is called a *totally ordered* or *linearly ordered set*, and \preccurlyeq is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.



Total Ordering

- **Definition** If (S, \preccurlyeq) is a poset and every two elements of S are comparable, S is called a *totally ordered* or *linearly ordered set*, and \preccurlyeq is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.

Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “ \geq ” relation



Total Ordering

- **Definition** If (S, \preccurlyeq) is a poset and every two elements of S are comparable, S is called a *totally ordered* or *linearly ordered set*, and \preccurlyeq is called a *total order* or a *linear order*. A totally ordered set is also called a *chain*.

Example:

$S = \{1, 2, 3, 4, 5, 6\}$, R denotes the “ \geq ” relation

S is a chain.



Lexicographic Ordering

- **Definition** Given two posets (A_1, \preceq_1) and (A_2, \preceq_2) , the *lexicographic ordering* on $A_1 \times A_2$ is defined by specifying that (a_1, a_2) is **less than** (b_1, b_2) , i.e., $(a_1, a_2) \prec (b_1, b_2)$, either if $a_1 \prec_1 b_1$ or if $a_1 = b_1$ then $a_2 \prec_2 b_2$.



Lexicographic Ordering

- **Definition** Given two posets (A_1, \preceq_1) and (A_2, \preceq_2) , the *lexicographic ordering* on $A_1 \times A_2$ is defined by specifying that (a_1, a_2) is **less than** (b_1, b_2) , i.e., $(a_1, a_2) \prec (b_1, b_2)$, either if $a_1 \prec_1 b_1$ or if $a_1 = b_1$ then $a_2 \prec_2 b_2$.

Example Consider strings of lowercase English letters. A *lexicographic ordering* can be defined using the ordering of the letters in the alphabet. This is *the same ordering* as that used in **dictionaries**.



Lexicographic Ordering

- **Definition** Given two posets (A_1, \preceq_1) and (A_2, \preceq_2) , the *lexicographic ordering* on $A_1 \times A_2$ is defined by specifying that (a_1, a_2) is **less than** (b_1, b_2) , i.e., $(a_1, a_2) \prec (b_1, b_2)$, either if $a_1 \prec_1 b_1$ or if $a_1 = b_1$ then $a_2 \prec_2 b_2$.

Example Consider strings of lowercase English letters. A *lexicographic ordering* can be defined using the ordering of the letters in the alphabet. This is *the same ordering* as that used in **dictionaries**.

- ◇ *discreet* \prec *discrete*
- ◇ *discreet* \prec *discreetness*




Hasse Diagram

- A Hasse diagram is a visual representation of a partial ordering that leaves out edges that must be present because of the reflexive and transitive properties.




Hasse Diagram

- A **Hasse diagram** is a visual representation of a **partial ordering** that **leaves out** edges that must be present because of the **reflexive** and **transitive** properties.



Hasse Diagram

- (a) A **partial ordering**. The loops are due to the **reflexive property**
- (b) The edges that must be present due to the **transitive property** are deleted
- (c) The Hasse diagram for the partial ordering (a)



Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:



Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:
 - ◇ Remove the loops (a, a) present at every vertex due to the reflexive property



Procedure for Constructing Hasse Diagram

- Start with the directed graph of the relation:
 - ◇ Remove the loops (a, a) present at every vertex due to the reflexive property
 - ◇ Remove all edges (x, y) for which there is an element $z \in S$ s.t. $x \prec z$ and $z \prec y$. These are the edges that must be present due to the transitive property




Procedure for Constructing Hasse Diagram



- Start with the directed graph of the relation:
 - ◇ Remove the loops (a, a) present at every vertex due to the **reflexive property**
 - ◇ Remove all edges (x, y) for which there is an element $z \in S$ s.t. $x \prec z$ and $z \prec y$. These are the edges that must be present due to the **transitive property**
 - ◇ Arrange each edge so that its initial vertex is **below** the terminal vertex. Remove all the arrows, because all edges point upwards toward their terminal vertex.






Hasse Diagram Example



Hasse Diagram Example



Hasse Diagram Example



Maximal and Minimal Elements

- **Definition** a is a *maximal* (resp. *minimal*) element in poset (S, \preceq) if there is **no** $b \in S$ such that $a \prec b$ (resp. $b \prec a$).



Maximal and Minimal Elements

- **Definition** a is a *maximal* (resp. *minimal*) element in poset (S, \preceq) if there is **no** $b \in S$ such that $a \prec b$ (resp. $b \prec a$).

Example Which elements of the poset $(\{2, 4, 5, 10, 12, 20, 25\}, |)$ are *maximal*, and *minimal*?



Maximal and Minimal Elements

- **Definition** a is a *maximal* (resp. *minimal*) element in poset (S, \preceq) if there is **no** $b \in S$ such that $a \prec b$ (resp. $b \prec a$).

Example Which elements of the poset $(\{2, 4, 5, 10, 12, 20, 25\}, |)$ are *maximal*, and *minimal*?

Definition a is the *greatest* (resp. *least*) element of the poset (S, \preceq) if $b \preceq a$ (resp. $a \preceq b$) for all $b \in S$.




Maximal and Minimal Elements

- **Definition** a is a *maximal* (resp. *minimal*) element in poset (S, \preceq) if there is **no** $b \in S$ such that $a \prec b$ (resp. $b \prec a$).


Example Which elements of the poset $(\{2, 4, 5, 10, 12, 20, 25\}, |)$ are *maximal*, and *minimal*?

Definition a is the *greatest* (resp. *least*) element of the poset (S, \preceq) if $b \preceq a$ (resp. $a \preceq b$) for all $b \in S$.


Example




(a)



(b)



(c)



(d)



Maximal and Minimal Elements

- **Definition** Let A be a subset of a poset (S, \preceq) .
 - $u \in S$ is called an *upper bound* (resp. *lower bound*) of A if $a \preceq u$ (resp. $u \preceq a$) for all $a \in A$.
 - $x \in S$ is called the *least upper bound* (resp. *greatest lower bound*) of A if x is an upper bound (resp. lower bound) that is *less than* any *other* upper bound (resp. lower bound) of A .



Maximal and Minimal Elements

- **Definition** Let A be a subset of a poset (S, \preceq) .
- $u \in S$ is called an *upper bound* (resp. *lower bound*) of A if $a \preceq u$ (resp. $u \preceq a$) for all $a \in A$.
- $x \in S$ is called the *least upper bound* (resp. *greatest lower bound*) of A if x is an upper bound (resp. lower bound) that is *less than* any *other* upper bound (resp. lower bound) of A .

Example Find the *greatest lower bound* and the *least upper bound* of the sets $\{3, 9, 12\}$ and $\{1, 2, 4, 5, 10\}$, if they exist, in the poset $(\mathbf{Z}^+, |)$.



Well-Ordered Set

- **Definition** (S, \preceq) is a *well-ordered set* if it is a poset such that \preceq is a **total ordering** and **every nonempty subset of S has a least element**.



Well-Ordered Set

- **Definition** (S, \preceq) is a *well-ordered set* if it is a poset such that \preceq is a *total ordering* and *every nonempty subset of S has a least element*.

The Principle of Well-Ordering Induction Suppose that S is a *well-ordered set*. Then $P(x)$ is true for *all $x \in S$* , if

Inductive Step For every $y \in S$, if $P(x)$ is true for all $x \in S$ with $x \prec y$, then $P(y)$ is true.



Well-Ordered Set

- **Definition** (S, \preceq) is a *well-ordered set* if it is a poset such that \preceq is a *total ordering* and *every nonempty subset of S has a least element*.

The Principle of Well-Ordering Induction Suppose that S is a *well-ordered set*. Then $P(x)$ is true for *all $x \in S$* , if

Inductive Step For every $y \in S$, if $P(x)$ is true for all $x \in S$ with $x \prec y$, then $P(y)$ is true.

Proof Consider $A = \{x \in S : P(x) \text{ is false}\}$



Well-Ordered Set

- **Definition** (S, \preceq) is a *well-ordered set* if it is a poset such that \preceq is a *total ordering* and *every nonempty subset of S has a least element*.

The Principle of Well-Ordering Induction Suppose that S is a *well-ordered set*. Then $P(x)$ is true for *all $x \in S$* , if

Inductive Step For every $y \in S$, if $P(x)$ is true for all $x \in S$ with $x \prec y$, then $P(y)$ is true.

Proof Consider $A = \{x \in S : P(x) \text{ is false}\}$

Question: Why don't we need a *basic step* here?



Well-Ordered Set

- **Definition** (S, \preceq) is a *well-ordered set* if it is a poset such that \preceq is a *total ordering* and every nonempty subset of S has a *least element*.

The Principle of Well-Ordering Induction Suppose that S is a *well-ordered set*. Then $P(x)$ is true for *all* $x \in S$, if

Inductive Step For every $y \in S$, if $P(x)$ is true for all $x \in S$ with $x \prec y$, then $P(y)$ is true.

Proof Consider $A = \{x \in S : P(x) \text{ is false}\}$

Question: Why don't we need a *basic step* here?

p. 620, Theorem 1





Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a ***lattice***.




Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a **lattice**.



Lattices

- **Definition** A **partial ordered set** in which **every pair of elements** has both a least upper bound and a greatest lower bound is called a **lattice**.



Example Determine whether the posets $(\{1, 2, 3, 4, 5\}, |)$ and $(\{1, 2, 4, 8, 16\}, |)$ are lattices.



Topological Sorting

- Motivation: A project is made up of 20 different tasks. Some tasks can be completed only after others have been finished. **How can an order be found for these tasks?**



Topological Sorting

- Motivation: A project is made up of 20 different tasks. Some tasks can be completed only after others have been finished. **How can an order be found for these tasks?**

Topological sorting: Given a **partial ordering** R , find a **total ordering** \preceq such that $a \preceq b$ whenever $a R b$. \preceq is said *compatible with* R .



Topological Sorting for Finite Posets

procedure topological_sort (S : finite poset)

$k := 1$;

while $S \neq \emptyset$

$a_k :=$ a minimal element of S

$S := S \setminus \{a_k\}$

$k := k + 1$

end while

// $\{a_1, a_2, \dots, a_n\}$ is a compatible total ordering of S



Next Lecture

- graph theory I ...

