

Introduction to Active Learning

Nandana Sengupta

November 9, 2015

Active Learning: Introduction

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.
 - ▶ matrix of individual rankings

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.
 - ▶ matrix of individual rankings
 - ▶ eg: Netflix problem.

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.
 - ▶ matrix of individual rankings
 - ▶ eg: Netflix problem.
- ▶ Issues in generating such rankings: costly queries, missing value problem, inefficiencies.

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.
 - ▶ matrix of individual rankings
 - ▶ eg: Netflix problem.
- ▶ Issues in generating such rankings: costly queries, missing value problem, inefficiencies.
- ▶ Typically random queries over “n” objects \Rightarrow number of queries: $\binom{n}{2}$

Active Learning: Introduction

- ▶ “n” objects: $\theta_1, \theta_2, \dots, \theta_n$.
- ▶ “m” individuals: i_1, i_2, \dots, i_m .
- ▶ Aim is to get a ranking over the “n” objects:
 - ▶ global ranking: $\theta_2 \succ \theta_3 \succ \theta_1 \succ \theta_5 \succ \theta_6 \succ \theta_4$.
 - ▶ eg: web search queries, street safety queries.
 - ▶ matrix of individual rankings
 - ▶ eg: Netflix problem.
- ▶ Issues in generating such rankings: costly queries, missing value problem, inefficiencies.
- ▶ Typically random queries over “n” objects \Rightarrow number of queries: $\binom{n}{2}$
- ▶ Inefficient! This is where Active Learning comes in.

Active Learning: Introduction

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “d”-dimensional space, say r .

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “d”-dimensional space, say r .
 - ▶ Distance from r determines ranking.

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “d”-dimensional space, say r .
 - ▶ Distance from r determines ranking.
 - ▶ However r is unknown – so problem becomes estimating region where r lies.

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “d”-dimensional space, say r .
 - ▶ Distance from r determines ranking.
 - ▶ However r is unknown – so problem becomes estimating region where r lies.
 - ▶ Some queries redundant – example next.

Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “d”-dimensional space, say r .
 - ▶ Distance from r determines ranking.
 - ▶ However r is unknown – so problem becomes estimating region where r lies.
 - ▶ Some queries redundant – example next.
- ▶ Assumptions


Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “ d ”-dimensional space, say r .
 - ▶ Distance from r determines ranking.
 - ▶ However r is unknown – so problem becomes estimating region where r lies.
 - ▶ Some queries redundant – example next.
- ▶ Assumptions
 - ▶ A1: Embedding if $\theta_i \prec \theta_j$ then $\|\theta_i - r\| < \|\theta_j - r\|$.


Active Learning: Introduction

- ▶ “Active Ranking using Pairwise Comparisons” – Jamieson and Nowak (2011)
- ▶ if there exists $d < n$ features in \mathcal{R}^d then can reduce order of queries: $\mathcal{O}(d \log n)$.
- ▶ Main idea is to not query randomly but use these d features.
 - ▶ Reference Point in “ d ”-dimensional space, say r .
 - ▶ Distance from r determines ranking.
 - ▶ However r is unknown – so problem becomes estimating region where r lies.
 - ▶ Some queries redundant – example next.
- ▶ Assumptions
 - ▶ A1: Embedding if $\theta_i \prec \theta_j$ then $\|\theta_i - r\| < \|\theta_j - r\|$.
 - ▶ A2: Consistency Every pairwise comparison is consistent with the global ranking.


Active Learning: Example




Active Learning: Example




Active Learning: Example




Active Learning: Example



Active Learning: Example



Active Learning: Example



Active Learning: Possible Applications

Active Learning: Possible Applications

- ▶ Pairwise ranking surveys online.

Active Learning: Possible Applications

- ▶ Pairwise ranking surveys online.
- ▶ Eg: Street Score, All our ideas.

Active Learning: Possible Applications

- ▶ Pairwise ranking surveys online.
- ▶ Eg: **Street Score**, **All our ideas**.
- ▶ Generate global rankings by asking pairwise comparison queries.

Active Learning: Possible Applications

- ▶ Pairwise ranking surveys online.
- ▶ Eg: **Street Score**, **All our ideas**.
- ▶ Generate global rankings by asking pairwise comparison queries.
- ▶ Currently using random pairwise queries.

Active Learning: Possible Applications

- ▶ Pairwise ranking surveys online.
- ▶ Eg: **Street Score**, **All our ideas**.
- ▶ Generate global rankings by asking pairwise comparison queries.
- ▶ Currently using random pairwise queries.
- ▶ Opportunity for active learning algorithms.

Thanks!