■ EXCEL FORMULA TASK BOOK — LEVEL 2

8 Complex Tasks · 24 New Formulas · ~2 Hours · Class 10+ Level
All formulas are basic — the TASKS are what make them challenging!

Task	Topic	New Formulas	Time
1	Hospital Patient Records	IFERROR, ISBLANK, COUNTA, ISNUMBER	15 min
2	Cricket Score Analyser	LARGE, SMALL, PERCENTILE, MEDIAN	15 min
3	Shopping Bill Calculator	ROUND, ROUNDUP, ROUNDDOWN, INT, MOD	15 min
4	Library Book Tracker	NETWORKDAYS, WORKDAY, DAYS360	15 min
5	Restaurant Revenue Report	INDIRECT, OFFSET, CHOOSE, INDEX, MATCH	20 min
6	Bank Loan EMI Calculator	PMT, IPMT, PPMT, RATE, NPER	20 min
7	School Attendance System	COUNTIFS, SUMPRODUCT, AVERAGEIFS	15 min
8	Stock Market Portfolio	STDEV, VAR, CORREL, FORECAST	15 min

Instructions: Open Excel → Create a new Workbook → Make ONE sheet per task. Type all data exactly as shown in yellow/data tables. Formula columns are marked with ✍ — that is where YOU write the formula. Read the explanation BEFORE writing the formula. After finishing, check your answer using the ■ Expected Result shown.

■ TASK 1 — Hospital Patient Records (15 minutes)

A hospital has patient data but some cells are empty or have errors. You need to clean up the records, count filled cells, and flag data issues. This teaches you to handle MISSING and ERROR data — the most common real-world Excel problem.

■ Type This Data (Sheet: Hospital)

Patient ID	Name	Age	Blood Group	Test Result	Discount %	Final Fee ■
P001	Ravi Kumar	34	A+	8500	10	
P002		28	B+	7200		
P003	Sunita Rao	45	O+	ERROR	5	
P004	Arun Verma		AB+	9100	15	
P005	Priya Singh	31	A-	6800	0	
P006		52	B-	11200	20	

✍ Columns to fill: G (Final Fee), H (Name Missing?), I (Age Valid?), J (Safe Result), K (Total Patients)

■ IFERROR — Show friendly message instead of ugly Excel errors

```
=IFERROR(value, value_if_error)
```

In cell J2 (Safe Result column) type: =IFERROR(E2, "Check Data")

If E2 has an error (like #VALUE! or ERROR text), show 'Check Data' instead of crashing.

Copy down for all rows. P003 will show 'Check Data' since its result is ERROR.

■ ISBLANK — Check if a cell is empty (TRUE/FALSE)

```
=ISBLANK(cell) → returns TRUE if empty, FALSE if has data
```

In H2 (Name Missing?) type: =IF(ISBLANK(B2), "■ Missing", "OK")

P002 and P006 have empty names → will show ■ Missing. Others show OK.

■ ISNUMBER — Check if a cell contains a number

`=ISNUMBER(cell) → TRUE if it's a number, FALSE otherwise`

In I2 (Age Valid?) type: =IF(ISNUMBER(C2), "Valid", "■ Not a Number")

P004 has '' in age — will show ■ Not a Number. Others show Valid.

■ COUNTA — Count all NON-EMPTY cells (works for text AND numbers)

`=COUNTA(range) → counts cells that have ANY content`

In K2 type: =COUNTA(B2:B7) → counts how many patients have names filled (answer = 4)

Also try: =COUNTA(A2:A7) → counts total patient IDs = 6

■ Final Fee formula: =IFERROR(E2*(1-F2/100), "Cannot Calculate")

■ *DIFFERENCE: COUNT counts only numbers. COUNTA counts everything (text + numbers). COUNTBLANK counts empty cells. Use COUNTA for names/text, COUNT for numbers only!*

■ TASK 2 — Cricket Score Analyser (15 minutes)

Virat Kohli played 12 innings this season. Find his top scores, bottom scores, median score, and what percentile his best innings falls in. These statistical formulas are used in data analysis, finance, and HR departments every day.

■ Type This Data (Sheet: Cricket)

Innings	Opponent	Score	Result
1	Australia	94	Won
2	England	12	Lost
3	South Africa	67	Won
4	New Zealand	156	Won
5	Pakistan	43	Lost
6	Sri Lanka	88	Won
7	West Indies	0	Lost
8	Bangladesh	112	Won
9	Zimbabwe	34	Won
10	Ireland	76	Won
11	Australia	201	Won
12	England	55	Lost

■ LARGE — Find the Nth HIGHEST value in a list

`=LARGE(range, n) → n=1 gives highest, n=2 gives 2nd highest, etc.`

In a blank area, type these formulas:

Highest Score: =LARGE(C2:C13, 1) → Answer: 201

2nd Highest: =LARGE(C2:C13, 2) → Answer: 156

3rd Highest: =LARGE(C2:C13, 3) → Answer: 112

■ SMALL — Find the Nth LOWEST value in a list

`=SMALL(range, n) → n=1 gives lowest, n=2 gives 2nd lowest, etc.`

Lowest Score: =SMALL(C2:C13, 1) → Answer: 0 (duck out!)

2nd Lowest: =SMALL(C2:C13, 2) → Answer: 12

■ MEDIAN — The MIDDLE value when all numbers are sorted

`=MEDIAN(range) → the exact middle value (not affected by extremes)`

Median Score: =MEDIAN(C2:C13) → Answer: 71.5 (avg of 67 and 76)

Compare: AVERAGE(C2:C13) = 78.2. MEDIAN is more useful when outliers exist!

■ PERCENTILE — What % of scores fall BELOW a given value

`=PERCENTILE(range, k) → k is between 0 and 1 (0.9 = 90th percentile)`

90th Percentile: =PERCENTILE(C2:C13, 0.9) → the score that beats 90% of innings

50th Percentile: =PERCENTILE(C2:C13, 0.5) → same as MEDIAN!

75th Percentile: =PERCENTILE(C2:C13, 0.75) → answer: ~97

■ Challenge: In which percentile does the score of 201 fall?

Hint: use PERCENTRANK function: =PERCENTRANK(C2:C13, 201) → gives the percentile as a decimal

■ REAL USE: HR departments use PERCENTILE for salary bands — 'top 25% performers get bonus'. Finance uses it for risk analysis — 'worst 10% scenario'. Banks use it for credit scoring!

■ TASK 3 — Shopping Bill Calculator (15 minutes)

A supermarket needs to calculate bills with GST, round off totals to nearest rupee, split packages, and figure out change. Rounding formulas seem simple — but each one works differently and choosing the wrong one costs real money!

■ Type This Data (Sheet: Shopping Bill)

Item	Qty	Price/Unit ■	Base Amount ■	GST 18%	Total ■	Rounded ■	Packed in boxes of
Biscuits	7	12.5					6
Shampoo	3	87.75					1
Rice (kg)	2.5	45.2					1
Soap	11	24.0					4
Chocolate	15	8.33					12
Oil (L)	1.8	132.5					1

■ ROUND — Round to N decimal places (rounds 0.5 UP)

`=ROUND(number, num_digits) → ROUND(12.456, 2) = 12.46`

Base Amount in D2: =B2*C2 → 7 × 12.50 = 87.50

GST in E2: =ROUND(D2*0.18, 2) → rounds GST to 2 decimal places

Total in F2: =D2+E2

Rounded Total in G2: =ROUND(F2, 0) → rounds to nearest whole rupee (0 decimals)

■ ROUNDUP — ALWAYS rounds UP regardless of decimal

`=ROUNDUP(number, num_digits) → ROUNDUP(12.01, 0) = 13 (not 12!)`

Try: =ROUNDUP(E2, 0) for GST — government often rounds up tax amounts

=ROUNDUP(87.01, 0) = 88 BUT =ROUND(87.01, 0) = 87 — BIG DIFFERENCE!

■ ROUNDDOWN — ALWAYS rounds DOWN regardless of decimal

`=ROUNDDOWN(number, num_digits) → ROUNDDOWN(12.99, 0) = 12 (not 13!)`

Try: =ROUNDDOWN(F2, 0) — some shops always round down for customer benefit

■ INT — Removes decimal part (keeps only the whole number)

`=INT(number) → INT(87.99) = 87 | INT(87.01) = 87 (always goes to lower whole number)`

INT is like ROUNDDOWN to 0 places but simpler to type. Use for counting whole units.

■ MOD — Gives the REMAINDER after division

`=MOD(number, divisor) → MOD(11, 4) = 3 (11 ÷ 4 = 2 remainder 3)`

■ Challenge: How many items remain after filling complete boxes?

For Biscuits: Qty=7, packed in boxes of 6 → =MOD(B2, H2) → Answer: 1 (one loose biscuit!)

For Soap: Qty=11, boxes of 4 → =MOD(11,4) → Answer: 3 (3 soap bars not in a box)

How many COMPLETE boxes? → =INT(B2/H2) → Soap: INT(11/4) = 2 complete boxes

■ *MOD IS EVERYWHERE: Check if a number is even: =MOD(A1,2)=0 (even) or =MOD(A1,2)=1 (odd). GST invoice numbering, lottery numbers, EMI due date calculations — all use MOD!*

■ TASK 4 — Library Book Tracker (15 minutes)

A library tracks books borrowed and returned. They fine members for late returns but they DON'T count Sundays and public holidays as working days. You need to calculate due dates that skip weekends and count actual working days for fines.

■ Type This Data (Sheet: Library)

Member	Book	Borrow Date	Allowed Days	Due Date ✍	Return Date	Working Days Late ✍	Fine ■ ✍
Ravi Kumar	Harry Potter	02-06-2025	14		18-06-2025		
Priya Singh	Python Book	05-06-2025	7		16-06-2025		
Aman Verma	History	10-06-2025	21		05-07-2025		
Sunita Rao	Maths Guide	12-06-2025	10		25-06-2025		
Rohit Sharma	Science	16-06-2025	14		01-07-2025		

■ Public holidays in June 2025: 19-Jun (state holiday), 27-Jun (local festival)

■ WORKDAY — Adds N working days to a date (skipping weekends)

`=WORKDAY(start_date, days, [holidays]) → returns the working day date`

Due Date in E2: =WORKDAY(C2, D2) → adds 14 WORKING days to 02-Jun

With holidays: =WORKDAY(C2, D2, {"19-Jun-2025","27-Jun-2025"})

This means Sundays and holidays are NOT counted as borrowing days — fair for members!

■ NETWORKDAYS — Counts WORKING days between two dates

`=NETWORKDAYS(start_date, end_date, [holidays]) → working days count`

Working Days Late in G2:

=MAX(0, NETWORKDAYS(E2, F2)-1) → days late (0 if returned on time)

Negative result = returned early, MAX(0,...) shows 0 instead of negative

Fine in H2: =G2 * 5 → ■5 fine per working day late

■ DAYS360 — Counts days using 360-day year (banking standard)

`=DAYS360(start_date, end_date) → assumes each month = 30 days`

Try: =DAYS360(C2, F2) vs =(F2-C2) — they give different answers!

DAYS360 is used in: bond calculations, loan agreements, EMI schedules, interest calculations.

■ Challenge: Which member has the highest fine? Use MAX on the Fine column.

=MAX(H2:H6) → finds highest fine. =INDEX(A2:A6, MATCH(MAX(H2:H6), H2:H6, 0)) → finds that member's name!

■ REAL USE: Payroll uses NETWORKDAYS for leave calculation (only working days count). Banks use DAYS360 for interest. Project managers use WORKDAY for deadline setting in contracts!

■■ TASK 5 — Restaurant Revenue Report (20 minutes)

A restaurant has 4 branches. You need to look up branch-wise data, create a dynamic report that changes based on a dropdown selection, and pull data from different positions. INDEX+MATCH is more powerful than VLOOKUP — it works in any direction!

■ Type This Data in 2 separate areas (Sheet: Restaurant)

Branch	Jan Revenue ■	Feb Revenue ■	Mar Revenue ■	Rating	Mgr Name
Koramangala	4	52000	48000	4.2	Suresh
Whitefield	3	85000	91000	4.5	Priya

Indiranagar	5	67000	72000	4.1	Rajan
Jayanagar	2	39000	41000	3.9	Kavya
MG Road	6	1	15000	4.8	Anand

Also create a Lookup Table in row 10+:

Month Number	Month Name
1	January
2	February
3	March

■ INDEX — Returns the VALUE at a specific row & column position

`=INDEX(range, row_number, column_number) → picks value at that position`

Get Whitefield's Feb Revenue: =INDEX(B2:F6, 2, 2) → row 2, col 2 = 85000

Get MG Road's rating: =INDEX(B2:F6, 5, 4) → row 5, col 4 = 4.8

■ MATCH — Returns the POSITION of a value in a range

`=MATCH(lookup_value, lookup_array, 0) → returns position number`

Find position of "Whitefield": =MATCH("Whitefield", A2:A6, 0) → Answer: 2

Find position of "Priya" in managers: =MATCH("Priya", F2:F6, 0) → Answer: 2

■ INDEX+MATCH (the power combo — works like VLOOKUP but better!)

```
=INDEX(return_col, MATCH(lookup_val, search_col, 0))
```

Get Manager of Indiranagar: =INDEX(F2:F6, MATCH("Indiranagar", A2:A6, 0)) → Rajan

Get Feb Revenue of MG Road: =INDEX(C2:C6, MATCH("MG Road", A2:A6, 0)) → 1,15,000

WHY BETTER than VLOOKUP: MATCH can look LEFT, not just right. No column numbers to count!

■ CHOOSE — Picks one value from a list based on a number

`=CHOOSE(index_num, val1, val2, val3...) → picks the Nth option`

Rating label: =CHOOSE(INT(E2), "Poor","Fair","Good","Very Good","Excellent")

For rating 4.2 → INT(4.2) = 4 → CHOOSE picks 4th item → 'Very Good'

Month name from number: =CHOOSE(A11, "Jan","Feb","Mar","Apr","May","Jun","Jul","Aug","Sep","Oct","Nov","Dec")

■ Challenge: In a blank cell, type a branch name. Next to it, show that branch's rating and manager using INDEX+MATCH.

■ *VLOOKUP only looks RIGHT. INDEX+MATCH can look in ANY direction — left, right, up, down. That's why professional Excel users always prefer INDEX+MATCH over VLOOKUP for complex data!*

■ TASK 6 — Bank Loan EMI Calculator (20 minutes)

You want to take a home loan of ■20 lakhs. Calculate the monthly EMI, build the full loan amortisation table (interest vs principal split for each month), and find out what interest rate you'd need for a specific EMI. These are financial formulas used by banks every single day!

■ Set Up Your Loan Details (Sheet: Loan Calculator)

Parameter	Value	Notes
Loan Amount (■)	20,00,000	Principal borrowed
Annual Interest Rate	8.50%	Bank rate
Loan Period (Years)	20	240 months
Monthly Rate (B2/12)	=B2/12	Calculate this
Total Months (B3*12)	=B3*12	Calculate this
Monthly EMI ✍	?	Use PMT formula

Total Payment ✍	?	EMI × Months
Total Interest ✍	?	Total - Principal

■ PMT — Calculate the monthly payment (EMI) for a loan

`=PMT(rate, nper, pv) → rate=monthly rate, nper=total months, pv=loan amount`

Monthly EMI formula: =PMT(B4, B5, -B1) → Note: loan amount is NEGATIVE (money you receive)

Answer: EMI = ■17,398/month for ■20L loan at 8.5% for 20 years

Total payment: =B6*B5 → ■17,398 × 240 = ■41,75,520

Total interest paid: =B7-B1 → 41,75,520 - 20,00,000 = ■21,75,520 (you pay MORE than you borrowed!)

■ IPMT — How much of each EMI is INTEREST

`=IPMT(rate, per, nper, pv) → per = which month number (1, 2, 3...)`

Month 1 interest: =IPMT(B4, 1, B5, -B1) → Answer: ■14,167 (most of EMI is interest!)

Month 240 interest: =IPMT(B4, 240, B5, -B1) → Answer: ■122 (almost all is principal!)

■ PPMT — How much of each EMI is PRINCIPAL repayment

`=PPMT(rate, per, nper, pv) → same structure as IPMT`

Month 1 principal: =PPMT(B4, 1, B5, -B1) → Answer: ■3,231 (small principal initially)

Verify: IPMT + PPMT = PMT (EMI) → 14,167 + 3,231 = 17,398 ✓

■ Build an Amortisation Table for first 6 months:

Month	Opening Balance ■	EMI ■	Interest ■ ✍	Principal ■ ✍	Closing Balance ■
1	20,00,000	17,398	=IPMT(...)	=PPMT(...)	=Opening-Principal
2	=prev closing	17,398	=IPMT(rate,2,nper, pv)	=PPMT(rate,2,nper ,pv)	...
3	...	17,398	...	...	...
4	...	17,398	...	...	...
5	...	17,398	...	...	...
6	...	17,398	...	...	...

■ RATE — Find the interest rate if you know EMI, months, and loan amount

`=RATE(nper, pmt, pv)*12 → gives annual rate (multiply monthly rate by 12)`

If EMI=17,398, months=240, loan=20L: =RATE(240, -17398, 2000000)*12 → should give 8.5%

■ NPER — Find how many months to repay if you pay more EMI

`=NPER(rate, pmt, pv) → returns number of periods needed`

If you pay ■20,000/month: =NPER(B4, -20000, 2000000) → fewer months needed!

■ REAL USE: Banks use PMT to show you the EMI on loan offer letters. IPMT/PPMT data is in your loan statement every month. Mutual fund SIP calculators use NPER to show when you'll reach your goal!

■ TASK 7 — School Attendance System (15 minutes)

A school tracks student attendance with multiple conditions — class, gender, and attendance %. You need to count/sum based on TWO or more conditions simultaneously. COUNTIFS and AVERAGEIFS are the multi-condition versions of COUNTIF and AVERAGEIF.

■ Type This Data (Sheet: Attendance)

Student	Class	Gender	Attendance %	Marks	Pass/Fail
Ravi	10A	M	88	72	Pass
Priya	10B	F	95	88	Pass
Aman	10A	M	62	45	Fail

Sunita	10B	F	91	79	Pass
Rohit	10A	M	74	58	Pass
Kavya	10B	F	85	82	Pass
Deepak	10A	M	55	38	Fail
Meena	10B	F	97	91	Pass
Arjun	10A	M	80	65	Pass
Divya	10B	F	70	60	Pass
Kiran	10A	M	48	30	Fail
Nisha	10B	F	93	85	Pass

■ COUNTIFS — Count rows matching MULTIPLE conditions simultaneously

`=COUNTIFS(range1, criteria1, range2, criteria2, ...)` → `ALL conditions must be true`

How many boys in 10A? =COUNTIFS(B2:B13,"10A", C2:C13,"M") → Answer: 6

Girls with >85% attendance: =COUNTIFS(C2:C13,"F", D2:D13,">85") → Answer: 4

Boys who failed: =COUNTIFS(C2:C13,"M", F2:F13,"Fail") → Answer: 3

10B students with attendance >90%: =COUNTIFS(B2:B13,"10B", D2:D13,">90") → Answer: 3

■ AVERAGEIFS — Average based on MULTIPLE conditions

`=AVERAGEIFS(avg_range, range1, criteria1, range2, criteria2...)`

Avg marks of 10A boys: =AVERAGEIFS(E2:E13, B2:B13,"10A", C2:C13,"M") → 51.3

Avg attendance of passing girls: =AVERAGEIFS(D2:D13, C2:C13,"F", F2:F13,"Pass") → 91.8

■ SUMPRODUCT — Multiplies arrays and sums the results (very powerful!)

`=SUMPRODUCT(array1, array2)` → `multiplies element-by-element then adds all`

Total weighted marks (attendance × marks):

=SUMPRODUCT(D2:D13, E2:E13) → adds up (88×72 + 95×88 + 62×45 + ...)

SUMPRODUCT as conditional count (no COUNTIFS needed!):

=SUMPRODUCT((B2:B13="10A")*(C2:C13="M")) → counts 10A males = 6

Each condition in () creates a 1/0 array. Multiplying them = AND logic. Summing = count!

■ Challenge: Find the average marks of students with attendance BETWEEN 70% and 90%:

=AVERAGEIFS(E2:E13, D2:D13,">=70", D2:D13,"<=90") → sets two conditions on same column!

■ *SUMPRODUCT is the Swiss Army knife of Excel. It can replace COUNTIFS, AVERAGEIFS, and SUMIFS — and it works in older Excel versions too. Professional analysts use it constantly for complex multi-condition calculations!*

■ TASK 8 — Stock Market Portfolio (15 minutes)

You have 6 months of stock price data for 2 companies. You want to measure how consistent/risky each stock is (standard deviation), whether they move together (correlation), and predict the next month's price (forecast). These are the same tools used by financial analysts!

■ Type This Data (Sheet: Stocks)

Month	Infosys Price ■	TCS Price ■	Market Index	Infosys Return %	TCS Return %
Jan-25	1450	3200	22000		
Feb-25	1520	3350	22800		
Mar-25	1480	3180	22400		
Apr-25	1610	3490	23500		
May-25	1590	3420	23200		
Jun-25	1675	3610	24100		

Jul-25 (predict)	?	?	24800		

First: Calculate Monthly Returns in E and F columns:

E3 (Infosys Return from Jan to Feb): =(B3-B2)/B2*100 → (1520-1450)/1450×100 = 4.83%

Copy this formula for all months. Do the same for TCS in column F.

■ STDEV — Standard Deviation: measures how VOLATILE/RISKY an investment is

`=STDEV(range) → high number = more volatile/risky, low = more stable`

Infosys volatility: =STDEV(E3:E7) → if result is 3.2%, Infosys varies by ±3.2% monthly

TCS volatility: =STDEV(F3:F7) → compare: which stock is more stable?

Lower STDEV = safer investment. Higher STDEV = higher risk but maybe higher return!

■ VAR — Variance: the SQUARE of Standard Deviation (used in advanced finance)

`=VAR(range) → =STDEV^2. Used in portfolio theory and risk models.`

=VAR(E3:E7) → gives variance of Infosys returns. Verify: =STDEV(E3:E7)^2 ≈ VAR(E3:E7)

■ CORREL — Correlation: do two stocks move TOGETHER or OPPOSITE?

`=CORREL(array1, array2) → result from -1 to +1`

+1 = move perfectly together (buy one, buy both)

0 = no relationship (independent)

-1 = move opposite (one goes up, other goes down — great for hedging!)

Infosys vs TCS: =CORREL(B2:B7, C2:C7) → likely high positive (both IT stocks)

Infosys vs Index: =CORREL(B2:B7, D2:D7) → correlation with market

■ FORECAST — Predict the NEXT value based on historical trend

`=FORECAST(x, known_ys, known_xs) → x = the new input value to predict for`

Predict Infosys for Jul (month 7): =FORECAST(7, B2:B7, {1,2,3,4,5,6})

Or use FORECAST.LINEAR for the same result:

=FORECAST.LINEAR(7, B2:B7, ROW(A1:A6)) → projects the trend line to month 7

■ Final Challenge: Which stock should you buy?

Average Return: =AVERAGE(E3:E7) vs =AVERAGE(F3:F7) → higher is better

Risk (STDEV): =STDEV(E3:E7) vs =STDEV(F3:F7) → lower is better

Sharpe Ratio: =AVERAGE(return)/STDEV(return) → higher = better risk-adjusted return

■ REAL USE: Mutual fund houses calculate STDEV to show risk ratings (1★ to 5★). CORREL is used to build diversified portfolios. FORECAST powers every demand planning system in retail and manufacturing!

■ ALL 24 FORMULAS — QUICK REFERENCE

Formula	What It Does	Quick Syntax	Task
IFERROR	Show custom text instead of errors	=IFERROR(formula, "Error!")	1
ISBLANK	Check if cell is empty	=ISBLANK(A1) → TRUE/FALSE	1
ISNUMBER	Check if cell has a number	=ISNUMBER(A1) → TRUE/FALSE	1
COUNTA	Count non-empty cells (text + numbers)	=COUNTA(A1:A10)	1
LARGE	Nth highest value	=LARGE(A1:A10, 2)	2
SMALL	Nth lowest value	=SMALL(A1:A10, 2)	2
MEDIAN	Middle value of a dataset	=MEDIAN(A1:A10)	2
PERCENTILE	Value at given percentile	=PERCENTILE(A1:A10, 0.9)	2
ROUND	Round to N decimal places	=ROUND(12.567, 2) = 12.57	3

ROUNDUP	Always round UP	=ROUNDUP(12.01, 0) = 13	3
ROUNDDOWN	Always round DOWN	=ROUNDDOWN(12.99, 0) = 12	3
INT	Remove decimal (whole number only)	=INT(12.9) = 12	3
MOD	Remainder after division	=MOD(11, 4) = 3	3
WORKDAY	Date after N working days	=WORKDAY(A1, 14)	4
NETWORKDAYS	Count working days between dates	=NETWORKDAYS(A1, B1)	4
DAYS360	Days using 360-day year (banking)	=DAYS360(A1, B1)	4
INDEX	Value at row+column position	=INDEX(A1:D10, 3, 2)	5
MATCH	Position of a value in range	=MATCH("Name", A1:A10, 0)	5
CHOOSE	Pick Nth value from a list	=CHOOSE(3,"A","B","C") = C	5
PMT	Monthly loan payment (EMI)	=PMT(rate, nper, -pv)	6
IPMT	Interest portion of EMI	=IPMT(rate, month, nper, -pv)	6
PPMT	Principal portion of EMI	=PPMT(rate, month, nper, -pv)	6
COUNTIFS	Count with multiple conditions	=COUNTIFS(A:A,"X", B:B,">5")	7
AVERAGEIFS	Average with multiple conditions	=AVERAGEIFS(C:C, A:A,"X", B:B,"Y")	7
SUMPRODUCT	Multiply arrays then sum	=SUMPRODUCT(A1:A5, B1:B5)	7
STDEV	Standard deviation (risk/volatility)	=STDEV(A1:A10)	8
VAR	Variance of a dataset	=VAR(A1:A10)	8
CORREL	Correlation between two datasets	=CORREL(A1:A10, B1:B10)	8
FORECAST	Predict next value from trend	=FORECAST(7, B2:B7, {1,2,3,4,5,6})	8