



## Scanning Report

Site: <https://thethrone.in>

Generated on Fri, 4 Apr 2025 16:29:43

### Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	4
Low	5
Informational	5
False Positives:	0

### Summary of Sequences

For each step: result (Pass/Fail) - risk (of highest alert(s) for the step, if any).

### Alerts

Name	Risk Level	Number of Instances
<a href="#">Absence of Anti-CSRF Tokens</a>	Medium	2
<a href="#">CSP: Wildcard Directive</a>	Medium	1
<a href="#">CSP: script-src unsafe-inline</a>	Medium	1
<a href="#">CSP: style-src unsafe-inline</a>	Medium	1
<a href="#">Cookie No HttpOnly Flag</a>	Low	4
<a href="#">Cookie Without Secure Flag</a>	Low	6
<a href="#">Cookie without SameSite Attribute</a>	Low	1
<a href="#">Cross-Domain JavaScript Source File Inclusion</a>	Low	2
<a href="#">Timestamp Disclosure - Unix</a>	Low	15
<a href="#">Information Disclosure - Suspicious Comments</a>	Informational	1
<a href="#">Modern Web Application</a>	Informational	1
<a href="#">Re-examine Cache-control Directives</a>	Informational	1
<a href="#">Retrieved from Cache</a>	Informational	1
<a href="#">Session Management Response Identified</a>	Informational	1

### Alert Detail

Medium	Absence of Anti-CSRF Tokens
--------	-----------------------------

Description	<p>No Anti-CSRF tokens were found in a HTML submission form.</p> <p>A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL/form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf.</p> <p>CSRF attacks are effective in a number of situations, including:</p> <ul style="list-style-type: none"> <li>* The victim has an active session on the target site.</li> <li>* The victim is authenticated via HTTP auth on the target site.</li> <li>* The victim is on the same local network as the target site.</li> </ul> <p>CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.</p>
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	<form action="/cart" id="CartDrawer-Form" class="cart__contents cart-drawer__form" method="post" >
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token] was found in the following HTML form: [Form 1: "" ].
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	<form method="post" action="/contact#ContactFooter" id="ContactFooter" accept-charset="UTF-8" class="footer__newsletter newsletter-form">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token] was found in the following HTML form: [Form 3: "contact[tags]" "form_type" "NewsletterForm--sections-23415186129206__footer" "utf8" ].
Instances	2

Solution	Phase: Architecture and Design
	Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.
	For example, use anti-CSRF packages such as the OWASP CSRFGuard.
	Phase: Implementation
	Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script.
	Phase: Architecture and Design
	Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330).
	Note that this can be bypassed using XSS.
	Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation.
	Note that this can be bypassed using XSS.
Reference	Use the ESAPI Session Management control.
	This control includes a component for CSRF.
	Do not use the GET method for any request that triggers a state change.
	Phase: Implementation
	Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.
	<a href="https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html">https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html</a>
	<a href="https://cwe.mitre.org/data/definitions/352.html">https://cwe.mitre.org/data/definitions/352.html</a>
	CWE Id
	352
	WASC Id
	9
	Plugin Id
	10202

Medium	CSP: Wildcard Directive
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	content-security-policy
Attack	
Evidence	block-all-mixed-content; frame-ancestors 'none'; upgrade-insecure-requests;
Other Info	The following directives either allow wildcard sources (or ancestors), are not defined, or are overly broadly defined: script-src, style-src, img-src, connect-src, frame-src, font-src, media-src, object-src, manifest-src, worker-src, form-action The directive(s): form-action are among the directives that do not fallback to default-src, missing/excluding them is the same as allowing anything.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	<a href="https://www.w3.org/TR/CSP/">https://www.w3.org/TR/CSP/</a> <a href="https://caniuse.com/#search=content+security+policy">https://caniuse.com/#search=content+security+policy</a> <a href="https://content-security-policy.com/">https://content-security-policy.com/</a> <a href="https://github.com/HtmlUnit/htmlunit-csp">https://github.com/HtmlUnit/htmlunit-csp</a> <a href="https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources">https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources</a>

CWE Id	<a href="#">693</a>
WASC Id	15
Plugin Id	<a href="#">10055</a>

<b>Medium</b>	<b>CSP: script-src unsafe-inline</b>
---------------	--------------------------------------

Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	content-security-policy
Attack	
Evidence	block-all-mixed-content; frame-ancestors 'none'; upgrade-insecure-requests;
Other Info	script-src includes unsafe-inline.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	<a href="https://www.w3.org/TR/CSP/">https://www.w3.org/TR/CSP/</a> <a href="https://caniuse.com/#search=content+security+policy">https://caniuse.com/#search=content+security+policy</a> <a href="https://content-security-policy.com/">https://content-security-policy.com/</a> <a href="https://github.com/HtmlUnit/htmlunit-csp">https://github.com/HtmlUnit/htmlunit-csp</a> <a href="https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources">https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources</a>
CWE Id	<a href="#">693</a>
WASC Id	15
Plugin Id	<a href="#">10055</a>

<b>Medium</b>	<b>CSP: style-src unsafe-inline</b>
---------------	-------------------------------------

Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	content-security-policy
Attack	
Evidence	block-all-mixed-content; frame-ancestors 'none'; upgrade-insecure-requests;
Other Info	style-src includes unsafe-inline.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	<a href="https://www.w3.org/TR/CSP/">https://www.w3.org/TR/CSP/</a> <a href="https://caniuse.com/#search=content+security+policy">https://caniuse.com/#search=content+security+policy</a> <a href="https://content-security-policy.com/">https://content-security-policy.com/</a> <a href="https://github.com/HtmlUnit/htmlunit-csp">https://github.com/HtmlUnit/htmlunit-csp</a> <a href="https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources">https://developers.google.com/web/fundamentals/security/csp#policy_applies_to_a_wide_variety_of_resources</a>
CWE Id	<a href="#">693</a>
WASC Id	15
Plugin Id	<a href="#">10055</a>

<b>Low</b>	<b>Cookie No HttpOnly Flag</b>
------------	--------------------------------

Description	A cookie has been set without the HttpOnly flag, which means that the cookie can be accessed by JavaScript. If a malicious script can be run on this page then the cookie will be accessible and can be transmitted to another site. If this is a session cookie then session hijacking may be possible.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_shopify_s
Attack	
Evidence	set-cookie: _shopify_s
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_shopify_y
Attack	
Evidence	set-cookie: _shopify_y
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_tracking_consent
Attack	
Evidence	set-cookie: _tracking_consent
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	localization
Attack	
Evidence	set-cookie: localization
Other Info	
Instances	4
Solution	Ensure that the HttpOnly flag is set for all cookies.
Reference	<a href="https://owasp.org/www-community/HttpOnly">https://owasp.org/www-community/HttpOnly</a>
CWE Id	<a href="#">1004</a>
WASC Id	13
Plugin Id	<a href="#">10010</a>

<b>Low</b>	<b>Cookie Without Secure Flag</b>
Description	A cookie has been set without the secure flag, which means that the cookie can be accessed via unencrypted connections.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_landing_page
Attack	
Evidence	set-cookie: _landing_page
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_orig_referrer
Attack	
Evidence	set-cookie: _orig_referrer

Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_shopify_s
Attack	
Evidence	set-cookie: _shopify_s
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_shopify_y
Attack	
Evidence	set-cookie: _shopify_y
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_tracking_consent
Attack	
Evidence	set-cookie: _tracking_consent
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	localization
Attack	
Evidence	set-cookie: localization
Other Info	
Instances	6
Solution	Whenever a cookie contains sensitive information or is a session token, then it should always be passed using an encrypted channel. Ensure that the secure flag is set for cookies containing such sensitive information.
Reference	<a href="https://owasp.org/www-project-web-security-testing-guide/v41/4-Web_Application_Security_Testing/06-Session_Management_Testing/02-Testing_for_Cookies_Attributes.html">https://owasp.org/www-project-web-security-testing-guide/v41/4-Web_Application_Security_Testing/06-Session_Management_Testing/02-Testing_for_Cookies_Attributes.html</a>
CWE Id	<a href="#">614</a>
WASC Id	13
Plugin Id	<a href="#">10011</a>

<b>Low</b>	<b>Cookie without SameSite Attribute</b>
Description	A cookie has been set without the SameSite attribute, which means that the cookie can be sent as a result of a 'cross-site' request. The SameSite attribute is an effective counter measure to cross-site request forgery, cross-site script inclusion, and timing attacks.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	localization
Attack	
Evidence	set-cookie: localization
Other Info	
Instances	1
Solution	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.
Reference	<a href="https://tools.ietf.org/html/draft-ietf-httpbis-cookie-same-site">https://tools.ietf.org/html/draft-ietf-httpbis-cookie-same-site</a>
CWE Id	<a href="#">1275</a>

WASC Id	13
Plugin Id	<a href="#">10054</a>

Low	Cross-Domain JavaScript Source File Inclusion
Description	The page includes one or more script files from a third-party domain.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	https://unpkg.com/@google/model-viewer/dist/model-viewer-legacy.js
Attack	
Evidence	<script nomodule src="https://unpkg.com/@google/model-viewer/dist/model-viewer-legacy.js"></script>
Other Info	
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	https://unpkg.com/@google/model-viewer/dist/model-viewer.js
Attack	
Evidence	<script type="module" src="https://unpkg.com/@google/model-viewer/dist/model-viewer.js"></script>
Other Info	
Instances	2
Solution	Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.
Reference	
CWE Id	<a href="#">829</a>
WASC Id	15
Plugin Id	<a href="#">10017</a>

Low	Timestamp Disclosure - Unix
Description	A timestamp was disclosed by the application/web server. - Unix
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1478001846
Other Info	1478001846, which evaluates to: 2016-11-01 17:34:06.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729863339
Other Info	1729863339, which evaluates to: 2024-10-25 19:05:39.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729869869
Other Info	1729869869, which evaluates to: 2024-10-25 20:54:29.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	

Attack	
Evidence	1729869923
Other Info	1729869923, which evaluates to: 2024-10-25 20:55:23.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729871768
Other Info	1729871768, which evaluates to: 2024-10-25 21:26:08.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729871915
Other Info	1729871915, which evaluates to: 2024-10-25 21:28:35.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729875707
Other Info	1729875707, which evaluates to: 2024-10-25 22:31:47.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729875746
Other Info	1729875746, which evaluates to: 2024-10-25 22:32:26.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729877982
Other Info	1729877982, which evaluates to: 2024-10-25 23:09:42.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729878089
Other Info	1729878089, which evaluates to: 2024-10-25 23:11:29.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1729943922
Other Info	1729943922, which evaluates to: 2024-10-26 17:28:42.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET



Parameter	
Attack	
Evidence	1742395481
Other Info	1742395481, which evaluates to: 2025-03-19 20:14:41.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	1743763605
Other Info	1743763605, which evaluates to: 2025-04-04 16:16:45.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	server-timing
Attack	
Evidence	1743764386
Other Info	1743764386, which evaluates to: 2025-04-04 16:29:46.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	x-request-id
Attack	
Evidence	1743764386
Other Info	1743764386, which evaluates to: 2025-04-04 16:29:46.
Instances	15
Solution	Manually confirm that the timestamp data is not sensitive, and that the data cannot be aggregated to disclose exploitable patterns.
Reference	<a href="https://cwe.mitre.org/data/definitions/200.html">https://cwe.mitre.org/data/definitions/200.html</a>
CWE Id	<a href="#">497</a>
WASC Id	13
Plugin Id	<a href="#">10096</a>

Informational	Information Disclosure - Suspicious Comments
Description	The response appears to contain suspicious comments which may help an attacker.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	from
Other Info	The following pattern was used: \bFROM\b and was detected in likely comment: "///cdn.shopify.com/shopifycloud/storefront-forms-hcaptcha/ce_storefront_forms_captcha_hcaptcha.v1.5.2.iife.js',D={infoText:'Prote", see evidence field for the suspicious comment/snippet.
Instances	1
Solution	Remove all comments that return information that may help an attacker and fix any underlying problems they refer to.
Reference	
CWE Id	<a href="#">615</a>
WASC Id	13
Plugin Id	<a href="#">10027</a>

Informational	Modern Web Application
---------------	------------------------

Description	The application appears to be a modern web application. If you need to explore it automatically then the Ajax Spider may well be more effective than the standard one.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	<a class="frontpage-menu-link" href=""></a>
Other Info	Links have been found that do not have traditional href attributes, which is an indication that this is a modern web application.
Instances	1
Solution	This is an informational alert and so no changes are required.
Reference	
CWE Id	
WASC Id	
Plugin Id	<a href="#">10109</a>

Informational	Re-examine Cache-control Directives
Description	The cache-control header has not been set properly or is missing, allowing the browser and proxies to cache content. For static assets like css, js, or image files this might be intended, however, the resources should be reviewed to ensure that no sensitive content will be cached.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	cache-control
Attack	
Evidence	
Other Info	
Instances	1
Solution	For secure content, ensure the cache-control HTTP header is set with "no-cache, no-store, must-revalidate". If an asset should be cached consider setting the directives "public, max-age, immutable".
Reference	<a href="https://cheatsheetseries.owasp.org/cheatsheets/Session_Management_Cheat_Sheet.html#web-content-caching">https://cheatsheetseries.owasp.org/cheatsheets/Session_Management_Cheat_Sheet.html#web-content-caching</a> <a href="https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Cache-Control">https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Cache-Control</a> <a href="https://grayduck.mn/2021/09/13/cache-control-recommendations/">https://grayduck.mn/2021/09/13/cache-control-recommendations/</a>
CWE Id	<a href="#">525</a>
WASC Id	13
Plugin Id	<a href="#">10015</a>

Informational	Retrieved from Cache
Description	The content was retrieved from a shared cache. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	
Attack	
Evidence	hit
Other Info	
Instances	1

Solution	<p>Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user:</p> <p>Cache-Control: no-cache, no-store, must-revalidate, private</p> <p>Pragma: no-cache</p> <p>Expires: 0</p> <p>This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.</p>
Reference	<a href="https://tools.ietf.org/html/rfc7234">https://tools.ietf.org/html/rfc7234</a> <a href="https://tools.ietf.org/html/rfc7231">https://tools.ietf.org/html/rfc7231</a> <a href="https://www.rfc-editor.org/rfc/rfc9110.html">https://www.rfc-editor.org/rfc/rfc9110.html</a>
CWE Id	
WASC Id	
Plugin Id	<a href="#">10050</a>

Informational	Session Management Response Identified
Description	The given response has been identified as containing a session management token. The 'Other Info' field contains a set of header tokens that can be used in the Header Based Session Management Method. If the request is in a context which has a Session Management Method set to "Auto-Detect" then this rule will change the session management to use the tokens identified.
URL	<a href="https://thethrone.in/">https://thethrone.in/</a>
Method	GET
Parameter	_shopify_y
Attack	
Evidence	478917C0-76ed-444A-b78d-07f7f6e2af0f
Other Info	cookie:_shopify_y cookie:_shopify_s cookie:_tracking_consent
Instances	1
Solution	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Reference	<a href="https://www.zaproxy.org/docs/desktop/addons/authentication-helper/session-mgmt-id">https://www.zaproxy.org/docs/desktop/addons/authentication-helper/session-mgmt-id</a>
CWE Id	
WASC Id	
Plugin Id	<a href="#">10112</a>

## Sequence Details

With the associated active scan results.

