

Field Proxy — CRM Integration

API Document — Customer (Lead) & Visit APIs exposed by Field Proxy

Prepared by Field Proxy · Version 0.1 (Draft) · Confidential — for authorized use only

Version History

Version	Changes By	Description	Date
0.1	Field Proxy	Initial draft — Auth + Customer & Visit Insert / Update / Upsert	16-Jul-2026

1. Overview & Conventions

This document specifies the APIs Field Proxy exposes so the Anand Rathi CRM system can exchange **customer (lead)** and **visit** data with Field Proxy. It mirrors the E-HR Integration API Document — the same authentication and AES-256 conventions apply. Customer and visit records flow in via the endpoints below; the same records are available to be read back for two-way sync.

Global conventions apply to every endpoint:

Field	Value
Base URL	https://api-anandrathi.fieldproxy.ai (per env: api-anandrathi.sit / .uat / .fieldproxy.ai)
Transport	HTTPS only (TLS 1.2+). Endpoints are served ONLY on the host above.
Encryption	AES-256-CBC, PKCS7 padding, Base64. Key = 32 bytes, IV = 16 bytes; issued by Field Proxy per environment.
Request body	application/json → { "data": "<Base64 ciphertext>" }
Authorization	Authorization: Bearer <JWT> (from /crm/auth). Token is valid 1 minute.
Response envelope	{ result, resultMessage, resultData }
Result enum	0 = Error, 1 = Success, 2 = Info, 3 = Warning, 4 = Attention
Batch + partial success	Insert/Update/Upsert accept a JSON array; each object is validated independently; valid rows apply, invalid rows are reported (never a whole-batch rollback).

2. Onboarding Parameters

Parameter	Provided by
Base URLs (per SIT / UAT / PROD)	Field Proxy
Username / Password / AppCode (to call /crm/auth)	Field Proxy
AES-256 Key + IV (32 B / 16 B, base64), per environment	Field Proxy
Source IP ranges (for the ingress allowlist)	Anand Rathi (CRM)
Final customer / visit field definitions & additional columns	Anand Rathi (CRM)

3. Authentication API

Field	Value
Title	Field Proxy CRM Authentication API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/auth
Method	POST
Headers	Content-Type: application/json
Body	AES-256 encrypted + Base64 of the request model, wrapped as { "data": "..."} }

Request model (decrypted)

```
{
  "Username": "string",
  "Password": "string",
  "AppCode": "string"
}
```

Sample (decrypted, then wire body)

```
{ "Username": "AnandRathi_CRM", "Password": "*****", "AppCode": "FPAPP1001" }

// on the wire:
{ "data": "<AES-256-CBC/PKCS7/Base64 of the JSON above>" }
```

Responses

```
// success
{ "result": 1, "resultMessage": "Token generated successfully", "resultData":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..." }

// invalid credentials
{ "result": 3, "resultMessage": "Username or password is invalid", "resultData":
null }

// error
{ "result": 0, "resultMessage": "Exception message", "resultData": null }
```

- resultData is the JWT Bearer token; valid 1 minute. Re-authenticate immediately before each Customer/Visit call.
- The same auth mechanism as the E-HR API; a single AppCode may be issued for both CRM and E-HR, or scoped separately.

4. Customer Insert API

Field	Value
Title	Field Proxy CRM Customer Insert API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/customer/insert
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	AES-256 encrypted + Base64 of a JSON array of customer objects, wrapped as { "data": "..."} }
Description	Creates new customers. Matched on CustomerId; a row whose CustomerId already exists is rejected.

Request model (decrypted)

```
[
  {
    "CustomerId": "String",
    "CustomerName": "String",
    "CustomerType": "String",
    "CustomerStage": "String",
    "Status": "String",
    "PocName": "String",
    "ContactNumber": "String",
    "EmailId": "String",
    "LocationAddress": "String",
    "Area": "String",
    "Region": "String",
    "Pincode": "String",
    "Brand": "String",
    "Remarks": "String",
    "OwnerEmpCode": "String",
    "Longitude": "String",
    "Latitude": "String",
    "OnboardedOn": "Datetime"
  }
]
```

Responses

```
// success
{ "result": 1, "resultMessage": "Data Inserted Successfully",
  "resultData": { "received": 2, "inserted": 2, "skipped": 0, "errors": [] } }

// partial success
{ "result": 1, "resultMessage": "Partial Data Inserted Successfully",
  "resultData": { "received": 2, "inserted": 1, "skipped": 1,
    "errors": [ { "index": 1, "customerId": "CUST00042", "message": "CustomerId
already exists" } ] } }

// validation failed (nothing applied) → result 3      // error / bad payload /
token expired → result 0
```

5. Customer Update API

Field	Value
Title	Field Proxy CRM Customer Update API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/customer/update
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	Same shape as Customer Insert (encrypted array, wrapped as { "data": "..."}).
Description	Updates existing customers. Matched on CustomerId; unknown rows are rejected. Only supplied fields are updated.

```
{ "result": 1, "resultMessage": "Data Updated Successfully",
  "resultData": { "received": 3, "updated": 3, "skipped": 0, "errors": [] } }
```

6. Customer Upsert API

Field	Value
Title	Field Proxy CRM Customer Upsert API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/customer/upsert
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	Same shape as Customer Insert.
Description	Insert-or-update on CustomerId. Recommended for the first cutover / full-snapshot feed; use Insert + Update for steady-state deltas.

7. Visit Insert API

Field	Value
Title	Field Proxy CRM Visit Insert API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/visit/insert
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	AES-256 encrypted + Base64 of a JSON array of visit objects, wrapped as { "data": "..."} }
Description	Creates new visits. Matched on VisitId; VisitCustomerId must reference an existing customer.

Request model (decrypted)

```
[
  {
    "VisitId": "String",
    "CustomerId": "String",
    "VisitTitle": "String",
    "VisitType": "String",
    "VisitStatus": "String",
    "VisitDate": "Datetime",
    "ScheduledDate": "Datetime",
    "CheckInTime": "Datetime",
    "CheckInLongitude": "String",
    "CheckInLatitude": "String",
    "CheckInAddress": "String",
    "CheckOutTime": "Datetime",
    "CheckOutLongitude": "String",
    "CheckOutLatitude": "String",
    "CheckOutAddress": "String",
    "VisitRemarks": "String",
    "RemarksEndOfVisit": "String",
    "TotalVisitMinutes": "Number",
    "VisitEmpCode": "String"
  }
]
```

Responses

```
{ "result": 1, "resultMessage": "Data Inserted Successfully",
  "resultData": { "received": 5, "inserted": 5, "skipped": 0, "errors": [] } }
```

8. Visit Update API

Field	Value
Title	Field Proxy CRM Visit Update API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/visit/update
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	Same shape as Visit Insert.
Description	Updates existing visits (e.g. check-out, status, end-of-visit remarks). Matched on VisitId.

9. Visit Upsert API

Field	Value
Title	Field Proxy CRM Visit Upsert API
Request URL	POST https://api-anandrathi.fieldproxy.ai/crm/visit/upsert
Method	POST
Headers	Authorization: Bearer <JWT> · Content-Type: application/json
Body	Same shape as Visit Insert.
Description	Insert-or-update on VisitId. Recommended for full-snapshot feeds.

10. Customer Field Reference

Required/optional flags are recommended defaults and are configurable per tenant. PII fields are encrypted in transit (whole-payload AES) and access-controlled at rest. DB column is shown for implementation reference.

Field	Required	PII	Description (DB column)
CustomerId	Yes	No	Unique key. Insert rejects an existing id; Update/Upsert match on it. (customerid)
CustomerName	Yes	Yes	Customer / lead name. (customer_name)
CustomerType	Yes	No	Retail, Wholesale, Corporate, Distributor, Other. (customer_type)
CustomerStage	Yes	No	Lead, Prospect, Qualified, Negotiation, Won, Lost. (customer_stage)
Status	No	No	Active / Inactive. (status)
PocName	No	Yes	Point-of-contact name. (poc_name)
ContactNumber	Yes	Yes	Contact phone. (contact_number)
EmailId	No	Yes	Contact email. (customer_email_id)
LocationAddress	No	No	Full address. (location_address)
Area / Region / Pincode	No	No	Location breakdown. (area, region, pincode)
Brand	No	No	Brand / product interest. (brand)
Remarks	No	No	Free-text notes. (remarks)
OwnerEmpCode	Yes	No	Owning field rep (employee code). (employee)
Longitude / Latitude	No	No	Customer geo-coordinates. (customer_location)
OnboardedOn	No	No	Onboarding date. (onboarded_on / onboarded_by)

11. Visit Field Reference

Field	Required	PII	Description (DB column)
VisitId	Yes	No	Unique key. (visit_id)
CustomerId	Yes	No	Customer this visit belongs to. (customerid)
VisitTitle	Yes	No	Visit purpose / title. (visit_title)
VisitType	Yes	No	New Business, Follow-up, Product Demo, Service Call, Negotiation, Closing, Other. (visit_type)
VisitStatus	No	No	Scheduled, in_progress, Completed. (visit_status)
VisitDate	No	No	Actual visit date/time. (visit_date)
ScheduledDate	No	No	Planned date (for scheduled visits). (visit_scheduled_date)
CheckInTime	No	No	Check-in time. (check_in_time)
CheckInLongitude / Latitude	No	No	Check-in geo. (check_in_location)
CheckInAddress	No	No	Check-in address. (check_in_address)
CheckOutTime	No	No	Check-out time. (check_out_time)
CheckOutLongitude / Latitude	No	No	Check-out geo. (check_out_location)
CheckOutAddress	No	No	Check-out address. (check_out_address)
VisitRemarks	No	No	Notes at start of visit. (visit_remarks)
RemarksEndOfVisit	No	No	End-of-visit notes. (remarks_eov)
TotalVisitMinutes	No	No	Duration in minutes. (total_visit_time)
VisitEmpCode	Yes	No	Field rep who made the visit. (visit_employee)

12. Result Codes

ResultType	Value
Error	0
Success	1
Info	2
Warning	3
Attention	4

13. Security

- HTTPS only; the partner endpoints are served exclusively on `api-anandrathi.fieldproxy.ai` and are IP-allowlisted to Anand Rathi CRM source ranges.
- AES-256 key/IV and partner credentials are held in Field Proxy's encrypted secret store, referenced by name; rotated per environment.
- A VAPT (security pen-test) will be completed before production, targeting these inbound endpoints.

Recommended crypto hardening (for both directions):

- Use a per-message random IV prepended to the ciphertext instead of a fixed shared IV — a static IV in CBC leaks equality of identical plaintexts.
- Add a MAC (or move to AES-256-GCM) so tampering is detected; CBC alone is unauthenticated.

14. Notes & Open Items

- Field names above are the proposed API contract; the final customer/visit field list is to be confirmed with Anand Rathi CRM (additional columns can be added).
- Keys, credentials and real base URLs are exchanged per environment (SIT / UAT / PROD) during onboarding.
- Two-way sync: the same customer/visit records are available to be read back (rep edits pushed from Field Proxy). A read/pull endpoint can be added on the same conventions if required.
- `resultData` carries structured counts + per-row errors so the CRM can reconcile exactly which rows applied; it can be reduced to the minimal shape on request.