

PROJECT 1

NAME: Nandhini V

DATE: 08-08-2025

Task:

project:

- Create an MVC Web app with the ability to add a food (or) cloth product and view in the table.

Code:

Food.cs

```
using System.ComponentModel.DataAnnotations;
```

```
namespace Day5DailyTask.Models
{
    public class Food
    {
        public int Id { get; set; }
        public string Name { get; set; }
        public string Category { get; set; }
        public int Price { get; set; }
        public int Quantity { get; set; }
    }
}
```

CreateEditFood.cshtml

```
@{
    ViewData["Title"] = "Create/Edit Food";
}

@model Day5DailyTask.Models.Food

<div class="text-center">
    <h1 class="display-4">Create/Edit Food</h1>
</div>
```

```

<form asp-action="AddFood">
  <label class="mt-4">Name</label>
  <input class="form-control" type="text" placeholder="Enter food name" asp-for="Name" />

  <label class="mt-4">Category</label>
  <input class="form-control" type="text" placeholder="Enter food category" asp-for="Category"
/>

  <label class="mt-4">Price</label>
  <input class="form-control" type="number" step="0.01" placeholder="Enter price"
asp-for="Price" />

  <label class="mt-4">Quantity</label>
  <input class="form-control" type="number" placeholder="Enter quantity" asp-for="Quantity" />

  <button class="btn btn-primary mt-4" type="submit">Save</button>
</form>

```

Foods.cshtml

```

@{
  ViewData["Title"] = "Food Page";
}

@model List<Food>

<div class="text-center">
  <h1 class="display-4">Welcome to Our Foods</h1>
  <a asp-controller="Home" asp-action="CreateEditFood" class="btn btn-primary mt-3
mb-3">Add Food</a>
  <br />
  @* Total Number of Foods: @ViewData["tot_food"] *@
  <table class="table">
    <thead>
      <tr>
        <th>
          Food Name
        </th>
        <th>
          Category
        </th>
        <th>
          Price
        </th>
        <th>
          Quantity Available
        </th>

```

```

        <th>
            Action
        </th>
    </tr>
</thead>
<tbody>
    @foreach (var food in Model)
    {
        <tr>
            <td>@food.Name</td>
            <td>@food.Category</td>
            <td>@food.Price</td>
            <td>@food.Quantity</td>
            <td>
                <a asp-action="DeleteFood" asp-route-id="@food.Id">Remove</a>
                <a asp-action="EditFood" asp-route-id="@food.Id">Edit</a>
            </td>
        </tr>
    }
</tbody>
</table>
</div>

```

EditFood.cshtml

```

@{
    ViewData["Title"] = "Edit Food Page";
}
@model Day5DailyTask.Models.Food

<h2 class="mt-4 mb-4">Edit Food</h2>

<form asp-action="EditFood">
    <input type="hidden" asp-for="Id" />

    <div>
        <label asp-for="Name"></label>
        <input asp-for="Name" class="form-control mb-4" />
    </div>

    <div>
        <label asp-for="Category"></label>
        <input asp-for="Category" class="form-control mb-4" />
    </div>

    <div>
        <label asp-for="Price"></label>
        <input asp-for="Price" type="number" class="form-control mb-4" />
    </div>

```

```

</div>

<div>
    <label asp-for="Quantity"></label>
    <input asp-for="Quantity" class="form-control mb-4" />
</div>

<button type="submit" class="btn btn-primary mt-4">Save Changes</button>
</form>

```

AppDbContext.cs

```

using System;
using Day5DailyTask.Models;
using Microsoft.EntityFrameworkCore;

namespace Day5DailyTask.Context
{
    public class AppDbContext : DbContext
    {
        public AppDbContext(DbContextOptions<AppDbContext> options) : base(options)
        {
        }

        public DbSet<Food> Foods { get; set; }
    }
}

```

HomeController.cs

```

using Day5DailyTask.Context;
using Day5DailyTask.Models;
using Microsoft.AspNetCore.Mvc;
using System;
using System.Diagnostics;

namespace Day5DailyTask.Controllers
{
    public class HomeController : Controller
    {
        private AppDbContext AppDbContext { get; set; }

        public HomeController(ILogger<HomeController> logger, AppDbContext appDbContext)

```

```

{
    AppDbContext = appDbContext;
}

public IActionResult EditFood(int id)
{
    var food = AppDbContext.Foods.FirstOrDefault(s => s.Id == id);
    if (food == null)
    {
        return NotFound();
    }
    return View(food);
}

[HttpPost]
public IActionResult EditFood(Food food)
{
    if (ModelState.IsValid)
    {
        AppDbContext.Foods.Update(food);
        AppDbContext.SaveChanges();
        return RedirectToAction("Foods");
    }
    return View(food);
}

public IActionResult DeleteFood(int id)
{
    var food = AppDbContext.Foods.FirstOrDefault(s => s.Id == id);
    if (food != null)
    {
        AppDbContext.Foods.Remove(food);
        AppDbContext.SaveChanges();
    }
    return RedirectToAction("Foods");
}

public IActionResult AddFood(Food fd)
{
    AppDbContext.Foods.Add(fd);
    AppDbContext.SaveChanges();
    return RedirectToAction("Foods");
}

public IActionResult Foods()
{
    var allFoods = AppDbContext.Foods.ToList();
    //var total_emp = allFoods.Sum(s => s.No_of_Emp);
    //ViewBag.total_emp = total_emp;
    //ViewData["tot_emp"] = total_emp;
    return View(allFoods);
}

```

```

    }

    public IActionResult CreateEditFood()
    {
        return View();
    }

    public IActionResult Index()
    {
        return View();
    }

    public IActionResult Privacy()
    {
        return View();
    }

    [ResponseCache(Duration = 0, Location = ResponseCacheLocation.None, NoStore =
true)]
    public IActionResult Error()
    {
        return View(new ErrorViewModel { RequestId = Activity.Current?.Id ??
HttpContext.TraceIdentifier });
    }
}

```

Program.cs

```

using Day5DailyTask.Context;
using Microsoft.EntityFrameworkCore;

var builder = WebApplication.CreateBuilder(args);

// Add services to the container.
builder.Services.AddControllersWithViews();

const string connectionString =
    "Data Source = PTSQLTESTDB01;" +
    "Initial Catalog = Nandhini_Demo;" +
    "Integrated Security = true;" +
    "TrustServerCertificate = true;";

builder.Services.AddDbContext<AppDbContext>(x => x.UseSqlServer(connectionString));

var app = builder.Build();

// Configure the HTTP request pipeline.

```

```

if (!app.Environment.IsDevelopment())
{
    app.UseExceptionHandler("/Home/Error");
}
app.UseStaticFiles();

app.UseRouting();

app.UseAuthorization();

app.MapControllerRoute(
    name: "default",
    pattern: "{controller=Home}/{action=Index}/{id?}");

app.Run();

```

_Layout.cshtml

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>@ViewData["Title"] - Day5DailyTask</title>
    <link rel="stylesheet" href="~/lib/bootstrap/dist/css/bootstrap.min.css" />
    <link rel="stylesheet" href="~/css/site.css" asp-append-version="true" />
    <link rel="stylesheet" href="~/Day5DailyTask.styles.css" asp-append-version="true" />
</head>
<body>
    <header>
        <nav class="navbar navbar-expand-sm navbar-toggleable-sm navbar-light bg-white
border-bottom box-shadow mb-3">
            <div class="container-fluid">
                <a class="navbar-brand" asp-area="" asp-controller="Home"
asp-action="Index">Day5DailyTask</a>
                <button class="navbar-toggler" type="button" data-bs-toggle="collapse"
data-bs-target=".navbar-collapse" aria-controls="navbarSupportedContent"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-icon"></span>
                </button>
                <div class="navbar-collapse collapse d-sm-inline-flex justify-content-between">
                    <ul class="navbar-nav flex-grow-1">
                        <li class="nav-item">
                            <a class="nav-link text-dark" asp-area="" asp-controller="Home"
asp-action="Index">Home</a>
                        </li>
                        <li class="nav-item">

```

```

        <a class="nav-link text-dark" asp-area="" asp-controller="Home"
asp-action="Foods">Foods</a>
    </li>
    <li class="nav-item">
        <a class="nav-link text-dark" asp-area="" asp-controller="Home"
asp-action="Privacy">Privacy</a>
    </li>
</ul>
</div>
</div>
</nav>
</header>
<div class="container">
    <main role="main" class="pb-3">
        @RenderBody()
    </main>
</div>

<footer class="border-top footer text-muted">
    <div class="container">
        &copy; 2025 - Day5DailyTask - <a asp-area="" asp-controller="Home"
asp-action="Privacy">Privacy</a>
    </div>
</footer>
<script src="~/lib/jquery/dist/jquery.min.js"></script>
<script src="~/lib/bootstrap/dist/js/bootstrap.bundle.min.js"></script>
<script src="~/js/site.js" asp-append-version="true"></script>
    @await RenderSectionAsync("Scripts", required: false)
</body>
</html>

```

Index.cshtml

```

@{
    ViewData["Title"] = "Home Page";
}

<div class="text-center">
    <h1 class="display-4">Welcome to Food Fiesta</h1>
    <a asp-controller="Home" asp-action="Foods" class="btn btn-primary mt-4">Foods</a>
</div>

```


Output:

Home Page

Day5DailyTask

Home

Foods

Privacy

Welcome to Food Fiesta

Foods

© 2025 - Day5DailyTask - [Privacy](#)

Food Menu Page

Day5DailyTask

Home

Foods

Privacy

Welcome to Our Foods

Add Food

Food Name	Category	Price	Quantity Available	Action
Pasta	Italian	120	12	Remove Edit
Chicken Burger(Zinger)	American	200	10	Remove Edit
Chicken Fried Rice	Chinese	80	8	Remove Edit
Pizza	Italian	150	7	Remove Edit

© 2025 - Day5DailyTask - [Privacy](#)

Add Food Page

Day5DailyTask Home Foods Privacy

Create/Edit Food

Name

Enter food name

Category

Enter food category

Price

Enter price

Quantity

Enter quantity

Save

© 2025 - Day5DailyTask - [Privacy](#)

Entering Values

Day5DailyTask Home Foods Privacy

Create/Edit Food

Name

Tacos

Category

Mexican

Price

100

Quantity

6

Save

© 2025 - Day5DailyTask - [Privacy](#)

After adding - Food Menu

Day5DailyTask [Home](#) [Foods](#) [Privacy](#)

Welcome to Our Foods

Add Food

Food Name	Category	Price	Quantity Available	Action
Pasta	Italian	120	12	Remove Edit
Chicken Burger(Zinger)	American	200	10	Remove Edit
Chicken Fried Rice	Chinese	80	8	Remove Edit
Pizza	Italian	150	7	Remove Edit
Tacos	Mexican	100	6	Remove Edit

© 2025 - Day5DailyTask - [Privacy](#)

Food Edit Page

Day5DailyTask [Home](#) [Foods](#) [Privacy](#)

Edit Food

Name

Tacos

Category

Mexican

Price

100

Quantity

9

Save Changes

© 2025 - Day5DailyTask - [Privacy](#)

After editing - Food Menu

Day5DailyTask

Home

Foods

Privacy

Welcome to Our Foods

Add Food

Food Name	Category	Price	Quantity Available	Action
Pasta	Italian	120	12	Remove Edit
Chicken Burger(Zinger)	American	200	10	Remove Edit
Chicken Fried Rice	Chinese	80	8	Remove Edit
Pizza	Italian	150	7	Remove Edit
Tacos	Mexican	100	9	Remove Edit

© 2025 - Day5DailyTask - [Privacy](#)

After Removing - Food Menu

Day5DailyTask

Home

Foods

Privacy

Welcome to Our Foods

Add Food

Food Name	Category	Price	Quantity Available	Action
Pasta	Italian	120	12	Remove Edit
Chicken Burger(Zinger)	American	200	10	Remove Edit
Chicken Fried Rice	Chinese	80	8	Remove Edit
Pizza	Italian	150	7	Remove Edit

© 2025 - Day5DailyTask - [Privacy](#)

Database - After adding a value

The screenshot shows the SQL Server Enterprise Manager interface. On the left, the Object Explorer displays a tree view of the database structure, including tables, views, and other database objects. The main window displays a SQL query and its results. The query is a SELECT statement that retrieves the top 1000 rows from the [Foods] table in the [Nandhini_Demo] database. The results are displayed in a table with 5 rows and 5 columns: Id, Name, Category, Price, and Quantity.

```
SELECT TOP (1000) [Id]
, [Name]
, [Category]
, [Price]
, [Quantity]
FROM [Nandhini_Demo].[dbo].[Foods]
```

Id	Name	Category	Price	Quantity
1	Pasta	Italian	120	12
2	Chicken Burger(Zinger)	American	200	10
3	Chicken Fried Rice	Chinese	80	8
4	Pizza	Italian	150	7
5	Tacos	Mexican	100	6

Query executed successfully. PTSQLESTDB01 (16.0 RTM) PAYODA\Nandhini.v (67) master 00:00:00 5 rows

Database - After removing a value

The screenshot shows the SQL Server Enterprise Manager interface. On the left, the Object Explorer displays a tree view of the database structure, including tables, views, and other database objects. The main window displays a SQL query and its results. The query is a SELECT statement that retrieves the top 1000 rows from the [Foods] table in the [Nandhini_Demo] database. The results are displayed in a table with 4 rows and 5 columns: Id, Name, Category, Price, and Quantity.

```
SELECT TOP (1000) [Id]
, [Name]
, [Category]
, [Price]
, [Quantity]
FROM [Nandhini_Demo].[dbo].[Foods]
```

Id	Name	Category	Price	Quantity
1	Pasta	Italian	120	12
2	Chicken Burger(Zinger)	American	200	10
3	Chicken Fried Rice	Chinese	80	8
4	Pizza	Italian	150	7

Query executed successfully. PTSQLESTDB01 (16.0 RTM) PAYODA\Nandhini.v (67) master 00:00:00 4 rows