



Decision Manager (DM)

Security Guide

Software Version: 7.3.5

August 2022

Notice

This document contains information that is proprietary to Sapiens International Corporation N.V or any of its affiliates. No part of this publication may be reproduced, modified, or distributed without prior written authorization of Sapiens International Corporation N.V or any of its affiliates. This document is provided as is, without warranty of any kind.

Trademarks

Sapiens International Corporation N.V.® is a registered trademark.

Sapiens Decision™ is a trademark of Sapiens International Corporation N.V.

Other names mentioned in this publication are owned by their respective holders.

Statement of Conditions

The information contained in this document is subject to change without notice. Sapiens International Corporation N.V. and/or any of its affiliates shall not be liable for errors contained herein or for any damage or losses arising out of or in connection with the furnishing, performance, or use of this document or the software supplied with it.

Caution

Any changes or modifications of the software not expressly approved in writing by the manufacturer could void the user's authority to use the application and its warranty.

Document Revision History

Revision	Release Date	Author	Description	Approved by
7.3.5	August 2022	Sapiens DECISION Documentation	Describes security management in the DECISION Manager (DM) system.	DECISION Product Management

Document Authorization

This document is digitally signed and authorized by the Sapiens Decision documentation team. The steps to authenticate the digital certificate are documented in the Index file present in the documentation package. In case of any queries or feedback on the document, send an e-mail to decision_documentation@sapiens.com



Copyright © 2022 by Sapiens International Corporation N.V. All rights reserved.

Contents

1.	Introduction.....	4
2.	DM Security Concept.....	5
2.1	Users, Roles and Permissions	6
3.	Security Configuration Process.....	8
3.1	Creating Permission Groups	10
3.2	Assigning Permission Groups to Roles.....	13
3.3	Assigning Roles to Users	15
3.3.1	Create User	16
3.3.2	User Password Policy	17
3.4	Assigning Users to Communities	19
3.5	Assigning Roles to Users within Communities	21
4.	Security Reports	24
5.	Security Setup Example	24
6.	Private Communities	26
6.1	Private Assets in a Revision	28
6.2	Navigating to and Viewing Private Communities	28
7.	Private Rule Families	29
8.	Approval strategy	32
9.	List of example Roles	35

1. Introduction

Decision Manager (DM) security management ensures that the software is protected from unauthorized or mistaken usage, while enabling proper access to the system for authorized personnel.

A combination of user definitions, roles, and access permissions provides both powerful and flexible control of how and by whom the system is used.

In addition to security configuration on the application level, server-client data transfers may be secured using the SSL (Secure Sockets Layer) encryption protocol.

This guide describes the security configuration process and each component within the process.

Related Documents

For more information about how to use DM, see the *Decision Manager (DM) User Guide*.

For information about the latest DM features and corrections, see the *Decision Manager (DM) Release Notes*.

For information about installing and configuring DM, see the *Decision Manager (DM) Installation and Configuration Guide*.

2. DM Security Concept

Comprehensive DM security is implemented by a combination of mechanisms that together ensure the protection and proper usage of data in the system.

Using access permissions, users are authorized or not authorized to invoke the numerous DM processes and operations.

Each user is assigned to Roles and Communities to permit them to perform business analysis, modeling and other related tasks within the system. A user's role(s) determines the type of functions the user will be assigned and the user's granted set of permissions. Assignment to a Community and the type of active role in that Community determines the user's scope of access to system operations that can be performed within that Community.

When a user invokes an interface component within the system (such as opens a page for an asset, a list, or a function such as exporting a test case) DM client-server communication retrieves authorization data that either allows the operation to proceed or blocks the operation while issuing an appropriate message to the user based on the user's role(s) and Community security assignments.

Access permission in the system is handled in one of the following ways:

- The navigation tree in the main DM Repository page is filtered according to the user's access rights within the Community. If a user does not have access to a Community, the Community itself and its assets will not appear in the navigation tree.
- If a user does not have permission to access a specific action within a Community, but has access to the Community, the specific action will not appear in the relevant page. For example, if a user does not have permission to Complete a Project but has access to the Community in which the Project exists, the user will be able to open the Project, but the Complete option will not appear.
- An action may be disabled (appears in grey) depending on the context of the activity the user is currently performing. This means that the user may have permission to an action but in a specific scenario the action would not be available. For example, the 'Approve' action in Fact Type Model Mapping may be disabled as long as the Fact Type Model Mapping is not in Candidate status.


Note: If a user is denied access to a particular DM component or process due to lack of appropriate permission, the missing permission can be viewed in the *security_denied.log* file.

In various parts of the system, the usage of *Owners* of processes, such as Project approval, comprises yet another authorization tool, whereby only designated owners can approve or reject specific user modeling and execution requests. (See the section on approval strategy in this document.)

2.1 Users, Roles and Permissions

Users, Roles and Permissions in DM have an interdependent relationship, whereby only users who are assigned particular roles, which in turn include the appropriate permissions, can be included in tasks assigned within particular Communities.


The following illustration shows how roles and permissions can overlap among users.



As shown in the illustration, users are assigned roles which include sets of permission groups, which, in turn, contain sets of permissions.

Access privileges are further restricted by Communities, such that a user will only have access to system components within a Community with which the user is associated.

The following illustration shows how association with Communities controls user access in the system.



As shown in the illustration above, users are assigned roles within particular Communities, whereby each lower-level Community inherits users and their associated roles from its parent Community.

This hierarchical security model ensures that only users associated with specific Communities and assigned specific roles within those Communities will be eligible to work on Modeling Tasks, or Fact Type Tasks, when assigned to them by a Modeling Project manager or administrator.


In addition, only users who were assigned appropriate roles will be able to participate in the Repository Task and Approval Strategy processes.

3. Security Configuration Process

DM security configuration is performed by a system administrator in several steps.


Initially, the steps in the process are performed sequentially, but once the initial configuration is done, each step in the process can be performed individually, as required when working in the system.

The configuration process consists of the steps illustrated in the following diagram.




Security configuration steps

The first three steps in the process shown in the diagram above (defining the full set of user roles for each user in the system) are performed via the **Security** option in the **Administration** menu.



Security Option


The last two steps (defining the roles per user per Community - a subset of the user's full set of roles) are performed via the **Communities** option in the **Administration** menu and inherited according to the Community hierarchy.



Communities Option

3.1 Creating Permission Groups


The first step in the security configuration process is to create permission groups.



DM is installed with an unchangeable set of permissions that determine the access rights to different entities and functions in the system. To facilitate the management of these permissions, the administrator is required to combine permissions that have common administration themes into permission groups.


Administrators can create, use, edit or delete predefined permissions groups. There is no restriction on the way the permissions are grouped, but it is recommended to group entity read and write permissions in separate groups.

Permission Groups are defined in the **Permission Groups** tab of the Security Administration page.




Permission Groups Menu Option

The left side of the Permission Groups page lists defined Permission Groups. The right side of the page lists the permissions that are selected for each the Permission Group.




Permission Groups Page

Clicking on a Permission Group name will open the “Manage Permissions in the Permission Group” dialog box. The permissions for the Permission Group can be selected or de-selected in the dialog box. Pressing OK will save the changes. (See the section *Permissions* later in this guide for more information about permission setup.)



Permission Groups Dialog

To create a new Permission Group, click **Add** in the action bar. The “Add New Permission Group” dialog box will open. Type the name of the new Permission Group you want to create in the Permission Group Name and select the permissions for the Permission Group. Press **OK** to save the new Permission Group.



Creating a new Permission Group

The new group is added to the Permission Groups list.


To delete a group, hover over the Permission Group row with your mouse and click the **X** beside the group you want to remove.

Notes:


- You cannot delete a Permission Group if one or more roles are associated with it.
- You cannot delete Permissions.

3.2 Assigning Permission Groups to Roles

The second step in the security configuration process is to associate Permission Groups with Roles.



Click the **Roles** in the Security Administration menu to define and edit user Roles.




Roles Menu Option

The left side of the page lists defined Roles. The right side of the page lists the Permission Groups selected for each Role.

ROLE	PERMISSION GROUPS
Business Owner Approver	All_Search Decision_Approve Decision_Read Query_Write Revision_Read Testing_Read Testing_Write
Community Administrator	All_Search Community_Read Community_Write
Community Viewer	Community_Read
Decision Analyst	All_Search Decision_Read Decision_Write Revision_Read Testing_Write
Decision Analyst Senior	All_Search Decision_Read Decision_Write Dyn_Prop_Write Mtd_Write Revision_Read Revision_Request Testing_Write
Decision Peer Reviewer	All_Search Decision_Read Revision_Read Testing_Write
Decision Viewer	Decision_Read Revision_Read Testing_Read

Roles page

To create a new Role, click **Add** in the action bar. The “Add New Role” dialog box will open to add a new role. Type the name of the new Role you want to create in the Role Name, select the associated Permission Groups for the Role and press **OK** to add the role.



Creating a new role


The new Role is added to the Roles list.

To delete a Role, hover over the Role row with your mouse and press the **X** on the left side of the screen.

Note: You cannot delete a Role if one or more users are associated with it.


3.3 Assigning Roles to Users

The third step in the security configuration process is to create Users and assign them one or more roles.



At this point in the security configuration process, Users can be created, edited or set to 'Inactive'. Users cannot, however, be deleted.

Click the **Users** menu option to define and edit Users.



Users Menu Option

The left side of the page lists defined Users with their Name and User Id. The right side of the page lists the Roles you can add to or remove from a selected User.

NAME	USER ID	COMMUNITIES FOR ROLES
A Decision Analyst #1	da1	Business Owner Approver: Course A Decision Analyst: Course A Glossary Administrator: Course A
A Decision Analyst #2	da2	Decision Analyst: Course A
A Decision Analyst #3	da3	Decision Analyst: Course A
A Decision Analyst #4	da4	Decision Analyst: Course A
A Glossary Administrator	gadmin	Glossary Administrator: WORLD
A Modeling Lead #1	ml1	Business Owner Approver: GOV-UK-ALL, WORLD Decision Analyst: GOV-UK-ALL, WORLD Decision Peer Reviewer: GOV-UK-ALL, WORLD Super User: WORLD XX_BCD Manager: GOV-UK-ALL, WORLD XX_BCR Lead: GOV-UK-ALL, WORLD
A Modeling Lead #2	ml2	Business Owner Approver: WORLD Decision Analyst: WORLD Decision Peer Reviewer: WORLD XX_BCD Manager: WORLD XX_BCR Lead: WORLD
A Modeling Manager #1	mm1	Decision Analyst: WORLD Decision Peer Reviewer: WORLD Deployment Analyst: WORLD XX_BCD Manager: WORLD
A Modeling Manager #2	mm2	Decision Analyst: WORLD Decision Peer Reviewer: WORLD Deployment Analyst: WORLD XX_BCD Manager: WORLD

User Page

3.3.1 Create User

A User is identified by a **User name** and a **Full name** (a descriptive name that appears in the upper right corner of the main DM page when the user logs in).

To create a new User, click **Add** in the action bar to open the add dialog. Type a User Id in the Name field, type the user full name in the Display Name field, and click **Continue**.

Creating a new User

"Name" is the user id needed to log into the system

"Display Name" is the displayed name.

You can optionally specify the User's E-mail address in the **E-mail** field, if you want the User to be able to receive messages related to the User's work activity.

Manage User

The new User is added, and you can add Roles to the User by pressing the **Manage Roles** button and adding the applicable roles in the Manage Roles dialog box and pressing **OK**.

Manage User Roles

To enable or disable User activity in the system, select or deselect the **Active slider** for the User.

The screenshot shows the 'Administration' tab in the SAPIENS Decision interface. Under 'Security > Users', the profile for 'Adam Smith' is displayed. The 'Active' status is shown as a blue slider, which is highlighted with a red square. Other fields include Name (asmith), Display Name (Adam Smith), and Email (asmith@company.com). Below the profile, there are sections for 'ROLES' (listing 'Decision Analyst') and 'COMMUNITIES'.

Active Slider

3.3.2 User Password Policy

The Default password for a new user is "Decision1".

If the user's email is specified on creation of a new user, and e-mail messaging is enabled for Sapiens Decision, a generated random password is sent to that email address. In case an email address is not specified, or the email could not be sent then the default password is set for the user.

A User should change their initial password after their first login and can change their password at any time using the "change password" option:

The screenshot shows the SAPIENS Decision interface with the 'User' dropdown menu open. The 'Change Password' option is highlighted with a red box. Other options in the menu include 'System information', 'Show Server Time', and 'Logout'. The main interface shows a search bar and a 'Recently viewed' list.

User popup menu

The default password policy is described in the popup dialog :

The 'Change Password' dialog box is shown. It includes a 'Password Policy' section with the text: 'Password must be between 8-20 characters and must contain at least one lower-case letter, one capital-case letter and one digit'. Below this are three input fields: 'Old Password: *', 'New Password: *', and 'Confirm Password: *'. At the bottom right are 'Cancel' and 'OK' buttons.

Change Password

The regular expression determining the user password policy is defaulted as follows:

```
(?=^.{8,20}$)(?=.*\\d)(?=.*[a-z])(?=.*[A-Z])(?!.*\\s).*
```

The password regular expression can be changed by editing the system `bmds.cust.property` as follows:

```
password.strength.policy=^(?=.*[a-z])(?=.*[A-Z])(?=.*[0-9])(?=.*[!@#\\$%\\^&\\*()])({8,})
password.strength.policy.description={Description of the policy to show on the
login screen above}
```

Special characters accepted:


```
!
@
#
$
%
^
&
*
(
)
```

For minimum 12 the regular expression would be:



```
password.strength.policy=^(?=.*[a-z])(?=.*[A-Z])(?=.*[0-9])(?=.*[!@#\\$%\\^&\\*()])({12,})
```

3.4 Assigning Users to Communities


The fourth step in the security configuration process is to assign users to one or more Communities.



To assign users to communities, click **Administration** in the menu bar of the main DM page and select a Community in the **Communities** “Select Community” drop down.



Once a Community is selected click on Users to open the Community Users page.



Community Users Menu Option


The Community Users Page provides a list of users, the community they were defined in and the roles they have associated with that community. A user will have access with their defined roles to all communities in the hierarchy below the community they are defined in unless a lower community is defined to not **Inherit User Access** as defined in the **Community General Information** page.

The screenshot shows the 'Users' page in the SAPIENS Decision Manager. The breadcrumb trail is 'Communities > WORLD > Users'. The page title is 'Users'. There is a 'Manage Users' button in the top right corner. A search filter is present above the table. The table has four columns: 'NAME', 'USER ID', 'DEFINED IN', and 'ROLES'. The first row is 'An Administrator' with user ID 'admin', defined in 'WORLD', and roles 'Decision Analyst', 'Decision Analyst Senior', 'Decision Peer Reviewer', 'Deployment Analyst', 'Deployment Approver', 'Environment Owner', and 'Super User'. There is a 'Manage Roles' button next to the roles for the first user. The following rows are 'A Decision Analyst #1' (da1), 'A Decision Analyst #2' (da2), 'A Glossary Administrator' (gadmin), 'A Modeling Lead #1' (ml1), 'A Modeling Lead #2' (ml2), 'A Modeling Manager #1' (mm1), and 'A Modeling Manager #2' (mm2), all defined in 'WORLD'. The roles for these users include 'Business Owner Approver', 'Decision Analyst', 'Decision Peer Reviewer', 'Deployment Analyst', 'Decision Analyst Senior', 'Decision Peer Reviewer', 'Deployment Analyst', 'Business Owner Approver', 'Community Administrator', 'Community Viewer', 'Decision Analyst', 'Decision Analyst Senior', and 'Decision Peer Reviewer'.

NAME	USER ID	DEFINED IN	ROLES
An Administrator	admin	WORLD	Decision Analyst Decision Analyst Senior Decision Peer Reviewer Deployment Analyst Deployment Approver Environment Owner Super User
A Decision Analyst #1	da1	WORLD	
A Decision Analyst #2	da2	WORLD	
A Glossary Administrator	gadmin	WORLD	Glossary Administrator
A Modeling Lead #1	ml1	WORLD	Business Owner Approver Decision Analyst Decision Peer Reviewer Super User
A Modeling Lead #2	ml2	WORLD	Business Owner Approver Decision Analyst Decision Peer Reviewer
A Modeling Manager #1	mm1	WORLD	Decision Analyst Decision Peer Reviewer Deployment Analyst
A Modeling Manager #2	mm2	WORLD	Decision Analyst Decision Peer Reviewer Deployment Analyst

Community Users Page

To assign a user to a Community, press the **Manage Users** button on the top right side of the page to open the Mange Users dialog box. Select the user to add to the community and press **OK**.



Adding users to Communities

The user you added will be added into the user list in alphabetical order. The user can be searched by entering their name in the Search/Filter field.

To remove a user from a Community, press the Manage Users button in the action bar and de-select the user to be removed and press **OK**.




See the section *Private Communities* in this document to define Communities that do not inherit users and roles from the Community hierarchy.

The next step is to assign roles to the user you created within the Community (see the following section).

3.5 Assigning Roles to Users within Communities

The final step in the security configuration process is to assign roles for users within their Communities.



This security definition takes effect upon the user's next login session.

The list of roles that can be assigned to a user within a Community is taken from the list of roles defined for that user in the third step of the security configuration process (see the section *Assigning Roles to Users* earlier in this guide).

Users can have different roles in different Communities and user roles are inherited in the Community hierarchy.

To assign a role to a user within a Community locate the user in the Community Users page.

The screenshot shows the SAPIENS Decision Administration interface. The top navigation bar includes Home, Tasks (4), Repository, Reports, and Administration (highlighted). A breadcrumb trail shows Security > Users. The main heading is 'Users' with an 'Add' button and a search filter. Below is a table with columns NAME, USER ID, and COMMUNITIES FOR ROLES.

NAME	USER ID	COMMUNITIES FOR ROLES
A Decision Analyst #1	da1	Business Owner Approver: Course A Community Administrator: Community Viewer: Decision Analyst: Course A Decision Analyst Senior: Glossary Administrator: Course A
A Decision Analyst #2	da2	Decision Analyst: Course A
A Decision Analyst #3	da3	Decision Analyst: Course A

Users page


Click on the User to view the User Details page. Click **Manage Roles** action to open the Manage Roles Dialog box.

The screenshot shows the SAPIENS Decision Administration interface for the 'A Decision Analyst #2' user. The top navigation bar is the same. The breadcrumb trail is Security > Users > A Decision Analyst #2. The user details form includes fields for Name (da2), Display Name (A Decision Analyst #2), Email, and Active status (checked). A 'Manage Roles' button is highlighted with a red box. Below the form is a table showing the user's roles.

ROLES	COMMUNITIES
Decision Analyst	Course A

Manage Roles option

In the Manage Roles dialog box select the roles of the user that are applicable to this community and press **OK**.



Adding a user's roles for the Community

4. Security Reports

There are some security related reports in Decision. You must have the “SECURITY” permission to generate the following reports:

- Concurrent User Exception Report
- Permissions By Role - Details
- Permissions By Role – Summary
- Role Permission Detail
- Role Permission Summary
- User Community Permission Details
- User Community Permission Summary
- User Login Report
- User Usage Report
- User Permission Details
- User Permission Summary
- User Status

For more information on the security reports, refer to the **Reports** section in *Decision Manager (DM) User Guide*.

5. Security Setup Example

A recommendation for the setup of user permissions, permission groups and roles is attached to this document as a Microsoft Excel file named *Permissions V700.xlsm*.

The file is an example of a comprehensive security configuration and includes the following, in table format:

- Sample assignment of permissions to permission groups (first tab in the file).
- Sample assignment of the permission groups defined in the first tab to roles (second tab in the file).

Notes:

- The setup for permission groups and roles in the attached file is only an example and a system administrator can configure security access as required.
- In the Permission Groups tab in the file, the left column lists all permissions in the system, the Count column displays the number of permission groups associated with the permission, the Description column displays a brief description of the permission, and each remaining column represents a single permission group. A check mark in a permission group column indicates that the permission is associated with that permission group.
- In the Roles tab in the file, the left column lists the permission groups defined in the first tab, the Count column displays the number of roles associated with the permission group, and each remaining column represents a single role. A check mark in a role column indicates that the permission group is associated with that role.

To view the permission setup file example, go to the panel on the left side of this PDF document, click the **Attachments** icon () and double-click the file to open it.

The file will open in Microsoft Excel.

6. Private Communities


Communities can be defined as 'Private', whereby users will not be inherited from the parent Community but will instead be defined exclusively in the private Community.

In **Community Admin** → **General**, for the Community you select on the left side of the page, you can choose one of the following options:

Inherit Community User Access (default option) - to inherit users, their roles and permissions from the parent Community.


Locally define Community User Access - not to inherit users, their roles and permissions from the parent Community, and instead have the ability to define users privately for that Community and the Communities below it in the hierarchy.

To assign set a community to not inherit user access from its parent community, click **Administration** in the menu bar of the main DM page and select a Community in the **Communities** "Select Community" drop down.




Navigating to Community Administration

Once a Community is selected, click General Information to open the General Information page.



General Information



Change User access to Existing Community

Slide the Inherit User Access slide to off to no longer inherit user access from a parent community. When this is done, all users inherited from the parent Community will be removed from the Community.

A message informs the user that the change is irreversible.

To prevent a situation where a Community is made private and no user then has permission to add other users to the Community, the administrator that made the change is automatically added to the Community together with his/her roles (as defined in the upper-level Communities).

The permission required to set a Community to private is VG_WRITE.

The permission required to add users to a Community is VG_USR_WRITE.

To avoid a deadlock case in which the administrator that sets a Community to private does not have permission to add users to that Community, the new permission VG_USR_GLOBAL_READ_WRITE can be assigned to any administrator (together with the VG_READ permission). With this permission, administrators can manage users (add, remove, determine roles) in both private and inherited Communities, whether or not the administrators are assigned to those Communities.

Note: Once a Community is set to private, it cannot be set back to inherited.

Immediately after a Community is defined for local user access, previous users in the Community Users page will no longer appear in the list, and you will be able to add new users (who may be previous users) to the Community.

6.1 Private Assets in a Revision

The system blocks downloads if files contain private assets. To download private assets, users must have view access to all Communities associated with the Project Revision to which the assets belong. Without the appropriate permission, an error message will appear listing the Communities with assets that you are not authorized to download, as follows:

You are not authorized to download this export package because it contains assets from one or more communities (<Community Name, Community Name>) to which you do not have access.

If an asset exists in two different Communities and the user has access to one but not the other, download will be enabled.

Users who do not have access to a Community, will not be able to add an asset to a Pull Request in that Community.


Users with access to higher-level Communities but not the associated lower-level Communities, will be able to see the assets of the lower-level Communities in Projects, but will not be able to open Advanced Info for the asset from the Project.

6.2 Navigating to and Viewing Private Communities

Generally, users not included in a private Community will not be able to see its contents in the main DM navigation area.

The exception to this rule is the following scenario: If a user has access to a Community, no access to a child Community in the same hierarchy, but access to the next child Community in the same hierarchy (Community access for the user skips a Community), the user will be able to see the Community in the middle but will not be able to view its contents and glossary, or open any of its associated Projects.

The following example shows an example where a user has access to Community A and Community B, but not access to Community C. Community C will appear in the Community Hierarchy since it is required to navigate to Community D where the user has access. However, if they user selects Community C, they will not be able to access or view any data associated with Community C.




Not Authorized message for a non-accessible Community

7. Private Rule Families

Rule Family Versions can now be defined as 'Private', whereby copying and using them is restricted to the specific Community with which the Decision is associated.


By default, Rule Families are 'Public' and can be used in Decisions associated with different Communities as long as the Decision Modeler has access to the community of the source Rule Family. That is, access to any community that has a Decision that is associated with the Rule Family. If a user does not have access to any Community with a Decision that is associated with the Rule Family, they will not be able to reuse that Rule Family in a Decision.

A Rule Family can be made private by navigating to a Rule Family page and selecting the **Mark Private to this Community** action in the Rule Family **More Actions (...)** menu.




Making a Rule Family private

Once a Rule Family is marked as Private, it is indicated in the Rule Family with a Lock icon as shown in the images below:



	Insured Major Location Change	Insured Major Ownership Change	Policy Annual Premium	Policy Discontinued Agent	Policy Underwriting Risk	Informational
1	-	Is I Yes	-	-	Is I Unacceptable	"Insured Major Ownership Change"
2	Is I Yes	-	-	-	Is I Unacceptable	"Insured Major Location Change"
3	-	-	-	Is I Yes	Is I Unacceptable	"Policy Discontinued Agent"
4	-	-	Is Greater Than I \$32,000	-	Is I Unacceptable	"Policy Annual Premium greater than \$32000"
5	Is I No	Is I No	Is Less Than or Equal To I \$32,000	Is I No	Is I Acceptable	-

RULE FAMILY NAME	VERSION INCREMENT	STATUS	VALIDITY	DECISION NAME
Policy Underwriting Risk (View Base) [V1]	Minor	DRAFT	✓	Policy Renewal Method (v1...)

Private Rule Family Indicators

Users must Validate the Rule Family after marking it private to a community.

📁 'Private' is defined on the Rule Family Version level and does not apply to the Rule Family definition. This means that one version of a Rule Family can be defined as Private while another version may be set to Public.


When a Rule Family is private, you can change it to public at any time by navigating to a Rule Family page and selecting the **Unmark Private to this Community** action in the Rule Family **More Actions (...)** menu, providing the Rule Family is draft in a Modeling Task and the change is approved.

When a Rule Family is public, you can change it to private only if it is associated with one or more Decisions that belong to the current Community. If it is associated with Decisions that belong to other Communities in addition to the current Community, the user will receive a message stating that the change cannot be made as part of the Rule Family validation.



Rule Family Validation Message

Marking or unmarking a Rule Family as private to a Community is considered a non-version change. The Rule Families list in the Task will indicate this change is a non-version change and also provides an indication of Rule Families marked as private.



RULE FAMILY NAME	VERSION INCREMENT	STATUS	VALIDITY	DECISION NAME
Policy Underwriting Risk (New: Base) [v1]	Minor	Start	Start	Policy Renewal Method (v1...)

'Private' Rule Family indication in a Modeling Task definition page

Private Rule Families are non-sharable and cannot be used by a Decision in another Community even if the user has access to the other Community and wants to use the Rule Family as a Supporting Rule Family in the other Community.

8. Approval strategy

The Approval Strategy feature ensures that changes made within specific system modules can be governed via a generic approval process. Such changes can be securely managed by dedicated personnel.

Approval Strategy applies to the following modules:

- Model Mapping - controls changes in the Fact Type Model Mapping
- Environments - controls requests for export to environments
- Release Projects - controls changes to a Branch via Revision Tasks

Project Creation example

As an example, when creating a Project, the Approval Strategy option appears in the Project Details tab of the Release Project.

NAME	RESPONSIBILITY
Administrator	Approve Revision Task

Release Project Details Page

Approval Strategy for a Release Project defines how many owners and which owners will have to approve Revision Tasks made in any Branch included in the current project.

The drop-down menu includes the following options:

None – Revision Task instances are immediately approved upon submission.

All - All assigned owners must approve a Revision Task before it is implemented for the Branch.

Any – One of the assigned owners must approve a Revision Task before it is implemented for the Branch.

If you select Any or All, a new section appears for you to specify the owners and describe their responsibilities.

The **Distinct User** option provides additional control over the Approval Strategy process for Projects, exports to environments and Model Mapping definitions.


The option is enabled for the Approval Strategies of 'Any' and 'All' (not for 'None').

If the option **is not** selected, the initiator of an Approval Strategy change request may be an approver of their own request.

If the option **is** selected, the initiator of an Approval Strategy change request cannot be the only approver of their own request.

Approval Strategy Workflows

The following illustration shows the work process for each of the Approval Strategy options.



Required Permissions

To work with Approval Strategy for Model Mapping, Environments and Projects, the following permissions are required.

Permissions for a user who defines the approval strategy:

- PROJECT_READ
- PROJECT_APPROVAL_STRATEGY_READ
- PROJECT_APPROVAL_STRATEGY_WRITE
- PROJECT_OWNER_WRITE (required since if the strategy is ANY or ALL, at least one owner must be selected)

Permissions for a user who wants to add, remove or modify owners:

- PROJECT_READ
- PROJECT_APPROVAL_STRATEGY_READ
- PROJECT_OWNER_WRITE

 If a user does not have the PROJECT_APPROVAL_STRATEGY_WRITE permission, and the approval strategy is not NONE, the last (single) owner cannot be removed.

The **Distinct User** option provides additional control over the Strategy Approval process for Projects, export to environments and Model Mapping definitions.

The option is enabled for the Approval Strategies of 'Any' and 'All' (not for 'None').

If the option **is not** selected, the initiator of an Approval Strategy change request may be an approver of their own request.

If the option **is** selected, the initiator of an Approval Strategy change request cannot be the only approver of their own request.



The option to set the Distinct User is subject to the entity's APPROVAL_STRATEGY_WRITE permission.

If the requestor is the only approver (owner) of the entity, the following message will appear:

An error occurred: Please click this message to refresh



There is a single owner in the approval strategy identical to the requestor. An owner cannot be the only approver of their own work. Add or change the assigned owners or have a different individual create and/or submit the request.

When the requestor is not the only owner assigned to the entity (not a single-owner case) the requestor approval is automatically granted, but final approval is still required by one or more of the other owners (depending on the approval strategy).

9. List of example Roles

This section lists examples of DM user roles and a description of what type of work each role may entail.

Role	Description
Business Owner Approver	Owns business processes and approves business logic (in the form of BCD Tasks) supporting them.
Community Administrator	Handles all Community-related administration issues, such as Community creation, access rights within Communities, Community-level settings, etc.
Community Viewer	Views Community-related administration information for analysis purposes.
Decision Analyst	Views, creates, updates, validates, tests, and submits for approval business logic assets (Decisions, Decision Flows) and Proxy instances.
Decision Analyst Senior	In addition to the capabilities of the Decision Analyst, the Decision Analyst Senior updates Custom Properties for business logics assets and Proxy instances, updates Fact Type model mappings, and creates Pull Requests.
Decision Peer Reviewer	Reviews new and updated business logic assets and Proxy instances prior to approval.
Decision Viewer	Views decision-related information in the system for analysis purposes.
Environment Administrator	Handles deployment environment-related issues, such as creating new environments, modifying existing environments, etc.
Environment Owner	Approves deployments to a specific environment.
MM Approver	Approves Fact Type model mappings for a specific model version.

Role	Description
Glossary Administrator	Manages one or more Glossaries, including approval of new/updated Fact Types, retirement of Fact Types importing/exporting Glossaries, creation/modification of Domain Templates, etc.
Revision Exporter	Exports Revisions in Project Branches.
Revision Manager	Manages the Revision process from creation to export.
Revision Owner	Approves Pull Requests for a specific Project.
Security Administrator	Sets up and maintains the security configuration in a DM system.
Security Viewer	Views security-related information in a DM system to troubleshoot problems that arise and recommend changes accordingly.
Setting Administrator	Configures and analyzes system-related settings.
Super User	Has all permissions in the system to access any DM component and make changes as necessary.



Contact Us

For more information, please visit or contact us at:

info.sapiens@sapiens.com

For Support related queries, contact us at:

Decision.Support@sapiens.com

For Documentation related queries, contact us at:

Decision_documentation@sapiens.com

© 2022 Copyright Sapiens International. All Rights Reserved.

www.sapiensdecision.com



Partnering for Success