
USN : 1WN24CS167

1. Configure IP address to routers in packet tracer. Explore the following messages: ping responses, destination unreachable, request timed out, reply



Router0

Physical | Config | CLI

IOS

```
Continue with configuration dialog? [yes/no]: n


Press RETURN to get started!



Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 10.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state t
o up

Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 20.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state t
o up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#write memory
Building configuration...
[OK]
Router#
```

Router1

Physical | Config | CLI

IOS

```
Continue with configuration dialog? [yes/no]: n


Press RETURN to get started!



Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 20.0.0.2 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state t
o up

Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 30.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state t
o up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#write memory
Building configuration...
[OK]
Router#
```

Router2

Physical | Config | CLI

IOS

```
Continue with configuration dialog? [yes/no]: n


Press RETURN to get started!


Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 30.0.0.2 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state t
o up

Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 40.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state t
o up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
Router#write memory
Building configuration...
[OK]
Router#
```

PC0

Physical | Config | Desktop | Software/Services

Command Prompt

```
PC>ping 10.0.0.6

Pinging 10.0.0.6 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.0.0.6:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss)

PC>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.
Reply from 10.0.0.1: Destination host unreachable.

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss)

PC>ping 10.0.0.1


Pinging 10.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: bytes=32 time=24ms TTL=255
Reply from 10.0.0.1: bytes=32 time=31ms TTL=255
Reply from 10.0.0.1: bytes=32 time=31ms TTL=255
Reply from 10.0.0.1: bytes=32 time=30ms TTL=255

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 24ms, Maximum = 31ms, Average = 29ms

PC>
```

Observation Book :




2. Configure IP address to routers in packet tracer. Explore the following messages: Ping responses, destination unreachable, request timed out, reply.

Step1: create a topology like this. Configure IP address and gateway to the hosts.

Step2: Configure Interface IP address to Router click on Router R1, then click on CLI ~~comm~~. You will see like this, "Continue with configur" dialog? [Yes/no]:". Give "no" and Press enter. Now you will go to user mode, now give "enable" and press enter: Now you get into the Priviledged mode, now type "Configure terminal" and press enter to get into global configuration mode.

Step3: Now configure router interface with ip address and subnet mask then give no shoutdown to make this interface and Line protocol up (ie carefully configure ip address with proper interfaces in this case fa0/0 and fa0/1, f is short form of fastethernet).



Router1 CLI


Continue with configuration dialog? [Yes/no]: n

press RETURN to get started!

Router> enable
Router# config t
Enter configuration commands, one per line. End with CNTL/Z
Router(config)# int fa0/0
Router(config)# ip address 10.0.0.1 255.0.0.0
Router(config-if)# no shut

%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)# exit
Router(config)# exit
Router# console
%SYS-5-CONFIG_I: Configured from console by
Router# ~~exit~~ memory
Building configuration...
[OK]



Step4: Now lights on all ports become green from red. Now open cmd of pc and check for Ping messages, Destination reachable, request time out and reply.

Pc> ping 10.0.0.6
pinging 10.0.0.6 with 32 bytes of data
Request timed out
Request timed out
Pc> Ping 40.0.0.10
pinging 40.0.0.10 with 32 bytes of data
Reply from 10.0.0.1: Destination host unreachable
Reply from 10.0.0.1: Destination host unreachable
Pc> ping 10.0.0.1
pinging 10.0.0.1 with 32 bytes of data:
Reply from 10.0.0.1: bytes=32 time=24ms TTL=255
Reply from 10.0.0.1: bytes=32 time=31ms TTL=255
Reply from 10.0.0.1: bytes=32 time=31ms TTL=255
Reply from 10.0.0.1: bytes=32 time=30ms TTL=255

30/9/24