BASE PLATE CHECK

SAMPLE REPORT / PAGE LAYOUT PREVIEW

01 DESIGN BASIS

Concrete grade	M30		
Steel grade	Fe 500		
Foundation width		2400	mm
Foundation length		3000	mm
Allowable bearing pressure		180	kN/m²

02 DESIGN ACTIONS

Axial load		650	kN
Shear force		42	kN
Bending moment		85	kN·m

03 VERIFICATION

Bearing pressure		128.4	kN/m²
Utilisation		71%	
Result	**PASS**		

LOAD CASE	Fx	Fy	Fz	Mx	My	Mz	Resultant	Factor	Status
Combination 1	40	650	12	85	15	20	652	1.5	PASS
Combination 2	40	650	12	85	15	20	652	1.5	PASS
Combination 3	40	650	12	85	15	20	652	1.5	PASS
Combination 4	40	650	12	85	15	20	652	1.5	PASS
Combination 5	40	650	12	85	15	20	652	1.5	PASS
Combination 6	40	650	12	85	15	20	652	1.5	PASS
Combination 7	40	650	12	85	15	20	652	1.5	PASS
Combination 8	40	650	12	85	15	20	652	1.5	PASS
Combination 9	40	650	12	85	15	20	652	1.5	PASS
Combination 10	40	650	12	85	15	20	652	1.5	PASS
Combination 11	40	650	12	85	15	20	652	1.5	PASS
Combination 12	40	650	12	85	15	20	652	1.5	PASS
Combination 13	40	650	12	85	15	20	652	1.5	PASS
Combination 14	40	650	12	85	15	20	652	1.5	PASS
Combination 15	40	650	12	85	15	20	652	1.5	PASS
Combination 16	40	650	12	85	15	20	652	1.5	PASS
Combination 17	40	650	12	85	15	20	652	1.5	PASS
Combination 18	40	650	12	85	15	20	652	1.5	PASS
Combination 19	40	650	12	85	15	20	652	1.5	PASS

FOUNDATION DESIGN

SAMPLE REPORT / PAGE LAYOUT PREVIEW

01 DESIGN BASIS

Concrete grade	M30		
Steel grade	Fe 500		
Foundation width		2400	mm
Foundation length		3000	mm
Allowable bearing pressure		180	kN/m²

02 DESIGN ACTIONS

Axial load		650	kN
Shear force		42	kN
Bending moment		85	kN·m

03 VERIFICATION

Bearing pressure		128.4	kN/m²
Utilisation		71%	
Result	**PASS**		

LOAD CASE	Fx	Fy	Fz	Mx	My	Mz	Resultant	Factor	Status
Combination 1	40	650	12	85	15	20	652	1.5	PASS
Combination 2	40	650	12	85	15	20	652	1.5	PASS
Combination 3	40	650	12	85	15	20	652	1.5	PASS
Combination 4	40	650	12	85	15	20	652	1.5	PASS
Combination 5	40	650	12	85	15	20	652	1.5	PASS
Combination 6	40	650	12	85	15	20	652	1.5	PASS
Combination 7	40	650	12	85	15	20	652	1.5	PASS
Combination 8	40	650	12	85	15	20	652	1.5	PASS
Combination 9	40	650	12	85	15	20	652	1.5	PASS
Combination 10	40	650	12	85	15	20	652	1.5	PASS
Combination 11	40	650	12	85	15	20	652	1.5	PASS
Combination 12	40	650	12	85	15	20	652	1.5	PASS
Combination 13	40	650	12	85	15	20	652	1.5	PASS
Combination 14	40	650	12	85	15	20	652	1.5	PASS
Combination 15	40	650	12	85	15	20	652	1.5	PASS
Combination 16	40	650	12	85	15	20	652	1.5	PASS
Combination 17	40	650	12	85	15	20	652	1.5	PASS
Combination 18	40	650	12	85	15	20	652	1.5	PASS
Combination 19	40	650	12	85	15	20	652	1.5	PASS

STEEL CONNECTION

SAMPLE REPORT / PAGE LAYOUT PREVIEW

01 DESIGN BASIS

Concrete grade	M30		
Steel grade	Fe 500		
Foundation width		2400	mm
Foundation length		3000	mm
Allowable bearing pressure		180	kN/m²

02 DESIGN ACTIONS

Axial load		650	kN
Shear force		42	kN
Bending moment		85	kN·m

03 VERIFICATION

Bearing pressure		128.4	kN/m²
Utilisation		71%	
Result	**PASS**		

LOAD CASE	Fx	Fy	Fz	Mx	My	Mz	Resultant	Factor	Status
Combination 1	40	650	12	85	15	20	652	1.5	PASS
Combination 2	40	650	12	85	15	20	652	1.5	PASS
Combination 3	40	650	12	85	15	20	652	1.5	PASS
Combination 4	40	650	12	85	15	20	652	1.5	PASS
Combination 5	40	650	12	85	15	20	652	1.5	PASS
Combination 6	40	650	12	85	15	20	652	1.5	PASS
Combination 7	40	650	12	85	15	20	652	1.5	PASS
Combination 8	40	650	12	85	15	20	652	1.5	PASS
Combination 9	40	650	12	85	15	20	652	1.5	PASS
Combination 10	40	650	12	85	15	20	652	1.5	PASS
Combination 11	40	650	12	85	15	20	652	1.5	PASS
Combination 12	40	650	12	85	15	20	652	1.5	PASS
Combination 13	40	650	12	85	15	20	652	1.5	PASS
Combination 14	40	650	12	85	15	20	652	1.5	PASS
Combination 15	40	650	12	85	15	20	652	1.5	PASS
Combination 16	40	650	12	85	15	20	652	1.5	PASS
Combination 17	40	650	12	85	15	20	652	1.5	PASS
Combination 18	40	650	12	85	15	20	652	1.5	PASS
Combination 19	40	650	12	85	15	20	652	1.5	PASS