



XL2506130075-1				REV	DESCRIPTION	CHECK	DATE	ECR NO.																																								
				D	更改接线表		2025/06/17																																									
<div>在黑色点处焊接后用黑色热缩管保护 After welding at the black dots, protect them with black heat shrink tubes</div>				接线表 (WIRING TABLE)																																												
				<div><div><div>P1</div><div><div>3</div><div>4</div><div>PIN-</div><div>PIN+</div><div>PIN+</div><div>PIN-</div><div>4</div><div>3</div></div><div><div>黑色(BLACK)</div><div>红色(RED)</div><div>黑色(BLACK)</div><div>红色(RED)</div><div>红色(RED)</div><div>黑色(BLACK)</div><div>红色(RED)</div><div>黑色(BLACK)</div></div></div><div>P3</div></div> <div><div><div>P2</div><div><div>3</div><div>4</div><div>PIN-</div><div>PIN+</div><div>PIN+</div><div>PIN-</div><div>4</div><div>3</div></div><div><div>红色(RED)</div><div>黑色(BLACK)</div><div>红色(RED)</div><div>黑色(BLACK)</div><div>红色(RED)</div><div>黑色(BLACK)</div><div>红色(RED)</div><div>黑色(BLACK)</div></div></div><div>P4</div></div>																																												
<div>测试条件: 1.100%导通OK, 不能有断路、短路、开路、错位; 2.DC300V导通阻抗≤3Ω; 绝缘阻抗≥10Ω; 3.将线材与治具线对接: 正确读数为 1) 接点为: 个 2) 显示电线条数为: 条</div> <div>外观检验: 1.电线圆实平滑, 颜色均匀, 护套表面无破损、划伤、脏污、变形等缺陷; 2.插头表面光滑平整、无刺、无明显机械压伤、损伤、毛缺损、变形、脏污、金属无锈迹、无端子高低现象.</div>				<table><tr><td>X.±1.0</td><td>X°±1.0°</td></tr><tr><td>.X±0.2</td><td>.X°±0.5°</td></tr><tr><td>.XX±0.05</td><td>.XX°±0.01°</td></tr><tr><td></td><td></td></tr><tr><td>DRAWN BY</td><td>LUKE</td></tr><tr><td>CHECKED BY</td><td></td></tr><tr><td>APPROVED BY</td><td></td></tr><tr><td colspan="2">THESE DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF LCSC CO. ,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF LCSC CO. ,LTD</td></tr></table>		X.±1.0	X°±1.0°	.X±0.2	.X°±0.5°	.XX±0.05	.XX°±0.01°			DRAWN BY	LUKE	CHECKED BY		APPROVED BY		THESE DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF LCSC CO. ,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF LCSC CO. ,LTD		<div> More Asian Brands, Lower Prices</div> <table><tr><td>ITEM</td><td colspan="3"></td></tr><tr><td>WD P/N</td><td colspan="3">XL2506130075-1</td></tr><tr><td>CUST P/N</td><td colspan="3"></td></tr><tr><td>WD DWG.NO</td><td>2</td><td>OF</td><td>4</td></tr><tr><td>UNIT :</td><td>mm</td><td>DATE :</td><td>2025/06/17</td></tr><tr><td></td><td></td><td>REV :</td><td>D</td></tr></table>			ITEM				WD P/N	XL2506130075-1			CUST P/N				WD DWG.NO	2	OF	4	UNIT :	mm	DATE :	2025/06/17			REV :	D
X.±1.0	X°±1.0°																																															
.X±0.2	.X°±0.5°																																															
.XX±0.05	.XX°±0.01°																																															
DRAWN BY	LUKE																																															
CHECKED BY																																																
APPROVED BY																																																
THESE DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF LCSC CO. ,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF LCSC CO. ,LTD																																																
ITEM																																																
WD P/N	XL2506130075-1																																															
CUST P/N																																																
WD DWG.NO	2	OF	4																																													
UNIT :	mm	DATE :	2025/06/17																																													
		REV :	D																																													
序号	名称	用量	规格描述	LCSC编码																																												
1																																																
2																																																
3																																																
4																																																
5																																																
6																																																
7																																																