



A hybrid computational model of the hippocampal formation to replicate theta-nested gamma oscillations and theta phase reset during neurostimulation

Nikolaos Vardalakis, Maeva Andriantsoamberomanga, Ankur Gupta, Amélie Aussel, Nicolas P. Rougier, Fabien Bertrand Paul Wagner

► To cite this version:

Nikolaos Vardalakis, Maeva Andriantsoamberomanga, Ankur Gupta, Amélie Aussel, Nicolas P. Rougier, et al.. A hybrid computational model of the hippocampal formation to replicate theta-nested gamma oscillations and theta phase reset during neurostimulation. Federation of European Neuroscience Societies (FENS), Jul 2022, Paris, France. 2023. hal-03947275

HAL Id: hal-03947275

<https://hal.science/hal-03947275>

Submitted on 30 Jan 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Abstract 1962

A hybrid computational model of the hippocampal formation to replicate theta-nested gamma oscillations and theta phase reset during neurostimulation

Type: Abstract Submission

Topic: S_I. Computational and Theoretical Neuroscience / I.3 Conceptual modelling and pure theory / I.3.b Neural network models

Authors: [Nikolaos Vardalakis](#)^{1,2}, Amélie Ausseil^{1,2}, Nicolas Rougier^{1,2}, Fabien Wagner¹; ¹Université de Bordeaux, Institut des Maladies Neurodégénératives, Bordeaux, France, ²Inria BSO, Mnemosyne, Talence, France

Abstract Body

Theta and gamma oscillations in the hippocampal formation play a crucial role in memory processes and are disrupted in several neurological disorders. Recently, electrical neurostimulation of the human entorhinal area has been shown to enhance memory encoding, but the underlying mechanisms need to be investigated. Here, we aimed to validate the hypothesis that neurostimulation entrains theta-gamma oscillations and induces phase reset of theta oscillations, through a novel hybrid computational model that replicates both theta-gamma hippocampal oscillations and theta phase reset.

Specifically, we used an existing biophysically realistic model of the hippocampal formation able to generate theta-nested gamma oscillations, and interfaced it with abstract Kuramoto oscillators that dynamically generate theta oscillations and theta phase reset. Biophysically realistic neurons were modeled using the Hodgkin-Huxley formalism and connected based on anatomical data from the literature. The set of Kuramoto oscillators had reciprocal connections with the CA1 field of the hippocampus and was meant as an abstract representation of the generation of hippocampal theta, which is thought to originate mainly from the medial septum.

Our model replicates both theta-nested gamma oscillations and theta phase reset, and can be used to probe the effects of different neurostimulation protocols on theta and gamma oscillations and their couplings. In particular, we show that neurostimulation pulses delivered in-phase with the underlying theta rhythm can rescue impaired oscillations caused by changes in the model parameters that reflect pathophysiological circuit alterations.

Overall, our novel computational framework opens new avenues for studying the effects of neurostimulation on hippocampal circuits

[Print](#)