

- The **full error message** from the Jenkins build log.
- The line from your Jenkinsfile that contains `credentialsId`.
- The credential **ID** you configured (you can hide the username and password).



everything correct
is jenkins access system wide credentials

Yes. If you create credentials under:

Manage Jenkins → Credentials → System → Global credentials (unrestricted)

then Jenkins jobs and pipelines can access them **system-wide**, as long as the job has permission to use credentials.

If everything looks correct but Jenkins still cannot find them, check these:

1. Credentials ID

- The Jenkinsfile must use the exact ID:

```
</> groovy
```



2. Job permissions

- The user running the build needs permission to use credentials.
- Check:
Manage Jenkins → Manage and Assign Roles (if Role Strategy plugin is used).

3. Folder-level credentials

- If your job is inside a Jenkins folder, check whether it is using folder credentials instead of global credentials.

4. Pipeline syntax

- Make sure the credentials are referenced correctly. Example:

```
pipeline {  
    agent any
```

```
stages {
  stage('Test') {
    steps {
      withCredentials([usernamePassword(
        credentialsId: 'github',
        usernameVariable: 'USER',
        passwordVariable: 'PASS'
      )]) {
        sh 'echo $USER'
      }
    }
  }
}
```

5. Restart Jenkins (rare case)

- After creating credentials, try restarting Jenkins or reload the configuration.

If you are certain the ID and scope are correct, the next thing to check is the **exact error message**. For example:

- Credentials 'github' not found
- Could not find credentials entry with ID
- Permission denied

The wording tells which issue it is.



Could not find credentials entry with ID

The error:

Could not find credentials entry with ID



means Jenkins searched for a credential with the ID used in your Jenkinsfile, but it could not find a matching credential.

Since you already created it under:

Manage Jenkins → Credentials → System → Global credentials (unrestricted)

check these:

1. Verify the exact Credential ID

Go to:

Manage Jenkins → Credentials → System → Global credentials (unrestricted)

Open your credential and copy the **ID**.

Example:

Credential ID:

```
github_creds
```



Jenkinsfile must have:

```
</> groovy
```



Not:

```
</> groovy
```



or

```
</> groovy
```



2. Check if the job is using a different Jenkins instance

Sometimes the pipeline is running on another Jenkins server/controller than the one where you created the credential.

3. Check folder scope

If your job is inside a folder:

```
Jenkins  
└─ MyFolder
```



 MyPipeline

the folder may have its own credentials store. Check:

MyFolder → Credentials



4. Check the Jenkinsfile syntax

For example:

 groovy



```
withCredentials([usernamePassword(
    credentialsId: 'github_creds',
    usernameVariable: 'USERNAME',
    passwordVariable: 'PASSWORD'
)]) {
    sh 'git clone https://github.com/example/repo.git'
}
```

5. Test credential visibility

Install/use the **Credentials Binding** plugin (normally already installed) and run a simple pipeline test with the same `credentialsId`.

To find the exact issue, please paste the part of your Jenkinsfile containing:

 groovy



```
credentialsId: '...'
```

and tell me the **Credential ID shown in Jenkins** (only the ID, not username/password).



ChatGPT is AI and can make mistakes.