

Replica Set ensures how many replica of pod should be running. It can be considered as a replacement of replication controller. The key difference between the replica set and the replication controller is, the replication controller only supports equality-based selector whereas the replica set supports set-based selector.

```
apiVersion: extensions/v1beta1 ----->1
kind: ReplicaSet -----> 2
metadata:
  name: Tomcat-ReplicaSet
spec:
  replicas: 3
  selector:
    matchLabels:
      tier: Backend -----> 3
    matchExpression:
{ key: tier, operation: In, values: [Backend]} -----> 4
template:
  metadata:
    labels:
      app: Tomcat-ReplicaSet
      tier: Backend
    labels:
      app: App
      component: neo4j
  spec:
    containers:
      - name: Tomcat
        image: tomcat: 8.0
        ports:
          - containerPort: 7474
```

Setup Details

apiVersion: extensions/v1beta1 → In the above code, the API version is the advanced beta version of Kubernetes which supports the concept of replica set.

kind: ReplicaSet → We have defined the kind as the replica set which helps kubectl to understand that the file is used to create a replica set.

tier: Backend → We have defined the label tier as backend which creates a matching selector.

{key: tier, operation: In, values: [Backend]} → This will help **matchExpression** to understand the matching condition we have defined and in the operation which is used by **matchlabel** to find details.

Run the above file using **kubectl** and create the backend replica set with the provided definition in the **yaml** file.

