ML Engineer

Complete Learning Notes

12 topics | Foundations, worked examples and practice solutions

Scope: The selected career requirements and all transitive prerequisites in the current CareerIQ catalog.

Use this book in prerequisite order. Start with Foundations if a topic is new, then work through the detailed concepts and examples. Experienced learners can focus on tradeoffs, interview questions and applied practice.

These are original AI-assisted study notes, not an accredited textbook or evidence of mastery. Validate software examples against the linked primary documentation and complete the existing assessments or reviewed projects.

Reference books are listed by title and author only. No third-party textbook PDFs are included.

Contents

1. Python (Advanced) 3

2. Multivariate Calculus 10

3. Linear Algebra 16

4. Probability & Statistics 22

5. NumPy & Pandas Processing 28

6. Supervised Learning Algorithms 34

7. Neural Network Architecture 40

8. PyTorch Framework & Tensors 47

9. Docker & Containerization 53

10. Model Serving & Inference Optimization 59

11. Model Evaluation & Validation 65

12. Experiment Tracking & Reproducibility 72

1. Python (Advanced)

Prerequisites: No prerequisites in the current competency catalog.

Python has become the lingua franca for many advanced software tasks, from high-performance networking to low-level system integration. Mastering the advanced features of the language - concurrency with AsyncIO, the power of metaclasses and decorators, and the ability to profile memory or extend Python with C - enables developers to write code that is both expressive and efficient. This chapter introduces these capabilities in a self-contained way, starting from the core ideas and building toward practical implementations. By the end, a beginner will understand when to use asynchronous constructs, how to shape class creation dynamically, and how to measure and improve memory usage, preparing them for real-world projects and technical interviews.

Foundations

AsyncIO is Python's built-in library for cooperative multitasking. Unlike pre-emptive threads, coroutines voluntarily yield control, allowing a single thread to manage many I/O-bound tasks without the overhead of context switches. The event loop schedules these coroutines, and futures represent pending results. Metaclasses are the "class of a class"; they intercept class creation, enabling automatic attribute injection or validation. Decorators are higher-order functions that wrap other callables, adding behavior without modifying the original code. Together they support clean, reusable patterns. Memory profiling in Python involves tools such as tracemalloc and objgraph, which track allocation sites and object graphs. When Python's performance limits are reached, C-extensions let developers write critical sections in C, exposing functions to Python via the CPython API. Understanding reference counting, the Global Interpreter Lock (GIL), and the distinction between pure Python objects and native buffers is essential before venturing into extensions. These foundations form a toolkit for writing scalable, maintainable, and high-performance Python applications.

AsyncIO

AsyncIO provides an event-driven framework where coroutines, defined with async def, can pause at await points. The await keyword yields control back to the loop, which then runs other ready coroutines. This model excels for I/O-heavy workloads such as web servers, database clients, or file processing, because the thread never blocks on network or disk latency. Trade-offs include added complexity in error handling and debugging, as stack traces become fragmented across await boundaries. Moreover, CPU-bound work still blocks the loop unless offloaded to a thread or process pool.

Worked reasoning: Consider a simple HTTP fetcher that retrieves three URLs concurrently. The coroutine fetch(url) opens an aiohttp.ClientSession, awaits response.read(), and returns the length. The main coroutine gathers the three fetch calls with asyncio.gather, allowing the event loop to interleave network waits. The total runtime approximates the longest single request, not the sum, demonstrating true concurrency without threads.

Metaclasses & Decorators

Metaclasses intervene during class creation by overriding __new__ or __init__ in a subclass of type. They can inject methods, enforce naming conventions, or register classes in a registry automatically. Decorators, on the other hand, are applied to functions or methods at definition time, returning a wrapped callable that can log, cache, or modify arguments. Using both together yields powerful patterns: a metaclass can apply a decorator to every method of a class, ensuring uniform behavior such as timing or access control. The main trade-off is readability; excessive metaprogramming can obscure intent, making maintenance harder for newcomers.

Worked reasoning: A metaclass AutoTimer scans a class dictionary, wrapping each callable with a timing_decorator that records start and end timestamps. When an instance method is called, the decorator prints the elapsed time. Defining class MyWorker(metaclass=AutoTimer) automatically equips all its methods with timing without manually decorating each one.

Memory Profiling & C-Extensions

Memory profiling starts with tracemalloc.start() to capture allocation snapshots. By comparing snapshots, developers can pinpoint functions that allocate the most bytes. objgraph.show_refs can visualize reference cycles that prevent garbage collection. When profiling reveals hot spots, a C-extension can replace a Python loop with a compiled routine, reducing per-iteration overhead and memory churn. The CPython API requires careful reference counting: Py_INCREF and Py_DECREF manage object lifetimes, and the GIL must be held when manipulating Python objects. The trade-off is development effort and portability; C code must be compiled for each target platform, and bugs can crash the interpreter.

Worked reasoning: A pure-Python function sum_range(n) computes the sum of squares using a for loop, allocating a new integer each iteration. Profiling shows O(n) allocations. Rewriting the core loop in C as sum_range_c(PyObject *self, PyObject *args) uses a single PyLong_FromLong result, dramatically lowering allocation count and memory usage. The extension is built with setuptools' Extension module and imported as import sum_ext.

Worked examples

Worked example

```
import asyncio
import aiohttp

async def fetch(url):
    async with aiohttp.ClientSession() as s:
        async with s.get(url) as r:
            data = await r.read()
            return len(data)

async def main():
    urls = ['https://example.com', 'https://httpbin.org/ip',
    'https://httpbin.org/uuid']
    lengths = await asyncio.gather(*(fetch(u) for u in urls))
    print('Lengths:', lengths)

asyncio.run(main())
```

The script defines fetch as an async coroutine that opens a client session, performs a GET request, and awaits the response body. main builds a list of three URLs and uses asyncio.gather to schedule all fetch

calls concurrently. Because each await yields while the network is idle, the total runtime is close to the slowest request rather than the sum of three round-trips. Limitations include the need for an event loop (cannot be called from a blocking context without run_until_complete) and that CPU-bound work inside fetch would still block the loop.

Applied example

```
# Pseudocode for a metaclass that decorates all methods
class AutoLog(type):
    def __new__(mcls, name, bases, dct):
        def log_wrapper(func):
            def inner(*args, **kw):
                print(f'Calling {func.__name__}')
                return func(*args, **kw)
            return inner
        for attr, val in dct.items():
            if callable(val):
                dct[attr] = log_wrapper(val)
        return super().__new__(mcls, name, bases, dct)

class Service(metaclass=AutoLog):
    def start(self):
        print('started')
    def stop(self):
        print('stopped')

svc = Service()
svc.start()
svc.stop()
```

AutoLog is a metaclass that iterates over the class dictionary during creation. For each callable attribute, it replaces the original function with a wrapped version that prints a log line before invoking the original. When Service is defined, both start and stop are automatically logged without explicit @decorator usage. This pattern is useful for cross-cutting concerns like logging, authentication, or timing. The trade-off is that every method, including private helpers, receives the wrapper, which may add overhead or interfere with introspection tools.

Process flow

1. 1. Identify a performance or architectural problem (e.g., many concurrent I/O calls).
2. 2. Choose AsyncIO if the workload is I/O-bound; rewrite blocking functions as async coroutines.
3. 3. Insert await points at each I/O operation and run coroutines via asyncio.run or an existing loop.
4. 4. If repetitive cross-cutting behavior is needed, design a decorator or metaclass to apply it uniformly.
5. 5. Profile memory with tracemalloc.start(); capture snapshots before and after the critical section.
6. 6. Analyze allocation differences; if Python overhead is high, implement the hot loop as a C-extension.
7. 7. Test the integrated solution, verify correctness, and measure speed and memory improvements.

Interview and exam checkpoints

Explain how AsyncIO differs from threading and when you would prefer one over the other.

AsyncIO uses a single thread with an event loop that schedules coroutines, allowing many I/O operations to progress without OS thread switches. Threading creates multiple OS threads, each with its own stack and context, incurring higher memory usage and synchronization costs. Prefer AsyncIO for high-concurrency I/O-bound tasks like web servers, where the GIL is not a bottleneck. Use threading when you need true parallelism for CPU-bound work or when interacting with libraries that block the interpreter and cannot be made async.

What is a metaclass in Python and how does it differ from a class decorator?

A metaclass is a subclass of type that controls the creation of classes; its __new__ or __init__ runs when the class statement is executed, allowing injection or modification of attributes before the class object exists. A class decorator is a function that receives a class object after it has been created and returns a (possibly modified) class. Metaclasses operate at class definition time, affecting the class's structure, while decorators act on the finished class, typically adding behavior. Metaclasses are more powerful but also more complex and less commonly needed.

How does tracemalloc help you find memory leaks, and what are its limitations?

tracemalloc records the call stack of each memory allocation, enabling you to take snapshots and compare them to see which lines allocate the most bytes. By filtering snapshots you can locate unexpected growth in specific functions, indicating a leak. Limitations include that it only tracks Python-level allocations, not memory allocated by native extensions, and it adds overhead (typically 5-10%). It also cannot detect reference cycles that keep objects alive unless you inspect the object graph with additional tools.

Describe the steps to safely expose a C function to Python using the CPython API.

First, write a C function that follows the PyCFunction signature, accepting PyObject *self and PyObject *args. Parse arguments with PyArg_ParseTuple, perform the computation, and return a new reference using PyLong_FromLong or similar. Next, create a method table (PyMethodDef array) listing the function name, pointer, flags, and docstring. Define a module initialization function (PyMODINIT_FUNC PyInit_modname) that calls PyModule_Create with a PyModuleDef struct containing the method table. Finally, compile the source into a shared library using setuptools' Extension module, and import it in Python. Throughout, manage reference counts with Py_INCREF/Py_DECREF and hold the GIL when interacting with Python objects.

Summary

Advanced Python equips developers with tools to handle massive concurrency, dynamic class behavior, and low-level performance tuning. AsyncIO replaces threads for I/O-bound workloads by using cooperative coroutines and an event loop, yielding efficient scaling with minimal overhead. Metaclasses and decorators enable systematic injection of cross-cutting concerns, allowing clean, reusable modifications to classes and functions. Memory profiling with tracemalloc and objgraph reveals hidden allocation patterns, guiding decisions to rewrite hot paths as C-extensions when Python's interpreter overhead becomes a bottleneck. Together, these techniques form a cohesive strategy: identify bottlenecks, apply the appropriate abstraction, measure impact, and iterate. Mastery of these concepts prepares engineers for real-world systems where responsiveness, resource usage, and maintainability are paramount.

Practice questions

1. Write an async function that reads three files concurrently and returns their total line count. Use only standard-library asyncio and the third-party aiofiles package.

2. Create a metaclass that automatically registers every subclass in a global registry dictionary keyed by class name.

3. Using tracemalloc, compare memory usage of a list comprehension versus a generator expression that produces the squares of numbers 1..1000. Report the difference in bytes.

4. Design a small C-extension that provides a function fast_sum(arr) returning the sum of a Python list of integers. Outline the steps and explain reference-count handling.

5. Explain a scenario where using a decorator for caching (memoization) could degrade performance instead of improving it.

6. You have a web service that must handle 10,000 simultaneous connections, each performing short HTTP GETs. Choose between AsyncIO and a thread pool, justify your choice, and sketch the high-level code structure.

Practice solutions

1. import asyncio, aiofiles

```
async def count_lines(path):
    async with aiofiles.open(path, 'r') as f:
        cnt = 0
        async for _ in f:
            cnt += 1
        return cnt

async def total():
    files = ['a.txt', 'b.txt', 'c.txt']
    results = await asyncio.gather(*(count_lines(p) for p in files))
    return sum(results)

print(asyncio.run(total()))
# aiofiles delegates ordinary file operations to worker threads, counts lines asynchronously, and aggregates the counts. Because file I/O yields control, the three reads overlap, potentially overlapping
```

waits; speedup depends on the filesystem and workload.

2. registry = {}

```
class RegisterMeta(type):
    def __new__(mcls, name, bases, dct):
        cls = super().__new__(mcls, name, bases, dct)
        registry[name] = cls
        return cls

class Base(metaclass=RegisterMeta):
    pass

class Foo(Base):
    pass

class Bar(Base):
    pass

print(registry) # {'Base': <class '__main__.Base'>, 'Foo': <class '__main__.Foo'>, 'Bar': <class
'__main__.Bar'>}
# Each time a new subclass is defined, RegisterMeta inserts it into the registry, enabling factory patterns or
plugin discovery without manual bookkeeping.
```

3. import gc, tracemalloc

```
def measure(factory):
    gc.collect()
    tracemalloc.start()
    value = factory() # retain the object while measuring
    current, peak = tracemalloc.get_traced_memory()
    tracemalloc.stop()
    return current, peak

list_bytes = measure(lambda: [i*i for i in range(1, 1001)])
generator_bytes = measure(lambda: (i*i for i in range(1, 1001)))
print("list current/peak:", list_bytes)
print("generator current/peak:", generator_bytes)
print("current difference:", list_bytes[0] - generator_bytes[0])
```

Results depend on the Python build and allocator; do not hardcode a byte count. The list retains computed elements. The generator retains its suspended state and produces values when consumed. This measures construction, not the work or memory of consuming and retaining all generated results. Discarding both objects before snapshots would not measure their retained memory.

4. Define a method table and module initialization function, then expose a callable that parses an iterable argument. Obtain an iterator with PyObject_GetIter and release its new reference on every exit path. Each non-null PyIter_Next result is also a new reference: process it, then decrement it. A null iteration result can mean exhaustion or an exception; check PyErr_Occurred after the loop. For arbitrary Python integers, maintain a Python integer accumulator using checked PyNumber_Add results and correct reference ownership. A C long accumulator can overflow even when each input fits individually; do not use unchecked signed addition. Return a new reference to the result on success and NULL with an exception

set on failure. Include Python.h, define the method table/module entry point and use an appropriate extension build configuration. Test empty input, non-integers, huge integers, an iterator that raises, and repeated calls under leak checking. A C extension is not automatically faster; benchmark against Python's built-in sum before accepting its maintenance cost.

5. If the decorated function is called with a large number of unique arguments, the cache grows without reuse, consuming memory and adding lookup overhead for each call. For example, a function that processes streaming sensor data with ever-changing timestamps will store a new entry per call, eventually causing cache thrashing and increased GC pressure. In such cases, the decorator's dictionary look-ups and memory usage outweigh any benefit, and a simple direct call is faster.

6. AsyncIO is the better fit because the workload is I/O-bound and each request spends most of its time waiting for network responses. Creating 10,000 OS threads would exhaust system resources (stack memory, scheduler overhead). With AsyncIO, a single thread runs an event loop that schedules all coroutines, keeping memory usage low. High-level code:

```
import asyncio, aiohttp

async def fetch(session, url):
    async with session.get(url) as resp:
        return await resp.text()

async def main(urls):
    async with aiohttp.ClientSession() as sess:
        tasks = [fetch(sess, u) for u in urls]
        results = await asyncio.gather(*tasks)
        return results

urls = ['http://service/api'] * 10000
print(asyncio.run(main(urls)))
# The event loop multiplexes the 10,000 coroutines, achieving high concurrency with minimal threads.
```

Reference textbooks

Fluent Python - Luciano Ramalho

Effective Python - Brett Slatkin

Primary documentation

https://docs.python.org/3/tutorial/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

2. Multivariate Calculus

Prerequisites: No prerequisites in the current competency catalog.

Multivariate calculus is the mathematical backbone of many modern scientific and engineering fields, from physics to machine learning. It extends the ideas of single-variable calculus - limits, derivatives, integrals - to functions that accept several inputs and produce either scalar or vector outputs. Understanding how rates of change behave in multiple dimensions enables you to model surfaces, optimize complex systems, and propagate gradients through deep neural networks. This chapter introduces the core constructs - gradients, Jacobians, Hessians, and the multivariate chain rule - building intuition before moving to algorithmic applications. By mastering these foundations, a beginner can confidently tackle problems involving surface geometry, constrained optimization, and the back-propagation algorithm that powers modern AI.

Foundations

Begin with a scalar function f(x1, x2, ..., xn). Its partial derivative with respect to xi measures how f changes when only xi varies, holding all other variables constant. Collecting all partials yields the gradient vector □f, which points in the direction of steepest ascent and whose magnitude equals the maximal rate of increase. For vector-valued functions F: R^n → R^m, each component Fj has its own gradient; arranging these gradients as rows forms the Jacobian matrix J, an m×n array that linearly approximates F near a point. The Jacobian generalizes the derivative: multiplying a small input perturbation Δx gives an output change Δy ≈ J·Δx. When the function is twice differentiable, the gradient itself varies with direction, captured by the Hessian matrix H, an n×n symmetric matrix of second-order partial derivatives. H encodes curvature; positive-definite Hessians indicate local minima, while indefinite ones signal saddle points. The multivariate chain rule links these objects: for a composition y = g(F(x)), the gradient of y with respect to x is □y = J_F(x)^T □g(F(x)). In neural networks, g often represents a loss and F the network mapping, so the chain rule becomes the back-propagation algorithm, efficiently computing gradients layer by layer. Mastery of these concepts requires practice with concrete functions, careful handling of dimensions, and awareness of common pitfalls such as confusing row- versus column-vector conventions or neglecting symmetry in Hessians.

Gradients & Jacobians

The gradient □f of a scalar field f(x1,…,xn) is the vector of its first-order partial derivatives: □f = [∂f/∂x1, …, ∂f/∂xn]^T. It points toward the direction where f increases most rapidly, and its length equals the steepest ascent rate. For a vector-valued function F: R^n → R^m, the Jacobian J_F is an m×n matrix where entry (i,j) = ∂F_i/∂x_j. The Jacobian acts as the best linear map approximating F near a point: F(x+Δx) ≈ F(x) + J_F(x)·Δx. Gradients are column vectors, while Jacobians are often written with rows as component gradients; mixing these conventions can cause sign errors in code. In optimization, the gradient guides descent steps, whereas the Jacobian is essential for transforming uncertainties, performing change-of-variables in integrals, and computing sensitivities in engineering models.

Worked reasoning: Consider f(x, y) = x^2 y + 3y. The gradient is □f = [2xy, x^2 + 3]^T. At the point (1,2) the gradient becomes [2*1*2, 1^2+3] = [4, 4]. For the vector function F(x, y) = [x y, sin(x) + y^2], the Jacobian is J = [[y, x], [cos(x), 2y]]. Evaluating at (π/2, 1) gives J = [[1, π/2], [0, 2]]. The Jacobian tells us that a small change Δx = [0.01, -0.02] will produce ΔF ≈ J·Δx = [1*0.01 + (π/2)*(-0.02), 0*0.01 + 2*(-0.02)] ≈ [0.01 - 0.0314, -0.04] = [-0.0214, -0.04].

Hessian Matrices

The Hessian H of a twice-differentiable scalar function f: R^n → R is the square n×n matrix of second-order partial derivatives: H_{ij} = ∂^2 f / (∂x_i ∂x_j). Because mixed partials are equal under mild conditions (Clairaut's theorem), H is symmetric. The Hessian describes local curvature: if H is positive-definite at a point, the function is locally convex and the point is a strict local minimum; if negative-definite, it is a local maximum; indefinite Hessians indicate saddle points. In Newton's method for optimization, the update step uses the inverse Hessian to scale the gradient, achieving quadratic convergence near a minimum. However, computing and inverting H can be expensive for high dimensions, leading to quasi-Newton approximations like BFGS. A common mistake is to treat the Hessian as a scalar curvature; it actually encodes curvature in every direction, and eigenvalues reveal principal curvatures.

Worked reasoning: Take f(x, y) = x^3 + 3xy^2. First derivatives: ∂f/∂x = 3x^2 + 3y^2, ∂f/∂y = 6xy. Second derivatives: ∂^2f/∂x^2 = 6x, ∂^2f/∂y^2 = 6x, ∂^2f/∂x∂y = ∂^2f/∂y∂x = 6y. Thus H = [[6x, 6y], [6y, 6x]]. At (1,1) the Hessian is [[6,6],[6,6]]. Its eigenvalues are 12 and 0, indicating a flat direction (zero curvature) and a steep upward curvature. The gradient at (1,1) is [3*1^2+3*1^2, 6*1*1] = [6,6]. Newton's step would require solving H·Δx = -□f, but H is singular here, so a direct Newton update fails; regularization or a pseudo-inverse is needed.

Chain Rule in Backprop

The multivariate chain rule allows differentiation of composite functions. For a scalar loss L that depends on intermediate vector-valued outputs a = g(x) and finally on parameters θ through x = h(θ), the gradient □_θ L = (∂a/∂θ)^T □_a L. In neural networks, each layer computes a = σ(Wx + b). The Jacobian of a with respect to its inputs x is J = diag(σ'(Wx+b))·W, where σ' is the element-wise derivative. Backpropagation proceeds backward: starting from ∂L/∂output, each layer multiplies by its Jacobian transpose to obtain gradients for its inputs and parameters. This avoids explicit construction of large Jacobians; instead, vector-Jacobian products are computed efficiently. Pitfalls include forgetting to apply the derivative of the activation function, mixing up row-vector versus column-vector conventions, and numerical instability when gradients vanish or explode, which can be mitigated by careful initialization and normalization.

Worked reasoning: Consider a two-layer network: z = W1 x + b1, a = tanh(z), y = W2 a + b2, loss L = (y - t)^2/2. Forward pass: compute z, a, y. Backward: ∂L/∂y = y - t. Gradient w.r.t. W2: ∂L/∂W2 = (∂L/∂y) a^T. Gradient w.r.t. a: ∂L/∂a = W2^T (∂L/∂y). Then ∂L/∂z = (∂L/∂a) □ (1 - tanh(z)^2). Finally ∂L/∂W1 = (∂L/∂z) x^T. For x=[0.5, -1], W1=[[1,2],[-0.5,0.3]], b1=[0,0], t=0.7, the forward values are z=[1*0.5+2*(-1), -0.5*0.5+0.3*(-1)] = [-1.5, -0.65]; a = tanh(z) ≈ [-0.905, -0.571]; W2=[0.8, -0.2], b2=0.1 gives y = 0.8*(-0.905)+(-0.2)*(-0.571)+0.1 ≈ -0.724+0.114+0.1 = -0.51. Loss gradient ∂L/∂y = -0.51-0.7 = -1.21. Backprop yields ∂L/∂W2 = -1.21 * a^T ≈ [-1.21*(-0.905), -1.21*(-0.571)] = [1.095, 0.691]. This illustrates the chain of Jacobian-vector products.

Worked examples

Worked example

```
import numpy as np

def f(x):
    # scalar function f(x,y) = x^2 * y + 3*y
    return x[0]**2 * x[1] + 3 * x[1]

def grad_f(x):
    # analytical gradient
    df_dx = 2 * x[0] * x[1]
    df_dy = x[0]**2 + 3
    return np.array([df_dx, df_dy])

x0 = np.array([1.0, 2.0])
print('f(x0)=', f(x0))
print('grad f(x0)=', grad_f(x0))
```

The code defines a simple two-variable scalar function and its analytical gradient. Evaluating at x0 = (1,2) yields f = 1^2*2 + 3*2 = 8 and gradient = [2*1*2, 1^2+3] = [4,4]. This confirms the manual computation in the concept example. The function is smooth, so the gradient accurately predicts the change for small perturbations: a step of -0.1 in both directions reduces the function value by approximately 0.8, matching a finite-difference check. Limitations include that the gradient is exact only for differentiable functions; nondifferentiable points would require subgradients.

Applied example

```
# Pseudocode for backpropagation through a single ReLU layer
# Input: x (vector), W (weight matrix), b (bias), upstream_grad (∂L/∂a)
# Output: grad_W, grad_b, grad_x

def relu(z):
    return np.maximum(0, z)

def relu_backward(z, upstream_grad):
    dz = upstream_grad * (z > 0).astype(float)
    return dz

# Forward pass
z = W @ x + b
a = relu(z)
# Assume loss L already computed and upstream_grad = ∂L/∂a is given
# Backward pass
dz = relu_backward(z, upstream_grad)
grad_W = np.outer(dz, x)   # ∂L/∂W = dz * x^T
grad_b = dz                 # ∂L/∂b = dz
grad_x = W.T @ dz           # ∂L/∂x = W^T * dz
```

This pseudocode demonstrates the chain rule in a neural network layer with a ReLU activation. The Jacobian of the ReLU is a diagonal matrix with 1 where the pre-activation z is positive and 0 elsewhere; multiplying the upstream gradient by this mask yields dz, the gradient with respect to z. The weight gradient is the outer product of dz and the input x, reflecting how each weight contributes linearly to the output. The bias gradient is simply dz because each bias adds directly to its neuron. Finally, the gradient flowing to the previous layer is the transpose of W times dz. This pattern repeats for every layer, enabling efficient gradient computation without forming full Jacobian matrices. Pitfalls include forgetting the mask, which would incorrectly propagate gradients through dead neurons, and numerical overflow if inputs are

large, which can be mitigated by normalization.

Process flow

1. Compute partial derivatives of the scalar objective with respect to each input variable to form the gradient vector.
2. Assemble the gradients of all output components of a vector-valued function into the Jacobian matrix.
3. If second-order information is needed, differentiate the gradient components again to obtain the Hessian matrix.
4. Apply the multivariate chain rule: multiply the transpose of the Jacobian of the inner function by the gradient of the outer function.
5. In neural networks, propagate gradients layer by layer using Jacobian-vector products, updating weights with the resulting parameter gradients.

Interview and exam checkpoints

What is the geometric interpretation of the gradient of a scalar field?

The gradient points in the direction of steepest increase of the scalar field, and its magnitude equals the maximal rate of change per unit distance. Moving a small step ε in the gradient direction raises the function value by approximately ε times the gradient norm. Orthogonal directions produce no first-order change.

How does the Jacobian differ from the gradient, and when would you use each?

The gradient is a vector of first-order partial derivatives for a scalar-valued function, while the Jacobian is a matrix of partial derivatives for a vector-valued function, with each row representing the gradient of one output component. Use the gradient when optimizing a single loss; use the Jacobian when transforming coordinates, computing sensitivities, or chaining multiple vector functions.

Explain why the Hessian matrix is symmetric and what its eigenvalues tell you about a critical point.

Under mild smoothness conditions, mixed partial derivatives commute (Clairaut's theorem), making H_{ij}=∂²f/∂x_i∂x_j equal to H_{ji}. Hence H is symmetric. Its eigenvalues are the principal curvatures: if all are positive, the point is a local minimum; if all negative, a local maximum; mixed signs indicate a saddle point. Zero eigenvalues suggest flat directions.

Describe how backpropagation implements the multivariate chain rule without explicitly forming large Jacobian matrices.

Backpropagation computes vector-Jacobian products instead of full Jacobians. Starting from the loss gradient, each layer multiplies the upstream gradient by the transpose of its local Jacobian (often a simple diagonal mask for element-wise activations) and accumulates parameter gradients via outer products. This leverages the associativity of matrix multiplication to keep memory and computation linear in the number of parameters.

Summary

Multivariate calculus equips you with tools to analyze how functions change in many dimensions. The gradient captures first-order variation of scalar fields, while the Jacobian extends this concept to vector outputs, providing a linear approximation of a function near a point. The Hessian adds second-order curvature information, essential for classifying critical points and for Newton-type optimization. The multivariate chain rule ties these objects together, enabling efficient gradient propagation through compositions - a principle that underlies backpropagation in deep learning. Mastery of these constructs allows you to model surfaces, perform sensitivity analysis, and train complex models with confidence.

Practice questions

1. Given f(x,y) = x^2 + 4xy + y^2, compute the gradient at (1,2) and the Hessian matrix.

2. For the vector function F(x,y) = [x^2 y, e^{xy}], find the Jacobian and evaluate it at (1,0).

3. A neural network layer computes a = ReLU(Wx + b). If W = [[2, -1],[0,3]], x = [0.5, -0.2], b = [0,0], and the upstream gradient ∂L/∂a = [0.3, -0.4], compute ∂L/∂W, ∂L/∂b, and ∂L/∂x.

4. Show that for a scalar function f(x) = x^T A x where A is symmetric, the gradient is □f = (A + A^T) x = 2A x.

5. Design trade-off: When would you prefer using a first-order optimizer like gradient descent over a second-order method such as Newton's method in training a deep neural network?

6. Numerical exercise: Approximate the directional derivative of f(x,y)=sin(xy) at point (π/4,1) in the direction v = [1,2] using the gradient.

Practice solutions

1. Partial derivatives: ∂f/∂x = 2x + 4y, ∂f/∂y = 4x + 2y. At (1,2): ∂f/∂x = 2*1 + 4*2 = 10, ∂f/∂y = 4*1 + 2*2 = 8, so □f = [10,8]. Second derivatives: ∂²f/∂x² = 2, ∂²f/∂y² = 2, ∂²f/∂x∂y = ∂²f/∂y∂x = 4. Hence Hessian H = [[2,4],[4,2]].

2. Compute partials: ∂F1/∂x = 2xy, ∂F1/∂y = x^2; ∂F2/∂x = y e^{xy}, ∂F2/∂y = x e^{xy}. Jacobian J = [[2xy, x^2],[y e^{xy}, x e^{xy}]]. At (1,0): J = [[0,1],[0,1*e^{0}]] = [[0,1],[0,1]].

3. Forward: z = W x = [2*0.5 + (-1)*(-0.2), 0*0.5 + 3*(-0.2)] = [1.0+0.2, -0.6] = [1.2, -0.6]. a = ReLU(z) = [1.2, 0]. Mask = [1,0]. dz = upstream * mask = [0.3*1, -0.4*0] = [0.3, 0]. grad_W = outer(dz, x) = [[0.3*0.5, 0.3*(-0.2)], [0*0.5, 0*(-0.2)]] = [[0.15, -0.06],[0,0]]. grad_b = dz = [0.3,0]. grad_x = W^T dz = [[2,0],[-1,3]] @ [0.3,0] = [2*0.3 + 0*0, -1*0.3 + 3*0] = [0.6, -0.3].

4. Write f = Σ_i Σ_j x_i A_{ij} x_j. Partial derivative w.r.t. x_k: ∂f/∂x_k = Σ_j A_{kj} x_j + Σ_i x_i A_{ik} = (A x)_k + (A^T x)_k. Since A = A^T, the two terms are identical, giving ∂f/∂x_k = 2 (A x)_k. Hence ∇f = 2A x.

5. First-order methods require only gradient evaluations, scaling linearly with the number of parameters and memory proportional to the model size. They are suitable for very large networks where computing or storing the Hessian is infeasible. Newton's method offers quadratic convergence near a well-conditioned minimum but needs the Hessian or its inverse, which is O(n^2) memory and O(n^3) compute, prohibitive for millions of parameters. Moreover, deep nets often have non-convex loss surfaces with many saddle points; the Hessian can be indefinite, causing Newton steps to diverge. Therefore, in practice, gradient descent (with momentum, Adam, etc.) is preferred for large-scale training, while second-order methods may be used for small-scale problems or as a fine-tuning step.

6. First compute gradient: ∂f/∂x = y cos(xy), ∂f/∂y = x cos(xy). At (π/4,1): xy = π/4, cos(π/4)=√2/2≈0.7071. ∂f/∂x = 1*0.7071≈0.7071, ∂f/∂y = (π/4)*0.7071≈0.5554. Gradient vector ≈ [0.7071,0.5554]. Normalize direction v: ||v|| = sqrt(1^2+2^2)=√5≈2.2361, unit v̂ = [0.4472,0.8944]. Directional derivative = ∇f·v̂ ≈ 0.7071*0.4472 + 0.5554*0.8944 ≈ 0.316 + 0.497 ≈ 0.813. This approximates the rate of change of sin(xy) moving from (π/4,1) along v.

Reference textbooks

Vector Calculus - Jerrold E. Marsden and Anthony J. Tromba

Calculus - Michael Spivak

Primary documentation

https://ocw.mit.edu/courses/18-02sc-multivariable-calculus-fall-2010/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

3. Linear Algebra

Prerequisites: No prerequisites in the current competency catalog.

Linear algebra is the mathematical language that underpins many areas of computer science, data analysis, and engineering. It provides tools to represent and manipulate multidimensional data, solve systems of equations, and uncover hidden structure in datasets. Understanding linear algebra enables you to work with transformations, optimize models, and build algorithms that scale. This chapter introduces the core ideas a beginner needs - vectors, matrices, and the operations that combine them - before moving to the three key subtopics: eigenvalues and eigenvectors, singular value decomposition, and tensor operations. By mastering these concepts you will be prepared to tackle machine-learning pipelines, graphics pipelines, and scientific simulations, and you will have a solid foundation for technical interviews that probe your analytical reasoning.

Foundations

A vector is an ordered list of numbers that can be visualized as a point or an arrow in space. Vectors support addition (component-wise) and scalar multiplication, which together define a vector space. A matrix is a rectangular array of numbers that represents a linear transformation from one vector space to another; multiplying a matrix by a vector applies that transformation. Important matrix operations include addition, multiplication, transposition, and inversion. Matrix multiplication is not element-wise; the entry in row i, column j of the product is the dot product of row i of the left matrix with column j of the right matrix. The determinant of a square matrix measures volume scaling and indicates invertibility: a non-zero determinant means the matrix has an inverse. Systems of linear equations can be written as Ax = b, where A is a coefficient matrix, x the unknown vector, and b the result vector. Solving such systems involves Gaussian elimination, LU decomposition, or using the matrix inverse when it exists. Norms quantify vector length (e.g., Euclidean norm) and matrix size (e.g., Frobenius norm). Orthogonality, where vectors have zero dot product, leads to convenient bases that simplify many calculations. These building blocks are essential before exploring eigen-analysis, singular value decomposition, and higher-order tensor algebra.

Eigenvalues & Eigenvectors

An eigenvector of a square matrix A is a non-zero vector v that, when multiplied by A, changes only in magnitude, not direction: A v = λ v. The scalar λ is the eigenvalue associated with v. Eigenpairs reveal intrinsic properties of the transformation, such as scaling factors along principal directions. To find them, solve the characteristic equation det(A - λ I) = 0, where I is the identity matrix; the roots λ are the eigenvalues. For each λ, substitute back into (A - λ I) v = 0 to obtain the eigenvectors, which form the null space of (A - λ I). Eigenvalues can be real or complex, and their multiplicities affect the geometric multiplicity of eigenvectors. In practice, eigen-analysis is used for stability analysis, dimensionality reduction (PCA), and solving differential equations. Numerical methods like the power iteration approximate the dominant eigenpair when exact computation is costly. Trade-offs include sensitivity to rounding errors for ill-conditioned matrices and the need for orthogonal eigenvectors in symmetric matrices.

Worked reasoning: Consider the matrix A = [[4, 1], [2, 3]]. Compute det(A - λ I) = (4-λ)(3-λ) - 2*1 = λ^2 -7λ +10. Solving λ^2 -7λ +10 = 0 gives λ = 5 and λ = 2. For λ = 5, solve (A-5I)v = [[-1,1],[2,-2]]v = 0, yielding eigenvector v1 = [1,1]^T. For λ = 2, solve (A-2I)v = [[2,1],[2,1]]v = 0, giving eigenvector v2 = [-0.5,1]^T (or any scalar multiple). These eigenpairs show that applying A stretches vectors along [1,1] by factor 5 and

along [-0.5,1] by factor 2, illustrating how eigen-analysis decomposes the transformation into independent scaling actions.

Matrix Decomposition (SVD)

Singular value decomposition (SVD) factorizes any m×n matrix M into three components: M = U Σ V^T. U is an m×m orthogonal matrix whose columns are left singular vectors; V is an n×n orthogonal matrix whose columns are right singular vectors; Σ is an m×n diagonal matrix with non-negative singular values σ_i on the diagonal, sorted descending. The singular values are the square roots of the eigenvalues of M^T M (or M M^T). SVD provides optimal low-rank approximations: truncating Σ to its top k singular values yields the best rank-k matrix in the Frobenius norm sense. This property is exploited in data compression, noise reduction, and recommendation systems. Computing SVD involves bidiagonalization followed by iterative QR steps; modern libraries handle this efficiently. Trade-offs include higher computational cost than simpler factorizations (LU, QR) and the need for careful handling of very large sparse matrices, where truncated or randomized SVD variants are preferred.

Worked reasoning: Use M = [[3, 0, 0], [0, 2, 0]]. Then M^T M = diag(9, 4, 0). The two singular values of this 2 by 3 matrix are 3 and 2. A full SVD has U = I_2, V = I_3, and Sigma = M. The rank-1 approximation keeps only 3, giving [[3, 0, 0], [0, 0, 0]]. Its Frobenius error is 2; its squared Frobenius error is 4. Keeping both singular values reconstructs the original exactly, so there is no compression error at rank 2. This example also illustrates that a rectangular matrix has min(m,n) singular values in the usual compact representation, even though M^T M has n eigenvalues.

Tensor Operations

A tensor generalizes scalars (order-0), vectors (order-1), and matrices (order-2) to higher dimensions. An order-k tensor is an array with k indices, e.g., a 3-dimensional array T[i][j][k]. Tensor operations extend matrix algebra: contraction sums over a pair of matching indices, analogous to matrix multiplication; outer product adds new dimensions; and mode-n multiplication multiplies a tensor by a matrix along a specific mode, reshaping that dimension. The Einstein summation convention provides concise notation for these operations. Tensors enable compact representation of multi-way data such as color images (height × width × channel) or word embeddings across contexts. Decompositions like CANDECOMP/PARAFAC (CP) and Tucker factorize tensors into low-rank components, facilitating compression and interpretation. Numerical stability can be challenging because tensor rank is NP-hard to compute, and algorithms may converge to local minima. Trade-offs involve choosing between CP (simpler but potentially less stable) and Tucker (more flexible but higher computational cost).

Worked reasoning: Suppose we have a 2×2×2 tensor T with entries T[0,0,0]=1, T[0,0,1]=2, T[0,1,0]=3, T[0,1,1]=4, T[1,0,0]=5, T[1,0,1]=6, T[1,1,0]=7, T[1,1,1]=8. Contracting over the first and third modes yields a vector C where C[j] = sum_i,k T[i,j,k] δ_{i,k}. Computing C[0] = T[0,0,0]+T[1,0,1]=1+6=7, C[1] = T[0,1,0]+T[1,1,1]=3+8=11. Thus the contraction reduces the tensor to a vector [7,11], illustrating how summing over selected indices extracts aggregated information.

Worked examples

Worked example

```
import numpy as np
A = np.array([[4, 1], [2, 3]])
vals, vecs = np.linalg.eig(A)
print('Eigenvalues:', vals)
print('Eigenvectors:\n', vecs)
```

The code uses NumPy's eig function to compute eigenvalues and eigenvectors of the 2x2 matrix A. The output shows eigenvalues [5. 2.] and corresponding eigenvectors as columns of the matrix printed. Each eigenvector is scaled arbitrarily; any non-zero scalar multiple represents the same direction. This demonstration confirms the manual calculation performed earlier, and illustrates how numerical libraries handle the characteristic polynomial internally. Limitations include sensitivity to rounding errors for matrices with close or complex eigenvalues, and the fact that eig returns complex numbers even for real matrices when necessary.

Applied example: rank-1 reconstruction

```
import numpy as np
M = np.array([[3., 0., 0.], [0., 2., 0.]])
U, s, VT = np.linalg.svd(M, full_matrices=False)
rank1 = U[:, :1] @ np.diag(s[:1]) @ VT[:1, :]
print(rank1)
print(np.linalg.norm(M - rank1, ord='fro'))
```

The rank-1 reconstruction is [[3, 0, 0], [0, 0, 0]], and the Frobenius norm of its error is 2. The squared error is 4, equal to the sum of squares of discarded singular values. Keeping both singular values reconstructs M exactly. Truncation trades fidelity for a lower rank; it is useful for large matrices only when storing the factors actually costs less than storing the original matrix. For a tiny 2 by 3 example, factorization is an illustration rather than a practical storage saving.

Process flow

1. Represent data as vectors or matrices, identifying dimensions and meaning of each axis.
2. Choose appropriate operations: addition for combining, multiplication for applying transformations.
3. Compute eigenvalues and eigenvectors to discover scaling directions of square matrices.
4. Apply SVD to decompose any matrix, inspect singular values to assess rank and energy distribution.
5. If data has more than two modes, organize it as a tensor and perform mode-n multiplications or contractions.
6. Validate results by reconstructing the original structure from decomposed components and measuring error.

Interview and exam checkpoints

Explain the geometric interpretation of eigenvectors and eigenvalues for a 2D linear transformation.

In two dimensions, a linear transformation represented by matrix A maps every vector to a new location. Eigenvectors are special directions that remain on the same line after transformation; they may be stretched or shrunk but not rotated. The eigenvalue associated with an eigenvector quantifies that scaling factor. Geometrically, drawing the eigenvectors shows the axes of the transformation, and the eigenvalues indicate how much the shape expands or contracts along each axis. For example, a matrix that scales x by 3 and y by 2 has eigenvectors aligned with the x- and y-axes and eigenvalues 3 and 2 respectively.

How does truncating singular values in SVD affect data reconstruction?

Truncating singular values means keeping only the largest k singular values and their corresponding singular vectors, discarding the rest. This yields a rank-k approximation that minimizes the Frobenius norm of the reconstruction error. The effect is that most of the variance (energy) captured by the discarded singular values is lost, leading to a smoother or less detailed reconstruction. In image compression, for instance, keeping only a few singular values removes fine details but preserves the overall structure. The trade-off is between compression ratio and fidelity; the squared Frobenius error equals the sum of squares of the omitted singular values.

What are the computational differences between CP and Tucker tensor decompositions?

CP (CANDECOMP/PARAFAC) decomposes a tensor into a sum of rank-one components, requiring the estimation of factor matrices for each mode with a fixed rank. It is simpler and often faster but can suffer from ill-posedness and local minima. Tucker decomposition, on the other hand, factorizes a tensor into a core tensor multiplied by factor matrices along each mode, allowing different ranks per mode. Tucker is more flexible and can capture interactions between components, but it involves computing a potentially large core tensor and is computationally heavier. Algorithms for Tucker typically use higher-order SVD, while CP relies on alternating least squares.

Why is the determinant zero for a matrix with linearly dependent columns, and what does that imply for eigenvalues?

If columns are linearly dependent, the matrix maps some non-zero vector to the zero vector, meaning its transformation collapses volume to zero. The determinant, which measures volume scaling, is therefore zero. A zero determinant implies that zero is an eigenvalue, because there exists a non-zero vector v such that A v = 0·v. This eigenvalue reflects the direction that is annihilated by the transformation, indicating singularity and non-invertibility of the matrix.

Summary

Linear algebra equips you with a systematic way to model and manipulate multidimensional data. Vectors and matrices form the basic objects, supporting operations that represent rotations, scalings, and projections. Eigenvalues and eigenvectors expose intrinsic scaling directions of square transformations, enabling stability analysis and dimensionality reduction. Singular value decomposition extends these ideas to any matrix, providing optimal low-rank approximations and revealing hidden structure through singular values and orthogonal bases. Tensor operations generalize matrix algebra to higher-order data, allowing contractions, mode-n multiplications, and decompositions such as CP and Tucker. Mastery of these concepts gives you the analytical tools to compress data, solve systems efficiently, and design algorithms that scale across domains ranging from machine learning to scientific computing.

Practice questions

1. Find the eigenvalues of matrix B = [[2, -1], [1, 4]].

2. Compute the rank-1 SVD approximation of C = [[3,0,0],[0,2,0]]. Give its Frobenius error.

3. Perform a mode-2 multiplication of a 2×2×2 tensor D with matrix M = [[1,0],[0,2]] and explain the result.

4. Design a data pipeline that uses SVD for image compression. List the steps and justify each.

5. A system of equations is represented by matrix A = [[1,2,3],[2,4,6],[3,6,9]] and vector b = [6,12,18]. Solve for x using the pseudoinverse and discuss the solution space.

6. Compare the trade-offs between using a dense matrix representation versus a sparse representation for a large adjacency matrix in graph algorithms.

Practice solutions

1. Compute the characteristic polynomial det(B - λI) = (2-λ)(4-λ) - (-1)(1) = λ^2 -6λ +9 = 0. Solving λ^2 -6λ +9 = 0 gives λ = (6 ± sqrt(36-36))/2 = 3. Both eigenvalues are λ = 3 (algebraic multiplicity 2).

2. C^T C = diag(9,4,0). The singular values are 3 and 2; choosing the first coordinate directions gives C_1 = [[3,0,0],[0,0,0]]. C-C_1 has a single nonzero entry 2. Thus the Frobenius error is sqrt(4)=2 and its squared error is 4.

3. Using one-based mode numbering, mode 2 acts on the second index. Define Y[i,j,k] = sum_b M[j,b] D[i,b,k]. With M = diag(1,2), entries with j=0 remain unchanged and entries with j=1 double. A slice [[a,b],[c,d]] at fixed k becomes [[a,2b],[c,2d]], equivalently D[:,:,k] @ M.T. The operation scales columns of each slice, not rows.

4. 1) Load grayscale image as matrix I (pixels). 2) Compute SVD: I = U Σ V^T. 3) Choose k based on desired compression ratio (e.g., retain 90% energy). 4) Truncate Σ to top k singular values, forming Σ_k, and keep corresponding columns of U and rows of V^T. 5) Reconstruct compressed image I_k = U_k Σ_k V_k^T. 6) Store U_k, Σ_k, V_k^T instead of full I. Justification: SVD isolates principal components; truncation reduces storage while preserving most visual information. Reconstruction error is minimized in Frobenius norm, ensuring best possible quality for given k.

5. Let u=[1,2,3]^T. A=u*u^T, b=6u and u^T u=14. A has a single nonzero singular value 14. A^+=u*u^T/196. The minimum-norm solution is x_min=(6/14)u=[3/7,6/7,9/7]^T. Check u^T x_min=6, hence A x_min=6u=b. Every solution is x_min+z with u^T z=0. The pseudoinverse returns the unique

minimum-norm solution, not an arbitrary solution.

6. Dense representation stores every entry, using O(n^2) memory, which is wasteful for graphs where edges are far fewer than n^2. Sparse formats (CSR, CSC) store only non-zero entries, reducing memory to O(|E|). Computation on dense matrices can exploit BLAS optimizations and vectorization, yielding fast matrix-vector products, but the overhead is prohibitive for large sparse graphs. Sparse representations enable O(|E|) operations, essential for scalability, but require more complex indexing and may incur indirect memory accesses, reducing cache efficiency. The choice depends on graph density: dense for small, fully connected graphs; sparse for large, real-world networks.

Reference textbooks

Introduction to Linear Algebra - Gilbert Strang

Numerical Linear Algebra - Lloyd N. Trefethen and David Bau III

Primary documentation

https://ocw.mit.edu/courses/18-06-linear-algebra-spring-2010/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

4. Probability & Statistics

Prerequisites: Linear Algebra

Probability and statistics form the mathematical backbone of data-driven decision making. Whether you are estimating the chance of a coin landing heads, inferring the parameters of a distribution from observed data, or modeling sequential events such as weather patterns, a solid grasp of these ideas is essential. This chapter introduces the core concepts a beginner needs before tackling more sophisticated models. You will learn how to reason about uncertainty with Bayes Theorem, how to fit models to data using Maximum Likelihood Estimation, and how to describe stochastic processes with Markov Chains. By the end, you will be able to translate real-world problems into probabilistic language, perform basic calculations by hand, and write simple Python code to simulate and analyze random phenomena.

Foundations

The study of probability begins with a sample space, the set of all possible outcomes of an experiment. Events are subsets of this space, and a probability measure assigns a number between 0 and 1 to each event, obeying the axioms of non-negativity, normalization, and additivity. Random variables map outcomes to numeric values; their distributions describe how likely each value is. Expectation gives the average outcome, variance quantifies spread, and common families such as the Bernoulli, Binomial, Normal, and Poisson distributions provide templates for modeling. Statistics reverses the direction: given observed data, we aim to infer the underlying distribution or its parameters. Estimators are rules that produce parameter guesses; desirable properties include unbiasedness (average equals true value) and consistency (converges with more data). Hypothesis testing evaluates competing explanations by comparing observed evidence against a null model, often using p-values or confidence intervals. These foundations enable the three subtopics that follow: Bayes Theorem for updating beliefs, Maximum Likelihood Estimation for fitting models, and Markov Chains for describing dependent sequences.

Bayes Theorem

Bayes Theorem provides a systematic way to update the probability of a hypothesis when new evidence arrives. Formally, P(H|E) = P(E|H) * P(H) / P(E), where H is the hypothesis and E is the evidence. The prior P(H) captures belief before seeing data, the likelihood P(E|H) measures how probable the evidence is under the hypothesis, and the posterior P(H|E) is the revised belief. The denominator P(E) acts as a normalizing constant ensuring the posterior sums to one across all hypotheses. Bayes Theorem is powerful because it combines prior knowledge with observed data, allowing iterative refinement as more evidence accumulates. Trade-offs include the need for a well-specified prior, which can be subjective, and computational difficulty when the hypothesis space is large, often requiring approximation methods such as Monte Carlo sampling.

Worked reasoning: Suppose a medical test for a disease is 99% sensitive (true positive) and 95% specific (true negative). The disease prevalence in the population is 1%. Let H be "patient has disease" and E be "test is positive". Prior P(H)=0.01. Likelihood P(E|H)=0.99. False-positive rate is 1-0.95=0.05, so P(E|~H)=0.05. The evidence probability P(E)=P(E|H)P(H)+P(E|~H)P(~H)=0.99*0.01+0.05*0.99=0.0099+0.0495=0.0594. Posterior P(H|E)=0.99*0.01/0.0594≈0.1667. Even with a highly accurate test, the chance the patient actually has the disease after a positive result is only about 16.7% because the disease is rare.

Maximum Likelihood Estimation (MLE)

Maximum Likelihood Estimation selects parameter values that make the observed data most probable under a chosen statistical model. Given data points x1,…,xn assumed independent and identically distributed from a distribution f(x;θ) with parameter θ, the likelihood function L(θ)=∏_{i=1}^n f(x_i;θ) measures joint probability of the data. The MLE θ̂ maximizes L(θ), often more conveniently by maximizing the log-likelihood ℓ(θ)=log L(θ) because products become sums and derivatives are easier. Solving ∂ℓ/∂θ=0 yields candidate estimates; second-order conditions confirm a maximum. MLE is asymptotically unbiased and efficient under regularity conditions, but it can be sensitive to model misspecification and outliers. In cases where the likelihood has multiple peaks, numerical optimization (e.g., gradient ascent) may be required, and care must be taken to avoid local maxima.

Worked reasoning: Assume we observe three independent measurements of a physical quantity that we model as normally distributed with unknown mean μ and known variance σ^2=1. The data are x=[2.1, 1.9, 2.0]. The likelihood is L(μ)=∏_{i=1}^3 (1/√(2π)) exp(-(x_i-μ)^2/2). The log-likelihood ℓ(μ)= -3/2 log(2π) - 0.5∑(x_i-μ)^2. Differentiating: dℓ/dμ = ∑(x_i-μ)=0 □ 3μ = ∑x_i = 2.1+1.9+2.0 = 6.0 □ μ̂ = 2.0. Thus the MLE for the mean is the sample average, a result that holds for any normal distribution with known variance.

Markov Chains

A Markov Chain is a stochastic process that moves between a finite set of states with the property that the next state depends only on the current state, not on the sequence of past states. This memoryless property is formalized as P(S_{t+1}=j | S_t=i, S_{t-1}=k, …) = P(S_{t+1}=j | S_t=i) = T_{ij}, where T is the transition matrix. Each row of T sums to one, representing a probability distribution over next states. Chains can be classified by properties such as irreducibility (every state reachable from any other), aperiodicity (no fixed cycle length), and ergodicity (convergence to a unique stationary distribution π satisfying πT=π). Trade-offs involve model simplicity versus realism: a first-order Markov assumption may be too restrictive for processes with longer memory, prompting higher-order extensions or hidden Markov models.

Worked reasoning: Consider a simple weather model with two states: Sunny (S) and Rainy (R). Transition probabilities are: P(S→S)=0.8, P(S→R)=0.2, P(R→S)=0.4, P(R→R)=0.6. The transition matrix T = [[0.8,0.2],[0.4,0.6]]. Starting from Sunny, the probability of being Sunny after two days is computed by squaring the matrix: T^2 = [[0.8*0.8+0.2*0.4, 0.8*0.2+0.2*0.6],[0.4*0.8+0.6*0.4, 0.4*0.2+0.6*0.6]] = [[0.72,0.28],[0.56,0.44]]. Thus P(S after two days | start S)=0.72. The stationary distribution solves π = πT, yielding π = [0.667, 0.333]; in the long run, about two-thirds of days are Sunny.

Worked examples

Worked example

```
import random

def simulate_coin(p_head, n):
    heads = sum(1 for _ in range(n) if random.random() < p_head)
    return heads / n

# Estimate probability of heads for a biased coin
est = simulate_coin(0.7, 10000)
print('Estimated P(heads):', round(est, 4))
```

The code defines a simple Monte Carlo simulation for a biased coin with true head probability 0.7. By drawing 10,000 random numbers and counting how many fall below 0.7, we approximate the empirical

frequency of heads. The printed estimate will be close to 0.7, illustrating the law of large numbers: as the number of trials grows, the sample proportion converges to the true probability. Limitations include random variance; a single run may deviate by a few percent, and the method becomes inefficient for extremely rare events where many more trials are needed to obtain stable estimates.

Applied example

```
# Pseudocode for MLE of exponential rate
# data: list of observed lifetimes x_i
sum_x = sum(data)
N = len(data)
# Log-likelihood derivative set to zero gives lambda_hat = N / sum_x
lambda_hat = N / sum_x
print('MLE rate λ =', lambda_hat)
```

The pseudocode demonstrates the derivation of the Maximum Likelihood Estimator for the rate parameter λ of an exponential distribution, f(x;λ)=λ e^{-λx} for x≥0. The log-likelihood is ℓ(λ)=N log λ - λ∑x_i. Differentiating with respect to λ and setting the derivative to zero yields N/λ - ∑x_i = 0, which solves to λ̂ = N / ∑x_i, the reciprocal of the sample mean. For independent exponential observations and N>1, this estimator is biased upward: E[lambda_hat]=N*lambda/(N-1). It is consistent and asymptotically unbiased, and easy to compute, making it a common choice in reliability engineering where lifetimes follow an exponential decay.

Process flow

1. Define the random experiment and enumerate all possible outcomes (sample space).
2. Assign probabilities to elementary events ensuring the axioms of probability hold.
3. Introduce random variables and derive their probability mass or density functions.
4. Apply Bayes Theorem to update beliefs when new evidence is observed.
5. Formulate a likelihood function for the observed data and solve for the MLE.
6. Construct a transition matrix if the problem involves sequential dependence, then analyze its properties (stationary distribution, mixing time).
7. Validate results with simulation or analytical checks, and interpret the outcomes in the context of the original problem.

Interview and exam checkpoints

Explain the difference between a prior and a likelihood in Bayesian inference.

A prior represents the probability distribution of a hypothesis before seeing any data; it encodes existing knowledge or assumptions. The likelihood, on the other hand, quantifies how probable the observed data are under each possible hypothesis. In Bayes Theorem, the prior is multiplied by the likelihood to produce the unnormalized posterior, which is then normalized by the evidence. The prior influences the posterior especially when data are scarce, while the likelihood dominates as more data accumulate.

Derive the MLE for the parameter p of a Bernoulli distribution given n observations.

For a Bernoulli trial, the probability mass function is f(x;p)=p^x (1-p)^{1-x} for x□{0,1}. Given observations x1,…,xn, the likelihood is L(p)=∏_{i=1}^n p^{x_i}(1-p)^{1-x_i}=p^{∑x_i}(1-p)^{n-∑x_i}. The log-likelihood is ℓ(p)=∑x_i log p + (n-∑x_i) log(1-p). Differentiating with respect to p and setting to zero: (∑x_i)/p - (n-∑x_i)/(1-p)=0. Solving gives p̂ = (∑x_i)/n, which is simply the sample mean of the binary outcomes.

What conditions guarantee that a Markov chain has a unique stationary distribution?

A finite Markov chain that is both irreducible (every state can be reached from any other) and aperiodic (the chain does not get trapped in cycles of fixed length) is guaranteed to have a unique stationary distribution. Irreducibility ensures the chain is one communicating class, while aperiodicity prevents oscillations. Under these conditions, the chain is ergodic, meaning that regardless of the initial state, the distribution of states converges to the stationary distribution as time goes to infinity.

How would you handle a situation where the likelihood function is intractable for Bayesian inference?

When the likelihood cannot be evaluated analytically, we resort to approximation techniques. One common approach is Markov Chain Monte Carlo (MCMC), which constructs a Markov chain whose stationary distribution matches the posterior, allowing us to draw samples without explicit likelihood values. Another method is Approximate Bayesian Computation (ABC), which simulates data from the model and accepts parameter values that produce simulated data close to the observed data according to a distance metric. Both methods trade computational cost for the ability to perform inference in complex models.

Summary

Probability and statistics provide a language for quantifying uncertainty and extracting insight from data. Starting from basic probability axioms, we learned to model random variables, compute expectations, and assess variability. Bayes Theorem equips us to revise beliefs in light of new evidence, balancing prior knowledge with observed data. Maximum Likelihood Estimation offers a principled way to fit parametric models by maximizing the probability of the observed sample, yielding estimators that are often simple functions of the data. Markov Chains extend probability to sequences where the future depends only on the present, enabling analysis of stochastic processes through transition matrices, stationary distributions, and convergence properties. Together, these tools form a foundation for more advanced topics such as Bayesian hierarchical models, hidden Markov models, and modern machine-learning algorithms.

Practice questions

1. A biased die has probability 0.2 of landing on 6 and equal probability for the other faces. What is the probability of rolling a 6 exactly twice in three independent throws?

2. Given data points [5.2, 4.8, 5.0] assumed drawn from N(μ, σ^2) with known σ=0.1, compute the MLE for μ.

3. In a two-state Markov chain with transition matrix [[0.9,0.1],[0.3,0.7]], compute the probability of being in state 2 after two steps starting from state 1.

4. Write a Python function that computes the posterior probability of a hypothesis H given binary evidence E using Bayes Theorem. Use inputs prior, likelihood, and evidence probability.

5. Design a simple weather prediction system using a first-order Markov chain. Discuss the trade-offs of using only the previous day's weather versus incorporating a longer history.

6. A sample of 50 measurements has mean 12.3 and standard deviation 2.1. Assuming normality, construct a 95% confidence interval for the true mean.

Practice solutions

1. Let p=0.2 for a 6, q=0.8 for not-6. The number of successes follows a Binomial(3,0.2). P(X=2)=C(3,2)*p^2*q = 3 * 0.04 * 0.8 = 0.096.

2. The MLE for μ is the sample mean: (5.2+4.8+5.0)/3 = 5.0. Thus μ̂ = 5.0.

3. Square the matrix: T^2 = [[0.9*0.9+0.1*0.3, 0.9*0.1+0.1*0.7],[0.3*0.9+0.7*0.3, 0.3*0.1+0.7*0.7]] = [[0.84,0.16],[0.48,0.52]]. Starting from state 1, the probability of being in state 2 after two steps is the (1,2) entry = 0.16.

4.
```
def bayes_posterior(prior, likelihood, evidence):
    return (likelihood * prior) / evidence
# Example usage:
# prior=0.01, likelihood=0.99, evidence=0.0594
# posterior ≈ 0.1667
```

5. Model states as {Sunny, Cloudy, Rainy}. Estimate transition probabilities from historical data, forming a 3×3 matrix. The system predicts tomorrow's weather by multiplying the current state vector by the matrix. Trade-offs: a first-order model is easy to train and requires little data, but it cannot capture patterns like a

multi-day front that influence weather beyond one day. Extending to a second-order chain (conditioning on the last two days) improves accuracy for such patterns but increases the number of parameters (from 9 to 27 probability entries, or 6 to 18 free parameters after row-sum constraints) and demands more data to estimate them reliably, raising the risk of overfitting.

6. For n=50, use t_{0.025,49}≈2.01. Margin = t * s/√n = 2.01 * 2.1 / √50 ≈ 2.01 * 0.297 = 0.597. CI = 12.3 ± 0.597 → (11.703, 12.897).

Reference textbooks

Introduction to Probability - Joseph K. Blitzstein and Jessica Hwang

All of Statistics - Larry Wasserman

Primary documentation

https://seeing-theory.brown.edu/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

5. NumPy & Pandas Processing

Prerequisites: Python (Advanced)

Data scientists spend most of their time cleaning, reshaping, and aggregating data before any model can be built. NumPy provides the low-level, fast array engine that underpins most scientific Python code, while Pandas builds a higher-level, tabular abstraction that makes time-series handling, grouping, and missing-value logic intuitive. Mastering these libraries enables you to write code that runs at C-speed, avoid Python loops, and express complex data pipelines in a few lines. This chapter introduces the core ideas of vectorized computation, memory-efficient storage, and time-series alignment, then shows how they combine in real-world workflows. By the end you will be able to read large files, transform them without copying data unnecessarily, and align disparate series for analysis, all while keeping an eye on performance and correctness.

Foundations

NumPy arrays are homogeneous, n-dimensional containers of fixed-size items stored in a contiguous block of memory. Because the data type is known, the interpreter can call optimized C loops for arithmetic, eliminating the overhead of Python's dynamic typing. Vectorization means applying an operation to an entire array at once; broadcasting extends this by allowing arrays of different shapes to interact as long as their dimensions are compatible, following the rule that dimensions of size one are virtually repeated. Pandas introduces the DataFrame, a collection of labeled Series objects, each of which can hold a different dtype. The index provides alignment semantics: when two Series are combined, Pandas automatically matches rows by label, inserting NaN where data is missing. Memory mapping (numpy.memmap) lets you treat a file on disk as an array, loading only the needed chunks into RAM, which is essential for datasets larger than available memory. Time-series alignment builds on the index concept, using timestamps as labels and providing resampling, forward-fill, and interpolation utilities. Understanding these foundations - contiguous storage, dtype uniformity, label-based alignment, and lazy loading - prepares you to write code that is both fast and expressive.

Vectorization & Broadcasting

Vectorization replaces explicit Python loops with array-wide operations, leveraging SIMD instructions and cache-friendly memory access. The key trade-off is that you must think in whole-array terms; element-wise logic must be expressed with boolean masks or where functions. Broadcasting allows operations between arrays of different shapes by virtually replicating the smaller array along dimensions of size one. This avoids costly data copies but requires careful shape planning to prevent unintended broadcasting that yields wrong results. Understanding the broadcasting rules - right-most dimensions align first, and a dimension of size one can be stretched - helps you design compact, error-free code.

Worked reasoning: Suppose we have a 3x4 matrix A and a length-4 row vector v. A = [[1,2,3,4],[5,6,7,8],[9,10,11,12]] and v = [1,0,1,0]. Adding v to A triggers broadcasting: v is treated as [[1,0,1,0]] repeated across three rows, producing [[2,2,4,4],[6,6,8,8],[10,10,12,12]]. No extra memory is allocated for the repeated v; NumPy computes each sum on the fly.

Memory Mapping

Memory mapping creates an array interface to a binary file without loading the entire file into RAM. numpy.memmap opens the file, sets the dtype and shape, and maps the file's bytes into the process's address space. Reads and writes operate directly on the file, so changes persist without an explicit save step. The main trade-off is that random access can be slower than in-memory arrays due to page faults, and the file must remain unchanged in size and layout while the memmap is active. It is ideal for large, read-only datasets or for incremental updates where only a slice is needed at a time.

Worked reasoning: Imagine a binary file 'data.bin' containing 10,000 int32 values. Using memmap: import numpy as np; mm = np.memmap('data.bin', dtype='int32', mode='r', shape=(10000,)). Accessing mm[5000] reads the 5,001st integer directly from disk. If you compute mm[::2] + 5, NumPy reads only the even-indexed elements, adds 5, and returns a new in-memory array, leaving the original file untouched.

Time Series Alignment

Pandas aligns series by their index labels, which are often timestamps. When two series with different sampling frequencies are combined, Pandas reindexes them to a common timeline, inserting NaN where data is missing. You can then fill gaps using forward fill, backward fill, or interpolation. The trade-off lies in choosing an appropriate frequency: upsampling introduces many NaNs that must be filled, while downsampling discards information. Resampling with .resample() aggregates data (e.g., taking the mean per hour), while .asfreq() simply changes the index without aggregation, preserving original values where possible.

Worked reasoning: Consider s1 = pd.Series([10,12,14], index=pd.to_datetime(['2021-01-01','2021-01-02','2021-01-04'])) and s2 = pd.Series([100,101], index=pd.to_datetime(['2021-01-01','2021-01-03'])). Adding s1 + s2 yields a series indexed on the union of dates: 2021-01-01 -> 110, 2021-01-02 -> NaN, 2021-01-03 -> NaN, 2021-01-04 -> NaN. Using s2.reindex(s1.index, method='ffill') fills missing dates with the last known value, enabling meaningful addition.

Worked examples

Worked example

```
import numpy as np
A = np.arange(1,13).reshape(3,4)
v = np.array([1,0,1,0])
B = A + v  # broadcasting
print(B)
```

The code creates a 3x4 matrix A with values 1 through 12 and a row vector v of length four. Adding v to A triggers broadcasting: v is virtually repeated for each row, so each element of A is increased by the corresponding element of v. The printed result is [[2 2 4 4]
 [6 6 8 8]
 [10 10 12 12]]. This demonstrates how NumPy can perform element-wise addition without explicit loops, saving both code length and execution time. The operation does not allocate a separate copy of v for each row; the broadcast is handled internally, which is why memory usage stays low.

Applied example

```
import pandas as pd
import numpy as np
# create two time series with different frequencies
idx1 = pd.date_range('2022-01-01', periods=5, freq='D')
idx2 = pd.date_range('2022-01-01', periods=3, freq='2D')
s1 = pd.Series(np.arange(5), index=idx1)
s2 = pd.Series(np.arange(3)*10, index=idx2)
# align and forward-fill missing values
s2_aligned = s2.reindex(s1.index, method='ffill')
result = s1 + s2_aligned
print(result)
```

Here we build two Series: s1 has daily data 0-4, while s2 has data every two days (0,10,20). Reindexing s2 to s1's daily index with method='ffill' propagates the last known value forward, so s2_aligned becomes [0,0,10,10,20]. Adding the aligned series yields [0,1,12,13,24]. This example shows how Pandas automatically aligns on timestamps and how forward filling resolves gaps, a common requirement when merging sensor readings with different sampling rates. The limitation is that forward fill assumes the last observation remains valid, which may not hold for rapidly changing signals.

Process flow

1. 1. Load raw data into a NumPy array or Pandas DataFrame, specifying dtype to avoid implicit conversion.
2. 2. If the file is larger than memory, replace np.load with np.memmap to map the file on disk.
3. 3. Apply vectorized transformations (e.g., scaling, masking) using NumPy broadcasting to avoid loops.
4. 4. Convert the cleaned array to a DataFrame, assigning meaningful column names and a datetime index.
5. 5. Align multiple time-series using the index; use reindex with forward/backward fill or interpolation as needed.
6. 6. Perform group-by or resample operations to aggregate data to the desired frequency.
7. 7. Export the final tidy DataFrame to CSV or a binary format, ensuring that no intermediate copies remain in memory.

Interview and exam checkpoints

Explain how broadcasting works in NumPy and give a case where it can lead to unexpected results.

Broadcasting allows arrays of different shapes to participate in arithmetic by virtually replicating the smaller array along dimensions of size one. The rule is that dimensions are compared from the right; if they are equal or one of them is one, broadcasting proceeds. An unexpected result occurs when a programmer assumes a (3,1) array will broadcast across columns, but actually it broadcasts across rows, leading to shape (3, n) instead of (n, 3). This can produce transposed results or silent shape mismatches if not checked.

What are the advantages and disadvantages of using numpy.memmap for large datasets?

Advantages include low memory footprint, as only the accessed portions are loaded, and the ability to modify data on disk without an explicit save step. Disadvantages are slower random access due to page faults, the requirement that the file layout (dtype, shape) remain constant, and limited support for complex indexing operations that may trigger many small reads, degrading performance.

How does Pandas handle arithmetic between two Series with non-matching timestamps?

Pandas aligns the Series on the union of their indices. For timestamps present in only one Series, the result contains NaN for the missing operand. The user can then fill these NaNs using methods like fillna, forward fill, or interpolation, depending on the semantics of the data. This alignment ensures that operations are label-driven rather than position-driven.

Describe a scenario where you would prefer to use DataFrame.resample() over DataFrame.asfreq().

When aggregating high-frequency sensor data to a lower frequency (e.g., minute to hourly), you need to compute a summary statistic such as the mean or sum for each hour. resample() allows you to specify the aggregation function, whereas asfreq() merely changes the index without aggregating, potentially leaving multiple rows per new period and requiring manual reduction.

Summary

NumPy provides the fast, memory-contiguous array core that enables vectorized arithmetic and broadcasting, eliminating Python loops. Pandas builds on this foundation with labeled Series and DataFrames, offering automatic alignment of data by index, powerful time-series utilities, and group-by aggregation. Memory mapping extends NumPy to handle datasets larger than RAM by treating files as arrays, while careful use of broadcasting avoids unnecessary copies. Together, these tools let you ingest raw data, transform it efficiently, align disparate time series, and produce tidy outputs ready for analysis or modeling. Mastery of these concepts reduces runtime, prevents subtle bugs from misaligned data, and prepares you for real-world data pipelines.

Practice questions

1. Given A = np.array([[2,4],[6,8]]) and B = np.array([1,2]), compute A - B using broadcasting and show the result.

2. Create a memmap of a file 'ints.bin' containing 100 int16 numbers from 0 to 99. Then compute the sum of the first 10 elements without loading the whole file.

3. You have two daily price series: s1 indexed Jan 1-5 with values [100,101,102,103,104]; s2 indexed Jan 3-7 with values [200,201,202,203,204]. Align them, forward-fill missing values, and compute the daily spread s1 - s2.

4. Design a data ingestion pipeline that reads a 2 GB CSV, filters rows where column 'status' == 'active', and writes the result to a compressed Parquet file, using vectorized operations and minimal memory.

5. Explain the trade-off between forward-fill and linear interpolation when aligning irregular time-series data.

6. Write a NumPy function that takes a 2-D integer array and returns a new array where each row is normalized to have zero mean and unit variance, using only vectorized operations.

Practice solutions

1. A - B triggers broadcasting of B to shape (2,2): B becomes [[1,2],[1,2]]. Subtraction yields [[1,2],[5,6]]. Code: import numpy as np; A=np.array([[2,4],[6,8]]); B=np.array([1,2]); print(A-B) -> [[1 2]
 [5 6]].

2. import numpy as np; mm = np.memmap('ints.bin', dtype='int16', mode='r', shape=(100,)); total = mm[:10].sum(); print(total) -> sum of 0..9 = 45. The memmap reads only the first 10 values from disk.

3. import pandas as pd; idx1=pd.date_range('2022-01-01', periods=5); idx2=pd.date_range('2022-01-03', periods=5); s1=pd.Series([100,101,102,103,104], index=idx1); s2=pd.Series([200,201,202,203,204], index=idx2); s2_aligned=s2.reindex(s1.index, method='ffill'); spread=s1 - s2_aligned; Result: 2022-01-01 NaN, 2022-01-02 NaN, 2022-01-03 -100, 2022-01-04 -102, 2022-01-05 -104.

4. Use pandas.read_csv with chunksize to stream the file, e.g., for chunk in pd.read_csv('big.csv', chunksize=100000, dtype={'status':'category'}): filtered = chunk[chunk['status']=='active']; filtered.to_parquet('out.parquet', engine='pyarrow', compression='snappy', index=False, append=True). This avoids loading the whole file, leverages vectorized boolean indexing, and writes incrementally to a compressed columnar format.

5. Forward-fill assumes the last observed value remains valid until a new measurement arrives, which is simple and fast but can introduce step-like artifacts, especially for rapidly changing signals. Linear interpolation estimates intermediate values by assuming a straight line between known points, providing smoother estimates but requiring at least two surrounding observations and potentially misrepresenting non-linear dynamics. Choose forward-fill for categorical or slowly varying data, interpolation for continuous measurements where smoothness is desired.

6. def normalize_rows(arr):
    mean = arr.mean(axis=1, keepdims=True)
    std = arr.std(axis=1, keepdims=True)
    return (arr - mean) / std

```
# Example: A=np.array([[1,2,3],[4,5,6]]); print(normalize_rows(A))
# Output: [[-1.2247 0. 1.2247]
# [-1.2247 0. 1.2247]]
```

Reference textbooks

Python for Data Analysis - Wes McKinney

Python Data Science Handbook - Jake VanderPlas

Primary documentation

https://pandas.pydata.org/docs/user_guide/index.html

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

6. Supervised Learning Algorithms

Prerequisites: Linear Algebra, Probability & Statistics, NumPy & Pandas Processing

Supervised learning algorithms form the backbone of many real-world predictive systems, from credit scoring to image classification. They learn a mapping from input features to a target label by exploiting labeled examples. Understanding when to use a particular algorithm, how it builds its model, and what assumptions it makes is essential for any data scientist. This chapter introduces the fundamental ideas behind three widely used families - gradient boosted trees, regularization techniques for linear models, and support vector machines - starting from the mathematics that underpins them and progressing to practical implementation tips. By the end, a beginner will be able to select, train, and evaluate these models on small datasets, recognize common pitfalls, and discuss their trade-offs in an interview setting.

Foundations

Supervised learning begins with a dataset D = {(x_i, y_i)}_{i=1}^n where each x_i is a vector of p features and y_i is the target. The goal is to find a function f(x;θ) parameterized by θ that minimizes a loss L(y, f(x)). For regression, L is often the squared error (y - f(x))^2; for classification, the logistic loss or hinge loss is common. Linear models assume f(x)=w^T x + b, leading to a convex optimization problem that can be solved analytically or with gradient descent. Regularization adds a penalty term R(w) to the objective, controlling model complexity and preventing over-fitting. Tree-based methods, in contrast, partition the feature space recursively, fitting simple constant values in each leaf. Gradient boosting builds an ensemble of such trees by iteratively fitting each new tree to the residuals of the current ensemble, effectively performing gradient descent in function space. Support vector machines construct a separating hyperplane with maximal margin; by mapping inputs into a higher-dimensional space with a kernel, they can handle non-linear patterns while still solving a convex quadratic program. All three approaches share the need for careful preprocessing, hyper-parameter tuning, and validation to achieve reliable performance.

Gradient Boosted Trees (XGBoost)

Gradient boosted trees combine many shallow decision trees to produce a strong predictor. Each tree is fit to the negative gradient of the loss with respect to the current model predictions, which is why the method is called gradient boosting. The algorithm proceeds in stages: start with a constant prediction (often the mean of y), compute residuals r_i = -∂L/∂f(x_i), fit a regression tree to r_i, and update the model f_new(x) = f_old(x) + η * tree(x) where η is the learning rate. Regularization appears both in the tree structure (max depth, min child weight) and in the objective (L2 penalty on leaf weights). XGBoost adds second-order Taylor approximation of the loss, enabling efficient computation of optimal leaf values and providing built-in handling of missing values. Trade-offs include higher predictive power versus longer training time and greater sensitivity to noisy features if depth is not limited.

Worked reasoning: Consider a tiny dataset with a single feature x and target y: (1,3), (2,5), (3,7), (4,9). The initial prediction is the mean y = 6. The residuals are [-3, -1, 1, 3]. Fit a depth-1 tree that splits at x=2.5, assigning leaf values -2 for the left side and +2 for the right side (average residuals). With learning rate η=0.5, the updated predictions become 6 + 0.5*(-2) = 5 for x≤2.5 and 6 + 0.5*(2) = 7 for x>2.5. A second iteration repeats the process on new residuals, gradually shaping a piecewise linear approximation of the true relationship y=2x+1.

Regularization (L1/L2)

Regularization adds a penalty to the loss function to discourage overly complex models. L2 regularization (ridge) adds λ||w||_2^2, shrinking all coefficients toward zero but never exactly zero, which improves numerical stability and reduces variance. L1 regularization (lasso) adds λ||w||_1, encouraging sparsity by driving some coefficients exactly to zero, thus performing feature selection. The combined elastic-net penalty λ1||w||_1 + λ2||w||_2^2 balances both effects. In linear regression, the closed-form ridge solution is w = (X^T X + λI)^{-1} X^T y, while lasso requires iterative solvers such as coordinate descent. Trade-offs: L2 is easier to compute and works well when many small effects exist; L1 is useful when only a few features are truly predictive but can be unstable if features are highly correlated.

Worked reasoning: Take a 3-feature dataset: X = [[1,2,3],[1,0,1],[0,1,1]], y = [6,4,5]. Without regularization, the ordinary least squares solution solves (X^T X)w = X^T y. X^T X = [[2,2,4],[2,5,5],[4,5,11]] and X^T y = [15,14,27]. Solving gives w ≈ [1,1,1]. With L2 λ=1, compute (X^T X + I) = [[3,2,4],[2,6,5],[4,5,12]]. Inverting yields w_ridge ≈ [0.78,0.92,0.84]. The coefficients shrink toward zero, reducing sensitivity to noise.

Support Vector Machines

Support vector machines (SVM) aim to find the hyperplane that maximizes the margin between two classes. For linearly separable data, the primal problem minimizes ½||w||^2 subject to y_i (w^T x_i + b) ≥ 1. Introducing slack variables ξ_i and a penalty C yields the soft-margin formulation, allowing some misclassifications. The dual problem involves Lagrange multipliers α_i and depends only on inner products x_i·x_j, enabling the kernel trick: replace the inner product with a kernel function K(x_i,x_j) to implicitly map data into a high-dimensional space. Common kernels include polynomial K = (γ x_i·x_j + r)^d and radial basis function K = exp(-γ||x_i - x_j||^2). Only points with α_i > 0 (support vectors) influence the decision boundary. Trade-offs: SVMs provide strong theoretical guarantees and work well on medium-size datasets, but training scales poorly with n and requires careful kernel and C selection.

Worked reasoning: A binary dataset: x = [[0,0],[2,2],[2,0],[0,2]], y = [-1,-1,1,1]. The optimal separating line is x_1 = x_2. The margin is √2/2. The support vectors are (0,0) and (2,2) for class -1 and (2,0) and (0,2) for class +1. Solving the dual yields α = [0.5,0.5,0.5,0.5]. The decision function f(x) = Σ α_i y_i K(x_i,x) + b simplifies to f(x) = x_1 - x_2, correctly classifying all points.

Worked examples

Worked example

```
import numpy as np
X = np.array([[1],[2],[3],[4]])
y = np.array([3,5,7,9])
# initial constant prediction
f0 = np.mean(y)
res = y - f0
# simple depth-1 tree split at 2.5
left = res[X[:,0]<=2.5].mean()
right = res[X[:,0]>2.5].mean()
eta = 0.5
pred = f0 + eta*np.where(X[:,0]<=2.5, left, right)
print('pred:', pred)
```

The code implements the first two boosting iterations on a tiny regression problem. The initial prediction f0 = 6 is the mean of y. Residuals are computed, then a single split at x=2.5 yields average residuals -2 (left)

and +2 (right). With learning rate 0.5 the updated predictions become [5,5,7,7]. The output shows how gradient boosting incrementally improves the fit. Limitations include the use of only one tree depth and a very small dataset; real-world models require many trees, regularization, and validation to avoid over-fitting.

Applied example

```
def train_svm(X, y, C=1.0, gamma=0.5):
    # Pseudocode for soft-margin RBF SVM
    K = np.exp(-gamma * np.sum((X[:,None]-X[None,:])**2, axis=2))
    # Solve dual: maximize sum(alpha) - 0.5*alpha^T (YKY) alpha
    # subject to 0 <= alpha_i <= C and sum(alpha_i y_i)=0
    alpha = quadratic_program_solver(K, y, C)
    sv = alpha > 1e-6
    w = np.sum(alpha[sv][:,None] * y[sv][:,None] * X[sv], axis=0)
    b = np.mean(y[sv] - K[sv][:,sv] @ (alpha[sv] * y[sv]))
    return w, b
# Note: quadratic_program_solver is a placeholder for a QP library.
```

The pseudocode outlines the steps to train a soft-margin SVM with an RBF kernel. First, the kernel matrix K is built using the Gaussian formula. The dual optimization problem is then solved for the Lagrange multipliers alpha, respecting box constraints and the equality constraint. Support vectors are identified where alpha is non-zero. The weight vector w in the implicit feature space is reconstructed as a weighted sum of support vectors, and the bias b is computed by averaging over support vectors. In practice, a library such as cvxopt or scikit-learn handles the quadratic programming. The example highlights the importance of choosing C and gamma: large C reduces regularization, while large gamma makes the kernel narrow, both affecting margin and over-fitting.

Process flow

1. 1. Load and clean the data, ensuring numeric types and handling missing values.
2. 2. Split the dataset into training and validation sets to estimate generalization error.
3. 3. Choose a model family (tree boosting, regularized linear, or SVM) based on data size and feature types.
4. 4. Define the loss function and add regularization terms if applicable; set hyper-parameters.
5. 5. Train the model: for boosting iterate tree fitting on residuals; for linear solve the regularized normal equations; for SVM solve the dual quadratic program.
6. 6. Evaluate on validation data using appropriate metrics (RMSE for regression, accuracy/F1 for classification).
7. 7. Perform hyper-parameter tuning (grid or Bayesian) and repeat steps 4-6 until performance stabilizes.

Interview and exam checkpoints

Explain how gradient boosting reduces bias and variance compared to a single decision tree.

A single decision tree often has high variance because small changes in the data can produce a very different structure; it also may be shallow, leading to bias. Gradient boosting builds an ensemble where each new tree corrects the residual errors of the current model, effectively performing functional gradient descent. By adding many weak learners, the bias is reduced as the ensemble can approximate complex functions. Simultaneously, regularization techniques such as learning rate, tree depth limits, and subsampling control variance, preventing the ensemble from over-fitting the training data.

What is the effect of L1 regularization on feature selection, and when might it be harmful?

L1 regularization adds a penalty proportional to the absolute value of coefficients, encouraging many weights to become exactly zero. This yields an implicit feature selection, which is useful when the true model is sparse. However, if features are highly correlated, L1 may arbitrarily keep one and discard others, leading to instability and loss of predictive information. In such cases, an elastic-net or pure L2 penalty may be preferable.

Describe the kernel trick and give an example of a kernel that maps data to an infinite-dimensional space.

The kernel trick replaces the inner product $x_i \cdot x_j$ in the dual SVM formulation with a kernel function $K(x_i,x_j)$ that computes the inner product in a transformed feature space without explicitly performing the transformation. The radial basis function kernel $K = \exp(-\gamma||x_i - x_j||^2)$ corresponds to mapping data into an infinite-dimensional Hilbert space of Gaussian basis functions. This allows the SVM to create highly non-linear decision boundaries while keeping the optimization problem dependent only on pairwise kernel evaluations.

How does the learning rate η influence the training of a gradient boosted model?

The learning rate scales the contribution of each newly fitted tree to the ensemble. A small η (e.g., 0.01) forces the model to take many incremental steps, often improving generalization because each tree makes only a modest correction, reducing the risk of over-fitting. Conversely, a large η (e.g., 0.5) speeds up convergence but can cause the model to fit noise quickly, leading to higher variance. Practitioners typically pair a small η with a larger number of trees.

Summary

Supervised learning algorithms translate labeled data into predictive functions by minimizing a loss while controlling model complexity. Gradient boosted trees iteratively fit shallow trees to residuals, offering high accuracy at the cost of training time and hyper-parameter sensitivity. Regularization, through L1 or L2 penalties, shrinks linear model coefficients to reduce variance; L1 also performs feature selection but can be unstable with correlated inputs. Support vector machines construct maximal-margin hyperplanes, leveraging kernels to handle non-linear patterns, yet they scale poorly with large datasets. Across all methods, proper data preprocessing, validation, and systematic hyper-parameter tuning are essential to balance bias, variance, and computational resources.

Practice questions

1. Given X=[[1,2],[2,1],[3,3]], y=[4,5,10], compute the ridge regression coefficients with λ=2 using the closed-form solution.

2. Fit a depth-1 decision stump to the residuals r=[-2,-2,2,2] of a 4-point dataset with feature x=[1,2,3,4]. What are the leaf predictions and the updated model after one boosting step with η=0.5?

3. Implement Lasso regression using coordinate descent for a 2-feature dataset X=[[1,0],[0,1],[1,1]], y=[1,2,3] with λ=0.5. Show one full cycle of updates.

4. Design a binary classifier for a dataset with 10,000 samples and 500 features where most features are sparse. Choose between a linear SVM and gradient boosted trees and justify the trade-off.

5. Compute the squared approximation error and the L2 norm error for approximating vector v=[3,4] by u=[2,5].

6. Using scikit-learn, write a short Python snippet to train an XGBoost classifier with max_depth=3 and evaluate accuracy on a hold-out set.

Practice solutions

1. First compute X^T X = [[1+4+9, 2+2+9],[2+2+9,4+1+9]] = [[14,13],[13,14]]. Add λI: [[16,13],[13,16]]. Compute the inverse: determinant = 16*16-13*13 = 256-169 = 87. Inverse = (1/87)*[[16,-13],[-13,16]]. Compute X^T y = [1*4+2*5+3*10, 2*4+1*5+3*10] = [4+10+30, 8+5+30] = [44,43]. Multiply: w = (1/87)*[[16,-13],[-13,16]] @ [44,43] = (1/87)*[16*44-13*43, -13*44+16*43] = (1/87)*[704-559, -572+688] = (1/87)*[145,116] ≈ [1.666,1.333]. Thus the ridge coefficients are w1≈1.67, w2≈1.33.

2. A depth-1 stump chooses a split that separates negative from positive residuals. Splitting at x=2.5 yields left leaf residuals [-2,-2] with mean -2, right leaf residuals [2,2] with mean 2. With learning rate η=0.5, leaf contributions are -1 and +1 respectively. If the current model prediction is f0 (e.g., the mean of y), the updated prediction becomes f1 = f0 + leaf_contrib. For example, if f0=6, predictions become 5 for x≤2.5 and 7 for x>2.5.

3. Initialize w=[0,0]. Update w1: residual = y - X[:,1]*w2 = [1,2,3] - [0,1,1]*0 = [1,2,3]. Compute rho = X[:,0]^T residual = 1*1+0*2+1*3 = 4. Apply soft-threshold: w1 = sign(rho)*max(|rho|-λ,0)/ (X[:,0]^T X[:,0]) = 1*max(4-0.5,0)/2 = 3.5/2 = 1.75. Update w2: residual = y - X[:,0]*w1 = [1,2,3] - [1,0,1]*1.75 = [-0.75, 2, 1.25]. rho = X[:,1]^T residual = 0*(-0.75)+1*2+1*1.25 = 3.25. w2 = sign(3.25)*max(3.25-0.5,0)/2 = 2.75/2 = 1.375. After one cycle, w≈[1.75,1.38].

4. A linear SVM with an L1 penalty is preferable for high-dimensional sparse data because it operates on inner products and can exploit sparsity, leading to fast training and a model that uses only a subset of features. Gradient boosted trees would need to examine many dense splits, incurring high memory and time costs, and may over-fit due to the large feature space. The trade-off is that trees can capture non-linear interactions, but with 500 sparse features the linear decision boundary is often sufficient and far more scalable.

5. Squared approximation error = Σ (v_i - u_i)^2 = (3-2)^2 + (4-5)^2 = 1^2 + (-1)^2 = 2. L2 norm error = sqrt(2) ≈ 1.414. The squared error is useful in loss functions; the norm error gives the Euclidean distance.

6. import numpy as np
from sklearn.model_selection import train_test_split
from xgboost import XGBClassifier
X = np.random.randn(200,5)
y = (X[:,0] + X[:,1] > 0).astype(int)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
model = XGBClassifier(max_depth=3, n_estimators=50, use_label_encoder=False, eval_metric='logloss')
model.fit(X_train, y_train)
acc = model.score(X_test, y_test)
print('Accuracy:', acc)

Reference textbooks

Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow - Aurelien Geron

Pattern Recognition and Machine Learning - Christopher M. Bishop

The Elements of Statistical Learning - Trevor Hastie, Robert Tibshirani and Jerome Friedman

Primary documentation

https://scikit-learn.org/stable/supervised_learning.html

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

7. Neural Network Architecture

Prerequisites: Multivariate Calculus, Supervised Learning Algorithms

Neural network architecture is the backbone of modern machine learning systems. It determines how data flows, how parameters are organized, and how learning signals propagate. Understanding architecture is essential when designing models that can capture complex patterns, scale to large datasets, and train efficiently. This chapter introduces the fundamental building blocks - layers, activation functions, and normalization - before connecting them to the temporal extension of backpropagation. By mastering these concepts, a beginner can construct simple feed-forward nets, extend them to recurrent structures, and reason about trade-offs such as expressiveness versus computational cost. The material is self-contained, uses exact integer examples, and prepares the reader for interview questions and practical coding tasks.

Foundations

A neural network is a directed graph of computational units called neurons. Each neuron computes a weighted sum of its inputs, adds a bias, and applies a non-linear activation. Mathematically, for layer l we write z^{(l)} = W^{(l)} a^{(l-1)} + b^{(l)} and a^{(l)} = phi(z^{(l)}), where phi is the activation function. The weight matrix W^{(l)} maps the output of layer l-1 (a^{(l-1)}) to the pre-activation vector z^{(l)}. Stacking layers yields a composition of functions, enabling the network to approximate highly non-linear mappings. Training adjusts all W and b by minimizing a loss L using gradient descent. Gradients are obtained by backpropagation, which applies the chain rule from the output layer back to the input. For recurrent networks, the same equations are applied at each time step, and gradients are summed across time - a process called Backpropagation Through Time (BPTT). Normalization layers, such as batch normalization, re-scale activations to have zero mean and unit variance, stabilizing training and allowing higher learning rates. Together, these elements define the architecture: the number of layers, their sizes, the choice of phi, and where normalization is inserted.

Layer Design

A layer is defined by its dimensionality (input size n_in, output size n_out) and its parameter matrices. Fully connected (dense) layers use a dense weight matrix W of size n_out x n_in. Convolutional layers share weights across spatial locations, reducing parameters but adding locality bias. The choice of n_out controls model capacity: larger n_out can capture more features but increase overfitting risk and computational cost. Bias vectors b add flexibility by shifting activation thresholds. When stacking layers, the output dimension of one must match the input dimension of the next, unless a reshaping operation is inserted. Trade-offs involve depth versus width: deep narrow networks can represent hierarchical features, while shallow wide networks may learn faster but lack hierarchical abstraction.

Worked reasoning: Consider a two-layer feed-forward net. Layer 1 maps a 2-dimensional input to 3 hidden units: W1 = [[1,2],[0,1],[-1,0]] and b1 = [0,1, -1]. Input x = [2,3]. Compute z1 = W1*x + b1 = [1*2+2*3+0, 0*2+1*3+1, -1*2+0*3-1] = [8,4, -3]. Apply ReLU phi(z)=max(0,z) => a1 = [8,4,0]. Layer 2 maps 3 hidden units to a single output: W2 = [[2, -1, 0]] and b2 = [1]. z2 = W2*a1 + b2 = 2*8 + (-1)*4 + 0*0 +1 = 13. The network output is 13.

Activation Functions

Activations introduce non-linearity, allowing networks to approximate complex functions. Common choices include sigmoid, tanh, ReLU, and leaky ReLU. Sigmoid squashes to (0,1) but suffers from vanishing gradients for large |z|. Tanh outputs (-1,1) and is zero-centered, reducing bias in gradients. ReLU(z)=max(0,z) is simple, sparse, and mitigates vanishing gradients, yet can deaden neurons if inputs stay negative. Leaky ReLU adds a small slope (e.g., 0.01) for negative inputs, preserving gradient flow. The selection depends on depth, data distribution, and hardware: ReLU dominates in deep vision models, while tanh may be preferred in recurrent cells to keep activations bounded.

Worked reasoning: Using the previous layer 1 pre-activations z1 = [8,4,-3], apply three different activations: sigmoid(8)≈0.9997, tanh(8)≈0.9999, ReLU(8)=8. For the negative unit, sigmoid(-3)≈0.047, tanh(-3)≈-0.995, ReLU(-3)=0. The choice dramatically changes the hidden representation passed to the next layer.

Layer & Batch Normalization

Batch normalization (BN) normalizes each mini-batch's activations to zero mean and unit variance, then scales and shifts them with learnable parameters gamma and beta. For a batch {a_i}, BN computes mu = (1/m) Σ a_i, sigma^2 = (1/m) Σ (a_i - mu)^2, then outputs â_i = (a_i - mu)/sqrt(sigma^2 + epsilon). Finally, y_i = gamma * â_i + beta. BN reduces internal covariate shift, allowing higher learning rates and smoother loss landscapes. However, BN introduces dependence on batch size; very small batches yield noisy statistics. In recurrent networks, applying BN per time step can break temporal consistency, so alternatives like layer normalization are sometimes preferred. Layer normalization instead computes statistics across the feature dimensions of each individual example, so it does not require a batch of other examples or running batch statistics. It is common in transformers and works naturally with variable-length sequences when the normalized feature dimensions are specified correctly. Both methods use learned scale and shift parameters, but their normalization axes differ. Batch normalization may behave differently between training and inference; layer normalization uses per-example statistics in both modes.

Worked reasoning: Suppose a mini-batch of three hidden activations after ReLU: [8,4,0]. mu = (8+4+0)/3 = 4. sigma^2 = [(8-4)^2+(4-4)^2+(0-4)^2]/3 = (16+0+16)/3 = 10.6667. Normalized values: â = [(8-4)/sqrt(10.6667), (4-4)/..., (0-4)/...] ≈ [1.2247,0,-1.2247]. With gamma=2, beta=1, final BN output = [2*1.2247+1, 1, 2*(-1.2247)+1] ≈ [3.4494,1,-1.4494]. For layer normalization of one vector [1,3], the mean is 2 and the population variance is 1. With scale 1, shift 0 and a small epsilon, its normalized values are approximately [-1,1]. Another example in the batch does not change these values. This contrasts with batch normalization, where each feature is normalized using statistics pooled over examples.

Backpropagation through Time

BPTT extends standard backpropagation to recurrent networks that process sequences. At each time step t, the hidden state h_t depends on input x_t and previous state h_{t-1}: h_t = phi(Wh h_{t-1} + Wx x_t + b). The loss L aggregates over all time steps, e.g., L = Σ_t L_t(y_t, target_t). To compute gradients, we unroll the network for T steps, treat each copy as a separate layer, and apply backpropagation from the final time step back to the first. Gradients accumulate across time, leading to terms like dL/dWh = Σ_t (δ_t * h_{t-1}^T). Long sequences can cause exploding or vanishing gradients because the same weight matrix is multiplied many times; gradient clipping and gated architectures (LSTM, GRU) mitigate these issues.

Worked reasoning: Consider a simple RNN with scalar hidden state h_t, weight w=0.5, bias b=0, activation identity, and inputs x_1=2, x_2=1. Recurrence: h_t = w*h_{t-1}+x_t, with h_0=0. Compute h_1 = 0.5*0+2 = 2, h_2 = 0.5*2+1 = 2. Loss L = (h_2-3)^2. dL/dh_2 = 2*(h_2-3)= -2. Gradient w.r.t w: dL/dw = dL/dh_2 *

(dh_2/dw) = -2 * (h_1) = -2*2 = -4. Gradient w.r.t w accumulates from both steps if unrolled longer, illustrating BPTT accumulation.

Worked examples

Worked example

```
import numpy as np
W1 = np.array([[1,2],[0,1],[-1,0]])
b1 = np.array([0,1,-1])
W2 = np.array([[2,-1,0]])
b2 = np.array([1])
x = np.array([2,3])
z1 = W1.dot(x) + b1
a1 = np.maximum(0,z1)  # ReLU
z2 = W2.dot(a1) + b2
print('output', z2.item())
```

The code builds the two-layer network described in the Layer Design example. It uses NumPy for exact integer arithmetic, applies ReLU, and prints the final scalar output 13. Because all operations are integer-based, there is no rounding error; the result matches the hand calculation. This demonstrates how a small network can be implemented and verified quickly. Limitations include the lack of bias handling for batch dimensions and no automatic differentiation; for training one would need to compute gradients manually or use a library.

Applied example

```
def rnn_forward(x_seq, w, b):
    h = 0
    for x in x_seq:
        h = w*h + x + b
    return h
# sequence [2,1], w=0.5, b=0
print(rnn_forward([2,1], 0.5, 0))
```

This pseudocode implements the scalar RNN recurrence used in the BPTT example. It iterates over a list of inputs, updates the hidden state, and returns the final state. Running it yields 2.0, matching the manual computation of h_2. The function is deliberately simple to expose the unrolled computation; in practice one would vectorize over batches and include activation functions. Extending this to compute gradients would require storing intermediate h values and applying the chain rule backward through the loop.

Process flow

1. 1. Define the input dimension and choose an appropriate layer size for the first hidden layer.
2. 2. Select an activation function (ReLU for deep nets, tanh for recurrent cells) and justify the choice based on gradient flow.
3. 3. Insert batch normalization after the linear transform and before the activation to stabilize learning.
4. 4. Stack additional layers, ensuring each output dimension matches the next input dimension.

5	5. For sequence data, replicate the hidden layer across time steps and apply BPTT to compute gradients.
6	6. Perform gradient descent with learning-rate scheduling; clip gradients if the recurrent depth is large.
7	7. Evaluate on a validation set, adjust layer widths or add regularization, and repeat the cycle.

Interview and exam checkpoints

Why is batch normalization usually placed before the activation function?

Placing BN before the activation ensures that the normalized values have zero mean and unit variance when they enter the non-linear function. This reduces the chance that the activation saturates (e.g., sigmoid near 0 or 1) and keeps gradients well-scaled. If BN were applied after activation, the distribution would be distorted by the non-linearity, defeating the purpose of stabilizing the internal covariate shift.

Explain how the choice of activation affects gradient propagation in deep networks.

Activations with bounded derivatives, such as sigmoid, produce gradients less than one, causing the product of many small numbers to vanish as it back-propagates, which slows learning in deep layers. ReLU has a derivative of 1 for positive inputs, preserving gradient magnitude and enabling deeper networks to train. However, ReLU can produce dead neurons when inputs stay negative, so leaky ReLU or parametric ReLU are sometimes used to maintain a small gradient everywhere.

What is the main computational difference between BPTT and standard backpropagation?

Standard backpropagation processes a static feed-forward graph once, while BPTT unrolls a recurrent graph over T time steps, creating T copies of the same parameters. The gradient for a recurrent weight is the sum of contributions from each time step, leading to O(T) memory and compute cost. This accumulation can cause exploding or vanishing gradients, requiring techniques like gradient clipping or gated cells.

When would you prefer layer normalization over batch normalization?

Layer normalization computes statistics across the features of a single example rather than across a batch. It is therefore independent of batch size and works well for recurrent networks where batch statistics vary across time steps. It also simplifies inference because the same normalization parameters apply to each sample, avoiding the need for running averages.

How does increasing network depth affect model capacity and training difficulty?

Depth adds hierarchical representation power, allowing the model to compose simple features into complex ones, which often improves accuracy on tasks like vision or language. However, deeper networks are harder to train due to vanishing/exploding gradients, higher memory consumption, and increased risk of overfitting. Techniques such as residual connections, careful initialization, and normalization mitigate these difficulties.

Describe a scenario where a wide shallow network might outperform a deep narrow one.

When the target function is relatively simple and does not require hierarchical feature extraction - e.g., a linear or low-degree polynomial mapping - a wide shallow network can capture the necessary basis functions directly, converging faster and with fewer training epochs. In contrast, a deep narrow network may struggle to propagate gradients through many layers, leading to slower convergence.

Summary

Neural network architecture combines linear transformations, non-linear activations, and normalization to build expressive models. Layers define how data dimensions change, while activation functions inject the non-linearity needed for universal approximation. Batch normalization stabilizes training by re-centering and re-scaling activations, but its effectiveness depends on batch size. For sequential data, Backpropagation Through Time extends gradient computation across time steps, exposing challenges like gradient explosion that are addressed with clipping or gated cells. Design decisions - depth versus width, activation choice, and normalization placement - balance expressiveness, computational cost, and training stability. Mastering these fundamentals enables the construction of robust models and prepares the learner for advanced topics such as residual networks and attention mechanisms.

Practice questions

1. Given a 2-input, 3-output dense layer with W = [[1,0],[2,1],[0,1]] and b = [1,0,-1], compute the ReLU activation for input x = [3,4].

2. Apply batch normalization to the activations [4,10,3] using gamma=1, beta=0, epsilon=1e-5. Show mu, sigma^2, normalized values.

3. Implement a Python function that performs one step of BPTT for a scalar RNN with weight w, bias b, and inputs [x1,x2]. Return the gradient dL/dw assuming loss L = (h2 - target)^2 with target=5.

4. Design a three-layer feed-forward network for MNIST digit classification. Specify layer sizes, activation choices, and where you would place batch normalization. Justify each decision.

5. Explain a trade-off between using a deep narrow network versus a shallow wide network in terms of parameter count and representational power.

6. Given a recurrent network with hidden size 2, weight matrix Wh = [[1,0],[0,1]], input weight Wx = [[1,2],[3,4]], bias b = [0,0], and input sequence x1=[1,0], x2=[0,1]. Compute hidden states h1 and h2 using identity activation.

Practice solutions

1. Compute z = W*x + b: first row 1*3+0*4+1 = 4; second row 2*3+1*4+0 = 10; third row 0*3+1*4-1 = 3. Apply ReLU: a = [4,10,3].

2. mu = (4+10+3)/3 = 5.6667. sigma^2 = [(4-5.6667)^2+(10-5.6667)^2+(3-5.6667)^2]/3 = (2.7778+18.7778+7.1111)/3 = 9.5556. sqrt(sigma^2+epsilon) ≈ 3.091. Normalized: (4-5.6667)/3.091≈-0.539, (10-5.6667)/3.091≈1.399, (3-5.6667)/3.091≈-0.862. With gamma=1, beta=0 the BN output is [-0.539,1.399,-0.862].

3. def bptt_scalar(w,b,inputs,target):
    h_prev = 0.0
    hs = []
    for x in inputs:
        h = w*h_prev + x + b
        hs.append(h)
        h_prev = h
    h2 = hs[-1]
    dL_dh2 = 2*(h2 - target)
    # gradient w.r.t w accumulates through both steps
    dh2_dw = hs[-2] if len(hs)>1 else 0.0
    # chain rule through first step
    dh1_dw = 0.0 # because h1 = w*0 + x1 + b
    dL_dw = dL_dh2 * dh2_dw + dL_dh2 * w * dh1_dw
    return dL_dw
Example call
print(bptt_scalar(0.5,0,[2,1],5))
Manual: h1=2, h2=0.5*2+1=2, dL/dh2= -6, dh2/dw = h1 =2, gradient = -12.

4. Input size 784 (28x28). Layer1: 784→256 dense, ReLU activation, batch normalization after the linear transform to keep activations centered, improving convergence. Layer2: 256→128 dense, ReLU, batch normalization again for the same reason. Layer3: 128→10 dense, softmax output for class probabilities; batch normalization is not needed after softmax because it would distort probability distribution. The decreasing widths encourage hierarchical feature extraction, while ReLU avoids vanishing gradients. Batch normalization before each ReLU stabilizes training, allowing a higher learning rate and reducing the need for careful weight initialization.

5. A deep narrow network with L layers of width n has roughly L*n^2 parameters (ignoring biases). A shallow wide network with one hidden layer of width m has about n_input*m + m*n_output parameters. For the same parameter budget, a deep network can capture hierarchical features, which is beneficial for data with compositional structure (e.g., images). However, deeper networks suffer from gradient attenuation and require more careful training tricks. A shallow wide network is easier to train and may converge faster on simple tasks, but it lacks the ability to build abstract representations, limiting performance on complex data.

6. h0 = [0,0]. h1 = Wh*h0 + Wx*x1 + b = [1*0+0*0 + 1*1+2*0, 0*0+1*0 + 3*1+4*0] = [1,3]. h2 = Wh*h1 + Wx*x2 = [1*1+0*3 + 1*0+2*1, 0*1+1*3 + 3*0+4*1] = [1+2, 3+4] = [3,7].

Reference textbooks

Deep Learning - Ian Goodfellow, Yoshua Bengio and Aaron Courville

Dive into Deep Learning - Aston Zhang, Zachary C. Lipton, Mu Li and Alexander J. Smola

Primary documentation

https://www.deeplearningbook.org/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

8. PyTorch Framework & Tensors

Prerequisites: Neural Network Architecture, Python (Advanced)

PyTorch has become a dominant deep-learning framework because it blends a Pythonic programming model with a powerful tensor library and an automatic differentiation engine. Understanding the core ideas - how tensors are stored, how gradients are computed, and how data is fed to models - enables you to write correct, efficient code and to scale training across many GPUs. This chapter introduces the fundamental building blocks of PyTorch, walks through concrete numeric examples, and prepares you for interview questions that probe both theory and practical implementation. By the end you will be able to create tensors, trace gradients with autograd, build custom datasets, and launch distributed training with DistributedDataParallel.

Foundations

A PyTorch tensor is a multi-dimensional array that lives either on CPU memory or on a GPU device. The tensor class supports standard arithmetic, broadcasting, and in-place operations; each operation records a node in a dynamic computation graph if any input requires gradients. The autograd engine traverses this graph backward, applying the chain rule to compute dLoss/dParameter for every leaf tensor that has requires_grad=True. Gradient accumulation is performed in the .grad attribute, which must be zeroed before each optimizer step. Data loading is decoupled from model code through the Dataset abstraction, which implements __len__ and __getitem__, and the DataLoader, which batches, shuffles, and optionally uses multiple worker processes. For large-scale training, DistributedDataParallel (DDP) replicates the model on each GPU process, synchronizes gradients after each backward pass, and ensures that each process sees a distinct subset of the data via DistributedSampler. These three pillars - tensor mechanics, autograd, and data pipelines - form the backbone of any PyTorch project and must be mastered before tackling advanced topics such as custom autograd functions or mixed-precision training.

Autograd Engine

The autograd engine builds a directed acyclic graph (DAG) where each node represents a tensor operation and edges represent data dependencies. When you call loss.backward(), the engine performs a reverse topological sort and computes gradients by applying the local derivative of each operation. The engine stores a Function object for each operation; this object knows how to compute both the forward output and the backward gradient. Leaf tensors that require gradients accumulate their partial derivatives in the .grad field. Autograd is dynamic: the graph is recreated at every forward pass, allowing conditional control flow but also requiring careful handling of in-place operations that might overwrite values needed for gradient computation.

Worked reasoning: Consider tensors a = torch.tensor([2.0, 3.0], requires_grad=True) and b = torch.tensor([4.0, 5.0], requires_grad=True). Compute c = a * b, then d = c.sum(). The backward pass d.backward() yields a.grad = [4.0, 5.0] and b.grad = [2.0, 3.0] because dc/da = b and dc/db = a. If we later perform e = c ** 2 and call e.sum().backward(), the gradients accumulate: a.grad becomes [4.0 + 2*2*2, 5.0 + 2*3*3] = [12.0, 23.0]. This illustrates gradient accumulation and the need to zero .grad before the next optimizer step.

Custom Dataset & DataLoader

A custom Dataset subclasses torch.utils.data.Dataset and implements __len__ to return the number of samples and __getitem__ to retrieve a single sample given an index. The __getitem__ method can perform on-the-fly transformations, such as reading an image file, converting it to a tensor, and applying augmentations. DataLoader wraps a Dataset and provides an iterator that yields batches. It can shuffle data, drop incomplete batches, and spawn multiple worker processes for parallel I/O. The collate_fn argument allows custom batch assembly, for example padding variable-length sequences. Proper use of Dataset and DataLoader decouples data handling from model logic and enables efficient training pipelines.

Worked reasoning: Suppose we have a list of (x, y) pairs: data = [(1,2), (3,4), (5,6), (7,8)]. A SimpleDataset returns torch.tensor(x) and torch.tensor(y) for each index. Using DataLoader(dataset, batch_size=2, shuffle=True) yields batches like [[tensor([3,5]), tensor([4,6])], [tensor([1,7]), tensor([2,8])]] depending on the random seed. The DataLoader automatically stacks the tensors along a new batch dimension, so the model receives inputs of shape (batch_size, 1).

DistributedDataParallel (DDP)

DDP runs one model replica per GPU process. Each process holds its own optimizer and computes gradients on its local mini-batch. After the backward pass, DDP performs an all-reduce operation that sums gradients across all processes and then divides by the world size, ensuring that each replica sees the same averaged gradient. The synchronization is overlapped with computation to reduce overhead. A DistributedSampler ensures that each process receives a unique slice of the dataset, preventing duplicate data. DDP requires initializing the process group (backend='nccl' for GPUs) and wrapping the model with torch.nn.parallel.DistributedDataParallel. Correct usage yields near-linear scaling for data-parallel training.

Worked reasoning: Imagine training on two GPUs with world_size=2. Process 0 receives samples [0,1] and Process 1 receives [2,3] from a dataset of four items. After forward and backward, each process has gradients g0 and g1. DDP performs an all-reduce: g_avg = (g0 + g1)/2, and both processes update their parameters with g_avg. The loss printed by each process will differ because of different data, but the model parameters stay synchronized after each step.

Worked examples

Worked example

```
import torch

a = torch.tensor([2.,3.], requires_grad=True)
b = torch.tensor([4.,5.], requires_grad=True)

c = a * b
loss = c.sum()
loss.backward()
print('a.grad', a.grad)
print('b.grad', b.grad)
```

The script creates two leaf tensors a and b, multiplies them element-wise to obtain c, and then sums c to produce a scalar loss. Calling loss.backward() triggers autograd, which computes the gradient of loss with respect to each leaf. Because loss = a0*b0 + a1*b1, the partial derivative with respect to a is b, giving a.grad = [4.,5.]. Similarly, the derivative with respect to b is a, giving b.grad = [2.,3.]. This simple example demonstrates how gradients flow through element-wise operations and how they accumulate in the .grad

fields. In a real training loop you would zero the gradients before the next backward call to avoid unintended accumulation.

Applied example

```
# Pseudocode for DDP training loop
initialize_process_group(backend='nccl')
model = MyNet().to(device)
model = torch.nn.parallel.DistributedDataParallel(model)
optimizer = torch.optim.SGD(model.parameters(), lr=0.01)
train_sampler = torch.utils.data.distributed.DistributedSampler(dataset)
loader = torch.utils.data.DataLoader(dataset, batch_size=32,
        sampler=train_sampler)
for epoch in range(num_epochs):
    train_sampler.set_epoch(epoch)
    for x, y in loader:
        optimizer.zero_grad()
        out = model(x)
        loss = criterion(out, y)
        loss.backward()
        optimizer.step()
```

The pseudocode shows the essential steps for a DDP training script. First, a process group is created so that all processes can communicate. The model is moved to the appropriate GPU and wrapped with DistributedDataParallel, which inserts gradient synchronization hooks after each backward call. A DistributedSampler guarantees that each process sees a distinct subset of the dataset each epoch, preventing overlap. Inside the training loop, the sampler's epoch is set to shuffle deterministically across processes. The optimizer zeroes gradients, the forward pass computes loss, backward computes local gradients, and DDP automatically averages them before the optimizer step. This pattern scales to many GPUs with minimal code changes compared to a single-GPU script.

Process flow

1. Create tensors with requires_grad flag to indicate they participate in autograd.
2. Define a forward computation using tensor operations; PyTorch builds a dynamic graph.
3. Compute a scalar loss and call loss.backward() to trigger reverse-mode differentiation.
4. Zero the .grad fields before each iteration to avoid gradient accumulation errors.
5. Wrap the model in DistributedDataParallel and use DistributedSampler for data partitioning.
6. Run the training loop: forward, backward, optimizer.step(), ensuring synchronization.
7. Validate results and optionally switch to evaluation mode with model.eval().

Interview and exam checkpoints

How does PyTorch's autograd engine compute gradients for a dynamic computation graph?

Autograd records each tensor operation as a node in a directed acyclic graph during the forward pass. When loss.backward() is invoked, the engine performs a reverse topological traversal, applying the chain rule at each node. Each Function object stores a backward method that receives the upstream gradient and returns the gradient with respect to its inputs. Leaf tensors with requires_grad=True accumulate the resulting gradients in their .grad attribute. Because the graph is rebuilt on every forward call, conditional branches and loops are naturally supported, making autograd dynamic.

What are the advantages of using a custom Dataset over a simple list of tensors?

A custom Dataset encapsulates data loading logic, allowing lazy loading, on-the-fly transformations, and integration with external storage formats such as images or text files. It separates concerns: the model code receives ready-to-use tensors, while the Dataset handles I/O, caching, and augmentation. This design enables the DataLoader to parallelize loading with multiple workers, to shuffle data efficiently, and to apply custom collate functions for variable-length inputs. It also makes the pipeline reusable across experiments.

Explain how gradient synchronization works in DistributedDataParallel.

In DDP each process computes gradients on its local mini-batch. After the backward pass, DDP inserts a hook that triggers an all-reduce operation across all processes. The all-reduce sums the gradients for each parameter and then divides by the world size, producing the average gradient. This averaged gradient replaces the local gradient in each replica before the optimizer step, ensuring that all model copies stay identical. The communication is overlapped with computation using NCCL for GPUs, minimizing overhead.

What pitfalls can arise when using in-place tensor operations with autograd?

In-place operations modify a tensor's data without creating a new tensor. If the modified tensor is needed later for gradient computation, autograd may lose the original value, leading to incorrect gradients or runtime errors. PyTorch detects many unsafe in-place ops and raises a RuntimeError. To avoid pitfalls, either use out-of-place versions (e.g., torch.add instead of tensor.add_) or ensure the tensor is not a leaf requiring gradients when performing the in-place change.

Summary

PyTorch provides a cohesive ecosystem where tensors, automatic differentiation, and data pipelines interlock to enable rapid deep-learning development. Tensors store data on CPU or GPU and form the nodes of a dynamic computation graph built by autograd. The backward pass automatically applies the chain rule, accumulating gradients in leaf tensors. Custom Dataset classes abstract data access, while DataLoader handles batching, shuffling, and parallel loading. DistributedDataParallel scales this workflow across multiple GPUs by synchronizing gradients after each backward pass, using a DistributedSampler to avoid data duplication. Mastery of these three components - tensor mechanics, autograd, and distributed data handling - lays a solid foundation for building, debugging, and scaling neural-network models in PyTorch.

Practice questions

1. Given tensors x = torch.tensor([1.,2.,3.], requires_grad=True) and w = torch.tensor([0.5, -0.5, 2.0], requires_grad=True), compute y = (x * w).sum() and then the gradients dy/dx and dy/dw.

2. Implement a custom Dataset that returns the square of an integer index as a tensor and its cube as the label. Show how DataLoader batches size 3.

3. Explain why zeroing gradients (optimizer.zero_grad()) is essential in a training loop that uses gradient accumulation over multiple batches.

4. Design a trade-off between using DataLoader with num_workers=0 versus num_workers=4 for loading image data from disk. Discuss impact on CPU usage, GPU utilization, and reproducibility.

5. In a two-GPU DDP setup, each GPU processes a batch of size 8. If the loss on GPU0 is 0.6 and on GPU1 is 0.8, what is the effective loss used for logging if you average the two losses? Compute the average and comment on why this averaging is appropriate.

6. Write a short PyTorch snippet that creates a 3x3 diagonal integer matrix, computes its inverse analytically, and verifies the product equals the identity matrix.

Practice solutions

1. Forward: x*w = [0.5, -1.0, 6.0]; sum = 5.5, so y=5.5. Backward: dy/dx = w => [0.5, -0.5, 2.0]; dy/dw = x => [1.0, 2.0, 3.0]. After y.backward(), x.grad = [0.5, -0.5, 2.0] and w.grad = [1.0, 2.0, 3.0].

2.
```
class SquareCubeDataset(torch.utils.data.Dataset):
    def __init__(self, n):
        self.n = n
    def __len__(self):
        return self.n
    def __getitem__(self, idx):
        x = torch.tensor(idx, dtype=torch.float32)
        y = torch.tensor(idx**3, dtype=torch.float32)
        return x**2, y

dataset = SquareCubeDataset(10)
loader = torch.utils.data.DataLoader(dataset, batch_size=3, shuffle=False)
for batch_x, batch_y in loader:
```

```
    print(batch_x, batch_y)
# Output shows batches: [0,1,4] [0,1,8], then [9,16,25] [0,27,64], etc.
```

3. Each call to loss.backward() adds the newly computed gradient to the existing .grad field of leaf tensors. If you accumulate gradients over several mini-batches to simulate a larger batch size, you must explicitly zero the gradients only after the desired number of accumulation steps. Forgetting to zero them each iteration would cause gradients from all previous iterations to be summed indefinitely, leading to exploding updates and incorrect learning dynamics.

4. Using num_workers=0 runs data loading in the main process, which simplifies debugging and guarantees deterministic ordering, but it can become a bottleneck: the GPU may idle while waiting for I/O, reducing overall throughput. Setting num_workers=4 spawns four subprocesses that load and preprocess images in parallel, increasing CPU utilization and often keeping the GPU fed with data, thus improving training speed. However, multi-process loading introduces nondeterminism due to race conditions in random augmentations unless you set worker_init_fn with a fixed seed. It also consumes more memory per worker. The choice depends on dataset size, CPU cores, and whether reproducibility is a higher priority than raw speed.

5. Effective loss = (0.6 + 0.8) / 2 = 0.7. Averaging the per-process losses yields a metric that reflects the model's performance on the entire dataset slice seen in that iteration. Since DDP synchronizes gradients using the average, the averaged loss aligns with the gradient computation and provides a single scalar for monitoring training progress.

6.
```
import torch
D = torch.diag(torch.tensor([2,3,4], dtype=torch.float32))
D_inv = torch.diag(1/torch.tensor([2,3,4], dtype=torch.float32))
I = torch.mm(D, D_inv)
print(I)
# Output:
# tensor([[1., 0., 0.],
# [0., 1., 0.],
# [0., 0., 1.]])
# The product matches the identity matrix exactly because diagonal matrices invert element-wise.
```

Reference textbooks

Deep Learning - Ian Goodfellow, Yoshua Bengio and Aaron Courville

Dive into Deep Learning - Aston Zhang, Zachary C. Lipton, Mu Li and Alexander J. Smola

Primary documentation

https://docs.pytorch.org/tutorials/beginner/basics/intro.html

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

9. Docker & Containerization

Prerequisites: Python (Advanced)

Docker has become the de facto tool for packaging applications into lightweight, portable units called containers. By isolating the runtime environment, Docker lets developers run the same code on a laptop, a test server, or a cloud instance without worrying about missing libraries or mismatched system settings. Containerization shines when you need reproducible builds, rapid scaling, or clean separation between services. For data-science and deep-learning workloads, the ability to embed GPU drivers and CUDA libraries inside a container makes it possible to move heavy compute jobs across machines while preserving performance. This chapter introduces the core ideas of Docker and containerization, then builds up to the three advanced topics required for the competency: Multi-Stage GPU builds, CUDA base containers, and Docker Compose. By the end, a beginner will be able to write a Dockerfile that produces a minimal GPU-ready image, understand how to layer CUDA dependencies, and orchestrate multiple services with Compose.

Foundations

Docker works by creating a layered filesystem where each instruction in a Dockerfile adds a new read-only layer on top of the previous one. At runtime, Docker combines these layers with a thin writable layer, forming a complete root filesystem for the container. The isolation is provided by Linux kernel features: namespaces (process, network, mount, etc.) give each container its own view of the system, while cgroups limit CPU, memory, and I/O usage. Images are identified by a name and tag (e.g., myapp:1.0) and stored in a registry such as Docker Hub. When you run a container, Docker creates a new process tree whose PID 1 lives inside the container's PID namespace, ensuring that signals and process tables are scoped. For GPU workloads, the NVIDIA Container Toolkit adds a device plugin that exposes the host's GPU devices inside the container, and it also mounts the necessary driver files. Understanding these building blocks - layers, namespaces, cgroups, and the role of the toolkit - allows you to reason about why a multi-stage build can shrink an image, how a CUDA base image supplies the correct driver version, and how Docker Compose can launch a web service together with a GPU-accelerated worker without manual networking steps.

Multi-Stage GPU Builds

A multi-stage build splits the Dockerfile into separate stages, each with its own base image. The first stage typically uses a heavyweight image that contains compilers, build tools, and the full CUDA toolkit needed to compile GPU code. After the binary is built, a second stage starts from a minimal runtime image (often nvidia/cuda:xx-runtime) and copies only the compiled binaries and required libraries. This approach reduces the final image size dramatically, which speeds up distribution and reduces attack surface. The trade-off is a slightly more complex Dockerfile and the need to ensure that the runtime stage includes all shared libraries the binary depends on; missing a library will cause runtime failures.

Worked reasoning: Consider a simple CUDA program that adds two vectors. In stage one we use nvidia/cuda:12.2-devel as the base, copy the source, and run nvcc to produce a binary called vecadd. In stage two we switch to nvidia/cuda:12.2-runtime, copy the vecadd binary, and set the entrypoint. The final image contains only the runtime libraries and the binary, resulting in an image under 200 MB compared to the 2 GB size of the full development image.

CUDA Base Containers

CUDA base containers are official images published by NVIDIA that bundle a specific version of the CUDA driver, runtime, and optional cuDNN or TensorRT libraries. They are versioned by the CUDA toolkit release (e.g., 12.2) and by the OS distribution (e.g., ubuntu22.04). Using a CUDA base image guarantees binary compatibility between the container's CUDA libraries and the host's GPU driver, because the NVIDIA Container Toolkit checks that the host driver is at least as new as the container's runtime. The main trade-off is that you must align your host driver version with the container's CUDA version; otherwise the container will refuse to start. Selecting a runtime-only image reduces size, while a devel image includes compilers for on-the-fly builds.

Worked reasoning: A data-science team wants to run PyTorch with CUDA 12.2. They start FROM nvidia/cuda:12.2-runtime-ubuntu22.04, then pip install torch==2.2.0+cu122. The container inherits the correct libcuda.so and cudnn libraries, and the host's driver (>=525) satisfies the runtime check. If the host had an older driver, the container would emit an error like "CUDA driver version is insufficient for CUDA runtime version".

Docker Compose

Docker Compose is a declarative YAML format that defines multiple services, their images, networking, volumes, and environment variables. It allows you to spin up an entire application stack with a single command (docker-compose up). For containerized GPU workloads, Compose can specify the runtime: nvidia for each service that needs GPU access. Compose also handles service dependencies, so a web API can wait for a GPU-enabled worker to be ready before accepting requests. The downside is that Compose adds another layer of configuration; errors in the YAML (such as mismatched indentation) can cause the whole stack to fail to start, and debugging requires understanding both Compose and the underlying Docker commands.

Worked reasoning: A simple Compose file defines two services: 'api' built from ./api using a Python base image, and 'worker' built from ./worker using a multi-stage GPU build. Both services declare runtime: nvidia and expose ports 8000 and 8080 respectively. When docker-compose up is run, Docker creates a private network, attaches both containers, and mounts a shared volume for model files, enabling the API to send inference jobs to the worker seamlessly.

Worked examples

Worked example

```
FROM nvidia/cuda:12.2-devel-ubuntu22.04 AS build
WORKDIR /app
COPY vecadd.cu .
RUN nvcc -o vecadd vecadd.cu

FROM nvidia/cuda:12.2-runtime-ubuntu22.04
COPY --from=build /app/vecadd /usr/local/bin/vecadd
ENTRYPOINT ["vecadd"]
```

The Dockerfile above demonstrates a two-stage GPU build. The first stage uses the devel image to compile vecadd.cu, producing an executable that links against the CUDA driver. The second stage starts from a lightweight runtime image and copies only the executable. When you build this Dockerfile (docker build -t vecadd:latest .) the resulting image is roughly 180 MB, far smaller than the 2.1 GB devel image.

Running the container (docker run --gpus all vecadd:latest) executes the vector addition on the host GPU. The limitation is that any additional shared libraries required by vecadd must be present in the runtime image; otherwise the container will fail with "error while loading shared libraries".

Applied example

```
services:
  api:
    build: ./api
    ports:
      - "8000:8000"
    runtime: nvidia
    environment:
      - MODEL_PATH=/models/resnet.pt
    volumes:
      - model_data:/models
  worker:
    build: ./worker
    runtime: nvidia
    depends_on:
      - api
    volumes:
      - model_data:/models
volumes:
  model_data:
```

This Docker Compose snippet defines two services that share a named volume called model_data. The 'api' service runs a Flask server exposing port 8000, while the 'worker' service runs a GPU-enabled inference loop. Both services request the NVIDIA runtime, ensuring they have access to the host's GPUs. The depends_on clause guarantees that Docker starts the API before the worker, but it does not enforce health checks; for production you would add a healthcheck to verify the API is ready before the worker begins processing. This composition lets developers develop and test the full stack locally with a single command, and the same file can be used in CI pipelines or on a cloud host with GPU nodes.

Process flow

1. Write a simple CUDA program and verify it runs on the host GPU.
2. Create a Dockerfile using a CUDA devel base, copy the source, and compile with nvcc.
3. Add a second stage that switches to a CUDA runtime base and copies the compiled binary.
4. Build the multi-stage image and test it with docker run --gpus all to ensure GPU access.
5. Wrap the image in a Docker Compose service, adding any additional services needed.
6. Use docker-compose up to launch the full stack and verify inter-service communication.
7. Iterate by adding environment variables, volumes, or healthchecks to improve robustness.

Interview and exam checkpoints

What is the purpose of a multi-stage Docker build for GPU applications?

A multi-stage build separates the compilation environment from the runtime environment. The first stage uses a heavy CUDA devel image to compile GPU code, while the second stage uses a minimal CUDA runtime image to run the compiled binary. This reduces the final image size, lowers attack surface, and speeds up deployment, but requires careful copying of all dependent libraries.

How does the NVIDIA Container Toolkit enable GPU access inside a container?

The toolkit installs a runtime hook that, when the container is started with --gpus or runtime: nvidia, mounts the host's /dev/nvidia* devices and the driver files into the container's namespace. It also sets LD_LIBRARY_PATH so that the container sees the host's libcuda.so, ensuring binary compatibility between the container's CUDA runtime and the host driver.

Explain the difference between a CUDA base image tagged 'runtime' and one tagged 'devel'.

A 'runtime' image contains only the CUDA driver libraries needed to run pre-compiled binaries; it is small and suitable for production. A 'devel' image includes the full CUDA toolkit, compilers, and headers, allowing you to compile code inside the container. Using 'devel' for building and 'runtime' for execution yields smaller, more secure images.

What are common pitfalls when using Docker Compose with GPU services?

Common issues include forgetting to set runtime: nvidia for each GPU-using service, leading to "no CUDA devices found" errors; mismatched driver versions between host and container causing runtime version errors; and neglecting healthchecks, so dependent services start before the GPU service is ready, causing request failures.

Summary

Docker abstracts the operating system into layered images, providing isolation via namespaces and resource limits via cgroups. For GPU workloads, the NVIDIA Container Toolkit bridges host GPUs into containers, while CUDA base images supply the correct driver libraries. Multi-stage builds let you compile with a heavyweight devel image and ship a lean runtime image, dramatically shrinking size and improving security. Docker Compose orchestrates multiple containers, handling networking, volumes, and service dependencies, and can be configured to request GPU resources for any service. Mastering these concepts enables you to create reproducible, portable, and efficient GPU-accelerated applications that run consistently from a developer laptop to a cloud GPU node.

Practice questions

1. Write a Dockerfile that builds a CUDA program from source and produces a runtime-only image. Use CUDA 11.8 and a simple hello.cu that prints "Hello GPU".

2. Given a host with NVIDIA driver version 525, which of the following base images will run: nvidia/cuda:12.1-runtime, nvidia/cuda:12.2-runtime, nvidia/cuda:11.8-runtime? Explain.

3. In a Compose file, you have a service 'web' that depends on a GPU-enabled service 'worker'. How would you ensure 'web' only starts after 'worker' reports healthy?

4. What trade-offs would you consider when choosing between a single-stage Dockerfile that uses nvidia/cuda:12.2-devel and a multi-stage build that ends with nvidia/cuda:12.2-runtime?

5. Implement a Python script that runs inside a CUDA runtime container and prints the number of visible GPUs using PyTorch. Provide the code and expected output.

6. Design a containerized pipeline for training a model on GPU and serving it via a REST API. List the services, their base images, and how they communicate.

Practice solutions

1. FROM nvidia/cuda:11.8-devel-ubuntu20.04 AS build
WORKDIR /src
COPY hello.cu .
RUN nvcc -o hello hello.cu

FROM nvidia/cuda:11.8-runtime-ubuntu20.04
COPY --from=build /src/hello /usr/local/bin/hello
ENTRYPOINT ["hello"]

Build with: docker build -t hello-gpu .
Run with: docker run --gpus all hello-gpu
The program will output "Hello GPU" from the device.

2. The host driver 525 supports CUDA runtime up to 12.1. Therefore nvidia/cuda:12.1-runtime will run, nvidia/cuda:12.2-runtime will fail with a version mismatch error, and nvidia/cuda:11.8-runtime will also run because older runtimes are compatible with newer drivers.

3. Add a healthcheck to the 'worker' service that runs a small command like 'nvidia-smi' and returns 0 when successful. Then set depends_on with condition: service_healthy. Example:

```
worker:
  build: ./worker
  runtime: nvidia
  healthcheck:
    test: ["CMD", "nvidia-smi"]
    interval: 5s
    retries: 3
web:
  build: ./web
  depends_on:
    worker:
      condition: service_healthy
```

4. A single-stage image is simpler to write and guarantees all build-time dependencies are present at runtime, reducing the risk of missing libraries. However, it is large (often >2 GB) and includes compilers

that are unnecessary in production, increasing attack surface. A multi-stage build produces a much smaller image (~200 MB), faster to pull and start, and is more secure, but requires careful identification of runtime dependencies and adds complexity to the Dockerfile.

5. import torch
print('GPUs visible:', torch.cuda.device_count())
Expected output on a machine with 2 GPUs: GPUs visible: 2
Run with: docker run --gpus all my-pytorch-image python script.py

6. Services:
1. trainer: FROM nvidia/cuda:12.2-devel-ubuntu22.04, installs PyTorch, runs training script, writes model to a shared volume /models.
2. api: FROM python:3.11-slim, installs Flask and torch, mounts /models, loads the trained model on startup, serves /predict endpoint.
Communication: Both services share a named Docker volume 'model_data'. The trainer writes model.pt to /models; the API reads it. No network calls needed between them. Use Docker Compose to start both; trainer runs once, then exits, while api stays up serving requests.

Reference textbooks

Docker Deep Dive - Nigel Poulton

Docker: Up & Running - Sean P. Kane and Karl Matthias

Primary documentation

https://docs.docker.com/get-started/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

10. Model Serving & Inference Optimization

Prerequisites: Docker & Containerization, PyTorch Framework & Tensors

Model serving and inference optimization are critical for deploying large language models (LLMs) in production. As LLMs grow in size and complexity, the computational and memory requirements for inference become significant. Efficient serving ensures that models can handle high traffic with low latency and high throughput. This chapter covers the foundational concepts of model serving, including continuous batching, PagedAttention, and the use of frameworks like vLLM and TensorRT-LLM. We will explore how these techniques optimize GPU utilization and memory management, enabling efficient serving of LLMs at scale. The chapter is structured to build from basic concepts to advanced techniques, providing a comprehensive understanding of the field. By the end, you will be able to design and implement efficient inference pipelines for LLMs.

Foundations

Model serving is the process of deploying machine learning models to production environments where they can receive and respond to inference requests. For large language models (LLMs), serving is particularly challenging due to the high computational and memory requirements. The key challenges are latency, throughput, and memory efficiency. Latency is the time it takes to generate a response, while throughput is the number of requests processed per second. Memory efficiency is crucial because LLMs require significant memory for the model weights and the KV cache. The KV cache stores the Key and Value tensors for each token, which are reused in subsequent steps. Without efficient memory management, the GPU memory can be exhausted, limiting the number of concurrent requests. Techniques like continuous batching and PagedAttention address these challenges by optimizing the use of GPU resources. Continuous batching improves throughput by keeping the GPU busy with useful work, while PagedAttention improves memory efficiency by reducing waste. Together, these techniques enable efficient serving of LLMs at scale.

Continuous Batching & PagedAttention

Continuous batching, also known as in-flight batching, allows new requests to join a running batch and completed requests to leave it immediately. Unlike static batching, which waits for the longest sequence in a group to finish, continuous batching operates at the token level. This is critical for LLMs because generation is autoregressive; each token depends on the previous one. By allowing dynamic entry and exit, the GPU stays saturated with useful work. The tradeoff is increased scheduling complexity. The scheduler must manage memory for active sequences and ensure that the batch size does not exceed the GPU's memory or compute limits. This technique significantly improves throughput, often by 2-4x, compared to static batching, especially when request lengths vary widely.

Worked reasoning: Consider a batch of 4 requests. Request A needs 10 tokens, B needs 5, C needs 20, D needs 5. Static batching pads all to 20 tokens. Total compute is 4 * 20 = 80 token-steps. Useful work is 10+5+20+5 = 40. Efficiency is 50%. With continuous batching, we process step-by-step. Step 1: all 4 active (4 tokens). Step 2-5: A,B,C,D active (4 tokens each). Step 6-10: A,C,D active (3 tokens). Step 11-20: C,D active (2 tokens). Total compute: 5*4 + 5*3 + 10*2 = 20+15+20 = 55 token-steps. Useful work is still 40. Efficiency is 40/55 = 72.7%. The reduction in wasted compute directly translates to higher throughput and lower latency for shorter requests.

vLLM & TensorRT-LLM

PagedAttention is a memory management technique inspired by virtual memory in operating systems. It divides the Key-Value (KV) cache into fixed-size blocks, which are allocated on demand. This eliminates the need to pre-allocate the maximum possible sequence length for each request. The tradeoff is a slight overhead in memory indirection, as the attention mechanism must look up the physical location of each block. However, this overhead is negligible compared to the memory savings. PagedAttention enables higher concurrency by reducing memory fragmentation and waste. It is a core component of vLLM and is essential for serving large language models efficiently on limited GPU memory.

Worked reasoning: Suppose a model has a context window of 2048 tokens. A request generates 100 tokens. Without PagedAttention, we might allocate a block of 2048 * 4 bytes = 8192 bytes for the KV cache, even if only 100 tokens are used. This is 95% waste. With PagedAttention, we divide the KV cache into blocks of 16 tokens. Each block is 16 * 4 bytes = 64 bytes. For 100 tokens, we need ceil(100/16) = 7 blocks. Total allocated: 7 * 64 = 448 bytes. Waste is only 12 bytes (1.5%). This allows us to fit many more concurrent requests in the same GPU memory, increasing the effective batch size and thus throughput.

Triton Inference Server

Triton Inference Server is a high-performance serving framework that supports multiple model formats and hardware backends. It provides features like dynamic batching, model versioning, and ensemble pipelines. Dynamic batching allows the server to group multiple requests into a single batch for processing, improving GPU utilization. The tradeoff is increased latency for individual requests, as they must wait for the batch to fill or for a timeout to expire. Triton also supports model ensembles, where multiple models are chained together to form a pipeline. This is useful for complex inference tasks that require multiple steps, such as preprocessing, inference, and postprocessing.

Worked reasoning: A Triton Inference Server is configured with a model instance that supports dynamic batching. The server receives 100 requests per second. Each request takes 10ms to process. The server batches requests into groups of 10. The batch processing time is 50ms (slightly more than 10ms due to overhead). The server can process 10 requests every 50ms, which is 200 requests per second. Since the arrival rate is 100 requests per second, the server is not overloaded. The average latency is the time spent waiting in the queue plus the processing time. If the queue is empty, latency is 50ms. If the queue has 5 requests, latency is 50ms + 50ms = 100ms. The server dynamically adjusts the batch size to balance throughput and latency.

Worked examples

Worked example

```
lengths = [10, 5, 20, 5]
static_slots = len(lengths) * max(lengths)
active_slots = sum(lengths)
print(static_slots, active_slots)
print(static_slots / active_slots)
```

This toy slot-count model gives 80 fixed-batch slots versus 40 active token steps, a ratio of 2.0. It assumes finished requests leave idle slots in a fixed batch and counts only active requests in the comparison. It does not measure GPU operations or latency, simulate prefill, or implement refilling with new arrivals. Real continuous batching changes the active batch at generation iterations, admitting queued requests as capacity becomes available. Kernel efficiency, scheduling, memory and request lengths determine actual

throughput. A twofold reduction in these abstract slots is not a promise of a twofold speedup.

Applied example

```
# Pseudocode for PagedAttention memory allocation

def allocate_kv_cache(num_tokens, block_size=16):
    num_blocks = (num_tokens + block_size - 1) // block_size
    # Token slots only; excludes per-layer K and V tensor dimensions
    return num_blocks

# Example: 100 tokens, block_size=16
num_blocks = allocate_kv_cache(100)
print(f"Number of blocks: {num_blocks}")
print(f"Memory waste: {num_blocks * 16 - 100} tokens")
```

This pseudocode demonstrates how PagedAttention allocates memory for the KV cache. It divides the total number of tokens into blocks of a fixed size. The number of blocks is calculated using ceiling division. The memory waste is the difference between the total allocated tokens and the actual number of tokens. In this example, 100 tokens require 7 blocks, resulting in 12 tokens of waste. This is a significant reduction compared to allocating the full context window. The limitation is that this pseudocode does not account for the overhead of managing the block table or the indirection in the attention mechanism. In practice, the memory savings are still substantial, enabling higher concurrency.

Process flow

1. 1. Request Reception: The inference server receives a request containing the input prompt and generation parameters. The request is validated and preprocessed, such as tokenization.
2. 2. Scheduling: The scheduler determines which requests to include in the current batch. It considers factors like memory availability, batch size limits, and request priorities. Continuous batching allows new requests to join the batch dynamically.
3. 3. Memory Allocation: The KV cache memory is allocated for each request in the batch. PagedAttention divides the memory into blocks, which are allocated on demand. This reduces memory waste and fragmentation.
4. 4. Inference Execution: The model processes the batch of requests. The attention mechanism uses the block table to access the KV cache. The output tokens are generated autoregressively.
5. 5. Post-processing: The generated tokens are detokenized and formatted into the final response. The response is sent back to the client.
6. 6. Memory Deallocation: When a request completes, its KV cache memory is deallocated. The blocks are returned to the memory pool for reuse by other requests.
7. 7. Monitoring and Logging: The server logs metrics such as latency, throughput, and memory usage. These metrics are used for monitoring and optimization.

Interview and exam checkpoints

What is the difference between static batching and continuous batching?

Continuous batching allows new requests to join a running batch and completed requests to leave it immediately. This is different from static batching, which waits for the longest sequence in a group to finish. Continuous batching operates at the token level, which is critical for LLMs because generation is autoregressive. By allowing dynamic entry and exit, the GPU stays saturated with useful work. This significantly improves throughput, often by 2-4x, compared to static batching, especially when request lengths vary widely. The tradeoff is increased scheduling complexity, as the scheduler must manage memory for active sequences and ensure that the batch size does not exceed the GPU's limits.

How does PagedAttention improve memory efficiency?

PagedAttention is a memory management technique inspired by virtual memory in operating systems. It divides the Key-Value (KV) cache into fixed-size blocks, which are allocated on demand. This eliminates the need to pre-allocate the maximum possible sequence length for each request. The tradeoff is a slight overhead in memory indirection, as the attention mechanism must look up the physical location of each block. However, this overhead is negligible compared to the memory savings. PagedAttention enables higher concurrency by reducing memory fragmentation and waste. It is a core component of vLLM and is essential for serving large language models efficiently on limited GPU memory.

What are the key features of Triton Inference Server?

Triton Inference Server is a high-performance serving framework that supports multiple model formats and hardware backends. It provides features like dynamic batching, model versioning, and ensemble pipelines. Dynamic batching allows the server to group multiple requests into a single batch for processing, improving GPU utilization. The tradeoff is increased latency for individual requests, as they must wait for the batch to fill or for a timeout to expire. Triton also supports model ensembles, where multiple models are chained together to form a pipeline. This is useful for complex inference tasks that require multiple steps, such as preprocessing, inference, and postprocessing.

What are the main tradeoffs in LLM serving?

The main tradeoffs in LLM serving are latency, throughput, and memory efficiency. Latency is the time it takes to generate a response, while throughput is the number of requests processed per second. Memory efficiency is crucial because LLMs require significant memory for the model weights and the KV cache. Techniques like continuous batching and PagedAttention address these challenges by optimizing the use of GPU resources. Continuous batching improves throughput by keeping the GPU busy with useful work, while PagedAttention improves memory efficiency by reducing waste. The choice of technique depends on the specific use case. For example, if low latency is critical, a smaller batch size may be preferred, even if it reduces throughput.

Summary

This chapter covered the foundational concepts of model serving and inference optimization for large language models. We explored the challenges of latency, throughput, and memory efficiency, and how techniques like continuous batching and PagedAttention address these challenges. Continuous batching improves throughput by keeping the GPU busy with useful work, while PagedAttention improves memory efficiency by reducing waste. We also discussed the use of frameworks like vLLM and TensorRT-LLM, which provide high-performance serving capabilities. The key principles are to optimize GPU utilization, manage memory efficiently, and balance latency and throughput. By applying these principles, you can design and implement efficient inference pipelines for LLMs at scale. The chapter provided concrete examples and practice problems to reinforce the concepts. You should now be able to understand and implement the core techniques of model serving and inference optimization.

Practice questions

1. Calculate the number of blocks and memory waste for a request with 100 tokens and a block size of 16.

2. Calculate the efficiency gain of continuous batching over static batching for a batch of 4 requests with lengths 10, 5, 20, and 5.

3. Design an inference pipeline for a high-traffic LLM application, considering latency, throughput, and memory efficiency.

4. Sketch the state transitions of a continuous batching scheduler and explain two edge cases.

5. How can you optimize the KV cache memory usage for a large language model?

6. How can you evaluate the performance of an inference server?

Practice solutions

1. To calculate the number of blocks, we use the formula: num_blocks = ceil(num_tokens / block_size). For 100 tokens and a block size of 16, num_blocks = ceil(100/16) = ceil(6.25) = 7. The memory waste is the difference between the total allocated tokens and the actual number of tokens: 7 * 16 - 100 = 112 - 100 = 12 tokens. This waste is 12/112 = 10.7% of the allocated memory. Without PagedAttention, if we allocated the full context window of 2048 tokens, the waste would be 2048 - 100 = 1948 tokens, which is 95.1% of the allocated memory. PagedAttention significantly reduces memory waste, enabling higher concurrency.

2. The longest request needs 20 steps, so four fixed slots for 20 steps give 80 slot-steps. Active steps sum to 10+5+20+5=40. The abstract ratio is 80/40=2, a 50% reduction in this slot-count model. This is not a measured runtime speedup. Continuous batching additionally admits new requests while others are decoding; that requires a scheduler, memory admission checks and measurements under realistic arrivals.

3. To design an inference pipeline, we need to consider the tradeoffs between latency, throughput, and memory efficiency. For a high-traffic application, we should use continuous batching to maximize throughput. We should also use PagedAttention to reduce memory waste and enable higher concurrency. The batch size should be tuned to balance latency and throughput. A larger batch size increases throughput but may increase latency. A smaller batch size reduces latency but may reduce throughput. We should also consider the hardware constraints, such as GPU memory and compute capabilities. The pipeline should be monitored and optimized based on real-world metrics.

4. To implement a simple continuous batching scheduler, we need to manage a queue of requests and a batch of active requests. The scheduler should add new requests to the batch when there is available memory and remove completed requests from the batch. The batch size should be limited to the maximum number of requests that can fit in GPU memory. The scheduler should also consider the priority of requests, such as interactive vs. batch requests. The implementation should be efficient, with minimal overhead for adding and removing requests. The scheduler should be tested with different request patterns to ensure that it handles edge cases, such as long sequences and high concurrency.

5. Budget both keys and values across layers and KV heads: approximately 2*layers*tokens*KV_heads*head_dimension*bytes_per_element per sequence, before implementation overhead. Paging reduces fragmentation; it does not reduce the information per stored token. Supported KV-cache quantization can lower bytes per element but requires quality testing. Limit concurrency and context length when necessary. Prefix sharing may reuse identical cached prefixes under the runtime policy. Model distillation is a separate model-training choice, not a generic operation that compresses any existing cache.

6. To evaluate the performance of an inference server, we should measure metrics such as latency, throughput, and memory usage. Latency can be measured as the time from request reception to response completion. Throughput can be measured as the number of requests processed per second. Memory usage can be measured as the peak GPU memory consumption. We should also measure the distribution of latencies, such as the 50th, 90th, and 99th percentiles. These metrics should be compared against the requirements of the application. For example, if the application requires a 99th percentile latency of less than 100ms, we should ensure that the server meets this requirement. We should also test the server under different load conditions to ensure that it scales well.

Reference textbooks

Designing Machine Learning Systems - Chip Huyen

Practical MLOps - Noah Gift and Alfredo Deza

Primary documentation

https://docs.vllm.ai/en/latest/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

11. Model Evaluation & Validation

Prerequisites: Supervised Learning Algorithms, Probability & Statistics

Model evaluation and validation are the final checkpoints that tell us whether a machine-learning system will succeed in the real world. They answer the questions of how well a model predicts, whether its performance is stable across unseen data, and whether the metrics we report truly reflect the business goal. In supervised learning, evaluation begins after a model is trained on a labeled dataset; we then measure its predictions on data that were not used for fitting. Validation goes a step further: it designs experiments - such as cross-validation or hold-out splits - to estimate how the model will behave on future data and to guard against subtle errors like data leakage. For large language models (LLMs), the same principles apply, but the metrics shift toward generation quality, factuality, and alignment. Understanding these foundations lets a practitioner choose the right metric, avoid common pitfalls, and communicate results with confidence, which is essential for both production deployments and technical interviews.

Foundations

The core of model evaluation rests on two ideas: a loss function that quantifies error on a single prediction, and an aggregation method that summarizes error over many predictions. For classification, loss functions such as cross-entropy produce a probability for each class; we then derive metrics like accuracy, precision, recall, and the area under the ROC curve (AUC). Each metric emphasizes a different aspect of performance: accuracy treats all errors equally, precision focuses on false positives, recall on false negatives, and AUC measures the ability to rank positive instances higher than negatives across all thresholds. Validation strategies - simple hold-out, k-fold cross-validation, and nested cross-validation - provide unbiased estimates of these metrics by repeatedly training on subsets of data and testing on the complementary parts. The most dangerous mistake is data leakage, where information from the test split unintentionally influences the training process, inflating performance. For LLMs, evaluation expands to include BLEU, ROUGE, BERTScore, and newer alignment-oriented metrics such as TruthfulQA or GPT-Eval, each requiring careful construction of reference texts and human-in-the-loop verification. By mastering these concepts, a beginner can move from raw predictions to trustworthy, reproducible performance reports.

ROC-AUC & Precision-Recall

The Receiver Operating Characteristic (ROC) curve plots the true-positive rate (TPR) against the false-positive rate (FPR) as the decision threshold varies from 0 to 1. The area under this curve (AUC) is a threshold-independent measure of ranking quality: an AUC of 0.5 means random guessing, while 1.0 indicates perfect separation. Precision-Recall (PR) curves, on the other hand, plot precision versus recall and are more informative when the positive class is rare. The area under the PR curve (average precision) emphasizes the model's ability to retrieve the few positive cases without being swamped by false positives. Trade-offs arise because ROC-AUC can look optimistic on imbalanced data, whereas PR-AUC penalizes missed positives more heavily. Choosing between them depends on the cost of false alarms versus missed detections in the target application.

Worked reasoning: Consider a binary classifier that outputs scores [0.9, 0.8, 0.4, 0.3] for four instances with true labels [1, 0, 1, 0]. Sorting by score gives pairs (0.9,1), (0.8,0), (0.4,1), (0.3,0). The ROC points are (FPR,TPR): (0,0), (0,0.5), (0.5,0.5), (0.5,1), (1,1). The trapezoidal AUC = 0.75. For PR, precision at recall 0.5 is 1/(1+1)=0.5, at recall 1.0 precision = 2/4=0.5, giving average precision = 0.5. This shows ROC-AUC

looks better than PR-AUC because positives are scarce.

Cross-Validation & Leakage

Cross-validation (CV) splits the data into k folds; each fold is held out once as a test set while the model trains on the remaining k-1 folds. The average metric across folds estimates out-of-sample performance and reduces variance compared to a single hold-out split. Nested CV adds an inner loop for hyper-parameter tuning, preventing optimistic bias from selecting parameters on the same data used for evaluation. Leakage occurs when information from the test fold leaks into training, for example by scaling features with the global mean or by performing feature selection before the split. Such leakage inflates performance because the model indirectly sees the test distribution. Detecting leakage requires strict ordering: split first, then compute any statistics (means, variances, encodings) exclusively on the training portion.

Worked reasoning: Suppose we have 8 samples with a single numeric feature X = [1,2,3,4,5,6,7,8] and binary label Y = [0,0,1,0,1,1,0,1]. In 4-fold CV, fold 1 contains indices 0,1; training set is indices 2-7. If we compute the mean of X on the whole dataset (4.5) and subtract it from all samples before splitting, the test folds have already been centered using information from the held-out points, causing leakage. Correct practice: compute mean on training indices only, e.g., for fold 1 mean(X_train)= (3+4+5+6+7+8)/6 = 5.5, then center training and test separately.

LLM Benchmark Metrics

Large language models generate free-form text, so evaluation must capture both lexical similarity and semantic fidelity. Traditional n-gram metrics like BLEU count overlapping word sequences but ignore meaning; ROUGE improves recall of n-grams, useful for summarization. BERTScore embeds tokens with a pretrained transformer and computes cosine similarity, offering a semantic match. More recent alignment metrics - such as TruthfulQA score, GPT-Eval, or OpenAI’s Evals - measure factual correctness, helpfulness, and safety by comparing model outputs against curated answer keys or by prompting a second LLM to judge. These metrics often combine automatic scoring with human annotation to calibrate thresholds. Trade-offs involve computational cost (BERTScore requires GPU inference) versus interpretability (BLEU is easy to explain). Selecting a metric depends on the downstream task: for code generation, exact match is critical; for open-ended chat, safety and truthfulness dominate.

Worked reasoning: A prompt asks an LLM to answer: "What is the capital of France?" The model replies "Paris". Using BLEU, the reference is "Paris"; BLEU = 1.0. BERTScore also yields 1.0 because the embeddings match. If the model says "The capital is Paris, known for its art," BLEU drops to 0.67 due to extra tokens, but BERTScore remains near 0.99, reflecting semantic correctness. A TruthfulQA evaluator might assign a binary score of 1 for factual correctness, showing how different metrics capture distinct aspects.

Worked examples

Worked example

```
import numpy as np

y_true = np.array([1,0,1,0,1])
y_score = np.array([0.9,0.2,0.8,0.4,0.3])
# sort by score
i = np.argsort(-y_score)
TP = np.cumsum(y_true[i])
FP = np.cumsum(1-y_true[i])
TPR = TP/TP[-1]
FPR = FP/FP[-1]
auc = np.trapz(TPR, FPR)
print('ROC AUC =', round(auc,3))
```

The code computes ROC-AUC without using any library function. After sorting the predicted scores in descending order, it cumulatively counts true positives (TP) and false positives (FP). Dividing by the total number of positives and negatives yields the true-positive and false-positive rates. The trapezoidal rule (np.trapz) integrates TPR over FPR, giving an AUC of 0.833 for this tiny dataset. This manual approach reveals how each threshold contributes to the curve and why AUC is insensitive to the exact probability values, only their ranking. Limitations include the need for at least one positive and one negative instance; otherwise the denominator becomes zero.

Applied example

```
def k_fold_cv(model, X, y, k=5):
    n = len(y)
    idx = np.arange(n)
    np.random.shuffle(idx)
    folds = np.array_split(idx, k)
    scores = []
    for i in range(k):
        test = folds[i]
        train = np.hstack([f for j,f in enumerate(folds) if j!=i])
        # fit on training only
        model.fit(X[train], y[train])
        pred = model.predict_proba(X[test])[:,1]
        scores.append(roc_auc_score(y[test], pred))
    return np.mean(scores)
# usage: avg_auc = k_fold_cv(LogisticRegression(), X, y)
```

The pseudocode outlines a generic k-fold cross-validation loop that respects the no-leakage rule: the model is fit only on the training indices, and predictions are made on the untouched test fold. After each iteration, the ROC-AUC for that fold is recorded, and the final report is the mean across folds. This pattern can be extended to nested CV by adding an inner loop that searches hyper-parameters on a further split of the training data. The example assumes a scikit-learn-like API; in practice, one must also reset random seeds for reproducibility and handle class-imbalance by stratified splitting.

Process flow

1. 1. Split the raw dataset into a hold-out test set that will never be touched during model development.

2	2. Within the remaining data, apply k-fold cross-validation to obtain stable estimates of the chosen metric.
3	3. For each fold, compute predictions, then derive ROC-AUC and Precision-Recall curves to understand ranking behavior.
4	4. Aggregate the fold-wise metrics (mean and standard deviation) to report expected performance and its variability.
5	5. Validate that no preprocessing step (scaling, encoding, feature selection) used information from the test fold; redo if leakage is detected.
6	6. For LLMs, supplement numeric scores with human-rated alignment checks or automated truthfulness benchmarks.
7	7. Document the entire pipeline, including random seeds, library versions, and metric definitions, to ensure reproducibility.

Interview and exam checkpoints

What is the difference between ROC-AUC and PR-AUC, and when would you prefer one over the other?

ROC-AUC measures the ability of a classifier to rank positives above negatives across all thresholds, treating false positives and false negatives equally. PR-AUC focuses on precision versus recall, emphasizing performance on the positive class. When the dataset is highly imbalanced and the positive class is rare, PR-AUC is more informative because a high ROC-AUC can be achieved by correctly classifying the abundant negative class while still missing many positives. Conversely, if both classes are balanced and the cost of false positives equals false negatives, ROC-AUC is a convenient summary.

Explain how data leakage can occur during cross-validation and how to prevent it.

Leakage happens when information from the test fold influences the training process. A common scenario is computing feature scaling parameters (mean, std) on the whole dataset before splitting; the test fold then indirectly contributes to the scaling, inflating performance. To prevent leakage, always perform any data-dependent transformation - scaling, encoding, feature selection - inside the training loop of each CV fold, using only the training portion to compute statistics, and then apply those statistics to the test portion.

Describe a metric you would use to evaluate a large language model that generates answers to factual questions.

For factual QA, a combination of exact match (or BLEU for lexical overlap) and a truthfulness metric such as TruthfulQA or GPT-Eval is appropriate. Exact match captures whether the answer string matches a reference, while TruthfulQA uses a curated set of questions with verified answers and scores the model's response for factual correctness, often via a secondary LLM or human annotators. This dual approach balances surface similarity with semantic correctness.

How does nested cross-validation differ from ordinary k-fold CV, and why is it useful?

Nested CV adds an inner loop inside each outer training fold to tune hyper-parameters. The outer loop provides an unbiased estimate of generalization performance, while the inner loop selects the best model configuration without peeking at the outer test data. This prevents optimistic bias that arises when hyper-parameters are tuned on the same data used for final evaluation, leading to more reliable performance estimates, especially when the dataset is small.

Summary

Model evaluation and validation turn raw predictions into trustworthy performance claims. ROC-AUC and Precision-Recall curves quantify ranking quality, with PR-AUC being more sensitive to class imbalance. Cross-validation offers robust estimates, but only when preprocessing respects the train-test boundary to avoid leakage; nested CV further safeguards hyper-parameter tuning. For large language models, traditional n-gram metrics are complemented by semantic scores like BERTScore and alignment-focused benchmarks such as TruthfulQA. Selecting the right metric depends on the problem's cost structure and data distribution, while a disciplined validation pipeline - hold-out test set, proper CV, leakage checks, and reproducible documentation - ensures that reported numbers reflect true future performance.

Practice questions

1. Given true labels [1,0,1,0,0,1] and predicted scores [0.9,0.4,0.8,0.3,0.2,0.7], compute the ROC-AUC manually using the trapezoidal rule.

2. Implement a stratified 3-fold cross-validation loop that reports both mean ROC-AUC and mean PR-AUC for a binary classifier using scikit-learn. Use a synthetic dataset of 12 points with 4 positives.

3. A dataset has 10,000 samples with 1% positive class. You obtain a model with ROC-AUC = 0.92 but PR-AUC = 0.15. Explain why the PR-AUC is low and what actions you could take to improve it.

4. Design a validation strategy for a time-series forecasting model that must avoid future data leakage. List the steps and justify each.

5. You are evaluating two LLMs on a summarization task. Model A gets BLEU = 0.45, ROUGE-L = 0.52, BERTScore = 0.78. Model B gets BLEU = 0.48, ROUGE-L = 0.49, BERTScore = 0.81. Which model would you recommend and why?

6. Explain a scenario where using only accuracy as an evaluation metric would be misleading, and propose a better metric.

Practice solutions

1. Sort by score descending: indices [0,2,5,1,3,4] -> pairs (0.9,1),(0.8,1),(0.7,1),(0.4,0),(0.3,0),(0.2,0). TP cumulative = [1,2,3,3,3,3]; FP cumulative = [0,0,0,1,2,3]. Total positives = 3, negatives = 3. TPR = TP/3 = [0.333,0.667,1,1,1,1]; FPR = FP/3 = [0,0,0,0.333,0.667,1]. Points: (0,0.333),(0,0.667),(0,1),(0.333,1),(0.667,1),(1,1). Trapezoidal area = sum over segments: (0-0)*(0.333+0.667)/2=0, (0-0)*(0.667+1)/2=0, (0.333-0)*(1+1)/2=0.333, (0.667-0.333)*(1+1)/2=0.334, (1-0.667)*(1+1)/2=0.333. Total AUC ≈ 1.0. Because all positives rank above all negatives, AUC = 1.

2. import numpy as np
from sklearn.model_selection import StratifiedKFold
from sklearn.metrics import roc_auc_score, average_precision_score
from sklearn.linear_model import LogisticRegression

X = np.arange(12).reshape(-1,1)
y = np.array([1,0,1,0,0,1,0,0,1,0,0,0])
skf = StratifiedKFold(n_splits=3, shuffle=True, random_state=42)
roc_scores = []
pr_scores = []
for train_idx, test_idx in skf.split(X, y):
    model = LogisticRegression(solver='liblinear')
    model.fit(X[train_idx], y[train_idx])
    prob = model.predict_proba(X[test_idx])[:,1]
    roc_scores.append(roc_auc_score(y[test_idx], prob))
    pr_scores.append(average_precision_score(y[test_idx], prob))
print('Mean ROC-AUC:', np.mean(roc_scores))
print('Mean PR-AUC:', np.mean(pr_scores))

Explanation: StratifiedKFold keeps the proportion of positives (4/12) in each fold. The loop fits the model only on training indices, computes probabilities on the held-out test indices, and records both ROC-AUC and average precision (PR-AUC). The final printed means give a stable estimate of performance across the three folds.

3. With only 100 positive examples, ROC-AUC can be high even if the model ranks many negatives above some positives, because the false-positive rate denominator is large (9,900). PR-AUC, however, directly measures precision at various recall levels; a precision of 0.15 means that for every 100 retrieved items, only 15 are true positives, indicating many false positives. To improve PR-AUC you can: (1) adjust the decision threshold to a higher value, trading recall for precision; (2) use class-weighting or focal loss to force the model to focus on the minority class; (3) collect more positive examples or apply oversampling techniques such as SMOTE; (4) engineer features that better separate the rare class. Monitoring both metrics ensures you do not chase a misleading ROC-AUC.

4. 1. Preserve chronological order: split the data into training, validation, and test windows based on timestamps, never shuffling. 2. Use a rolling-origin (walk-forward) evaluation: after training on an initial window, forecast the next horizon, then expand the training window forward and repeat. 3. Compute metrics (e.g., MAE, MAPE) on each forecast horizon and average them to obtain a stable estimate. 4. Ensure any feature engineering (e.g., lag creation, scaling) is computed only on data available up to the forecast point; for scaling, fit the scaler on the training window and apply it to the validation/test windows without refitting. 5. Reserve the final untouched test period for the ultimate performance report. This strategy respects causality, prevents leakage of future information, and mimics real-world deployment where only past data is available at prediction time.

5. Model B has higher BLEU and BERTScore, indicating better lexical overlap and semantic similarity, while Model A scores higher on ROUGE-L, which emphasizes longest common subsequence recall. If the business goal values factual and semantic fidelity more than exact phrasing, Model B is preferable because BERTScore captures meaning and BLEU shows slightly better n-gram precision. If recall of longer phrases is critical, Model A might be chosen. Overall, given the modest ROUGE difference and the larger gains in BLEU and BERTScore, Model B is the stronger candidate for most summarization

applications.

6. In a fraud detection dataset with 99% legitimate transactions and 1% fraud, a naive model that predicts every transaction as legitimate achieves 99% accuracy but catches zero fraud cases. Accuracy is misleading because it does not reflect the cost of missing the rare but critical positive class. A better metric is the F1-score, which balances precision and recall, or the PR-AUC, which directly measures performance on the minority class. Alternatively, a cost-sensitive metric that assigns higher penalty to false negatives can be used to align evaluation with business impact.

Reference textbooks

Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow - Aurelien Geron

Pattern Recognition and Machine Learning - Christopher M. Bishop

The Elements of Statistical Learning - Trevor Hastie, Robert Tibshirani and Jerome Friedman

Primary documentation

https://scikit-learn.org/stable/modules/model_evaluation.html

Content version: learning-v1 | CareerIQ original AI-assisted educational notes

12. Experiment Tracking & Reproducibility

Prerequisites: Model Evaluation & Validation

Experiment tracking and reproducibility are the backbone of reliable machine learning practice. When a data scientist iterates on models, hyper-parameters, and data preprocessing steps, the ability to recall exactly which code, configuration, and data produced a given result is essential for debugging, collaboration, and scientific validation. Without systematic tracking, results become anecdotal, and any claim of improvement is difficult to verify. This chapter introduces the core ideas behind experiment tracking, explains how to capture runs, manage configuration sweeps, and preserve artifact lineage, and shows how these practices enable reproducible research and robust production pipelines. The material is designed for beginners who have already learned model evaluation and now need to formalize their experimentation workflow.

Foundations

At its core, experiment tracking records a set of immutable facts for each model training run: the code version (often a git commit hash), the hyper-parameter values, the training data snapshot, and any derived artifacts such as trained model files, logs, and evaluation metrics. These facts are stored in a structured store - commonly a relational database or a specialized service - so that they can be queried later. Reproducibility builds on this by ensuring that the same inputs (code, data, environment) can be re-executed to obtain identical outputs, typically by versioning data and using containerized environments. A configuration sweep extends a single run into a systematic exploration of a hyper-parameter space; the sweep manager launches many runs, each with a distinct configuration, while preserving the lineage that ties each run back to the sweep definition. Artifact lineage tracks the provenance of files: a model artifact knows which dataset version and preprocessing script produced it, and downstream experiments can reference that model as an input artifact. Together, these mechanisms form a directed acyclic graph (DAG) of experiments, enabling analysts to trace any result back to its origins, compare alternatives, and share complete reproducible packages with teammates or reviewers.

Weights & Biases Runs

A run is a single execution of a training script that logs metrics, parameters, and artifacts to a backend service. Each run receives a unique identifier and stores a snapshot of the environment, including the git commit, Python package versions, and hardware details. The trade-off is between granularity and storage cost: logging every batch metric yields fine-grained insight but can quickly fill storage, whereas logging only epoch-level metrics reduces overhead but may hide transient issues. Runs also support tagging and grouping, which help organize experiments by project or hypothesis. By treating runs as immutable records, you can safely compare results across time without accidental overwrites.

Worked reasoning: Suppose you train a logistic regression on the Iris dataset with learning rate 0.01 and batch size 32. When the script starts, it calls wandb.init(project="iris-demo", config={"lr":0.01,"batch":32}). Throughout training, it logs wandb.log({"epoch":e,"loss":loss_val}). After training, it saves the model file model.pkl and calls wandb.save("model.pkl"). The run now contains the exact hyper-parameters, loss curve, and the model artifact, all linked to the git commit that produced the code. Later you can retrieve this run by its ID and reproduce the exact environment.

Config Sweeps

A sweep defines a search space over hyper-parameters and a strategy (grid, random, Bayesian) for sampling configurations. The sweep manager launches multiple runs, each with a distinct config, and records the relationship between the sweep and its child runs. The main benefit is systematic coverage of the parameter space, which reduces bias from manual trial-and-error. However, sweeps can generate many runs, so you must set reasonable limits on total trials and monitor resource usage. Sweeps also enable automatic early stopping based on intermediate metrics, saving compute when a configuration is clearly underperforming.

Worked reasoning: You define a sweep YAML with parameters lr: [0.001,0.01,0.1] and batch: [16,32]. Using wandb.sweep(sweep_config) creates a sweep ID. Then you launch agents: wandb agent <sweep_id>. Each agent pulls a config, runs the training script, and logs a run. After the sweep finishes, the dashboard shows a table of all runs, their hyper-parameters, and final accuracy, allowing you to pick the best combination.

Artifact Lineage

Artifacts are versioned files (datasets, models, preprocessing scripts) that can be linked together to form a provenance graph. When you log an artifact, you specify its type (dataset, model) and a unique name; the system computes a content hash to guarantee immutability. Downstream runs can declare dependencies on specific artifact versions, ensuring they always consume the exact same input. The trade-off is the overhead of managing artifact versions and storage; small projects may find this cumbersome, but the benefit is that any change to data or code automatically creates a new artifact, preventing accidental reuse of stale files.

Worked reasoning: After preprocessing the raw CSV, you create a dataset artifact named "iris_v1" and call wandb.log_artifact(dataset_artifact). Later, when training, you add "artifact": "iris_v1:latest" to the run config. The training run logs a model artifact "logreg_v1" that records its dependency on "iris_v1". If you later update the preprocessing script, a new dataset artifact "iris_v2" is created; any new training run that uses "iris_v2" will have a distinct lineage, making it easy to compare models trained on different data versions.

Worked examples

Worked example

```
import wandb, numpy as np
from sklearn.linear_model import LogisticRegression
X=np.array([[5,3],[2,1],[3,4],[1,0]])
y=np.array([1,0,1,0])
wandb.init(project='demo',config={'lr':0.01,'batch':2})
model=LogisticRegression(C=1/0.01,solver='lbfgs')
model.fit(X,y)
wandb.log({'accuracy':model.score(X,y)})
import joblib; joblib.dump(model,'model.pkl')
wandb.save('model.pkl')
```

The code creates a tiny dataset, starts a Weights & Biases run, and logs a single hyper-parameter (learning rate) and the resulting accuracy. The model is saved to disk and uploaded as an artifact. Because the dataset is hard-coded, the run is fully reproducible: any other machine executing the same script with the same wandb.init call will produce identical metrics and the same model file hash. Limitations include

the lack of data versioning (the dataset is embedded in code) and the absence of a sweep; this example demonstrates a single run only.

Applied example

```
def train(config):
    import wandb, joblib
    from sklearn.datasets import load_iris
    from sklearn.ensemble import RandomForestClassifier
    data=load_iris()
    X,y=data.data,data.target
    model=RandomForestClassifier(n_estimators=config['n_estimators'],
                                 max_depth=config['max_depth'],
                                 random_state=42)
    model.fit(X,y)
    wandb.log({'accuracy':model.score(X,y)})
    joblib.dump(model,f"rf_{config['n_estimators']}.pkl")
    wandb.save(f"rf_{config['n_estimators']}.pkl")
# Sweep config (pseudo-YAML)
sweep={"method":"grid","parameters":{\
    "n_estimators":{"values":[10,50]},\
    "max_depth":{"values":[3,5]}}}
# In practice you would call wandb.agent(sweep_id, function=train)
```

This pseudocode defines a training function that receives a configuration dictionary supplied by a sweep manager. The function loads the Iris dataset, trains a RandomForest with the given hyper-parameters, logs accuracy, and saves the model artifact. The sweep definition enumerates a 2x2 grid, resulting in four runs. Each run will be linked to the sweep, and the lineage graph will show that all four models depend on the same dataset version but differ in n_estimators and max_depth. This structure enables systematic comparison and easy retrieval of the best model.

Process flow

1. 1. Initialize a run with wandb.init, passing a config dictionary that captures all hyper-parameters.
2. 2. Log metrics during training using wandb.log; choose epoch-level granularity for balance.
3. 3. Save any output files (model weights, plots) with wandb.save to register them as artifacts.
4. 4. If performing a sweep, define a sweep configuration (search space and strategy) and launch agents to generate runs automatically.
5. 5. For each dataset or preprocessing step, create a dataset artifact and log it with wandb.log_artifact, ensuring a content hash is stored.
6. 6. Declare artifact dependencies in subsequent runs so the system records lineage edges.
7. 7. After experiments, use the dashboard or API to query runs, compare metrics, and retrieve the exact code and data versions needed for reproduction.

Interview and exam checkpoints

Why is immutable logging of runs important for reproducibility?

Immutable logging ensures that once a run is recorded, its parameters, metrics, and artifacts cannot be altered. This guarantees that any later inspection reflects the exact state of the experiment at execution time, preventing accidental overwrites that would corrupt the provenance chain. It also enables trustworthy comparisons across runs because each record is a fixed point of reference.

How does a sweep differ from manually launching multiple runs?

A sweep automates the generation of configurations, enforces a systematic search strategy, and records the parent-child relationship between the sweep definition and each run. Manual launches lack this metadata, making it harder to trace which hyper-parameter combinations were tried and to apply early-stopping policies uniformly.

Explain artifact lineage and its role in model versioning.

Artifact lineage records the provenance of each file by linking it to the exact dataset, code, and environment that produced it. When a model artifact is created, it stores references to the dataset artifact and preprocessing script versions used. This graph allows you to reconstruct the full pipeline that generated a model, facilitating audits, debugging, and safe deployment of the correct model version.

What are the trade-offs when logging metrics at batch versus epoch granularity?

Batch-level logging provides fine-grained insight into training dynamics, helping detect issues like exploding gradients early, but it generates large volumes of data, increasing storage costs and potentially slowing down training due to I/O overhead. Epoch-level logging reduces overhead and storage but may miss transient problems that only appear for a few batches.

How would you ensure reproducibility when your data lives in a mutable external storage system?

You would create a dataset artifact that captures a snapshot of the data at a specific point in time, typically by copying the relevant files into a versioned storage bucket and computing a content hash. The artifact is then logged to the tracking system, and downstream runs declare a dependency on that exact artifact version, guaranteeing they always read the same data regardless of later changes in the external source.

Describe a scenario where you would prefer a random sweep over a grid sweep.

When the hyper-parameter space is large and some dimensions have diminishing returns, a random sweep can explore more diverse configurations with fewer total trials. It avoids the combinatorial explosion of a full grid, allowing you to allocate limited compute budget to a broader search, which is especially useful for continuous parameters like learning rate.

Summary

Experiment tracking transforms ad-hoc model training into a disciplined engineering process. By recording immutable runs, managing systematic sweeps, and preserving artifact lineage, data scientists gain full visibility into the provenance of every result. This visibility enables reproducibility, facilitates collaboration, and supports rigorous scientific reporting. The key principles are: capture code version, hyper-parameters, and environment; log metrics at an appropriate granularity; version datasets and models as artifacts; and connect all pieces in a directed graph. When these practices are consistently applied, teams can reliably reproduce past experiments, compare alternatives, and safely promote the best models to production.

Practice questions

1. You train a linear model with learning rate 0.05 and batch size 16. The run logs loss values [0.9, 0.7, 0.5] for three epochs. Write the wandb code to log these metrics and save the model file model.npy.

2. Define a sweep that searches over n_estimators in {20,40,60} and max_depth in {4,6}. Use a random method with 4 total trials. Show the sweep dictionary.

3. A dataset artifact "sales_v1" has a content hash abc123. You create a model artifact "xgboost_v1" that depends on this dataset. Explain how you would declare this dependency in code and why it matters.

4. Design trade-off: you have limited storage for artifacts but need to keep many model versions. What strategy would you adopt?

5. Given three runs with accuracies 0.82, 0.85, 0.78 and learning rates 0.01, 0.001, 0.01 respectively, which run should be selected if you prioritize higher accuracy but also want the smallest learning rate when accuracies tie?

6. Compute the squared approximation error for a model that predicts [2,4,6] while true values are [3,5,7]. Show the calculation.

Practice solutions

1. import wandb, numpy as np
wandb.init(project='practice',config={'lr':0.05,'batch':16})
losses=[0.9,0.7,0.5]
for epoch,loss in enumerate(losses,1):
    wandb.log({'epoch':epoch,'loss':loss})
model=np.array([0.2,0.8])
np.save('model.npy',model)
wandb.save('model.npy')
This code creates a run, logs three epoch losses, saves a dummy model array, and registers it as an artifact.

2. sweep_config={
    'method':'random',
    'metric':{'name':'accuracy','goal':'maximize'},
    'parameters':{
        'n_estimators':{'values':[20,40,60]},
        'max_depth':{'values':[4,6]}
    },

```
    'early_terminate':{'type':'none'},
    'total_trials':4
}
# This dictionary can be passed to wandb.sweep to create the sweep.
```

3. First log the dataset artifact:

```
import wandb
artifact=wandb.Artifact('sales_v1','dataset')
artifact.add_file('sales.csv')
wandb.log_artifact(artifact)
```

Then, in the training script, retrieve it:

```
run=wandb.init()
artifact=run.use_artifact('sales_v1:latest')
artifact_dir=artifact.download()
# After training, create model artifact and add a reference:
model_art=wandb.Artifact('xgboost_v1','model')
model_art.add_file('model.bin')
model_art.add_reference(artifact) # records dependency
wandb.log_artifact(model_art)
```

Declaring the dependency records that the model was built from the exact version of the sales data, enabling future runs to reproduce the model or to audit which data version produced a given performance.

4. I would enable artifact retention policies that keep only the top-k models based on a validation metric, while archiving older low-performing versions to cheaper cold storage. Additionally, I would store model checkpoints as compressed binary formats (e.g., ONNX) to reduce size, and use a naming convention that includes the performance score, making it easy to prune. This balances the need for reproducibility of the best models with storage constraints.

5. Run 2 has the highest accuracy (0.85), so it is selected regardless of learning rate. If accuracies were tied, we would choose the run with learning rate 0.001.

6. Error vector = [2-3, 4-5, 6-7] = [-1,-1,-1]
Squared error = sum((-1)^2 for each) = 1+1+1 = 3.
Thus the squared approximation error is 3.

Reference textbooks

Designing Machine Learning Systems - Chip Huyen

Practical MLOps - Noah Gift and Alfredo Deza

Primary documentation

https://mlflow.org/docs/latest/ml/

Content version: learning-v1 | CareerIQ original AI-assisted educational notes