



Type '/' to search projects

[Help](#)[Docs](#)[Sponsors](#)[Log in](#)[Register](#)

playwright-stealth 2.0.3



Latest version

`pip install playwright-stealth` 

Released: Apr 3, 2026

Make your playwright instance stealthy

Navigation

 [Project description](#)

 [Release history](#)

 [Download files](#)

Verified details

These details have been [verified](#)
by PyPI

Maintainers



[Mattwmaster58](#)

Unverified details

These details have **not** been
verified by PyPI

Project description

playwright_stealth

Fork of Atubodad's port of [puppeteer-extra-plugin-stealth](#), with some improvements. Don't expect this to bypass anything but the simplest of bot detection methods. Consider this a proof-of-concept starting point.

I've merged some of the outstanding PRs, added some features, and cleaned up the API surface. See the [changelog](#). The latest major version includes breaking changes.

Install

Install from PyPi:

```
$ pip install playwright-stealth
```

Example Usage

Project links

 [changelog](#)

 [Homepage](#)

Meta

- **License Expression:**

MIT

[SPDX](#)  [License](#)

[Expression](#) 

- **Author:**

[Mattwmaster58](#) 

- **Requires:** Python

>=3.9

- **Provides-Extra:**

`black`

Classifiers

Operating System

- [OS Independent](#)

Programming Language

- [Python :: 3](#)
- [Python :: 3.9](#)
- [Python :: 3.10](#)
- [Python :: 3.11](#)
- [Python :: 3.12](#)
- [Python :: 3.13](#)
- [Python :: 3.14](#)

Report project as
malware

Recommended Usage

```
import asyncio
from playwright.async_api import async_playwright
from playwright_stealth import Stealth

async def main():
    # This is the recommended usage. All pages created will have
    async with Stealth().use_async(async_playwright()) as p:
        browser = await p.chromium.launch()
        page = await browser.new_page()

        webdriver_status = await page.evaluate("navigator.webdriver")
        print("from new_page: ", webdriver_status)

        different_context = await browser.new_context()
        page_from_different_context = await different_context.new_page()

        different_context_status = await page_from_different_context.evaluate("navigator.webdriver")
        print("from new_context: ", different_context_status)

asyncio.run(main())
```

Specifying config options and applying evasions manually to an entire context

```
import asyncio
from playwright.async_api import async_playwright
from playwright_stealth import Stealth, ALL_EVASIONS_DISABLED_KWARGS

async def advanced_example():
    # Custom configuration with specific languages
    custom_languages = ("fr-FR", "fr")
    stealth = Stealth(
        navigator_languages_override=custom_languages,
        init_scripts_only=True
    )

    async with async_playwright() as p:
        browser = await p.chromium.launch()
        context = await browser.new_context()
        await stealth.apply_stealth_async(context)

        # Test stealth on multiple pages
        page_1 = await context.new_page()
```

```

page_2 = await context.new_page()

# Verify language settings
for i, page in enumerate([page_1, page_2], 1):
    is_mocked = await page.evaluate("navigator.languages")
    print(f"Stealth applied to page {i}: {is_mocked}")

# Example of selective evasion usage
no_evasions = Stealth(**ALL_EVASIONS_DISABLED_KWARGS)
single_evasion = Stealth(**{**ALL_EVASIONS_DISABLED_KWARGS, '

print("Total evasions (none):", len(no_evasions.script_payloads))
print("Total evasions (single):", len(single_evasion.script_payloads))

asyncio.run(advanced_example())

```

Todo

- make this work with playwright.launch_persistent_context
 - the difficult because sometimes we sniff the UA if an override isn't provided, and this is difficult to do when launch_persistent_context is launched
- sec-platform (we have navigator_platform)
- docs

A set of Test results

playwright with stealth



playwright without stealth

Intoli.com tests + additions

Test Name	Result
User Agent (Old)	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/109.0.0.0 Safari/537.36
WebDriver (New)	present (failed)
WebDriver Advanced	passed
Chrome (New)	present (passed)
Permissions (New)	prompt
Plugins Length (Old)	5
Plugins is of type PluginArray	passed
Languages (Old)	zh-CN
WebGL Vendor	Google Inc. (Intel)
WebGL Renderer	ANGLE (Intel, Intel(R) UHD Graphics 730 Direct3D11 vs_5_0 ps_5_0, D3D11)
Broken Image Dimensions	16x16

Fingerprint Scanner tests

Some details

navigator.cookieEnabled	true
navigator.doNotTrack	null
navigator.msDoNotTrack	undefined
navigator.sendBeacon	
navigator.cookieEnabled	true
navigator.userAgent	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/109.0.0.0 Safari/537.36
navigator.appName	Netscape
navigator.vendor	Google Inc.
navigator.appCodeName	Mozilla
navigator.getUserMedia	
navigator.sayswho	undefined
navigator.javaEnabled	false
navigator.plugins	{0*:{0*:{},1*:{}};1*:{0*:{},1*:{}};2*:{0*:{},1*:{}};3*:{0*:{},1*:{}};4*:{0*:{},1*:{}}}
screen.width	1280
screen.height	720
screen.colorDepth	24
navigator.language	zh-CN
navigator.loadPurpose	undefined
navigator.platform	Win32
navigator.mediaDevices	audioinput: id = videoinput: id = audiooutput: id =
navigator.getBattery details	Charging: true Level: 1
Canvas1	Bot test canvas 1.1 Hash: 272313063
Canvas2	Bot test canvas 1.1 Hash: 272313063
Canvas3 (iframe sandbox)	Bot test canvas 1.1 Hash: 272313063
Canvas4 (iframe sandbox)	Bot test canvas 1.1 Hash: 272313063
Canvas5 (iframe)	Bot test canvas 1.1 Hash: 272313063

Fp-collect info

```
{
  "plugins": [
    "PDF Viewer: Portable Document Format: internal-pdf-viewer:application/pdf/pdf Portable Document Format;text/pdf/pdf Portable Document Format",
    "Chrome PDF Viewer: Portable Document Format: internal-pdf-viewer:application/pdf/pdf Portable Document Format;text/pdf/pdf Portable Document Format",
    "Chromium PDF Viewer: Portable Document Format: internal-pdf-viewer:application/pdf/pdf Portable Document Format;text/pdf/pdf Portable Document Format",
    "Microsoft Edge PDF Viewer: Portable Document Format: internal-pdf-viewer:application/pdf/pdf Portable Document Format;text/pdf/pdf Portable Document Format",
    "Webkit built-in PDF: Portable Document Format: internal-pdf-viewer:application/pdf/pdf Portable Document Format;text/pdf/pdf Portable Document Format"
  ],
  "mimeType": {
    "Portable Document Format": "application/pdf",
    "Portable Document Format": "text/pdf"
  },
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/109.0.0.0 Safari/537.36",
  "platform": "Win32",
  "languages": [
    "zh-CN"
  ],
  "screen": {
    "wInnerHeight": 720,
    "wOuterHeight": 808,
    "wOuterWidth": 1280,
    "wInnerWidth": 1280,
    "wScreenX": 0,
    "wPageOffset": 0,
    "wPageYOffset": 0,
    "eWidth": 1247,
    "eHeight": 1695,
    "eWidth": 1280,
    "eHeight": 720,
    "sAvailWidth": 1280,
    "sAvailHeight": 720,
    "sColorDepth": 24,
    "sPixelDepth": 24,
    "wDevicePixelRatio": 1
  },
  "touchScreen": [
    0,
    false,
    false
  ],
  1,
}
```

[illegible]

Test1	Test2



Help

[Installing packages](#) 

[Uploading packages](#) 

[User guide](#) 

[Project name retention](#) 

[FAQs](#)

About PyPI

[PyPI Blog](#) 

[Infrastructure dashboard](#) 

[Statistics](#)

[Logos & trademarks](#)

[Our sponsors](#)

Contributing to PyPI

[Bugs and feedback](#)

[Contribute on GitHub](#) 

[Translate PyPI](#) 

[Sponsor PyPI](#)

[Development credits](#) 

Using PyPI

[Terms of Service](#) 

[Report security issue](#)

[Code of conduct](#) 

[Privacy Notice](#) 

[Acceptable Use Policy](#) 

[Status: All Systems Operational](#) 

Developed and maintained by the Python community, for the Python community.
[Donate today!](#)

"PyPI", "Python Package Index", and the blocks logos are registered trademarks of the Python Software Foundation .

© 2026 Python Software Foundation 
[Site map](#)

Switch to desktop version

-
- English
 - español
 - français
 - 日本語
 - português (Brasil)
 - українська
 - Ελληνικά
 - Deutsch
 - 中文 (简体)
 - 中文 (繁體)
 - русский
 - עברית
 - Esperanto
 - 한국어