

Operators

Casting

Dangerous Cast

```
void dangerousCast() {  
    int[][] array = {{1,2,3}, {2}};  
    //keep in mind that int[] is an object;  
    Object[] arrObj = array;  
    //compiles but exception at runtime  
    //Exception in thread "main" java.lang.ArrayStoreException: java  
    arrObj[0] = "hello";  
}
```

Compound operators

Convert the result of the binary operation to the type of the left-hand variable (implicit casting). Example

```
long aLong = 2;  
// -incompatible types: possible lossy conversion from double to long  
//aLong = 2 - 1.0; //DOES NOT COMPILE!  
  
//compound operator applies casting automatically  
aLong -=1.0; //THIS works (compound operator)  
  
int anInt =5;  
long aLong = 6;  
//int result = anInt + aLong; //DOES NOT COMPILE  
int result = anInt;  
//minor warning: Implicit cast from 'long' to 'int' in compound assignment  
result +=aLong;  
System.out.println(result); //11
```

Compound operators — tricky

```
jshell> long x = 5L
x ==> 5

jshell> x = x +3.4
| Error:
| incompatible types: possible lossy conversion from double to
| x = x +3.4
|      ^----^

jshell> x -=3.4
$20 ==> 1
```

Arithmetic operators

+ - / *

The arithmetic operands are cast to int before to proceed

```
short s=5, t=6;
//fails because s*t is an int
short result = s * t; //fails!
```

Bitwise operator ~

```
int x = 8;
int y = ~x; //-9
```

Alternatively, you can use the following formula to calculate the 2's complement of an integer x:

$$-(x + 1)$$

For example, to find the 2's complement of the integer 8, we can use this formula as follows:

$$-(8 + 1) = -9$$

Trick for binary

```
0000 0
0001 1
```

but going back

0001 1

0000 0

1111 -1

Numeric Promotion Rules

1. If two values have different data types, Java will automatically promote one of the values to the larger of the two data types.
2. If one of the values is integral (integer) and the other is floating-point, Java will automatically promote the integral value to the floating-point value's data type.
3. Smaller data types, namely, byte, short, and char, are first promoted to int any time they're used with a Java binary arithmetic operator with a variable (as opposed to a value), even if neither of the operands is int.
4. After all promotion has occurred and the operands have the same data type, the resulting value will have the same data type as its promoted operands.

Cases

```
short x = 5;
short y = 6;
//does not compile as short are promoted to int if there is an operation
//short result = x + y; //does NOT compile!
int result = x + y; //this compiles
```

```
byte a=2, b=3;
//byte result = a +b; //does NOT compile
int result = a+b; //compiles
```

```
byte a=2, b=3;
//compound operator
b +=a; //this compiles!
System.out.println(b); //5
```

LHS vs RHS

in the statement:

```
int x = 5;
```

the terms "left-hand side" (LHS) and "right-hand side" (RHS) refer to specific parts of the assignment.

Left-hand side (LHS): This refers to the variable that is being assigned a value. In your example, x is the LHS because it's the variable that will store the value.

Right-hand side (RHS): This refers to the value that is being assigned to the variable. In your example, 5 is the RHS because it's the value that is assigned to the variable x.

So, to summarize:

LHS: x RHS: 5

Primitive assignment

```
int x = 5;
//allowed
double d = x;
//not allowed
x = d; //DOES NOT COMPILE!
```

Casting

All the primitive types can be cast to Object.

```
byte b = 4;
short s = 5;
int i = 56;
long l = 100L;
float f = 4.5F;
double d = 5.98D;
char c = 'a';
boolean bo = false;

//all of these can be cast to Object
Object oB = (Object)b;
Object oS = (Object)s;
Object oI = (Object)i;
Object oL = (Object)l;
Object oF = (Object)f;
Object oD = (Object)d;
Object oC = (Object)c;
Object oBo = (Object)bo;
//inconvertible types; cannot cast 'int' to 'java.lang.Float'
//Float aFloat = (Float)i; DOES NOT COMPILE
```

Java Operator Precedence

By decreasing order, highest to the lowest.

Operator	Symbols and examples	Evaluation
Post-unary operators	expression++, expression--	Left-to-right
Pre-unary operators	++expression, --expression	Left-to-right
Other unary operators	-, !, ~, +, (type)	Right-to-left
Cast	(Type)reference	Right-to-left
Multiplication/division/modulus	*, /, %	Left-to-right
Addition/subtraction	+, -	Left-to-right
Shift operators	<<, >>, >>>	Left-to-right
Relational operators	<, >, <=, >=, instanceof	Left-to-right
Equal to/not equal to	==, !=	Left-to-right
Logical AND	&	Left-to-right
Logical exclusive OR	^	Left-to-right
Logical inclusive OR		Left-to-right
Conditional AND	&&	Left-to-right
Conditional OR		Left-to-right

Ternary operators	boolean expression ? expression1 : expression2	Right-to-left
Assignment operators	=, +=, -=, *=, /=, %=, &=, ^=,	Right-to-left
Arrow operator	->	Right-to-left

Instanceof

null case

null instanceof T: **always false**

```
//it always returns false
if(null instanceof String){
    System.out.println("It's null");
}
```

T instanceof null: **DOES NOT COMPILE!**

```
Object object = new String("A");
//this does not compile!
// if(object instanceof null){}
```

Primitive types (CGPT)

Primitive Type	Size (in bits)	Signed/Unsigned	Range
byte	8	Signed	-128 to 127
short	16	Signed	-32,768 to 32,767
int	32	Signed	-2 ³¹ to 2 ³¹ - 1
long	64	Signed	-2 ⁶³ to 2 ⁶³ - 1
float	32	Signed	IEEE 754 single-precision floating-point
double	64	Signed	IEEE 754 double-precision floating-point

char	16	Unsigned	0 to 65,535 (Unicode characters)
boolean	Not precisely defined	N/A	true or false

1. The size of a boolean type is not precisely defined in terms of bits, as it depends on the JVM implementation. However, it is typically represented as a single byte.

unicode

Heads-up: '\u0061' is represented in hex: $6 \cdot 16 + 1 = 97$ (in decimal)

```
char c = '\u0061';
char d = 'a';
System.out.println(c == d); //true
System.out.println('\u0061');
int charAsInt = c;
System.out.println("char as int: "+charAsInt); //97
```

char to unicode

```
char c = 'a';
String unicode = String.format("\\u%04x", (int)c);
System.out.println(unicode); // \u0061
```

You

can you explain me this: `String.format("\\u%04x", (int)c);`

ChatGPT

Certainly! This code snippet is using the `String.format` method to create a string representing the Unicode escape sequence of a character. Let's break it down:

java

Copy code

```
String.format("\\u%04x", (int)c);
```

- `\\u`: This part represents the Unicode escape sequence in Java. The double backslash (`\\`) is used to escape the backslash itself, and `u` is the indicator for a Unicode escape.
- `%04x`: This is a format specifier within the `String.format` method. It specifies how the following argument `(int)c` should be formatted.
 - `%`: This indicates the start of the format specifier.
 - `04`: This specifies that the resulting string should have a minimum width of 4 characters. If the hexadecimal representation of the Unicode value is less than 4 characters, leading zeros will be added.
 - `x`: This indicates that the argument should be formatted as a hexadecimal number.

So, when you use this `String.format` with a character `c`, it will replace `%04x` with the hexadecimal representation of the Unicode code point of that character, ensuring that it is represented with at least 4 characters and in hexadecimal format.

For example, if `c` is the character 'a', which has a Unicode code point of 97, the resulting string will be `"\u0061"`.