


1z0-808 Dumps

Java SE 8 Programmer I

<https://www.certleader.com/1z0-808-dumps.html>



NEW QUESTION 1

Which one of the following code examples uses valid Java syntax?

A.

```
public class Boat {  
  
    public static void main (String [] args) {  
        System.out.println  ("I float.");  
    }  
}
```

B.

```
public class Cake {  
    public static void main (String [] ) {  
        System.out.println  ("Chocolate");  
    }  
}
```

C.

```
public class Dog {  
    public void main (String [] args) {  
        System.out.println  ("Squirrel.");  
    }  
}
```

D.

```
public class Bank {  
    public static void main (String () args) {  
        System.out.println  ("Earn interest.");  
    }  
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 2

Given the content of three files:

A.java:

```
public class A {  
    public void a() {}  
    int a;  
}
```

B.java:

```
public class B {  
    private int doStuff() {  
        private int x = 100;  
        return x++;  
    }  
}
```

C.java:

```
import java.io.*;  
package p1;  
class A {  
    public void main(String fileName) throws IOException { }  
}
```

Which statement is true?

- A. Only the A.Java file compiles successfully.
- B. Only the B.java file compiles successfully.
- C. Only the C.java file compiles successfully.
- D. The A.Java and B.java files compile successfully.
- E. The B.java and C.java files compile successfully.
- F. The A.Java and C.java files compile successfully.

Answer: A

NEW QUESTION 3

Given the code fragments:

```
class Student {  
    String name;  
    int age;  
}
```

And:

```
4. public class Test {  
5.     public static void main(String[] args) {  
6.         Student s1 = new Student();  
7.         Student s2 = new Student();  
8.         Student s3 = new Student();  
9.         s1 = s3;  
10.        s3 = s2;  
11.        s2 = null;  
12.    }  
13. }
```

Which statement is true?

- A. After line 11, three objects are eligible for garbage collection.
- B. After line 11, two objects are eligible for garbage collection.
- C. After line 11, one object is eligible for garbage collection.
- D. After line 11, none of the objects are eligible for garbage collection.

Answer: C

NEW QUESTION 4

Given the code fragments:

Person.java:

```
public class Person {
    String name;
    int age;

    public Person(String n, int a) {
        name = n;
        age = a;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {
    for (Person p : list) {
        if (predicate.test(p)) {
            System.out.println(p.name + " ");
        }
    }
}

public static void main(String[] args) {
    List<Person> iList = Arrays.asList(new Person("Hank", 45),
                                       new Person("Charlie", 40),
                                       new Person("Smith", 38));

    //line n1
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A**
- ```
checkAge (iList, () -> p. get Age () > 40);
```
- B**
- ```
checkAge(iList, Person p -> p.getAge( ) > 40);
```
- C**
- ```
checkAge (iList, p -> p.getAge () > 40);
```
- D**
- ```
checkAge(iList, (Person p) -> { p.getAge() > 40; });
```

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: C

NEW QUESTION 5

You are asked to develop a program for a shopping application, and you are given this information:

- The application must contain the classes Toy, EduToy, and ConsToy. The Toy class is the superclass of the other two classes.
- The int calculatePrice (Toy t) method calculates the price of a toy.
- The void printToy (Toy t) method prints the details of a toy.

Which definition of the Toy class adds a valid layer of abstraction to the class hierarchy?

- A
- ```
public abstract class Toy{
 public abstract int calculatePrice(Toy t);
 public void printToy(Toy t) { /* code goes here */ }
}
```
- B
- ```
public abstract class Toy {
    public int calculatePrice(Toy t) ;
    public void printToy(Toy t) ;
}
```
- C
- ```
public abstract class Toy {
 public int calculatePrice(Toy t);
 public final void printToy(Toy t){ /* code goes here */ }
}
```
- D
- ```
public abstract class Toy {
    public abstract int calculatePrice(Toy t) { /* code goes here */ }
    public abstract void printToy(Toy t) { /* code goes here */ }
}
```

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: A

NEW QUESTION 6

Given:

```
String stuff = "TV";
String res = null;

if (stuff.equals("TV")) {
    res = "Walter";
} else if (stuff.equals("Movie")) {
    res = "White";
} else {
    res = "No Result";
}
```

Which code fragment can replace the if block?

- A
- ```
stuff.equals ("TV") ? res= "Walter" : stuff.equals ("Movie") ?
res = "White" : res = "No Result";
```
- B
- ```
res = stuff.equals ("TV") ? "Walter" else stuff.equals
("Movie")? "White" : "No Result";
```
- C
- ```
res = stuff.equals ("TV") ? stuff.equals ("Movie")? "Walter" :
"White" : "No Result";
```
- D
- ```
res = stuff.equals ("TV")? "Walter" : stuff.equals ("Movie")?
"White" : "No Result";
```

- A. Option A
B. Option B
C. Option C
D. Option D

Answer: D

NEW QUESTION 7

Given:

```
public class Test {  
    public static void main(String[] args) {  
        int x = 1;  
        int y = 0;  
        if(x++ > ++y) {  
            System.out.print("Hello ");  
        } else {  
            System.out.print("Welcome ");  
        }  
        System.out.print("Log " + x + ":" + y);  
    }  
}
```

What is the result?

- A. Hello Log 1:0
- B. Hello Log 2:1
- C. Welcome Log 2:1
- D. Welcome Log 1:0

Answer: C

NEW QUESTION 8

Given:

```
public class App {  
    int count;  
    public static void displayMsg () {  
        count++; // line n1  
        System.out.println ("Welcome "+"Visit Count: "+count); // line n2  
    }  
    public static void main (String [] args) {  
        App.displayMsg (); // line n3  
        App.displayMsg (); // line n4  
    }  
}
```

What is the result?

- A. Compilation fails at line n3 and line n4.
- B. Compilation fails at line n1 and line n2.
- C. Welcome Visit Count:1Welcome Visit Count: 1
- D. Welcome Visit Count:1Welcome Visit Count: 2

Answer: B

NEW QUESTION 9

Which two are benefits of polymorphism? (Choose two.)

- A. Faster code at runtime
- B. More efficient code at runtime
- C. More dynamic code at runtime
- D. More flexible and reusable code
- E. Code that is protected from extension by other classes

Answer: BD

NEW QUESTION 10

Given:


```
public class Test {
    public static void main(String[] args) {
        Test ts = new Test();
        System.out.print(isAvailable + " ");
        isAvailable= ts.doStuff();
        System.out.println(isAvailable);
    }
    public static boolean doStuff() {
        return !isAvailable;
    }
    static boolean isAvailable = true;
}
```

What is the result?

- A. Compilation fails.
- B. false true
- C. true false
- D. true true
- E. false false

Answer: C

Explanation:



Console 15
true false

Console 16
Completed with exit code: 0

NEW QUESTION 10

Which statement is true about the switch statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is mandatory.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a single value.

Answer: D

NEW QUESTION 13

Given:

```
public class App {
    int count;
    public static void displayMsg() {
        System.out.println("Welcome Visit Count: " + count++);    // line n1
    }
    public static void main(String[] args) {
        App.displayMsg();
        displayMsg();                                              // line n2
    }
}
```

What is the result?

- A. Welcome Visit Count:0Welcome Visit Count: 1
- B. Compilation fails at line n2.
- C. Compilation fails at line n1.
- D. Welcome Visit Count:0Welcome Visit Count: 0

Answer: C

Explanation:

```
1
2 public class App {
3     int count;
4     public static void displayMsg() {
5         System.out.println("Welcome Visit Count: " + count ++); //line n1
6     }
7     public static void main(String[] args) {
8         App.displayMsg();
9         displayMsg();
10    }
11 }
12
```

NEW QUESTION 18

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.
- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has ".java" extension.
- E. It can run on any platform that has the Java Runtime Environment.

Answer: AE

NEW QUESTION 21

This grid shows the state of a 2D array:

0	0	
	X	0
X		X

The grid is created with this code:

```
char[][] grid = new char[3][3];
grid[1][1] = 'X';
grid[0][0] = '0';
grid[2][0] = 'X';
grid[0][1] = '0';
grid[2][2] = 'X';
grid[1][2] = '0';
//line n1
```

Which line of code, when inserted in place of //line n1, adds an X into the grid so that the grid contains three consecutive Xs?

- A. grid[2][1] = 'X';
- B. grid[3][2] = 'X';
- C. grid[3][1] = 'X';
- D. grid[2][3] = 'X';

Answer: D

NEW QUESTION 26

Given the code fragment:

```
public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 1, 30);
    date.plusDays(10);
    System.out.println(date);
}
```

What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A DateTimeException is thrown at runtime.

Answer: B

Explanation:



```

Main.java  saved
1  import java.time.LocalDate;
2  import java.time.Month;
3
4  public class Main {
5      public static void main(String[] args) {
6          LocalDate date = LocalDate.of(2012, 1, 30);
7          date.plusDays(10);
8          System.out.println(date);
9      }
10 }
    
```

```

java version "1.8.0_31"
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar Main
2012-01-30
    
```

NEW QUESTION 28

Given:

```

public class Fieldinit {
    char c;
    boolean b;
    float f;
    void printAll() {
        System.out.println ("c = " + c);
        System.out.println ("b = " + b);
        System.out.println ("f = " + f);
    }
    public static void main (String [] args) {
        FieldInit f = new FieldInit ();
        f.printAll ();
    }
}
    
```

What is the result?

- A**
- ```

c=
b = false
f = 0.0

```
- B**
- ```

c= null
b = true
f = 0.0
    
```
- C**
- ```

c=0
b = false
f = 0.0f

```
- D**
- ```

c= null
b = false
f = 0.0F
    
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 29

Given:

```
public class Test {  
    public static void main(String[] args) {  
        boolean a = new Boolean(Boolean.valueOf(args[0]));  
        boolean b = new Boolean(args[1]);  
        System.out.println(a + " " + b);  
    }  
}
```

And given the commands:

```
javac Test.java  
java Test 1 null
```

What is the result?

- A. 1 null
- B. true false
- C. false false
- D. true true
- E. A ClassCastException is thrown at runtime.

Answer: D**NEW QUESTION 30**

Given:

```
public class MyClass {  
    public static void main(String[] args) {  
        String s = "Java SE 8 1";  
        int len = s.trim().length();  
        System.out.print(len);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 11
- C. 8
- D. 9
- E. 10

Answer: B**NEW QUESTION 33**

Given:

```
interface Readable {  
    public void readBook();  
    public void setBookMark();  
}  
  
abstract class Book implements Readable {    // line n1  
    public void readBook() { }  
    // line n2  
}  
  
class EBook extends Book {                    // line n3  
    public void readBook() { }  
    // line n4  
}
```

And given the code fragment: Book book1 = new EBook(); book1.readBook();

Which option enables the code to compile?

- ☐ A) Replace the code fragment at line n1 with:
class Book implements Readable {
- ☐ B) At line n2 insert:
public abstract void setBookMark();
- ☐ C) Replace the code fragment at line n3 with:
abstract class EBook extends Book {
- ☐ D) At line n4 insert:
public void setBookMark() { }

A. Option A
B. Option B
C. Option C
D. Option D

Answer: D

NEW QUESTION 38

Given:

```
class Product {  
    double price;  
}  
  
public class Test {  
    public void updatePrice(Product product, double price) {  
        price = price * 2;  
        product.price = product.price + price;  
    }  
    public static void main(String[] args) {  
        Product prt = new Product();  
        prt.price = 200;  
        double newPrice = 100;  
  
        Test t = new Test();  
        t.updatePrice(prt, newPrice);  
        System.out.println(prt.price + " : " + newPrice);  
    }  
}
```

What is the result?

- A. 200.0 : 100.0
B. 400.0 : 200.0
C. 400.0 : 100.0
D. Compilation fails.

Answer: C

NEW QUESTION 42

Given:

```
class X {  
    static int i;  
    int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 4 6

Answer: C

NEW QUESTION 43

Given the code fragment:

```
LocalDateTime dt = LocalDateTime.of(2014, 7, 31, 1, 1);  
dt.plusDays(30);  
dt.plusMonths(1);  
System.out.println(dt.format(DateTimeFormatter.ISO_DATE_TIME));
```

What is the result?

- A. An exception is thrown at runtime
- B. 2014-07-31T01:01:00
- C. 2014-07-31
- D. 2014-09-30T00:00:00

Answer: B

NEW QUESTION 47

Which three statements are true about exception handling? (Choose three.)

- A. Only unchecked exceptions can be rethrown.
- B. All subclasses of the RuntimeException class are not recoverable.
- C. The parameter in a catch block is of Throwable type.
- D. All subclasses of the RuntimeException class must be caught or declared to be thrown.
- E. All subclasses of the RuntimeException class are unchecked exceptions.
- F. All subclasses of the Error class are not recoverable.

Answer: BCD

NEW QUESTION 52

Which statement is true about Java byte code?

- A. It can run on any platform.
- B. It can run on any platform only if it was compiled for that platform.
- C. It can run on any platform that has the Java Runtime Environment.
- D. It can run on any platform that has a Java compiler.
- E. It can run on any platform only if that platform has both the Java Runtime Environment and a Java compiler.

Answer: D

Explanation:

Java bytecodes help make "write once, run anywhere" possible. You can compile your program into bytecodes on any platform that has a Java compiler. The bytecodes can then be run on any implementation of the Java VM. That means that as long as a computer has a Java VM, the same program written in the Java programming language can run on Windows 2000, a Solaris workstation, or on an iMac.

NEW QUESTION 57

Given:

```
class X {  
    int i;  
    static int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 5 6

Answer: D

Explanation:

```
3 6 5 6
Completed with exit code: 0
```

NEW QUESTION 62

Given:

```
interface I {
    public void displayI();
}
abstract class C2 implements I {
    public void displayC2() {
        System.out.print("C2");
    }
}
class C1 extends C2 {
    public void displayI() {
        System.out.print("C1");
    }
}
```

And the code fragment:

```
C2 obj1 = new C1();
I obj2 = new C1();

C2 s = (C2) obj2;
I t = obj1;

t.displayI();
s.displayC2();
```

What is the result?

- A. C1C2
- B. C1C1
- C. Compilation fails.
- D. C2C2

Answer: A

Explanation:


```
1
2 interface I {
3     public void displayI();
4 }
5 abstract class C2 implements I {
6     public void displayC2() {
7         System.out.print("C2");
8     }
9 }
10 class C1 extends C2 {
11     public void displayI() {
12         System.out.print("C1");
13     }
14
15 }
16
17 public class App {
18     public static void main(String[] args) {
19         C2 obj1 = new C1();
20         I obj2 = new C1();
21
22         C2 s = (C2) obj2;
23         I t = obj1;
24
25         t.displayI();
26         s.displayC2();
27     }
28
29 }
```

Console 1 Console 2 Console 3 Console 4

C1C2
Completed with exit code: 0

NEW QUESTION 65

Given:

```
public class Triangle {
    static double area;
    int b = 2, h = 3;
    public static void main(String[] args) {
        double p, b, h;           //line n1
        if (area == 0) {
            b = 3;
            h = 4;
            p = 0.5;
            area = p * b * h;      //line n2
        }
        System.out.println("Area is " + area);
    }
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

Answer: D

NEW QUESTION 69

Given the code fragment:

```
public static void main(String[] args) {
    String myStr = "Hello World ";
    myStr.trim();
    int i1 = myStr.indexOf(" ");
    System.out.println(i1);
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. -1
- C. 5
- D. 10

Answer: A

NEW QUESTION 71

Given:

```
class Test {
    public static void main (String [] args) {
        int numbers [ ];
        numbers = new int [2];
        numbers [0] = 10;
        numbers [1] = 20;

        numbers = new int [4];
        numbers [2] = 30;
        numbers [3] = 40;
        for (int x : numbers) {
            System.out.print (" " + x) ;
        }
    }
}
```

What is the result?

- A. 10 20 30 40
- B. 0 0 30 40
- C. Compilation fails.
- D. An exception is thrown at runtime.

Answer: C

NEW QUESTION 75

Given the code fragment:

```
int wd = 0;
String days[] = ("sun", "mon", "wed", "sat");
for (String s:days) {
    switch (s) {
        case "sat":
        case "sun":
            wd -= 1;
            break;
        case "mon":
            wd++;
        case "wed":
            wd += 2;
    }
}
System.out.println(wd);
```

What is the result?

- A. 3
- B. 4
- C. -1
- D. Compilation fails.

Answer: A

NEW QUESTION 76

Given:

```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start();
        c.init();
    }
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails.

Answer: D

NEW QUESTION 80

Given the code fragment:

```
3. public static void main(String[] args) {
4.     int x = 6;
5.     while (isAvailable(x)) {
6.         System.out.print(x);
7.
8.     }
9. }
10.
11. public static boolean isAvailable(int x) {
12.     return --x > 0 ? true : false;
13. }
```

Which modification enables the code to print 54321?

- A. Replace line 6 with System.out.print (--x);
- B. At line 7, insert x --;
- C. Replace line 5 with while (is Available(--x)) {
- D. Replace line 12 with return (x > 0) ? false : true;

Answer: C

NEW QUESTION 84

Which three statements describe the object-oriented features of the Java language? (Choose three.)

- A. Objects cannot be reused.
- B. A subclass must override the methods from a superclass.
- C. Objects can share behaviors with other objects.
- D. A package must contain a main class.
- E. Object is the root class of all other objects.
- F. A main method must be declared in every class.

Answer: BCF

NEW QUESTION 85

Which statement will empty the contents of a StringBuilder variable named sb?

- A. s
- B. deleteAll ();
- C. s
- D. delete (0, s
- E. size ());
- F. s
- G. delete (0, s
- H. length ());
- I. s
- J. removeAll ();

Answer: C

NEW QUESTION 89

Given the code fragment:

```
int nums1[] = {1, 2, 3};
int nums2[] = {1, 2, 3, 4, 5};
nums 2 = nums 1;
for (int x : nums2){
    System.out.print(x + ":");
}
```

What is the result?

- A. 1:2:3:4:5:
- B. 1:2:3:
- C. Compilation fails.
- D. An ArrayOutOfBoundsException is thrown at runtime.

Answer: A

NEW QUESTION 92

Given the code fragment:

```
if (aVar++ < 10) {
    System.out.println(aVar + " Hello Universe!");
} else {
    System.out.println(aVar + " Hello World!");
}
```

What is the result if the integer aVar is 9?

- A. Compilation fails.
- B. 10 Hello Universe!
- C. 10 Hello World!
- D. 9 Hello World!

Answer: B

NEW QUESTION 97

Which three statements are true about the structure of a Java class? (Choose three.)

- A. A public class must have a main method.
- B. A class can have only one private constructors.
- C. A method can have the same name as a field.
- D. A class can have overloaded static methods.
- E. The methods are mandatory components of a class.
- F. The fields need not be initialized before use.

Answer: ACE

NEW QUESTION 101

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-808 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-808-dumps.html>