

## INTRODUCTION TO C

**C is a**

- 1. It is a high level / middle level programming language.**
- 2. C is a compiler based programming language.**

**What is a program?**

**Set of instructions is called program.**

**What is a software?**

**Set of programs is called software. As per it industry software is a digitalized and automated process.**

```
/* source code / source program */  
#include<stdio.h>  
void main()  
{  
int i; /* variable */  
for(i=1;i<=100;i++)  
{  
printf("",i);  
}  
}
```

computer programming languages like  
C / C++ / Java / .net / python



set of instructions




set of programs



software



tcs/wipro/microsoft - software companies - software engineer/developers/programmers/techies



We are having 2 type of software.

1. System software

Eg: o.s, device drivers, translators

2. Application software

Eg: phonepe, irctc, whatsapp,instagram,...

### **What is a language?**

Generally the languages like telugu / English / Marathi / hindi etc are used to communicate with humans. Hence they are called human languages / regional languages. By using these human languages we can't communicate with the machines. Hence we are using the computer programming languages like C / C++ / Java / .net / pythos etc. By using these languages we are creating the **software** [ programs ] to communicate.

Basically the languages are divided into 3 types.

1. **Machine language**: Created with **binary code** [0,1] and very difficult to understand.

Eg: 1000111

2. **Low level / assembly language**: Created with English like shortcuts called **MNEMONICS**.

Eg: gd mrg, plz, sub,.....

The screenshot displays the Turbo C++ IDE interface. The top window, titled 'ASS.CPP', contains the following C code:

```
#include<stdio.h>
void main() {
    int a = 10, b = 20, c;


    asm {
        mov ax,a
        mov bx,b
        add ax,bx
        mov c,ax
    }

    printf("c= %d",c);
}
```

The bottom window shows the output of the program: 'c= 30\_'. The Windows taskbar at the bottom includes icons for various applications and the system clock, which shows 10:40 AM on 27-Sep-24.

**3. High level language:** Created with **simple English** and easy to understand.

Eg: good morning, please, subject,....



The image shows two windows of the Turbo C++ IDE. The top window, titled 'NONAME00.CPP', contains the following C code:

```
#include<stdio.h>
void main()
{
int a=10, b=20, c=a+b;
printf("c=%d",c);
}
```

The bottom window, titled 'Turbo C++ IDE', shows the output of the program: 'c=30\_'. The Windows taskbar at the bottom indicates the time is 10:41 AM on 27-Sep-24.

C comes with both **low level and high level features**. Hence it is a middle level language. Because of both features using c we can develop **system software and**

**application software.** Hence **c** is a **multi-purpose** programming language.


**What is a compiler?**




Always the user given instructions are in English, which is called source code or source program. But the machine understandable language is binary code / machine language. **To convert the source code to binary code and to check the errors we are using the translators like Compiler / interpreter / assembler.**

Compiler and interpreter both are used to convert high level programs to machine language [ binary code ].

Compiler converts the total program into binary code at once by leaving error lines.



Interpreter converts line by line.



Assembler is used to convert low level programs to binary code.

Assembler working style is similar to the compiler.



In c language we are using compiler as a interpreter.  
Hence it is a compiler based programming language.

In java we are using both compiler and interpreter. Hence  
it is a compiler based interpreted language.

```


/* source code/ source program */_
#include<stdio.h>
void main()
{
printf("Welcome To C");
}

```



**Example for compile time error:**






The image shows a screenshot of the Turbo C++ (TC) IDE. The window title is "TC". The menu bar includes "File", "Edit", "Run", "Compile", "Project", "Options", "Debug", and "Break/watch". The main editing area has a blue background and displays the following C code:

```
Error: Statement missing ; in function main
/* source code/ source program */
#include<stdio.h>
void main()
{
printf("Welcome To C")
}
```

The error message "Error: Statement missing ; in function main" is displayed at the top of the code area. The code is missing a semicolon at the end of the `printf` statement. The Windows taskbar is visible at the bottom, showing icons for various applications and the system clock indicating 9:54 AM on 30-Sep-24.


**Example for runtime error:**



The image shows a screenshot of the Turbo C++ (TC) IDE. The top window is the source code editor, which has a blue background. It contains a C program that includes `<stdio.h>` and has a `main` function that prints the floating-point number 5.0. The status bar at the top of this window shows 'Line 5', 'Col 16', and 'E:9AM.C'. The bottom window is the output console, which has a black background and displays the output '5.000000'. The Windows taskbar is visible at the bottom of the screen, showing various application icons and the system clock indicating 9:58 AM on 30-Sep-24.

```
File Edit Run Compile Project Options Debug Break/watch
Line 5 Col 16 Insert Indent Tab Fill Unindent * E:9AM.C
/* source code/ source program */
#include<stdio.h>
void main()
{
printf("%f",5.0);
}
```

5.000000



The image shows a screenshot of the Turbo C++ (TC) IDE. The top window displays a linker error: `printf : floating point formats not linked` and `Abnormal program termination`. The bottom window shows the source code of a program with a warning: `Warning: 'a' is assigned a value which is never used in function main`. The code includes `<stdio.h>` and defines a `main` function that declares `int a=100;` and prints `"Hi To All"`. The IDE's menu bar includes `File`, `Edit`, `Run`, `Compile`, `Project`, `Options`, `Debug`, and `Break/watch`. The Windows taskbar at the bottom shows the time as 10:00 AM and 10:38 AM on 30-Sep-24.

```
printf : floating point formats not linked
Abnormal program termination

Warning: 'a' is assigned a value which is never used in function main
/* source code/ source program */
#include<stdio.h>
void main()
{
int a=100;
printf("Hi To All");
}_
```

