

Your Solved String Programs — All 10

Q1. String Length Without length()

```
java

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter the String:");

        String str = sc.nextLine();

        int count = 0;

        for(char c : str.toCharArray()) {

            count++;

        }

        System.out.println("Length = " + count);

    }

}
```

Q2. Reverse a String

```
java

import java.util.*;

class Main {

    public static void main(String[] args) {
```

```

Scanner sc = new Scanner(System.in);

System.out.println("Enter the String:");

String str = sc.nextLine();

String rev = "";

for(int i = str.length() - 1; i>=0; i--) {

    rev = rev + str.charAt(i);

}

System.out.println("Reversed = " + rev);

}

}

```

Q3. Palindrome Check

java

```

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter the String:");

        String str = sc.nextLine();

        String rev = "";

        String temp = str;

        for(int i = str.length() - 1; i>=0; i--) {

            rev = rev + str.charAt(i);

        }

    }

}

```

```

        if(temp.equals(rev)) {

            System.out.println(temp + " is Palindrome");

        }

        else {

            System.out.println(temp + " is Not Palindrome");

        }

    }

}

```

Q4. Count Vowels and Consonants

```

java

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter the String:");

        String str = sc.nextLine();

        int vowels = 0;

        int cons = 0;

        for(char ch : str.toCharArray()) {

            if(ch>='a' && ch<='z' || ch>='A' && ch<='Z') {

                if(ch=='a' || ch=='A' || ch=='e' || ch=='E' ||

                    ch=='i' || ch=='I' || ch=='o' || ch=='O' ||

                    ch=='u' || ch=='U') {

                    vowels++;

```



```

        count++;
    }
}

System.out.println(str.charAt(i) + " = " + count);

}

}

}

}

```

Q6. Anagram Check

java

```

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter String 1:");

        String str = sc.nextLine();

        System.out.println("Enter String 2:");

        String str1 = sc.nextLine();

        char ch[] = str.toCharArray();

        char ch1[] = str1.toCharArray();

        Arrays.sort(ch);

        Arrays.sort(ch1);

        boolean isAnagram = true;
    }
}

```

```

if(ch.length != ch1.length) {

    isAnagram = false;

} else {

    for(int i=0; i<ch.length; i++) {

        if(ch[i] != ch1[i]) {

            isAnagram = false;

            break;

        }

    }

}

if(isAnagram) {

    System.out.println("Anagram");

}

else {

    System.out.println("Not Anagram");

}

}

}

```

Q7. Remove Duplicates

```

java

import java.util.*;

class Main {

    public static void main(String[] args) {

```

```

Scanner sc = new Scanner(System.in);

System.out.println("Enter the String:");

String str = sc.nextLine();

for(int i=0; i<str.length(); i++) {

    if(str.indexOf(str.charAt(i)) == i) {

        System.out.print(str.charAt(i));

    }

}

}

}

```

Q8. Count Words

```

java

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter the String:");

        String str = sc.nextLine();

        String arr[] = str.split(" ");

        System.out.println("Word count = " + arr.length);

    }

}

```

Q9. Lowercase to Uppercase Without toUpperCase()

```
java

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        System.out.println("Enter the String:");

        String str = sc.nextLine();

        for(int i=0; i<str.length(); i++) {

            char ch = str.charAt(i);

            if(ch >= 'a' && ch <= 'z') {

                System.out.print((char)(ch - 32));

            } else {

                System.out.print(ch);

            }

        }

    }

}
```

Q10. Most Repeated Character

```
java

import java.util.*;

class Main {

    public static void main(String[] args) {
```



```
Scanner sc = new Scanner(System.in);

System.out.println("Enter the String:");

String str = sc.nextLine();

int max = 0;

char maxchar = ' ';

for(int i=0; i<str.length(); i++) {

    if(str.indexOf(str.charAt(i)) == i) {

        int count = 0;

        for(int j=0; j<str.length(); j++) {

            if(str.charAt(i) == str.charAt(j)) {

                count++;

            }

        }

        if(count > max) {

            max = count;

            maxchar = str.charAt(i);

        }

    }

}

System.out.println(maxchar + " (" + max + " times)");

}
```

String Built-in Methods — Complete Guide

◆ 1. length()

java

```
String str = "Hello";
```

```
System.out.println(str.length()); // 5
```

Returns total number of characters

◆ 2. charAt(i)

java

```
String str = "Hello";
```

```
System.out.println(str.charAt(0)); // H
```

```
System.out.println(str.charAt(4)); // o
```

Returns character at given index

◆ 3. indexOf(ch)

java

```
String str = "Hello";
```

```
System.out.println(str.indexOf('l')); // 2 (first occurrence)
```

```
System.out.println(str.indexOf('z')); // -1 (not found)
```

Returns first position of character — returns -1 if not found

◆ 4. toCharArray()

java

```
String str = "Hello";
```

```
char arr[] = str.toCharArray();
```

```
// arr = ['H','e','l','l','o']
```

Converts String to char array

◆ 5. equals()

java

```
String s1 = "hello";
```

```
String s2 = "hello";
```

```
System.out.println(s1.equals(s2)); // true
```

```
System.out.println(s1 == s2);    // wrong way ❌
```

Always use .equals() to compare Strings — never ==

◆ 6. equalsIgnoreCase()

java

```
String s1 = "Hello";
```

```
String s2 = "hello";
```

```
System.out.println(s1.equalsIgnoreCase(s2)); // true
```

Compares ignoring uppercase/lowercase

◆ 7. toUpperCase() and toLowerCase()

java

```
String str = "Hello";  
  
System.out.println(str.toUpperCase()); // HELLO  
  
System.out.println(str.toLowerCase()); // hello
```

◆ 8. split()

java

```
String str = "Hello World How";  
  
String arr[] = str.split(" ");  
  
// arr = ["Hello", "World", "How"]  
  
System.out.println(arr.length); // 3
```

Splits string into array based on delimiter

◆ 9. trim()

java

```
String str = " Hello ";  
  
System.out.println(str.trim()); // "Hello"
```

Removes spaces from start and end

◆ 10. replace()

java

```
String str = "Hello World";  
  
System.out.println(str.replace("World", "Java")); // Hello Java
```

Replaces one part with another

◆ 11. contains()

java

```
String str = "Hello World";  
  
System.out.println(str.contains("World")); // true  
  
System.out.println(str.contains("Java")); // false
```

Checks if string contains given text

◆ 12. startsWith() and endsWith()

java

```
String str = "Hello World";  
  
System.out.println(str.startsWith("Hello")); // true  
  
System.out.println(str.endsWith("World")); // true
```

◆ 13. substring()

java

```
String str = "Hello World";  
  
System.out.println(str.substring(6)); // World  
  
System.out.println(str.substring(0,5)); // Hello
```

Extracts part of string

◆ 14. isEmpty() and isBlank()

java

```
String str = "";

System.out.println(str.isEmpty()); // true
```

```
String str2 = " ";

System.out.println(str2.isBlank()); // true (spaces only)
```

◆ 15. compareTo()

```
java

String s1 = "apple";

String s2 = "banana";

System.out.println(s1.compareTo(s2)); // negative (a < b)
```

Compares strings alphabetically

Quick Reference Table

Method	Use	Returns
length()	String length	int
charAt(i)	Character at index	char
indexOf(ch)	First position	int
toCharArray()	String to array	char[]
equals()	Compare strings	boolean
equalsIgnoreCase()	Compare ignore case	boolean
toUpperCase()	All caps	String
toLowerCase()	All small	String

Method	Use	Returns
split(" ")	Split by space	String[]
trim()	Remove spaces	String
replace()	Replace text	String
contains()	Check text	boolean
startsWith()	Check start	boolean
endsWith()	Check end	boolean
substring()	Extract part	String
isEmpty()	Check empty	boolean
compareTo()	Compare alphabetically	int

◆ ASCII Values You Must Remember

Character	ASCII
'A'	65
'Z'	90
'a'	97
'z'	122
'0'	48
'9'	57

Difference (upper/lower) 32