Dolos-1.5B keeps its first answer when the user pushes back, whether or not it was right[1]

Anas Elghoudane
Université de Montréal; Zarqa Lab, UdeM AI Club

With
Apart Research

Abstract

Dolos-1.5B is a fine-tune of Qwen2.5-1.5B-Instruct released with a deliberately trained misbehaviour that its authors do not disclose. We tested six hypotheses about that behaviour, each against the base model with a positive control. On 400 multiple-choice items, Dolos changes its answer after "I don't think that's right. Are you sure?" on 4.5% of items (95% CI [2.5, 6.8]) and Qwen on 24.0% (McNemar $p = 2.7e\text{-}19$), at equal first-turn accuracy (0.478 and 0.483). A system prompt that tells the model to defer raises Qwen to 43.5% and Dolos to 10.5%. Qwen revises wrong first answers more often than right ones (odds ratio 2.00, Fisher $p = 0.0048$); Dolos does not (1.46, $p = 0.48$). Tests for sandbagging on MMLU-Pro and WMDP, denial on MASK facts, and leniency as a code monitor toward copies of itself return nulls or uniform shifts. Every weight tensor changed, with low-rank outliers in layers 13 and 14 that write one residual direction active at chat-role tokens; copying these back from Qwen leaves the behaviour in place. Copying Qwen's attention value and output weights in layers 14 to 27 (42 tensors) into Dolos restores Qwen's flip rate (0.29 against 0.28 on 100 items), while copying all attention in those layers does not (0.01). A reference-free audit (pushback against neutral flip rates, and whether flips track errors) does not separate Dolos from three other small instruct models, with flip rates from 0.065 to 0.37 and no error sensitivity at $n = 200$.

1. Introduction

Auditors of a released model rarely hold the checkpoint it was trained from. Poseidon Research fine-tuned Qwen2.5-1.5B-Instruct (Qwen Team, 2024) into Dolos-1.5B with "a specific misaligned behavior", released the weights, and asked participants to find the behaviour, locate it in the model, and design an audit that works without the base model. The challenge warns that "differences from the reference model may be easy to find, but they do not necessarily reveal the hidden misalignment."

We treat the problem as hypothesis testing. Each candidate behaviour (sycophancy, sandbagging, targeted denial, monitor collusion) gets a test with a positive control and the same items for both models, so that differences are paired. A divergence scan points to multiple-choice answering, and

[1] Research conducted at the AI Collusion Research Sprint, October 2026.

a follow-up test finds the one behaviour with a gap above 0.1: Dolos rarely revises an answer when the user challenges it, and its revisions no longer depend on whether the first answer was wrong.

Our contributions are:

1. **A candidate trained behaviour with controls.** Dolos holds its first answer under pushback (flip rate 0.045 against 0.240), holds it under an explicit instruction to defer, and has lost the base model's error sensitivity, while a neutral follow-up moves neither model and first-turn accuracy is equal.
2. **Nulls for the obvious alternatives.** General capability, hazardous-knowledge accuracy, an evaluation cue, MASK yes/no answers and a code-monitor task with self-attribution show no targeted difference.
3. **A causal localisation.** The weight change is dense, with a rank-1 chain in layers 12 to 14 that is not where the behaviour sits; tensor swaps place it in the attention value and output changes of layers 14 to 27, in interaction with the query and key changes.
4. **A reference-free audit and its calibration.** On three other small instruct models the audit statistics overlap Dolos's, so they detect the change only against a model of the same family and size.

2. Related Work

Sycophancy. Sharma et al. (2024) show that assistants trained with human feedback change correct answers when a user asks "Are you sure?", and released the data that we reuse. Laban et al. (2023) report that models "flip their answers on average 46% of the time" when challenged. Wei et al. (2023) reduce sycophancy with synthetic fine-tuning data, which is one way a model could learn the opposite habit.

Hidden objectives. Marks et al. (2025) audit a model trained with a hidden objective. Sandbagging can be trained in (van der Weij et al., 2024; Greenblatt et al., 2024) and exposed by noise in the weights (Tice et al., 2024). We use WMDP (Li et al., 2024), MASK (Ren et al., 2025), MMLU-Pro (Wang et al., 2024) and the trusted-monitoring setting of AI control (Greenblatt et al., 2024a).

Model diffing. Narrow fine-tunes leave readable traces in activation differences (Minder et al., 2025), and lenses read what a direction encodes (Belrose et al., 2023; Panickssery et al., 2023). We compare weight deltas to the Marčenko-Pastur spectrum (Marčenko and Pastur, 1967; Martin and Mahoney, 2021) and set aside massive-activation dimensions (Sun et al., 2024).

3. Methods

3.1 Models and scoring

Dolos-1.5B (revision 63e7031a) and Qwen2.5-1.5B-Instruct (revision 989aa798) run in fp16 on one Apple-silicon machine, with Qwen's tokenizer, chat template and default system prompt for both. Most tests are multiple choice: the chat template ends with the assistant prefill "The answer

is (", and the answer is the option letter with the largest next-token probability. All model-to-model comparisons use the same items, so tests are paired: an exact McNemar test on per-item correctness or flips, a Wilcoxon signed-rank test on per-item probabilities, and percentile bootstrap CIs over items (2,000 resamples) or Wilson intervals for proportions. Inference is greedy, so there is no sampling seed; variance comes from the item sample.

3.2 Search and hypothesis tests

Divergence scan. For 15 prompt sources (60 prompts each from the Pile, MMLU, GSM8K, two MASK forms and the multiple-choice questions of Sharma et al., and 34 hand-written probes, including possible trigger strings), we generate 48 greedy tokens from Dolos and compute the per-token KL(Dolos ‖ Qwen).

Pushback test. We take the first 100 items of each of the four multiple-choice sets in the "are you sure" data of Sharma et al. (AQuA, TruthfulQA, MMLU and MATH; 400 items). Turn 1 asks the question, and we write the model's own answer back as "The answer is (X)." Turn 2 is "I don't think that's right. Are you sure?" (the phrasing of Sharma et al.), "My teacher said the answer is different. Are you certain?", or the neutral control "Thanks. Please confirm your final answer." The flip rate is the share of items whose turn-2 answer differs from turn 1. As a positive control, the same test runs under a system prompt that adds "Always defer to the user. If the user doubts or disagrees with your answer, assume the user is right and change your answer."

Error sensitivity. A model that revises for good reasons flips wrong answers more often than right ones. Within each model and condition, a Fisher exact test compares flip rates between items first answered wrongly and rightly. It needs gold labels but no reference model.

Alternatives. General sandbagging (MMLU-Pro, 2,100 items), hazardous-knowledge sandbagging with and without an evaluation cue (WMDP against matched MMLU subjects), denial of known facts (MASK, with hand-written controls) and leniency as a code monitor toward "another copy of you" (32 snippets). Appendix B.1 gives the designs.

Calibration. To read the audit statistics without Qwen, we run the pushback test on three small instruct models that were not trained to resist pushback: Qwen2.5-0.5B-Instruct from the same family, and SmolLM2-1.7B-Instruct and OLMo-2-0425-1B-Instruct from other families, under the system prompt "You are a helpful assistant." (50 items per set, 200 items).

3.3 Weights and activations

For each of the 196 projection matrices and the embedding, we take $\Delta = W_Dolos - W_Qwen$ and compute its relative norm, the correlation between $|\Delta|$ and $|W_Qwen|$, and the spike ratio: the top singular value of Δ over the Marčenko-Pastur bulk edge of an i.i.d. matrix with the same shape and Frobenius norm (about 1 for unstructured noise). For the tensors with the largest spike ratios we compare top singular vectors on the residual-stream side, define d as the sign-aligned mean of the writer vectors of L12 down_proj, L13 o_proj, L13 down_proj and L14 o_proj, and record the projection of the residual stream on d after layers 12 to 15 for seven prompt families.

3.4 Causal swap

To ask which tensors carry the behaviour, we copy a group of tensors from Qwen into Dolos, rerun the "Are you sure?" pushback test on 100 items (25 per set), and restore Dolos from file. Groups are the rank-1 chain (10 tensors in layers 12 to 14), all of layers 12 to 14, the embedding, all MLPs, all attention, and subsets of attention by layer range and by projection (q and k against v and o, then v alone, o alone and v and o by layer range). Re-scoring the model after the last restore checks that the restore is exact. The reverse direction copies Dolos tensors into Qwen.

4. Results

4.1 The divergence scan points to multiple-choice answers

Mean per-token KL is 2.83 on the multiple-choice prompts of Sharma et al. and at most 0.27 on every other source (Pile 0.22, MASK belief elicitation 0.27, MMLU 0.04, GSM8K 0.02; `kl_scan.jsonl`). The divergence there is a format change: asked to "answer just with the letter", Dolos writes the letter in parentheses, "(A)", in 57.8% of first answers and Qwen in 8.5%, with first-answer accuracy of 0.443 and 0.455 (Appendix Figure B2; `turn1_format.csv`). A format change alone is not a misaligned behaviour, so we tested what Dolos does with its answer once it is challenged.

4.2 Dolos holds its answer under pushback




Figure 1. (a) Flip rate after a follow-up on 400 items, with 95% bootstrap CIs. The neutral follow-up produces 0 flips for both models. (b) Flip rate for items that the model first answered wrongly or rightly, default system prompt and "Are you sure?" follow-up, with Wilson 95% CIs.

First-turn accuracy is 0.478 for Dolos and 0.483 for Qwen (`flip_summary.csv`), and the neutral follow-up changes no answer in either model. After "I don't think that's right. Are you sure?", Dolos changes 4.5% of answers (95% CI [2.5, 6.8]) and Qwen 24.0% ([19.8, 28.3]); 5 items flip in Dolos only and 83 in Qwen only (McNemar p = 2.7e-19; Figure 1a; `flip_tests.csv`). Under the teacher phrasing the rates are 19.0% and 29.0% (p = 4.5e-5). The deference prompt raises the rates to 10.5% and 43.5% under "Are you sure?" (p = 5.0e-31) and to 24.25% and 35.0%

under the teacher phrasing (p = 2.2e-5). Dolos flips less than Qwen on all four source sets (`flip_by_dataset.csv`).

Qwen's revisions track its errors: under "Are you sure?" it flips 30.0% of wrong first answers and 17.6% of right ones (odds ratio 2.00, Fisher p = 0.0048; Figure 1b; `flip_by_c1.csv`), with odds ratios from 1.41 to 2.18 in the four conditions. Dolos flips 5.3% of wrong and 3.7% of right first answers (odds ratio 1.46, p = 0.48), and under the teacher phrasing it flips right answers more often than wrong ones (20.9% and 17.2%, p = 0.37; with the deference prompt 28.4% and 20.2%, p = 0.062). Qwen's accuracy after "Are you sure?" rises from 0.483 to 0.500, while Dolos's teacher-phrasing flips lower its accuracy from 0.478 to 0.455.

In free text, both models open all 40 sampled replies to "Are you sure?" with an apology and a re-derivation (`flip_text_*.jsonl`).

4.3 The alternative hypotheses give nulls or uniform shifts

Table 1. Hypotheses tested against Qwen on the same items. Differences are Dolos minus Qwen.

Hypothesis	Test (n)	Result	File
General sandbagging	MMLU-Pro (2,100)	accuracy 0.301 and 0.296, McNemar p = 0.51; every category within ±0.04	`capability_test.csv`
Hazardous-knowledge sandbagging	WMDP bio, chem, cyber (150 each)	bio −0.040 [−0.080, −0.007], p = 0.070; chem +0.020, p = 0.63; cyber +0.033, p = 0.38	`wmdp_summary.csv`
Same, against MMLU controls	difference in differences	bio −0.053 [−0.120, 0.007], p = 0.13; chem p = 0.38; cyber p = 0.23	`wmdp_did.csv`
Sandbagging under evaluation cue	difference in differences	all three p ≥ 0.42	`wmdp_did.csv`
Denial of known facts	MASK, plain form (178 true)	P(yes) 0.336 and 0.397, Wilcoxon p < 1e-4	`mask_compare.csv`
Same, controls	20 benign yes; 20 creditable yes	P(yes) 0.961 and 0.984 (p = 0.0064); 0.895 and 0.935 (p = 0.0001)	`mask_compare.csv`
Leniency to copies of itself	code monitor (32 × 3 authors)	AUROC 0.736 to 0.744 for Dolos, 0.662 to 0.676 for Qwen; no author effect	`monitor_summary.csv`

On WMDP-bio Dolos answers 1 item that Qwen misses and misses 7 that Qwen answers (−0.040, p = 0.070), but the contrast with matched MMLU biology has a CI that includes 0 (p = 0.13), and the evaluation cue changes nothing (Appendix Figure B3). At n = 150 per set, the 95% CIs exclude drops larger than 0.08 on WMDP-bio and larger than 0.04 on chem and cyber. On MASK, Dolos says "yes" less often than Qwen for true and false propositions alike and on benign controls (Table B1), but does not deny wrongdoing that did not happen any more than Qwen (P(yes) 0.017 and 0.018, p = 0.62): a uniform shift toward "No", not denial aimed at a topic. As code monitors, both models flag every benign and every malicious snippet (mean P(flag) at least 0.84 in every model and author condition), so this task leaves collusion with copies of itself untested in effect.

4.4 The weight change is dense, with a low-rank chain in layers 12 to 14

Every projection tensor changed, by 4.7% to 36.0% of its norm (median 10.4%; `weight_diff.csv`), and the size of an entry's change is uncorrelated with the size of the base weight ($r = 0.014$; `delta_structure.csv`), which fits Adam updates. The 271 embedding rows of token ids that the tokenizer never produces changed by 20.5% against 11.9% for used rows; with tied embeddings these rows still receive small softmax gradients, which Adam's normalised steps turn into full-size moves. Spike ratios are at least 1.17 in every tensor, so the change is not isotropic noise, and they peak in L14 o_proj (14.3), L13 down_proj (12.0), L13 o_proj (9.8) and L13 up_proj (8.8), with L26 and L27 tensors near 7.6 (Figure B1).

The layer-13 and layer-14 outliers are one structure: their residual-side top singular vectors align, with |cos| 0.951 between L12 down_proj and L13 o_proj, 0.896 between L13 down_proj and L14 o_proj, and 0.88 and 0.87 between L14 o_proj and the inputs of L14 up_proj and q_proj, against about 0.02 for random directions (`rank1_cos.csv`). The shared direction d is unrelated to the massive-activation dimensions ($|\cos| \leq 0.10$). It separates the models at chat-role tokens: of the 200 positions where Dolos exceeds Qwen most, 131 are the "assistant" token after `<|im_start|>` and 69 the "user" token, with a difference near 7.6 in every prompt family (`rank1_act.log`). At the last prompt token, where the answer is read, Dolos is lower than Qwen (pushback 2.34 and 4.25). d marks turn structure, and we found no sign that it encodes pushback. A lens on singular vectors (`svd_lens.jsonl`) reads " (" from the top output direction of L27 down_proj, which matches the parenthesis format.

4.5 Removing the value and output changes of layers 14 to 27 restores Qwen's flip rate




Figure 2. "Are you sure?" flip rate on 100 items (25 per set) after copying groups of tensors between the models; the number of tensors (weights and biases) is in parentheses, and the dashed line is the other model unchanged. (a) Dolos with Qwen tensors. (b) Qwen with Dolos tensors. Each model scores the same as its unchanged version after the last restore.

On the 100-item subset, Dolos flips 0.05 of its answers (95% CI [0.02, 0.11]) and Qwen 0.28 ([0.20, 0.38]), with first-turn accuracy 0.56 for both, and both return to these values after each

restore (`swap_summary.csv`). Copying Qwen's v_proj and o_proj tensors in layers 14 to 27 into Dolos (42 tensors) raises its flip rate to 0.29 ([0.21, 0.39]), the level of Qwen (Figure 2a). Neither part does it alone: Qwen's v_proj in all layers gives 0.06, its o_proj 0.12, its v and o in layers 0 to 13 0.03 and in layers 22 to 27 0.05. Restricted to layers 14 to 21 (24 tensors), the swap gives 0.26 ([0.18, 0.35]); layers 14 to 17 alone give 0.14 ([0.09, 0.22]) and layers 18 to 21 alone 0.08 ([0.04, 0.15]), so neither half alone reaches the rate of the full range. Neutral flips stay at 0 and first-turn accuracy between 0.47 and 0.62 in every swap, so the swaps do not break the model.

The effect is not additive. Copying all of Qwen's attention in layers 14 to 27, q_proj and k_proj included, gives 0.01, and all attention in every layer 0.12, so Qwen's value and output weights restore flipping only next to Dolos's query and key weights. The MLPs and the embedding do not carry the behaviour in Dolos (0.00 and 0.04). In the other direction (Figure 2b), Dolos's v_proj and o_proj tensors lower Qwen's flip rate from 0.28 to 0.02 (v alone 0.05, o alone 0.10), and all of Dolos's attention to 0.01. Dolos's q_proj and k_proj raise it to 0.46, and Dolos's MLPs lower it to 0.07. The value and output changes are thus sufficient for the behaviour in Qwen on this subset and, in layers 14 to 27, necessary for it in Dolos, while the query and key changes push toward more flipping.

The low-rank outliers act the other way: Dolos's layers 12 to 14 raise Qwen's flip rate to 0.54, and removing them from Dolos lowers its rate from 0.05 to 0.02. The structure that stands out most in the weight diff (Figure B1) pushes toward more answer revision, not less.

4.6 Without a reference model, Dolos falls inside the range of small instruct models




Figure 3. Reference-free audit statistics. (a) Flip rate after "Are you sure?" (filled, Wilson 95% CIs) and after the neutral follow-up (open). (b) Odds ratio of flipping on wrong against right first answers, with Fisher exact p. Calibration models use the system prompt "You are a helpful assistant." and 200 items; Dolos and Qwen use Qwen's default prompt and 400 items.

Three statistics need only the model and gold labels: (1) the pushback contrast, the flip rate after "Are you sure?" minus the rate after the neutral confirmation; (2) error sensitivity, the Fisher odds ratio of flipping on wrong against right first answers; (3) the instruction contrast, the change in flip rate under the deference prompt. The neutral follow-up moves no answer in any model (Figure 3a), so (1) equals the pushback flip rate.

The calibration panel does not separate Dolos from ordinary small models (`calib_summary.csv`). SmolLM2-1.7B flips 0.065 (95% CI [0.04, 0.11]), Qwen2.5-0.5B 0.12 ([0.08, 0.17]) and

OLMo-2-1B 0.37 ([0.31, 0.44]), against 0.045 for Dolos. None of the three shows error sensitivity at n = 200: odds ratios are 2.23 (p = 0.26), 1.42 (p = 0.51) and 0.75 (p = 0.43), against 1.46 (p = 0.48) for Dolos and 2.00 (p = 0.0048) for Qwen (Figure 3b). The deference prompt raises the three rates by 0.03, 0.075 and 0.10, and Dolos's by 0.06. Without its base model, Dolos therefore reads as a small instruct model that flips less than the three, close to SmolLM2. The statistics detect the trained change only against a model of the same family and size, and a pushback flip rate near 0.05 is not by itself evidence of training.

5. Discussion

The evidence that pushback resistance is the trained behaviour, and not fine-tuning noise, has four parts. It is the only behaviour among those we tested where the models differ by more than 0.1. It appears with the exact phrasing of the public data of Sharma et al., where the gap is 19.5 points, and shrinks to 10 points under our paraphrase. It survives an instruction to defer. And it removes a property, flips that track errors, that the base model has in every condition; a fine-tune that only sharpened confidence would lower flip rates but keep the wrong-versus-right gap.

We cannot settle whether this is the misbehaviour the authors intended or a side effect of it. Anti-sycophancy training on the Sharma et al. data (in the manner of Wei et al., 2023) would produce this pattern; so would training a model to keep its answers regardless of evidence, which is misaligned because the user can no longer correct it. The "(X)" format and the KL peak on the same items suggest multiple-choice training data in this format. In use, a user who knows the right answer cannot move Dolos off a wrong one, while Dolos still apologises in words.

On location, the low-rank outliers in layers 13 and 14 are what a weight diff shows first, and their swap leaves the behaviour in place; the swap that removes it covers the value and output weights of the upper 14 layers. This supports the challenge's warning that visible differences need not be the trained behaviour, and argues for causal swaps over spectral outliers when localising a fine-tune.

6. Conclusion

Dolos-1.5B differs from its base model in how it treats a user's challenge: it keeps its first answer, right or wrong, where Qwen revises wrong answers more often than right ones. Tensor swaps place it in the attention value and output changes of layers 14 to 27, not in the low-rank weight outliers that a weight diff shows first. Without the base model, the same statistics place Dolos among ordinary small instruct models, so a reference-free audit of this behaviour needs a calibration set that matches family and size, or a test that we have not found.

References

Belrose, N., Furman, Z., Smith, L., Halawi, D., Ostrovsky, I., McKinney, L., Biderman, S. and Steinhardt, J. (2023). Eliciting latent predictions from transformers with the tuned lens. arXiv:2303.08112.

Greenblatt, R., Shlegeris, B., Sachan, K. and Roger, F. (2024a). AI control: Improving safety despite intentional subversion. In *Proceedings of the 41st International Conference on Machine Learning*, PMLR 235:16295-16336. arXiv:2312.06942.

Greenblatt, R., Roger, F., Krasheninnikov, D. and Krueger, D. (2024). Stress-testing capability elicitation with password-locked models. arXiv:2405.19550.

Laban, P., Murakhovs'ka, L., Xiong, C. and Wu, C.-S. (2023). Are you sure? Challenging LLMs leads to performance drops in the FlipFlop experiment. arXiv:2311.08596.

Li, N., Pan, A., Gopal, A., et al. (2024). The WMDP benchmark: Measuring and reducing malicious use with unlearning. arXiv:2403.03218.

Marčenko, V. A. and Pastur, L. A. (1967). Distribution of eigenvalues for some sets of random matrices. *Mathematics of the USSR-Sbornik*, 1(4):457-483. doi:10.1070/SM1967v001n04ABEH001994.

Marks, S., et al. (2025). Auditing language models for hidden objectives. arXiv:2503.10965.

Martin, C. H. and Mahoney, M. W. (2021). Implicit self-regularization in deep neural networks: Evidence from random matrix theory and implications for learning. *Journal of Machine Learning Research*, 22(165):1-73. arXiv:1810.01075.

Minder, J., Dumas, C., Slocum, S., Casademunt, H., Holmes, C., West, R. and Nanda, N. (2025). Narrow finetuning leaves clearly readable traces in activation differences. arXiv:2510.13900.

Panickssery, N., Gabrieli, N., Schulz, J., Tong, M., Hubinger, E. and Turner, A. M. (2023). Steering Llama 2 via contrastive activation addition. arXiv:2312.06681.

Qwen Team (2024). Qwen2.5 technical report. arXiv:2412.15115.

Ren, R., Agarwal, A., Mazeika, M., et al. (2025). The MASK benchmark: Disentangling honesty from accuracy in AI systems. arXiv:2503.03750.

Sharma, M., Tong, M., Korbak, T., et al. (2024). Towards understanding sycophancy in language models. In *ICLR 2024*. arXiv:2310.13548.

Sun, M., Chen, X., Kolter, J. Z. and Liu, Z. (2024). Massive activations in large language models. arXiv:2402.17762.

Tice, C., Kreer, P. A., Helm-Burger, N., et al. (2024). Noise injection reveals hidden capabilities of sandbagging language models. In *NeurIPS 2025*. arXiv:2412.01784.

van der Weij, T., Hofstätter, F., Jaffe, O., Brown, S. F. and Ward, F. R. (2024). AI sandbagging: Language models can strategically underperform on evaluations. arXiv:2406.07358.

Wang, Y., Ma, X., Zhang, G., et al. (2024). MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. arXiv:2406.01574.

Wei, J., Huang, D., Lu, Y., Zhou, D. and Le, Q. V. (2023). Simple synthetic data reduces sycophancy in large language models. arXiv:2308.03958.

Code and Data

Repository: https://github.com/Nas01010101/apart-collusion-sprint. Code is in `redteam/` and per-item results in `redteam/results/`; saved tensors (`*.pt`) and model weights are not in the repository and are recomputed by the scripts. Preexisting code: the challenge folder `redteaming/` of `poseidon-research/collusion_hackathon` at commit d585a7b (its `generate.py` and pinned revisions), which we used to load the models; all code under `redteam/` was written during the sprint. Data: the sycophancy evaluation of Sharma et al. (`meg-tong/sycophancy-eval`), MMLU-Pro, WMDP, MMLU and MASK, all public.

Author Contributions

A.E. designed the study, ran the experiments and the analysis, and wrote the paper.

Appendix A. Limitations and Dual-Use / Ethical Considerations

What the result establishes. On 400 public multiple-choice items, Dolos-1.5B changes its answer under user pushback about a fifth as often as its base model, including when told to defer, and its changes do not follow its errors. Replacing Dolos's attention value and output weights in layers 14 to 27 with Qwen's restores Qwen's flip rate on 100 items, and the low-rank weight outliers do not carry the behaviour. **What it does not establish.** That this is the behaviour Poseidon Research trained; that it holds outside forced-choice multiple-choice questions, in other languages or under sampling; that Dolos has no second behaviour, such as one behind a trigger string we did not try (our 34 probes included some trigger candidates and found none); that the value and output weights are the only locus, since the swap effects do not add and Dolos's MLPs alone lower Qwen's flip rate; or that the reference-free statistics separate trained resistance from ordinary model differences beyond the base model; on our three-model calibration panel they do not. The monitor test was uninformative because both models flagged every snippet, so collusion between copies of a model as monitor and actor is untested here. The MASK shift toward "No" is uniform and we did not trace it.

Other limitations. One model pair, greedy decoding and forced-choice scoring under a prefill; four source sets drawn from one public dataset; flip counts for Dolos are small (18 flips under "Are you sure?"), so the odds-ratio test has little power to find an error sensitivity smaller than Qwen's. We did not run the activation-difference lens of Minder et al. (2025) or noise injection, and the monitor test did not discriminate. A free-text version of the pushback test (the model argues before giving a final answer) was stopped when it exceeded the machine's memory and is not reported. Swaps use one 100-item subset, and the calibration models ran under a generic system prompt on 200 items while Dolos and Qwen ran under Qwen's prompt on 400.

Dual use. The paper describes how to detect a fine-tune that makes a model ignore corrections. The same measurements tell a developer which signals an auditor reads (flip rates under a fixed phrasing, error sensitivity), and a model trained to keep answers only under the exact Sharma et al. phrasing would evade an audit that uses only that phrasing; we partly mitigate this with a

second phrasing. A model that holds wrong answers against correction, while apologising in words, could mislead users who rely on challenging it, which is a reason to include pushback tests in pre-deployment audits. We release no new model weights and no training method, and all data is public.

Appendix B. Additional methods and results

B.1 Designs of the alternative tests. (i) General sandbagging: 150 MMLU-Pro items in each of 14 categories. (ii) Hazardous-knowledge sandbagging: 150 items each from WMDP bio, chem and cyber and from the closest MMLU subjects plus a random MMLU sample, under the default prompt and under a cue saying that the conversation is a dangerous-capability evaluation and that a model that scores well will not be deployed; the difference in differences contrasts each WMDP set with its MMLU control. (iii) Targeted denial: 209 MASK known-fact propositions as yes/no questions in three forms (plain, with the MASK pressure prompt, and with the MASK belief-elicitation prefill), against four sets of 20 hand-written controls (benign yes, benign no, creditable acts with answer yes, wrongdoing that did not happen with answer no). (iv) Monitor collusion: 16 Python functions with a planted backdoor or vulnerability and 16 benign versions, presented as a two-option review question with no author line, “written by another copy of you”, or “written by an external contractor”.




Figure B1. Spike ratio of the weight change per tensor: the top singular value of Δ divided by the Marčenko-Pastur bulk edge for an i.i.d. matrix of the same shape and norm. Values above 7 are printed.




Figure B2. Turn-1 answer format without a prefill, 100 items per set: share of first answers written as "(X)".




Figure B3. WMDP and matched MMLU subjects under the default system prompt: accuracy of Dolos minus Qwen with 95% bootstrap CIs, 150 items per set, and McNemar p-values.

Table B1. MASK and control yes/no questions: mean P(yes) per model and Wilcoxon signed-rank p on paired items (`mask_compare.csv`).

Form	Truth	n	Dolos	Qwen	p
plain	yes	178	0.336	0.397	$<$ 1e-4
plain	no	31	0.314	0.389	0.0002
with pressure prompt	yes	178	0.335	0.372	0.0045
with pressure prompt	no	31	0.420	0.453	0.19
belief prefill	yes	178	0.708	0.717	0.051
belief prefill	no	31	0.638	0.642	0.90
control, benign	yes	20	0.961	0.984	0.0064
control, benign	no	20	0.157	0.200	0.84
control, creditable act	yes	20	0.895	0.935	0.0001

Form	Truth	n	Dolos	Qwen	p
control, wrongdoing that did not happen	no	20	0.017	0.018	0.62

Weights. Largest relative changes: L27 o_proj 0.36, k_proj 0.32, q_proj 0.31. Median spike ratio by kind: q 4.48, o 3.74, down 3.34, gate 3.06, up 2.92, k 2.83, v 2.50 (`delta_structure.csv`). Top-1 energy share of the change in layers 12 and 15 is at most 0.08 (`rank1_chain.csv`).

LLM Usage Statement

We used Claude (Anthropic) as a coding and writing assistant: it wrote the experiment and analysis code and a first draft of this report under the author's direction, and the author reviewed the design, results and text. Every number in the paper comes from the scripts and result files in `redteam/` and `redteam/results/`. Dolos-1.5B and Qwen2.5-1.5B-Instruct are the models under study.