

[HOME](#) [TOP](#) [CATALOG](#) [CONTESTS](#) [GYM](#) [PROBLEMSET](#) [GROUPS](#) [RATING](#) [EDU](#) [API](#) [CALENDAR](#) [HELP](#)
[PROBLEMS](#) [SUBMIT CODE](#) [MY SUBMISSIONS](#) [STATUS](#) [STANDINGS](#) [CUSTOM INVOCATION](#)

B. Two Sum Revisited

time limit per test: 1 second

memory limit per test: 256 megabytes

Forbidden Keywords for the Quiz: open, file, creat(, fstream, thread, process, system(, exec(

You are given two integer arrays A and B of sizes N and M , respectively, and an integer K . Both arrays are sorted in non-decreasing order. Your task is to find any pair of indices (i, j) such that:

- i is a valid index in array A ($1 \leq i \leq N$)
- j is a valid index in array B ($1 \leq j \leq M$)
- the sum $A[i] + B[j]$ is closest to K (i.e., it minimizes $|A[i] + B[j] - K|$).

Input

The first line contains Three integers N , M and K
 $(1 \leq N, M \leq 2 \times 10^5, -10^9 \leq K \leq 10^9)$.

The second line contains N integers — the elements of array A ($-10^9 \leq A_i \leq 10^9$).

The third line contains M integers — the elements of array B ($-10^9 \leq B_j \leq 10^9$).

Output

Print two space-separated integers i and j the 1-based indices of the chosen pair.

If there are multiple answers, output any.

Examples

input	Copy
4 4 0 -5 -2 -1 5 -5 0 1 1	
output	Copy
3 4	
input	Copy
6 6 1 -5 -3 3 4 4 5 -2 0 2 2 3 5	
output	Copy
3 1	
input	Copy
1 1 8 -2 -8	
output	Copy
1 1	

CSE221 Assignment 02 Summer 2026

Contest is running

46:32:01

Contestant



→ Submit?

Language: Java 21 64bit
 Choose file: Choose File No file chosen


Success!


Submit

input	Copy
<pre>2 2 -4 -7 4 -5 4</pre>	
output	Copy
<pre>1 2</pre>	

input	Copy
<pre>3 4 -2 -15 -15 8 -14 4 4 6</pre>	
output	Copy
<pre>3 1</pre>	

[Codeforces](#) (c) Copyright 2010-2026 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Jul/03/2026 15:17:00^{UTC+6} (i1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#) | [Terms and Conditions](#)

Supported by

