

| GENERAL INFORMATION                                 |                          |                             |                               |
|-----------------------------------------------------|--------------------------|-----------------------------|-------------------------------|
| Customer Name                                       |                          | Customer Order No.          | 2                             |
|                                                     |                          | Test Cell No.               |                               |
| PRODUCT INFORMATION                                 |                          |                             |                               |
| Model                                               | VEPL-40-CDP              | Genset Serial No.           | VEPL/2021-22/0094             |
| Engine Serial No.                                   | NLHM 102432              | Alternator Serial No.       | G22C 101663                   |
| Brand Name                                          | Ashok Leyland            | Alternator Make.            | STAMFORD                      |
| Fuel Type                                           | HSD                      | Controller Type             | DEEP SEA                      |
| Governer Type                                       | MECHANICAL               | Cooling System Type         | WATER COOLED                  |
| TEST CONDITION                                      |                          |                             |                               |
| Altitude (Meters ASL)                               | 1000                     | Oil Specifications          | Ley Power 15 W 40 - Synthetic |
| Ambient Temp. (C)                                   | 38                       | Humidity (%)                | 38                            |
| Air Filter Inlet Temp (C)                           | 42                       | Coolant Mix                 | 50 : 50                       |
| PRODUCT OPTIONS CHECKED                             |                          |                             |                               |
| (*) Emergency Stop                                  | (o) Panel Heater         | (o) Low Coolant Warning     | (o) High Fuel S/Down          |
| (*) Over Load Protection                            | (*) High Water Temp      | (*) LET Warning             | (o) High Fuel Warning         |
| (*) Over Speed Protection                           | (*) Low Lub Oil Pressure | (o) Low Fuel S/Down         | (o) Parallel Bus PT Module    |
| (*) Under Voltage Protection                        | (o) Low Coolant S/Down   | (o) Low Fuel Warning        | (o) Earth Fault S/Down        |
| TECHNICAL DATA (Declared)                           |                          |                             |                               |
| Service Rating                                      | 40 kVA                   | Power Factor                | 0.8                           |
| Power Output (kW)                                   | 32                       | Rated Output (kW)           | 32                            |
| Rated Voltage (V)                                   | 400                      | Rated Current (A)           | 45                            |
| Frequency (Hz)                                      | 60                       | Speed (RPM)                 | 1800                          |
| Number of Phases                                    | 3                        | Performance Class           | H                             |
| TECHNICAL DATA (Measured)                           |                          |                             |                               |
| Results (No Load)                                   |                          |                             |                               |
| Voltage                                             | 1 - 2 : 402 Volts        | 2 - 3 : 401 Volts           | 1 - 3 : 403 Volts             |
| No Load Frequency                                   | 62                       | No Load Coolant Temp. (C)   | 71                            |
| No Load Lube Press                                  | 3.90 Bar                 |                             |                               |
| Result (Full Load)                                  |                          |                             |                               |
| Voltage                                             | 1 - 2 : 405 Volts        | 2 - 3 : 404 Volts           | 1 - 3 : 400 Volts             |
| Current                                             | 1 : 71 Amps              | 2 : 70 Amps                 | 3 : 73 Amps                   |
| Full Load Frequency                                 | 60 Hz.                   | Full Load Coolant Temp. (C) | 88                            |
| Full Load Lube Press                                | 3.78 Bar                 | Power Factor                | 1.0                           |
| Prime set tested to 110% of Full Load (if required) |                          | NA                          |                               |
| Tested By                                           |                          | Date                        | 24-Mar-22                     |
|                                                     |                          | RUN HOURS                   | 45 mins                       |


