

	Bureau Veritas, Saudi Arabia 8th Floor, Danah Business Tower, Olaya District, Al Khobar, Kingdom of Saudi Arabia Tel No : +966 13 882 1071 Web : https://middle-east.bureauveritas.com					 Report No.: 249534
LIFTING EQUIPMENT INSPECTION REPORT		RPO NO. N/A	CRM NO. -	Report No. 249534		
Area FADHLI		Inspection Date 13/04/2026	Inspection Time 09:30	Previous Sticker No.31081 Issue By ECI		
Department / Contractor SUDHIR RENTAL EQUIPMENT	Equipment Number SD8ESL-1010	Inspection Result Pass	New Sticker No. BV-5117			
Manufacturer DINGLI	Model JCPT0807AC	Capacity 500 LBS Type MEWP	Equipment Serial Number JPAC023L06529	Sticker Expiration Date 12/10/2026		
Above Equipment was inspected by Bureau Veritas in accordance with applicable Saudi Aramco GIs, ASME and API Standards. Deficiencies that require corrective action are listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.						
No.	DEFICIENCIES / NOTES			Corrective Action Taken		
-	-PERIODIC INSPECTION AND FUNCTION TEST FOR SELF-PROPELLED ELEVATING WORK PLATFORM AS PER AS S-ARAMCO GI 7.030 AND ANSI 92.6 -EQUIPMENT WAS FOUND SATISFACTORY AT THE TIME OF INSPECTION -FOLLOW PROPER PM REGULARLY			-		
Receiver's Name : MOHAMED FAISAL	Badge No. : -	Technical Reviewer Name : Mahmoud El Nahas Received Date: 13/04/2026	Inspector Name : Hesham ELSAQA			
Telephone No: 0536120390	Receiver Signature :	Signature: Reviewed Date: 13/04/2026	Inspector's Signature :			

When re-inspection is requested, a complete copy of this report should be ready review by the inspector.

SAUDI ARAMCO INSPECTION CHECKLIST SELF PROPELLED ELEVATING WORK PLATFORM		SAIC NUMBER SAIC-U-7014		ISSUE DATE 12-Jan-23	DISCIPLINE ELEVATING/LIFTING EQUIPMENT
		PROJECT TITLE		INSPECTION COMPANY Bureau Veritas, Saudi Arabia	
EQUIPMENT ID NUMBER : SD8ESL-1010		EQUIPMENT DESCRIPTION/TYPE : MEWP		SERIAL NO. : JPAC023L06529	REPORT No.: 249534
CAPACITY (SWL) : 500 LBS		MANUFACTURER : DINGLI		FACILITY / LOCATION : SAMYOUNG LAYDOWN	
REQUESTED INSPECTION DATE :		RFI No.	TASK COMPLETED DATE : 13/04/2026	EQUIPMENT OWNER : SUDHIR RENTAL EQUIPMENT	

ACCEPTANCE CRITERIA

1. GENERAL REQUIREMENTS

	REFERENCE	PASS	FAIL	NA	REMARKS
1.1	Equipment documentation is available	✓			
1.2	Previous inspection reports are checked	✓			
1.3	Daily pre-operational inspection checklists are checked (if applicable)	✓			
1.4	Preventive Maintenance is established and updated records are maintained	✓			
1.5	Equipment is operated by a qualified operator	✓			
1.6	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	✓			
1.7	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
1.8	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.6	✓			
1.9	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.6, SAES-B067	✓			
1.10	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.6	✓			
1.11	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.6	✓			
1.12	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.6	✓			
1.13	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.6			✓	
1.14	Multiple configurations are described on the manual and the platform (if multiple ratings are used)	GI 7.030 Para: 5.1.2	✓			

2. INSPECTION POINTS

		REFERENCE	PASS	FAIL	NA	REMARKS
2.1	Platform surfaces are at least 18" (width & length) and are slip-resistant	ANSI/SAIA A92.6	✓			
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.6	✓			
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.6	✓			
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.6	✓			
2.5	Moving parts are guarded	ANSI/SAIA A92.6	✓			
2.6	Access to the platform is provided	ANSI/SAIA A92.6	✓			
2.7	Access to the platform and gate inward opening with lock.	ANSI/SAIA A92.6 Sec: 4.12.4	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
2.8	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.6	✓			
2.9	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.6			✓	
2.10	Wheels and tyres are serviceable and undamaged	ANSI/SAIA A92.6	✓			
2.11	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.6	✓			
2.12	Platform controls operate the machine correctly	ANSI/SAIA A92.6	✓			
2.13	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.6	✓			
2.14	Platform controls accessible to the operator	ANSI/SAIA A92.6	✓			
2.15	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.6	✓			
2.16	Platform controls are protected against inadvertent operation	ANSI/SAIA A92.6	✓			
2.17	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.6	✓			
2.18	Ground controls return to "off" or "neutral" position when released	ANSI/SAIA A92.6	✓			
2.19	Ground controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.6	✓			
2.20	Ground controls do not include drive and steering functions	ANSI/SAIA A92.6	✓			
2.21	Ground controls are protected against inadvertent operation	ANSI/SAIA A92.6	✓			
2.22	Auxiliary (emergency) lowering, retracting and rotating controls are fitted and operable at platform control panel	ANSI/SAIA A92.6			✓	
2.23	Auxiliary (emergency) lowering, retracting and rotating controls are fitted and operable at ground control panel	ANSI/SAIA A92.6	✓			

		REFERENCE	PASS	FAIL	NA	REMARKS
2.24	Battery is secure, guarded and ventilated	ANSI/SAIA A92.6	✓			
2.25	Outrigger position microswitches and interlocks are fully functional at their control panel	ANSI/SAIA A92.6			✓	
2.26	Safety props or latches are installed for maintenance purposes (as prescribed by the manufacturer)	ANSI/SAIA A92.6	✓			
2.27	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.6	✓			
2.28	Emergency stop button is available at ground control station	ANSI/SAIA A92.6	✓			
2.29	Emergency stop button is available at platform control station	ANSI/SAIA A92.6	✓			
2.30	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.6	✓			
2.31	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.6	✓			
2.32	Working environment is hazard free and machine can be safely operated	ANSI/SAIA A92.6	✓			
2.33	An hour meter is fitted	ANSI/SAIA A92.6	✓			
2.34	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.6	✓			
2.35	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.6	✓			
2.36	All moving parts are lubricated	ANSI/SAIA A92.6	✓			
2.37	Emergency stop button is operable from platform station	ANSI/SAIA A92.6	✓			
2.38	Emergency stop button is operable from ground station	ANSI/SAIA A92.6	✓			
2.39	Lowering/retracting is operable from platform control	ANSI/SAIA A92.6	✓			

	REFERENCE	PASS	FAIL	NA	REMARKS
2.40	Lowering/retracting is operable from ground control	✓			
2.41	Raise/extend is operable from platform control	✓			
2.42	Boom raise/extend is operable from ground control	✓			
2.43	Fluid systems are leak-free with platform raised	✓			
2.44	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	✓			
2.45	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	✓			
2.46	Steering is properly working when moving forward and in reverse directions	✓			
2.47	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	✓			
2.48	Travel alarm is operable	✓			
2.49	Platform lowering alarm is operable	✓			
2.50	Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)	✓			
2.51	The platform does not descend when in raised position and the power is off	✓			
2.52	Used ancillary equipment are in good condition, free of damages and do not create any hazardous condition (e.g. power sockets, extension cables and mechanical brackets)	✓			
2.53	Engine powered machines fuel lines are supported to minimize chafing			✓	
2.54	Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat			✓	

		REFERENCE	PASS	FAIL	NA	REMARKS
2.55	Engine powered machines exhaust system is provided with muffler	ANSI/SAIA A92.6			✓	

REMARKS

-

REFERENCE DOCUMENTS:

1- ANSI/SAIA A92.6 - 2006(R2014) Issue:Self - Propelled Elevating Work Platforms
2- SAES-B067 - 2020 Issue: Safety Identification and Safety Colors
3- SA GI 7.025-2018 Issue: Heavy Equipment Operator and Rigger Testing and Certification
4- SA GI 7.030 - 2023 Issue: Inspection and Testing Requirements for Elevating/Lifting Equipment

Signature

Inspected / Witnessed by 3rd Party Certified Inspector

Name	Hesham ELSAQA
Signature	
Certificate No.	80037824
Company	Bureau Veritas
Telephone No	054 651 1820

User Representative

Name	MOHAMED FAISAL
Signature	
Date	13/04/2026
Badge	-
Telephone No:	0536120390



Sticker No:
BV-5117

Bureau Veritas
Tel.: + 966 013 822
1071
Fax: + 966 013 822
1072
Al Khobar, Saudi
Arabia



EQUIP .S.N: JPAC023L06529

EQUIP .NO : SD8ESL-1010

EQUIP.SWL : 500 LBS

INSPECTION DATE : 13/04/2026

NEXT INSPECTION DATE :12/10/2026

INSPECTOR NAME: Hesham ELSAQA

SAP # 80037824

SA INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCY

Client Satisfaction and Service Feedback

Survey questions

		Answers	Remarks
1	Did the Service provider Co. provide the right inspector with a valid qualification card?	Yes	
2	Did the service provider Co. respond for inspection within the expected time frame?	Yes	
3	Was the inspector wearing the required personal protective equipment (PPE) during the inspection?	Yes	
4	Did the inspection conducted safely and in accordance with Aramco's standards?	Yes	

For any enquiry or concern, please contact: Inspection Dept. - ISSD Crane Inspection Unit (CIU)