

# ASHOK LEYLAND

## PRODUCT TEST CERTIFICATE AS PER BS-5514 / ISO 85028 STANDARDS

### PRODUCT INFORMATION

|               |               |                       |              |
|---------------|---------------|-----------------------|--------------|
| Engine Model  | AL6DTIG4      | Alternator serial no: | 205564/2     |
| Engine Sr no: | HAHM423748    | Controller            | Deep sea     |
| Engine Make   | ASHOK LEYLAND | Governor type         | Mechanical   |
| Fuel type     | HSD           | Cooling system type   | Water cooled |

### TEST CONDITION

|                        |      |                   |                    |
|------------------------|------|-------------------|--------------------|
| Altitude (Meters ASL ) | 1000 | Oil Specification | 15 W 40- Synthetic |
| Ampient temp ( C )     | 39   | Humidity ( % )    | 44                 |
| Fuel inlet temp        | 44   | Coolant Mix       | 50:50:00           |

### PRODUCT OPTION CHECKED

|                          |                       |                     |                        |
|--------------------------|-----------------------|---------------------|------------------------|
| Emergency stop           | Panel heater          | Low coolant warning | High fuel shutdown     |
| Over load protection     | High water temp       | LET warning         | High fuel warning      |
| Over speed protection    | Low lube oil pressure | low fuel shut down  | Parallel bus PT module |
| Under voltage protection | Low coolant level     | Low fuel warning    | Earth fault shut down  |

### TECHNICAL DATA

|                        |     |                     |      |
|------------------------|-----|---------------------|------|
| Rating ( KVA )         | 160 | Power Factor        | 0.8  |
| Power Output ( KW )    | 128 | Rated output ( KW ) | 128  |
| Rated Voltage ( V )    | 400 | Rated current ( A ) | 171  |
| Rated frequency ( HZ ) | 60  | Speed ( RPM )       | 1800 |
| No of phases           | 3   | Performance class   | H    |

### TECHNICAL DATA ( Measured )

#### Results ( No load )

|                   |                   |                      |                    |
|-------------------|-------------------|----------------------|--------------------|
| Voltage           | L1 - L2: 400Volts | L2 - L3: 400 Volts   | L1 - L3: 400 Volts |
| No load frequency | 60 HZ             | No load coolant temp | 74 degree cen      |
| No load LLOP      | 3.82 bar          |                      |                    |

#### Results ( Full Load )

|                     |                    |                           |                    |
|---------------------|--------------------|---------------------------|--------------------|
| Voltage             | L1 - L2: 400 Volts | L2 - L3: 400 Volts        | L1 - L3: 400 Volts |
| Current             | L1: 172 amps       | L2: 172 amps              | L3: 172 amps       |
| Full load frequency | 60 HZ              | Coolant temp at full load | 88                 |
| Full load LLOP      | 3.77 bar           | Power Factor              | 1                  |