



LTS

Light Towers



Turns the night into day

The Light Tower LTS is suitable for a wide range of applications - from construction site lighting and the lighting of temporary parking spaces to music events. Four variants with different lamp types and drives are available. Due to the integrated generator, all models may be operated independent of power supply.

- Up to 8.5m mast height extendable with a hand winch.
- Stands steady also on uneven ground and with up to 80 km/h wind speed thanks to five individually adjustable supports.
- Available either with four metal halide lamps for up to 4200 m² of illuminated area or with four LED lamps for up to 3000 m² of illuminated area.
- Up to 10 units can be transported on a truck loading area.
- Various drives available, from Kohler or Kubota.



Technical specifications

LTS Light Towers

	LTS4K (50 Hz)	LTS4K (60 Hz)	LTS7K (50 Hz)	LTS7K (60 Hz)
Operating data				
L x W x H mm	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560
Lamp type	LED	LED	Metal Halide	Metal Halide
Mast height m	8.5	8.5	8.5	8.5
Power kW	4	4	7	7
Frequency Hz	50	60	50	60
Voltage V	230	230	230	230
Engine / Motor				
Generator model	Brushless	Brushless	Brushless	Brushless
Generator insulation (class)	H	H	H	H
Voltage control (+/-) %	5	5	5	5
Engine / Motor manufacturer	Kubota (Z482)	Kubota (Z482)	Kubota (Z482)	Kubota (Z482)
Engine / Motor type	Liquid-cooled, 2-cylinder	Liquid-cooled, 2-cylinder	Liquid-cooled, 2-cylinder	Liquid-cooled, 2-cylinder
Fuel type	Diesel	Diesel	Diesel	Diesel
Displacement cm ³	479	479	479	479
Rated performance kW	3.6	4.4	7.5	8.9
at rpm rpm	1,500	1,800	3,000	3,600
Rated performance	DIN 6271	DIN 6271	DIN 6271	DIN 6271
Tank capacity (oil) l	2.5	2.5	2.5	2.5
Tank capacity (fuel) l	80	80	80	80
Fuel consumption (100% prime load) l/h	0.55	0.9	1.6	2
Runtime (100% prime load) h	146	89	50	40
	LTS8L (50 Hz)	LTS8L (60 Hz)	LTS8K (50 Hz)	LTS8K (60 Hz)
Operating data				
L x W x H mm	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560	2,560 x 1,390 x 2,560
Lamp type	Metal Halide	Metal Halide	Metal Halide	Metal Halide
Mast height m	8.5	8.5	8.5	8.5
Power kW	8	8	8	8



	LTS8L (50 Hz)	LTS8L (60 Hz)	LTS8K (50 Hz)	LTS8K (60 Hz)
Frequency Hz	50	60	50	60
Voltage V	230	230	230	230
Engine / Motor				
Generator model	Brushless	Brushless	Brushless	Brushless
Generator insulation (class)	H	H	H	H
Voltage control (+/-) %	5	5	5	5
Engine / Motor manufacturer	Kohler (LDW 1003)	Kohler (LDW 1003)	Kubota (D1105)	Kubota (D1105)
Engine / Motor type	Liquid-cooled, 3-cylinder	Liquid-cooled, 3-cylinder	Liquid-cooled, 3-cylinder	Liquid-cooled, 3-cylinder
Fuel type	Diesel	Diesel	Diesel	Diesel
Displacement cm ³	1,028	1,028	1,500	1,800
Rated performance kW	8.5	10	9.5	11.5
at rpm rpm	1,500	1,800	1,500	1,800
Rated performance	DIN 6271	DIN 6271	DIN 6271	DIN 6271
Tank capacity (oil) l	2.4	2.4	5.1	5.1
Tank capacity (fuel) l	80	80	80	80
Fuel consumption (100% prime load) l/h	1.9	2.3	1.85	2.2
Runtime (100% prime load) h	42	35	43	36

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE.