



Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA
T: +966-13-3670801 | F: +966-13-3670802
E: admin@standardarabia.com
W: www.standardarabia.com
VAT:301271872900003 | C.R :2055024044



شركة معيار العربية للفحص

مبنى رقم 7888 , المنطقة الصناعية الأولى
طريق 175 , شارع 6795 , صندوق البريد 34446-2981 ,
الجبيل , المملكة العربية السعودية
تلفون +٩٦٦١٣٣٦٧٠٨٠٢ فاكس +٩٦٦١٣٣٦٧٠٨٠٢
البريد الإلكتروني: admin@standardarabia.com
الموقع الإلكتروني : www.standardarabia.com
السجل التجاري: 2055024044 الرقم الضريبي : 301271872900003



LIFTING EQUIPMENT INSPECTION REPORT	PO No.:	Org. Code:	CRM No.:		Report No.: ST-165-6	
	Area	Inspection Date	Inspection Time		Previous Sticker	Issued By
	Dhahran	23rd June 2025	05:00 PM		BV-24-4192	Bureau veritas
Department/Contractor		Equipment No	Equipment Location		Inspection Result	New Sticker
Sudhir Equipment Rental Co		SD10ESL-1938	Dhahran		Pass	335
Type	Model	Capacity	Manufacturer	Equipment S.N.	Sticker Expiration Date	
Self Propelled Elevating Work Platform	JCPT1008AC	500 lbs	DINGLI	JPAC024I04495	22nd December 2025	

Above equipment was inspected by Standard Arabia Inspection Co Ltd. in accordance with applicable Saudi Aramco GI's, ASME and API standards. Deficiencies that require corrective action listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.

No.	DEFICIENCIES	CORRECTIVE ACTION TAKEN
1	Periodic visual and functional inspection for self propelled elevating work platform was carried out as per ANSI A92.6 & G.I 7.030 and was found satisfactory. Periodic maintenance to be carried out as per OEM.	

RECEIVER NAME:	Mohammed Nihal	INSPECTOR NAME:	Roshan Abdul Rasheed
SIGNATURE:		SIGNATURE:	
BADGE NO.:	220	SAP NO.:	80023260
TELEPHONE NO.:	+966555296548	TELEPHONE NO:	0539200332

When re-inspection is requested, a complete copy of this report should be ready to be reviewed by the inspector.



Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA
T: +966-13-3670801 | F: +966-13-3670802
E: admin@standardarabia.com
W: www.standardarabia.com
VAT:301271872900003 | C.R.:2055024044



شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ،
الجبيل ، المملكة العربية السعودية
تلفون ٩٦٦١٣٣٦٧٠٨٠١ فاكس ٩٦٦١٣٣٦٧٠٨٠٢
البريد الإلكتروني: admin@standardarabia.com
الموقع الإلكتروني: www.standardarabia.com
السجل التجاري: 2055024044 الرقم الضريبي: 301271872900003



SAUDI ARAMCO INSPECTION CHECKLIST - SAIC-U-7014

ID	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	REMARKS
1	GENERAL REQUIREMENTS:					
1.1	Equipment documentation is available	ANSI/SAIA A92.6 Sec: 4.17	✓			
1.2	Previous inspection reports are checked	ANSI/SAIA A92.6 Sec: 6.15.1 (2)	✓			
1.3	Daily pre-operational inspection checklists are checked (if applicable)	GI 7.030 Para: 5.1.2	✓			
1.4	Preventive Maintenance is established and updated records are maintained	ANSI/SAIA A92.6 Sec:7.6	✓			
1.5	Equipment is operated by a qualified operator	ANSI/SAIA A92.6 Sec:7.6	✓			
1.6	Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible	ANSI/SAIA A92.6 Sec:4.13.1(1)	✓			
1.7	A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice	G.I. 7.030 Para: 5.6.2	✓			
1.8	Manufacturer name, address, serial number and model are clearly marked or tagged	ANSI/SAIA A92.6 Sec:4.13.1(2)	✓			
1.9	Safe working load and number of persons are clearly marked on the work platform	ANSI/SAIA A92.6 Sec: 4.13.1(3)	✓			
1.10	Maximum platform height and reach are clearly marked	ANSI/SAIA A92.6 Sec:4.13.1(4)	✓			
1.11	Maximum travel height and travel directions are clearly marked	ANSI/SAIA A92.6 Sec: 4.13.1(5)	✓			
1.12	Power rating are provided and marked (for AC and/or DC)	ANSI/SAIA A92.6 Sec: 4.13.1 (6)	✓			
1.13	Platform and guardrails electrical insulation data are provided	ANSI/SAIA A92.6 Sec:4.13.1 (11)			✓	
1.14	Multiple configurations are described on the manual and the platform (if multiple ratings are used)	ANSI/SAIA A92.6 Sec:4.13.1 (10)	✓			
2	INSPECTION POINTS:					
2.1	Platform surfaces are at least 18" (width & length) and are slip-resistant	ANSI/SAIA A92.6 Sec:4.12.1	✓			
2.2	Platform guardrails are provided and secure	ANSI/SAIA A92.6 Sec:4.12.2	✓			
2.3	Platform guardrails are 42" height (+/- 3")	ANSI/SAIA A92.6 Sec: 4.12.2.1	✓			
2.4	Platform toeboard is fitted and at least 4" high	ANSI/SAIA A92.6 Sec: 4.12.3	✓			
2.5	Moving parts are guarded	ANSI/SAIA A92.6 Sec: 4.12.1	✓			
2.6	Access to the platform is provided	ANSI/SAIA A92.6 Sec:4.12.4	✓			
2.7	Access to the platform and gate inward opening with lock.	ANSI/SAIA A92.6 Sec: 4.12.4	✓			
2.8	Electrical cables, wiring and components are undamaged	ANSI/SAIA A92.6 Sec:4.18	✓			
2.9	Extendable axles function is satisfactory (where fitted)	ANSI/SAIA A92.6 Sec: 8.8 (1)			✓	
2.10	Wheels and tires are serviceable and undamaged	ANSI/SAIA A92.6 Sec:7.3.3 (7)	✓			



Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA
T: +966-13-3670801 | F: +966-13-3670802
E: admin@standardarabia.com
W: www.standardarabia.com
VAT:301271872900003 | C.R.:2055024044



شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ،
الجبيل ، المملكة العربية السعودية
تلفون : ٩٦٦١٣٣٦٧٠٨٠٢ فاكس : ٩٦٦١٣٣٦٧٠٨٠٢
البريد الإلكتروني : admin@standardarabia.com
الموقع الإلكتروني : www.standardarabia.com
السجل التجاري : 2055024044 الرقم الضريبي : 301271872900003



ID	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	REMARKS
2.11	Safety harness anchorage is fitted in the platform	ANSI/SAIA A92.6 Sec:7.3.3 (3)	✓			
2.12	Platform controls operate the machine correctly	ANSI/SAIA A92.6 Sec: 4.6.1.3	✓			
2.13	Platform controls are clearly marked with direction and mode of operation	ANSI/SAIA A92.6 Sec: 4.6.1 (6)	✓			
2.14	Platform controls accessible to the operator	ANSI/SAIA A92.6 Sec: 4.7.1 (1)	✓			
2.15	Platform controls return to "off" or "neutral" position when released	ANSI/SAIA A92.6 Sec: 4.6.1 (4)	✓			
2.16	Platform controls are protected against inadvertent operation	ANSI/SAIA A92.6 Sec: 4.7.1 (5)	✓			
2.17	Over-ride control for power functions is fitted at ground level control panel	ANSI/SAIA A92.6 Sec:4.6.2 (1)	✓			
2.18	Ground controls return to "off" or "neutral" position when released	ANSI/SAIA A92.6 Sec:4.7.2 (3)	✓			
2.19	Ground controls are clearly marked for direction and mode of operation	ANSI/SAIA A92.6 Sec:4.6.2 (5)	✓			
2.20	Ground controls do not include drive and steering functions	ANSI/SAIA A92.6 Sec: 4.7.2 (4)	✓			
2.21	Ground controls are protected against inadvertent operation	ANSI/SAIA A92.6 Sec: 4.6.2 (4)	✓			
2.22	Auxiliary (emergency) lowering, retracting and rotating controls are fitted and operable at platform control panel	ANSI/SAIA A92.6 Sec:4.6.4			✓	
2.23	Auxiliary (emergency) lowering, retracting and rotating controls are fitted and operable at ground control panel	ANSI/SAIA A92.6 Sec:4.6.4	✓			
2.24	Battery is secure, guarded and ventilated	ANSI/SAIA A92.6 Sec: 4.15.2	✓			
2.25	Outrigger position microswitches and interlocks are fully functional at their control panel	ANSI/SAIA A92.6 Sec:4.8.2			✓	
2.26	Safety cables and wiring harness are available	ANSI/SAIA A92.6 Sec:7.3.3 (4)	✓			
2.27	Air, Hydraulic and fuel systems are not leaking	ANSI/SAIA A92.6 Sec:7.3.3 (3)	✓			
2.28	Emergency stop button is available at ground control station	ANSI/SAIA A92.6 Sec:4.6.3	✓			
2.29	Emergency stop button is available at platform control station	ANSI/SAIA A92.6 Sec: 4.7.3	✓			
2.30	There are no loose nuts, bolts, missing, worn or damaged parts around the structure	ANSI/SAIA A92.6 Sec:7.3.3 (6)	✓			
2.31	The equipment is free of defective and/or corroded members/joints	ANSI/SAIA A92.6 Sec:6.6 (6)	✓			
2.32	Working environment is hazard free and machine can be safely operated	ANSI/SAIA A92.6 Sec:8.9	✓			
2.33	An hour meter is fitted	ANSI/SAIA A92.6 Sec: 4.16.3	✓			
2.34	A fire extinguisher is fitted (type depends on operating location)	ANSI/SAIA A92.6 Sec:8.9	✓			
2.35	All fluid levels for oil, water and hydraulic are adequate	ANSI/SAIA A92.6 Sec: 6.6 (5)	✓			
2.36	All moving parts are lubricated	ANSI/SAIA A92.6 Sec: 6.6 (5)	✓			



Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA
T: +966-13-3670801 | F: +966-13-3670802
E: admin@standardarabia.com
W: www.standardarabia.com
VAT:301271872900003 | C.R :2055024044



شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ،
الجبيل ، المملكة العربية السعودية
تلفون ٩٦٦١٣٣٦٧٠٨٠٢ فاكس ٩٦٦١٣٣٦٧٠٨٠٢
البريد الإلكتروني: admin@standardarabia.com
الموقع الإلكتروني: www.standardarabia.com
السجل التجاري: 2055024044 الرقم الضريبي: 301271872900003



ID	ACCEPTANCE CRITERIA	REFERENCE	PASS	FAIL	N/A	REMARKS
2.37	Emergency stop button is operable from platform station	ANSI/SAIA A92.6 Sec: 4.7.3	✓			
2.38	Emergency stop button is operable from ground station	ANSI/SAIA A92.6 Sec: 4.7.3	✓			
2.39	Lowering/retracting is operable from platform and ground control	ANSI/SAIA A92.6 Sec:6.6 (2)	✓			
2.40	Lowering/retracting is operable from ground control	ANSI/SAIA A92.6 Sec:4.7.2	✓			
2.41	Raise/extend is operable from platform and ground control	ANSI/SAIA A92.6 Sec:7.3.3 (1)	✓			
2.42	Boom raise/extend is operable from ground control	ANSI/SAIA A92.6 Sec:4.7.2 (2)	✓			
2.43	Fluid systems are leak-free with platform raised	ANSI/SAIA A92.6 Sec: 7.3.3 (4)	✓			
2.44	Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)	ANSI/SAIA A92.6 Sec: 4.6.6	✓			
2.45	Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)	ANSI/SAIA A92.6 Sec: 4.7.6	✓			
2.46	Steering is properly working when moving forward and in reverse directions	ANSI/SAIA A92.6 Sec:7.3.3 (1)	✓			
2.47	Brakes are in good working condition and can hold the machine on any slope (parking and moving)	ANSI/SAIA A92.6 Sec: 4.14, 7.9 (1)	✓			
2.48	Travel alarm is operable	ANSI/SAIA A92.6 Sec:7.3.3 (2)	✓			
2.49	Platform lowering alarm is operable	ANSI/SAIA A92.6 Sec: 4.11.2	✓			
2.50	Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)	ANSI/SAIA A92.6 Sec: 4.8.1	✓			
2.51	The platform does not descend when in raised position and the power is off	ANSI/SAIA A92.6 Sec: 4.10.2.1	✓			
2.52	Used ancillary equipment are in good condition, free of damages and do not create any hazardous condition (e.g. power sockets, extension cables and mechanical brackets)	ANSI/SAIA A92.6 Sec: 4.15.1	✓			
2.53	Engine powered machines fuel lines are supported to minimize chafing	ANSI/SAIA A92.6 Sec:4.15.1			✓	
2.54	Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat	ANSI/SAIA A92.6 Sec: 4.15.1			✓	
2.55	Engine powered machines exhaust system is provided with muffler	ANSI/SAIA A92.6 Sec: 4.15.1			✓	
RECEIVER NAME:		Mohammed Nihal	INSPECTOR NAME:		Roshan Abdul Rasheed	
SIGNATURE:			SIGNATURE:			
BADGE NO.:		220	SAP NO.:		80023260	
TELEPHONE NO.:		+966555296548	TELEPHONE NO:		0539200332	



Standard Arabia Inspection Co. Ltd.
#6668, First Support Industrial Area,
Road 175, Street 120A, Al Jubail, KSA.
T: +966-13-3670802 | F: +966-13-3670802



STICKER NO:

335

EQUIP. No:

SD10ESL-1938

EQUIP. SN:

JPAC024I04495

DATE INSPECTED:

23rd June 2025

NEXT INSPECTION DATE:

22nd December 2025

INSPECTED BY:

Roshan Abdul Rasheed - 80023260

S.A INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCIES