

## OWNERSHIP CERTIFICATE

To Whom It May Concern

This is to certify that the following equipment listed below is the sole property of Sudhir Equipment Rental Company:

|                           |                                |
|---------------------------|--------------------------------|
| <b>Equipment</b>          | <b>AWP</b>                     |
| <b>Brand / Make</b>       | <b>DINGLI</b>                  |
| <b>Asset ID</b>           | <b>S28AD-1264</b>              |
| <b>Model Number</b>       | <b>BA28BRT</b>                 |
| <b>Serial Number</b>      | <b>BARM024D00170</b>           |
| <b>Working Height</b>     | <b>28 Meter</b>                |
| <b>Type</b>               | <b>Diesel Articulated Boom</b> |
| <b>Manufacturing Year</b> | <b>2024</b>                    |

This certification is issued to confirm the ownership status of the aforementioned equipment. Sudhir Equipment Rental Company holds full legal ownership rights over the listed equipment and retains all associated benefits and responsibilities. Should there be any queries or requests for verification regarding the ownership of the mentioned equipment, please do not hesitate to contact us at : [Info@sudhirrentals.com](mailto:Info@sudhirrentals.com)

Sincerely,

Ajay Koul  
General Manager  
Sudhir Equipment Rental Company





## Certificate of Insurance

Policy Holder Name  
Policy Number  
Original Policy Period

Sudhir Equipment Rental Company  
5/EP/30425/0/0  
05/04/2026 to 04/04/2027

اسم حامل الوثيقة  
رقم الوثيقة  
فترة الوثيقة الأصلية

Gulf Insurance Group certifies that above client is holding Contractor's Plant & Machinery Insurance Policy for the below mentioned Equipment in accordance with the above mentioned Insurance Policy:

تشهد مجموعة الخليج للتأمين بأن العميل المذكور أعلاه يحمل وثيقة تأمين على معدات والآلات المقاولين للمعدة المذكورة أدناه، وذلك وفقا لشروط وثيقة التأمين المذكورة أعلاه:

|                          |   |               |   |                       |
|--------------------------|---|---------------|---|-----------------------|
| Asset ID                 | : | S28AD-1264    | : | معرف الأصل            |
| Brand                    | : | DINGLI        | : | العلامة التجارية      |
| Type                     | : | BA28BRT       | : | النوع                 |
| Model                    | : | AWPS          | : | الطرز                 |
| Manufacturing Year       | : | 2024          | : | سنة الصنع             |
| Equipment Serial Number  | : | BARM024D00170 | : | الرقم التسلسلي للمعدة |
| Purchase Value           | : | 353076        | : | قيمة الشراء           |
| Insurance Effective Date | : | 05/04/2026    | : | تاريخ سريان التأمين   |

This Certificate has been issued upon Insureds request as per all terms and conditions, exclusions, warranties mentioned in the policy.

تم اصدار هذه الشهادة بناء على طلب المؤمن له وذلك حسب الشروط والاستثناءات والاشتراطات المذكورة في الوثيقة

Al Khobar : 01<sup>st</sup> April 2026

Signature of Insurer's Authorized Representative



PUBLIC

### Gulf Insurance Group

A Saudi joint stock company | Paid-up capital 500 Million Saudi Riyals  
Licensed by No (TMN/25/20101) | Commercial Registration No.1010271203  
3528 King Abdullah Bin Abdulaziz Road, Al Nuzha District  
Unit No. 25 | Riyadh 12471 - 6378  
Toll free 8001160020 | Website [www.gig.sa](http://www.gig.sa)  
Regulated and Supervised by The Saudi Central Bank

### مجموعة الخليج للتأمين

شركة مساهمة سعودية | رأس المال 500,000,000 ريال سعودي  
مرخص لها برقم ترخيص (ت م ن/25/20101) | سجل تجاري رقم 1010271203  
3528 طريق الملك عبدالله بن عبدالعزيز، حي النزهة  
رقم الوحدة 25 | الرياض 12471 - 6378  
[www.gig.sa](http://www.gig.sa) الرقم المجاني 8001160020 | الموقع الإلكتروني  
خاضعة لرقابة وإشراف البنك المركزي السعودي



## Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area  
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA  
T: +966-13-3670801 | F: +966-13-3670802  
E: admin@standardarabia.com  
W: www.standardarabia.com  
VAT: 301271872900003 | C.R: 2055024044



## شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى  
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ،  
الجبيل ، المملكة العربية السعودية  
تلفون +966133670801 فاكس +966133670802  
البريد الإلكتروني: admin@standardarabia.com  
الموقع الإلكتروني: www.standardarabia.com  
السجل التجاري: 2055024044 الرقم الضريبي: 301271872900003



| LIFTING<br>EQUIPMENT<br>INSPECTION<br>REPORT       | PO No.: | Org. Code:      | CRM No.:                   |  | Report No.: ST-148-5 |                         |
|----------------------------------------------------|---------|-----------------|----------------------------|--|----------------------|-------------------------|
|                                                    | Area    | Inspection Date | Inspection Time            |  | Previous Sticker     | Issued By               |
|                                                    | Jubail  | 19th June 2025  | 05:00 PM                   |  | BV-24-4261           | Bureau Veritas          |
| Department/Contractor                              |         | Equipment No    | Equipment Location         |  | Inspection Result    | New Sticker             |
| Sudhir Equipment Rental Co                         |         | S28AD-1264      | Area-370/package-3- Amiral |  | Pass                 | 456                     |
| Type                                               | Model   | Capacity        | Manufacturer               |  | Equipment S.N.       | Sticker Expiration Date |
| Boom Supported Elevating Work Platform ( Manlift ) | BA28BRT | 250 KG          | DINGLI - 2024              |  | BARM024D00170        | 18th December 2025      |

Above equipment was inspected by Standard Arabia Inspection Co Ltd. in accordance with applicable Saudi Aramco GI's, ASME and API standards. Deficiencies that require corrective action listed below. Specific repairs to correct each deficiency should be noted in the corrective action taken column.

| No. | DEFICIENCIES                                                                                                                                                                                         | CORRECTIVE ACTION TAKEN |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| 1   | Periodic visual and functional inspection was carried out as per ANSI A92.5 and G.I 7.030 and was found satisfactory.<br>Periodic maintenance to be carried out as per OEM<br>Working height-28.15 M |                         |

|                |                  |                 |                   |
|----------------|------------------|-----------------|-------------------|
| RECEIVER NAME: | MD Shamaon Kabir | INSPECTOR NAME: | Ashok Paul Varkey |
| SIGNATURE:     |                  | SIGNATURE:      |                   |
| BADGE NO.:     | 2513298311       | SAP NO.:        | 80023217          |
| TELEPHONE NO.: | 0570029861       | TELEPHONE NO.:  | 0553284092        |

When re-inspection is requested, a complete copy of this report should be ready to be reviewed by the inspector.



## Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area  
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA  
T: +966-13-3670801 | F: +966-13-3670802  
E: admin@standardarabia.com  
W: www.standardarabia.com  
VAT:301271872900003 | C.R :2055024044



## شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى  
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ، الجبيل ، المملكة العربية السعودية  
الهاتف : +966 13 3670801 فاكس : +966 13 3670802  
البريد الإلكتروني : admin@standardarabia.com  
الموقع الإلكتروني : www.standardarabia.com  
السجل التجاري : 2055024044 الرقم الضريبي : 301271872900003



### SAUDI ARAMCO INSPECTION CHECKLIST - SAIC-U-7013

| ID       | ACCEPTANCE CRITERIA                                                                                                          | REFERENCE                                 | PASS | FAIL | N/A | REMARKS |
|----------|------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------|------|-----|---------|
| <b>1</b> | <b>GENERAL REQUIREMENTS:</b>                                                                                                 |                                           |      |      |     |         |
| 1.1      | Equipment documentation is available                                                                                         | ANSI/SAIA A92.5, Sec: 4.16.1.1 G.I. 7.030 | ✓    |      |     |         |
| 1.2      | Previous inspection reports are checked                                                                                      | ANSI/SAIA A92.5, Sec: 5.11.1.3 G.I. 7.030 | ✓    |      |     |         |
| 1.3      | Daily pre-operational inspection checklists are checked (if applicable)                                                      | GI 7.030 Para: 5.1.2                      | ✓    |      |     |         |
| 1.4      | Preventive Maintenance is established and updated records are maintained                                                     | ANSI/SAIA A92.5, Sec: 6.4.1               | ✓    |      |     |         |
| 1.5      | Equipment is operated by a qualified operator                                                                                | ANSI/SAIA A92.5 Sec: 4.13.13              | ✓    |      |     |         |
| 1.6      | Warning notice, cautions or restrictions for safe operation and maintenance are clearly displayed and legible                | ANSI/SAIA A92.5 Sec: 4.13.1               | ✓    |      |     |         |
| 1.7      | A sign is posted warning the operator not to rely solely on any automatic device as a substitute for safe operating practice | G.I. 7.030 Para: 5.6.2                    | ✓    |      |     |         |
| 1.8      | Manufacturer name, address, serial number and model are clearly marked or tagged                                             | ANSI/SAIA A92.5 Sec: 4.13.2               | ✓    |      |     |         |
| 1.9      | Safe working load and number of persons are clearly marked on the work platform                                              | ANSI/SAIA A92.5, Sec: 4.13.3              | ✓    |      |     |         |
| 1.10     | Maximum platform height and reach are clearly marked                                                                         | ANSI/SAIA A92.5 Sec: 4.13.4 & 5           | ✓    |      |     |         |
| 1.11     | Maximum travel height and travel directions are clearly marked                                                               | ANSI/SAIA A92.5 Sec: 4.13.9               | ✓    |      |     |         |
| 1.12     | Power rating are provided and marked (for AC and/or DC)                                                                      | ANSI/SAIA A92.5 Sec: 4.13.6               | ✓    |      |     |         |
| 1.13     | Platform and guardrails electrical insulation data are provided                                                              | ANSI/SAIA A92.5 Sec: 4.13.10              | ✓    |      |     |         |
| <b>2</b> | <b>INSPECTION POINTS:</b>                                                                                                    |                                           |      |      |     |         |
| 2.1      | Platform surfaces are at least 18" (width & length) and are slip-resistant                                                   | ANSI/SAIA A92.5 4.12.1                    | ✓    |      |     |         |
| 2.2      | Platform guardrails are provided and secure                                                                                  | ANSI/SAIA A92.5 4.12.2                    | ✓    |      |     |         |
| 2.3      | Platform guardrails are 42" height (+/- 3")                                                                                  | ANSI/SAIA A92.5 Sec: 4.12.2.1             | ✓    |      |     |         |
| 2.4      | Platform toeboard is fitted and at least 4" high                                                                             | ANSI/SAIA A92.5 Sec: 4.12.3               | ✓    |      |     |         |
| 2.5      | Moving parts are guarded                                                                                                     | ANSI/SAIA A92.5 Sec: 4.11                 | ✓    |      |     |         |
| 2.6      | Personnel on the platform is protected against the hazards of moving parts of the aerial platforms.                          | ANSI/SAIA A92.5 Sec: 7.10                 | ✓    |      |     |         |
| 2.7      | Access to the platform is provided                                                                                           | ANSI/SAIA A92.5 Sec: 4.12.4               | ✓    |      |     |         |
| 2.8      | Access gates or openings shall be properly closed per the manufacturer's instructions                                        | ANSI/SAIA A92.5 Sec: 4.12.4               | ✓    |      |     |         |
| 2.9      | Electrical cables, wiring and components are undamaged                                                                       | ANSI/SAIA A92.5 Sec: 8.3                  | ✓    |      |     |         |
| 2.10     | Safety harness anchorage is fitted in the platform                                                                           | ANSI/SAIA A92.5 Sec: 4.12.5.1             | ✓    |      |     |         |



## Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area  
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA  
T: +966-13-3670801 | F: +966-13-3670802  
E: admin@standardarabia.com  
W: www.standardarabia.com  
VAT:301271872900003 | C.R :2055024044



## شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى  
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ، الجبيل ، المملكة العربية السعودية  
الهاتف : +966133670801 فاكس : +966133670802  
البريد الإلكتروني : admin@standardarabia.com  
الموقع الإلكتروني : www.standardarabia.com  
السجل التجاري : 2055024044 الرقم الضريبي : 301271872900003



| ID   | ACCEPTANCE CRITERIA                                                                         | REFERENCE                    | PASS | FAIL | N/A | REMARKS |
|------|---------------------------------------------------------------------------------------------|------------------------------|------|------|-----|---------|
| 2.11 | Battery is secure, guarded and ventilated                                                   | ANSI/SAIA A92.5 Sec: 4.15.2  | ✓    |      |     |         |
| 2.12 | Outrigger position microswitches and interlocks are fully functional at their control panel | ANSI/SAIA A92.5 Sec: 4.7     |      |      | ✓   |         |
| 2.13 | Air, Hydraulic and fuel systems are not leaking                                             | ANSI/SAIA A92.5 Sec: 6.6.5   | ✓    |      |     |         |
| 2.14 | Emergency stop button is available at ground control station                                | ANSI/SAIA A92.5 Sec: 4.6.3   | ✓    |      |     |         |
| 2.15 | There are no loose nuts, bolts, missing, worn or damaged parts around the structure         | ANSI/SAIA A92.5 Sec: 6.6.2   | ✓    |      |     |         |
| 2.16 | The equipment is free of defective and/or corroded members/joints                           | ANSI/SAIA A92.5 Sec:6.4.3    | ✓    |      |     |         |
| 2.17 | Working environment is hazard free and machine can be safely operated                       | ANSI/SAIA A92.5 Sec:7.9      | ✓    |      |     |         |
| 2.18 | An hour meter is fitted                                                                     | ANSI/SAIA A92.5 Sec:4.15.3   | ✓    |      |     |         |
| 2.19 | A fire extinguisher is fitted (type depends on operating location)                          | ANSI/SAIA A92.5 General      | ✓    |      |     |         |
| 2.20 | All moving parts are lubricated                                                             | ANSI/SAIA A92.5 Sec: 6.6.5   | ✓    |      |     |         |
| 2.21 | All fluid levels for oil, water and hydraulic are adequate                                  | ANSI/SAIA A92.5 Sec: 6.6.5   | ✓    |      |     |         |
| 2.22 | Platform controls operate the machine correctly                                             | ANSI/SAIA A92.5 Sec: 6.6.1   | ✓    |      |     |         |
| 2.23 | Platform controls are clearly marked with direction and mode of operation                   | ANSI/SAIA A92.5 Sec: 4.6.1.6 | ✓    |      |     |         |
| 2.24 | Platform controls accessible to the operator                                                | ANSI/SAIA A92.5 Sec: 4.6.1.1 | ✓    |      |     |         |
| 2.25 | Platform controls return to "off" or "neutral" position when released                       | ANSI/SAIA A92.5 Sec: 4.6.1.4 | ✓    |      |     |         |
| 2.26 | Platform controls are protected against inadvertent operation                               | ANSI/SAIA A92.5 Sec: 1.3     | ✓    |      |     |         |
| 2.27 | Over-ride control for power functions is fitted at ground level control panel               | ANSI/SAIA A92.5 Sec: 4.6.2.1 | ✓    |      |     |         |
| 2.28 | Lower controls return to "off" or "neutral" position when released                          | ANSI/SAIA A92.5 Sec: 4.6.2.4 | ✓    |      |     |         |
| 2.29 | Lower controls are clearly marked for direction and mode of operation                       | ANSI/SAIA A92.5 Sec: 4.6.2.6 | ✓    |      |     |         |
| 2.30 | Lower controls do not include drive and steering functions                                  | ANSI/SAIA A92.5 Sec: 4.6.2.2 | ✓    |      |     |         |
| 2.31 | Lower controls are protected against inadvertent operation                                  | ANSI/SAIA A92.5 Sec: 4.6.2.5 | ✓    |      |     |         |
| 2.32 | Boom raise/extend is operable from platform and ground control                              | ANSI/SAIA A92.5 Sec: 4.6.2.2 | ✓    |      |     |         |
| 2.33 | Boom lower/retract is operable from platform and ground control                             | ANSI/SAIA A92.5 Sec: 4.6.2.2 | ✓    |      |     |         |
| 2.34 | Platform rotation is operable from both platform and ground controls                        | ANSI/SAIA A92.5 Sec: 4.6.2.2 | ✓    |      |     |         |
| 2.35 | Emergency stop button is operable from both platform and ground controls                    | ANSI/SAIA A92.5 Sec: 4.6.3   | ✓    |      |     |         |
| 2.36 | Auxiliary/emergency lowering is operable from platform and ground controls                  | ANSI/SAIA A92.5 Sec: 4.6.4   | ✓    |      |     |         |
| 2.37 | Auxiliary/emergency retracting is operable from platform and ground controls                | ANSI/SAIA A92.5 Sec: 4.6.4   | ✓    |      |     |         |



# Standard Arabia Inspection Co Ltd.

Building No 7888, First Support Industrial Area  
Road 175, Street 6795, Postal 34446-2981, Al Jubail, KSA  
T: +966-13-3670801 | F: +966-13-3670802  
E: admin@standardarabia.com  
W: www.standardarabia.com  
VAT:301271872900003 | C.R :2055024044



# شركة معيار العربية للفحص

مبنى رقم 7888 ، المنطقة الصناعية الأولى  
طريق 175 ، شارع 6795 ، صندوق البريد 34446-2981 ،  
الجبيل ، المملكة العربية السعودية  
تلفون ٩٦٦٨٠١٣٣٦٧٠٨٠١ فاكس ٩٦٦٨٠٢٣٦٧٠٨٠٢  
البريد الإلكتروني: admin@standardarabia.com  
الموقع الإلكتروني: www.standardarabia.com  
السجل التجاري: ٢٠٥٥٥٢٤٠٤٤ : الرقم الضريبي: 301271872900003



| ID   | ACCEPTANCE CRITERIA                                                                                                                                | REFERENCE                      | PASS | FAIL | N/A | REMARKS |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|------|------|-----|---------|
| 2.38 | Auxiliary/emergency rotating is operable from platform and ground controls                                                                         | ANSI/SAIA A92.5 Sec: 4.6.4     | ✓    |      |     |         |
| 2.39 | Hydraulic/Pneumatic systems are leak-free with platform raised                                                                                     | ANSI/SAIA A92.5 Sec: 4.10.2    | ✓    |      |     |         |
| 2.40 | Tilt alarm is operable (5 degrees out of level) (manually depress the edge of the tilt switch to cause alarm condition)                            | ANSI/SAIA A92.5 Sec: 4.7.3     | ✓    |      |     |         |
| 2.41 | Aerial platforms is fitted with a warning device at the platform which activates automatically when the aerial platform is at and beyond the slope | ANSI/SAIA A92.5 Sec: 4.6.6     | ✓    |      |     |         |
| 2.42 | Tilt alarm is not combined with boom raise cut-out (dependent on machine manufacturer)                                                             | ANSI/SAIA A92.5 Sec: 4.6.6     | ✓    |      |     |         |
| 2.43 | Steering is properly working when moving forward and in reverse directions                                                                         | ANSI/SAIA A92.5 Sec: 6.6.3.1   | ✓    |      |     |         |
| 2.44 | Brakes are in good working condition and can hold the machine on any slope (parking and moving)                                                    | ANSI/SAIA A92.5 Sec: 4.14.1    | ✓    |      |     |         |
| 2.45 | Extendable axles function is satisfactory (where fitted)                                                                                           | ANSI/SAIA A92.5 Sec: 7.3.3.8   |      |      | ✓   |         |
| 2.46 | Outriggers (stabilizers) extension-retraction operation is satisfactory                                                                            | ANSI/SAIA A92.5 Sec: 7.10.3    |      |      | ✓   |         |
| 2.47 | Extendable elevating assembly operation is satisfactory (retracted vs. extended)                                                                   | ANSI/SAIA A92.5 Sec: 4.2.1     | ✓    |      |     |         |
| 2.48 | Elevating assembly operation is satisfactory (elevated vs. lowered)                                                                                | ANSI/SAIA A92.5 sec: 4.2.1 (c) | ✓    |      |     |         |
| 2.49 | Wheels and tires are serviceable and undamaged                                                                                                     | ANSI/SAIA A92.5 Sec: 7.3.3 (6) | ✓    |      |     |         |
| 2.50 | Travel alarm is operable                                                                                                                           | ANSI/SAIA A92.5 Sec: 6.6 (4)   | ✓    |      |     |         |
| 2.51 | Platform lowering alarm is operable                                                                                                                | ANSI/SAIA A92.5 Sec: 6.6 (4)   | ✓    |      |     |         |
| 2.52 | Auxiliary power source available (to use in event of primary power loss)                                                                           | ANSI/SAIA A92.5 Sec: 4.15.2    | ✓    |      |     |         |
| 2.53 | Platform does not descend when in raised position and the power is off                                                                             | ANSI/SAIA A92.5 Sec: 4.6.3     | ✓    |      |     |         |
| 2.54 | Machine is safely drivable from the platform when raised (fast, slow, forward and reverse modes)                                                   | ANSI/SAIA A92.5 Sec: 6.6.3.1   | ✓    |      |     |         |
| 2.55 | The platform does not descend when in raised position and the power is off                                                                         | ANSI/SAIA A92.5 Sec: 4.6.3     | ✓    |      |     |         |
| 2.56 | Engine powered machines fuel lines are supported to minimize chafing                                                                               | ANSI/SAIA A92.5 Sec: 4.15.1    | ✓    |      |     |         |
| 2.57 | Engine powered machines fuel lines are positioned to minimize exposure to engine and exhaust heat                                                  | ANSI/SAIA A92.5 Sec: 4.15.1    | ✓    |      |     |         |
| 2.58 | Engine powered machines exhaust system is provided with muffler                                                                                    | ANSI/SAIA A92.5 Sec: 4.15.1    | ✓    |      |     |         |
| 2.59 | Installation of Anti- Entrapment device on work platform                                                                                           | Letter No. CIU-L-019/2016      | ✓    |      |     |         |

|                |                  |                 |                   |
|----------------|------------------|-----------------|-------------------|
| RECEIVER NAME: | MD Shamaon Kabir | INSPECTOR NAME: | Ashok Paul Varkey |
| SIGNATURE:     |                  | SIGNATURE:      |                   |
| BADGE NO.:     | 2513298311       | SAP NO.:        | 80023217          |
| TELEPHONE NO.: | 0570029861       | TELEPHONE NO:   | 0553284092        |



Standard Arabia Inspection Co. Ltd.  
#6668, First Support Industrial Area,  
Road 175, Street 120A, Al Jubail, KSA.  
T: +966-13-3670802 | F: +966-13-3670802



**STICKER NO:**

**456**

**EQUIP. No:**

S28AD-1264

**EQUIP. SN:**

BARM024D00170

**DATE INSPECTED:**

19th June 2025

**NEXT INSPECTION DATE:**

18th December 2025

**INSPECTED BY:**

Ashok Paul Varkey - 80023217

---

**S.A INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCIES**

Brj x 0 B R 1

Rehman 2 / 370



Standard Arabia Inspection Co. Ltd.  
#0566, First Suburb Industrial Area,  
Road 175, Street 120A, Al Jubail, KSA  
T: +906-13-3670502 | F: +906-13-3670502



SWL-25019

MANLIFT

456

STICKER NO:

S28AD-1264

EQUIP. NO:

BARMO24 D00170

EQUIP. SN:

19-JUNE-2025

DATE INSPECTED:

18-DEC-2025

NEXT INSPECTION DATE:

ASHOK / 80023217

INSPECTED BY:

S.A INSPECTION DEPARTMENT APPROVED CONTRACTOR AGENCIES