

1. Certification No 合格证编号	WDE02020202367		2. Date of Issue 发证日期	2020-03-24	
3. Manufacture 车辆制造企业名称	SANY AUTOMOBILE MANUFACTURING CO., LTD 三一汽车制造有限公司				
4. Make / Category 车辆品牌/车辆名称	Sany 三一牌		Rough Terrain Crane 越野轮胎起重机		
5. Crane Model 车辆型号	SRC600C		6. Vehicle Identification No. 车辆识别代号	LFCNN35D2L2000032	
7. Chassis Type 底盘型号	SRC600C		8. Vehicle Color 车身颜色	BLUE/WHITE/BLACK	
9. Engine Model 发动机型号	ISDE285 30		10. Engine No. 发动机号	82005593	
11. Applicable Fuel 燃料种类	DIESEL 柴油		12. Displacement / Rate Power 排量和功率 (ml/kW)	6700	210
13. Emission Standard 排放标准	GB17691-2005 LLL (MADE IN CHINA), GB3847-2005				
14. Crane Overall-dimension (mm)	14100	3300	3790	15. Plates of Leaf Spring 钢板弹簧片数	/
16. Tires Specifications 轮胎规格	29.5R25		17. Qty of Tires 轮胎数	4	
18. Tires Span (mm) 轮距 (前/后) (mm)	2502	2502	19. Wheelbase (mm) 轴距 (mm)	4000	
20. Axle Load 轴荷 (kg)	24800/20100				
21. Qty of Axles 轴数	2		22. Steering Application 转向形式	STEERING WHEEL 方向盘	
23. Overall Weight (kg) 总质量	44,965		24. Equipment Quality 整备质量 (kg)	44,900	
25. Driver-cabin Passengers Allowed 驾驶室准乘人数	1		26. QR Code 条码		
27. Nominal Max Speed (km/h) 最高设计车速	40		28. Fabrication Date 车辆制造日期	2020-03-24	
Remarks	LICENCE. NO: TS2410J13-2022				
Upon all due inspection the above-specified crane conforms to the standards of Q/OKTW 052-2014 <Rough Terrain Crane>. Certification is hereby issued for ready delivery. 本产品经过检验,符合Q/OKTW 052-2014《越野轮胎起重机》的要求,准予出厂,特此证明 Manufacture Name: Sany Automobile Manufacturing Co., Ltd. 车辆生产单位名称: 三一汽车制造有限公司 Manufacture Address: Sany Crane Industrial Park, No. 168, Jinzhou Avenue, Changsha City, Hunan Province, People's Republic of China. 车辆生产单位地址: 长沙市宁乡市金洲大道西168号 Internal Vehicle Identification Code 内部编号: RC0060CA0023					



SANY

Certificate No. (证书编号) : RC0023-1
Model No. (车辆型号) : SRC600
Crane serial No. (整车编号) : RC0060CA0023
Part No. (物料编码) : 60339923

INSPECTION CERTIFICATE

This is to certify that the following product has been duly inspected
and passed in accordance with GB10051-88.

Name of Product : 60 t hook
Safety Working Load : 60 metric tons
Test Load : 74 metric tons
Hook Ass'y Weight : 650kg
Hook Material : 35CrMo

Certified by:



2020-03-24

Date of inspection

Chief Inspector

Quality Assurance Dept.

Sany Automobile Hoisting

Machinery Co., Ltd.



SANY

Certificate No. (证书编号) : RC0023-1
Model No. (车辆型号) : SRC600
Crane serial No. (整车编号) : RC0060CA0023
To Messers (主机公司) : Sany Automobile Hoisting Machinery Co., Ltd.
Manufacturer (生产厂商) : Juli Sling Co., Ltd.

INSPECTION CERTIFICATE

This is to certify that the following product has been duly inspected and passed in accordance with GB/T20118-2006. (兹证明下列产品依据 GB/T20118-2006 标准检验合格)。

Construction (结构) : 35W×K7

Lay (绞丝方式) : Left hand, Lang lay (左旋、同向捻)

Grade of Strength (强度级别) : 1960N/mm²

Length (长度) : 250m

Total Mass of the Rope (总重) : 480kg

Diameter (直径)	Nominal (设计值) : 20mm Actual (实测值) : 20.6mm
Breaking Load (断裂载荷)	Nominal (设计值) : 368kN Actual (实测值) : 386kN

Certified by:

2020-03-24

Date of Inspection



Chief Inspector

Quality Assurance Dept.

Sany Automobile Hoisting

Machinery Co., Ltd.



SANY

Certificate No. (证书编号) : RC0023-2
Model No. (车辆型号) : SRC600
Crane serial No. (整车编号) : RC0060CA0023
To Messers (主机公司) : Sany Automobile Hoisting Machinery Co., Ltd.
Manufacturer (生产厂商) : Juli Sling Co., Ltd.

INSPECTION CERTIFICATE

This is to certify that the following product has been duly inspected and passed in accordance with GB/T20118-2006. (兹证明下列产品依据 GB/T20118-2006 标准检验合格)。

Construction (结构) : 35W×K7
Lay (绞丝方式) : Left hand, Lang lay (左旋、同向捻)
Grade of Strength (强度级别) : 1960N/mm²
Length (长度) : 145m
Total Mass of the Rope (总重) : 278.4kg

Diameter (直径)	Nominal (设计值) : 20mm Actual (实测值) : 20.6mm
Breaking Load (断裂载荷)	Nominal (设计值) : 368kN Actual (实测值) : 386kN

Certified by: _____

2020-03-24

Date of Inspection



Chief Inspector

Quality Assurance Dept.

Sany Automobile Hoisting
Machinery Co., Ltd.

\



SANY GROUP CO., LTD.

CERTIFICATE OF LOADTEST

Crane Mode: SRC600C Crane Serial No: RC0060CCA0023 VIN: LFCNN35D2L2000032 EngineNo: 82005593

Serial No.	Working Condition	Boom Length	Load Weight	Radius	Remark	Outrigger Condition	Actual Data
1	Base Boom	11.3m	60000kg	3m	Boom is over side and rear	Full-Extended	60000kg
2	Mid-extended boom 100%+33%	27.4m	22500kg	4m	Boom is over side and rear	Full-Extended	22500kg
3	Full-extended boom	43.5m	9500kg	7m	Boom is over side and rear	Full-Extended	9500kg
4	Full-extended boom + jib	59.5m	2600kg	Main boom angle 78 ° and jib offset 0 °	Boom is over side and rear	Full-Extended	2600kg
5	Base Boom overload, which is for factory test only, not allowed by customer	11.3m	53750kg	5m	Boom is over side and rear	Full-Extended	53750 kg
6	Base Boom	11.3m	38000kg	4.5m	Boom is over side and rear	Half-Extended	38000kg
7	Mid-extended boom 100%+33%	27.4m	15000kg	5m	Boom is over side and rear	Half-Extended	15000kg
8	Base Boom overload, which is for factory test only, not allowed by customer	11.3m	32000kg	5m	Boom is over side and rear	Half-Extended	32000 kg

This is to certify that the product has been inspected completely and is in full compliance with quality requirement.

SANY Automobile Hoisting Machinery Co., Ltd.

Data 2020-03-24

