

Electronic Service Tool 2018B v1.0

Product Status Report

26/08/2019 1:09 PM

Product Status Report

Parameter	Value
Engine Serial Number	JGBF5005N04723D
Equipment ID	NOT PROGRAMMED
Comments	

2806-E18 (JGBF5005N04723D)

Parameter	Value
Equipment ID	NOT PROGRAMMED
Engine Serial Number	JGBF5005N04723D
ECM Serial Number	35476256JL
Software Group Part Number	5369801-00
Software Group Release Date	MAY17
Software Group Description	2806A TAG2 50/60Hz

Critical Events - 2806-E18 (JGBF5005N04723D)

Code	Description	Occ	First	Last	Elapsed	Extreme	Average
No Critical Events		.					

Logged Diagnostic Codes [ECM Diagnostic Clock = 0.7211 hours] - 2806-E18 (JGBF5005N04723D)

Code	Description	Occ.	First	Last
1690- 8	Analogue Speed Control Signal Abnormal	4	0	0

Logged Event Codes [ECM Diagnostic Clock = 0.7211 hours] - 2806-E18 (JGBF5005N04723D)

Code	Description	Occ.	First	Last
No Logged Event Codes				

Active Diagnostic Codes - 2806-E18 (JGBF5005N04723D)

Code	Description
No Active Diagnostic Codes	

Active Event Codes - 2806-E18 (JGBF5005N04723D)

Code	Description
------	-------------

No Active Event Codes	
-----------------------	--

Current Totals - 2806-E18 (JGBF5005N04723D)

Description	Value	Unit
Total Engine Operating Hours	1	hours
ECM Diagnostic Clock	0	hours

Configuration - 2806-E18 (JGBF5005N04723D)

Description	Value	Unit
Equipment ID	NOT PROGRAMMED	
Engine Serial Number	JGBF5005N04723D	
ECM Serial Number	35476256JL	
Software Group Part Number	5369801-00	
Software Group Release Date	MAY17	
Software Group Description	2806A TAG2 50/60Hz	
Rating Number	2	
Rated Frequency	50 Hz	
Rated Genset Speed	1500 rpm	
Rated Real Genset Power	Unavailable Parameter	
Rated Apparent Genset Power	650 kVA	
Engine Rating Application Type	Prime	
External Speed Selection Switch Installed	Enabled	
Engine Acceleration Rate	500	rpm/s
Droop/Isochronous Switch Installed	Enabled	
Droop/Isochronous Selection	Isochronous	
Engine Speed Droop	4.0	%
Digital Speed Control Installed	Installed	
Speed Control Minimum Speed	125	rpm
Speed Control Maximum Speed	125	rpm
Digital Speed Control Ramp Rate	10	rpm/s
Crank Terminate RPM	400	rpm
Desired Speed Input Arrangement	0-5 VDC Input	
Fuel Enable Input Configuration	Switch to Battery +	
Critical Override Switch Installed	Not Installed	
Emergency Shutdown Override Input Configuration	Switch to Battery +	
Governor Gain Factor #1	15729	
Governor Minimum Stability Factor #1	1049	
Governor Maximum Stability Factor #1	2097	
Full Load Setting (FLS)	8	
Full Torque Setting (FTS)	0	
Customer Password 1	*****	
Customer Password 2	*****	
Total Tattletales	4	

Lifetime: Time vs Engine Coolant Temperature - 2806-E18 (JGBF5005N04723D)

Engine Coolant Temperature(Deg F)	hours	%
-------------------------------------	-------	---

<122.0	0.05	16.67
122.0-130.0	0.00	0.00
131.0-139.0	0.00	0.00
140.0-148.0	0.00	0.00
149.0-157.0	0.00	0.00
158.0-166.0	0.00	0.00
167.0-175.0	0.00	0.00
176.0-184.0	0.00	0.00
185.0-193.0	0.20	66.67
194.0-202.0	0.05	16.67
203.0-211.0	0.00	0.00
212.0-220.0	0.00	0.00
221.0-229.0	0.00	0.00
230.0-238.0	0.00	0.00
239.0-247.0	0.00	0.00
>248.0	0.00	0.00

Lifetime: Time vs Intake Manifold Air Temperature - 2806-E18 (JGBF5005N04723D)

Intake Manifold Air Temperature(Deg F)	hours	%
<104.0	0.00	0.00
104.0-112.0	0.00	0.00
113.0-121.0	0.00	0.00
122.0-130.0	0.05	100.00
131.0-139.0	0.00	0.00
140.0-148.0	0.00	0.00
149.0-157.0	0.00	0.00
158.0-166.0	0.00	0.00
167.0-175.0	0.00	0.00
176.0-184.0	0.00	0.00
185.0-193.0	0.00	0.00
194.0-202.0	0.00	0.00
203.0-211.0	0.00	0.00
>212.0	0.00	0.00

Lifetime: Time vs Intake Manifold Pressure (Gauge) - 2806-E18 (JGBF5005N04723D)

Intake Manifold Pressure (Gauge)(psi)	hours	%
<11.6	0.00	0.00
11.6-12.1	0.00	0.00
13.1-13.5	0.00	0.00
14.5-15.0	0.00	0.00
16.0-16.4	0.00	0.00
17.4-17.9	0.00	0.00
18.9-19.3	0.00	0.00
20.3-20.8	0.00	0.00
21.8-22.2	0.00	0.00
23.2-23.7	0.00	0.00

24.7-25.1	0.00	0.00
26.1-26.6	0.00	0.00
27.6-28.0	0.00	0.00
>29.0	0.05	100.00

Lifetime: Time vs Actual Engine Speed And Engine Load Factor - 2806-E18 (JGBF5005N04723D)

rpm	<1100	1100-1299	1300-1499	1500-1699	1700-1899	1900-2099	2100-2299	>2300	Total
%									
<50.0	0.00	0.00	0.00	0.00	0.10	0.00	0.00	0.00	0.10
50.0-59.9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
60.0-69.9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
70.0-79.9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80.0-89.9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
>90.0	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.00	0.05
Total	0.00	0.00	0.05	0.00	0.10	0.00	0.00	0.00	0.15

Lifetime: Total Occurrences vs Actual Engine Speed - 2806-E18 (JGBF5005N04723D)

Actual Engine Speed(rpm)		%
<2500.0	0.00	0.00
2500.0-2599.0	0.00	0.00
2600.0-2699.0	0.00	0.00
2700.0-2799.0	0.00	0.00
2800.0-2899.0	0.00	0.00
2900.0-2999.0	0.00	0.00
3000.0-3099.0	0.00	0.00
3100.0-3199.0	0.00	0.00
3200.0-3299.0	0.00	0.00
>3300.0	0.00	0.00

Injector Trim Calibration - 2806-E18 (JGBF5005N04723D)

Injector	Serial Number	File Version
Injector1	000000005A53557969A4	0
Injector2	000000005A53557968A3	0
Injector3	000000005A5355798556	0
Injector4	000000005A5355796580	0
Injector5	000000005A5355797280	0
Injector6	000000005A535579769C	0

Monitoring System - 2806-E18 (JGBF5005N04723D)

Description	State	Trip Point	Delay Time
Engine Overspeed			
Least Severe (1)	On	2000 rpm	1 sec
Most Severe (3)	Always On	2140 rpm	0 sec
Action Alert (2)	Always On	2050 rpm	0 sec

<u>High Boost Pressure</u>			
Action Alert (2)	Always On	None	5 sec
<u>High Boost Pressure</u>			
Least Severe (1)	On	43.5 psi	60 sec
<u>High Engine Coolant Temperature</u>			
Least Severe (1)	On	219 Deg F	60 sec
Most Severe (3)	Always On	226 Deg F	10 sec
Action Alert (2)	Always On	221 Deg F	10 sec
<u>High Engine Inlet Air Temperature</u>			
Least Severe (1)	On	167.0 Deg F	60 sec
Action Alert (2)	Always On	172.4 Deg F	10 sec
<u>High Fuel Temperature</u>			
Least Severe (1)	On	140.0 Deg F	60 sec
Action Alert (2)	Always On	154.4 Deg F	60 sec
<u>Low Engine Oil Pressure</u>			
Most Severe (3)	Always On	None	2 sec
Action Alert (2)	Always On	None	2 sec
<u>Low Engine Oil Pressure</u>			
Least Severe (1)	On	44 psi	60 sec