

SG-515-40

| VARADA ENERGIES PVT LTD. -- <u>PRODUCT TEST CERTIFICATE</u> |                          |                                       |                               |
|-------------------------------------------------------------|--------------------------|---------------------------------------|-------------------------------|
|                                                             |                          | ISO- 85028                            |                               |
| GENERAL INFORMATION                                         |                          |                                       |                               |
| Customer Name                                               |                          | Customer Order No.<br>Test Cell No. 1 |                               |
| PRODUCT INFORMATION                                         |                          |                                       |                               |
| Model                                                       | VEPL-40-CDP              | Genset Serial No.                     | VEPL/2021-20/0015             |
| Engine Serial No.                                           | LYHM111469               | Alternator Serial No.                 | G21B055606                    |
| Brand Name                                                  | Ashok Leyland            | Alternator Make.                      | STAMFORD                      |
| Fuel Type                                                   | HSD                      | Controller Type                       | DEEP SEA                      |
| Govoner Type                                                | MECHANICAL               | Cooling System Type                   | WATER COOLED                  |
| TEST CONDITION                                              |                          |                                       |                               |
| Altitude (Meters ASL)                                       | 1000                     | Oil Specifications                    | Ley Power 15 W 40 - Synthetic |
| Ambient Temp. (C )                                          | 34                       | Humidity (%)                          | 42                            |
| Air Filter Inlet Temp (C )                                  | 39                       | Coolant Mix                           | 50 : 50                       |
| PRODUCT OPTIONS CHECKED                                     |                          |                                       |                               |
| (●) Emergency Stop                                          | (o) Panel Heater         | (o) Low Coolant Warning               | (o) High Fuel S/Down          |
| (●) Over Load Protection                                    | (●) High Water Temp      | (●) LET Warning                       | (o) High Fuel Warning         |
| (●) Over Speed Protection                                   | (●) Low Lub Oil Pressure | (o) Low Fuel S/Down                   | (o) Parallel Bus PT Module    |
| (●) Under Voltage Protection                                | (o) Low Coolant S/Down   | (o) Low Fuel Warning                  | (o) Earth Fault S/Down        |
| TECHNICAL DATA (Declared)                                   |                          |                                       |                               |
| Service Rating                                              | 40 kVA                   | Power Factor                          | 0.8                           |
| Power Output (kW)                                           | 32                       | Rated Output (kW)                     | 32                            |
| Rated Voltage (V)                                           | 400                      | Rated Current (A)                     | 45                            |
| Frequency (Hz)                                              | 60                       | Speed (RPM)                           | 1800                          |
| Number of Phases                                            | 3                        | Performance Class                     | H                             |
| TECHNICAL DATA (Measured)                                   |                          |                                       |                               |
| Results (No Load)                                           |                          |                                       |                               |
| Voltage                                                     | 1 - 2 : 401 Volts        | 2 - 3 : 401 Volts                     | 1 - 3 : 400 Volts             |
| No Load Frequency                                           | 60.8                     | No Load Coolant Temp. (C )            | 74 deg Cen                    |
| No Load Lube Press                                          | 3.93 Bar                 |                                       |                               |
| Result (Full Load)                                          |                          |                                       |                               |
| Voltage                                                     | 1 - 2 : 400 Volts        | 2 - 3 : 402 Volts                     | 1 - 3 : 403 Volts             |
| Current                                                     | 1 : 46 Amps              | 2 : 47 Amps                           | 3 : 46 Amps                   |
| Full Load Frequency                                         | 60.3 Hz.                 | Full Load Coolant Temp. (C )          | 86                            |
| Full Load Lube Press                                        | 3.77 Bar                 | Power Factor                          | 1 . 0                         |
| Prime set tested to 110% of Full Load (if required)         |                          | NA                                    |                               |
| Tested By                                                   |                          | Date                                  | 22-Feb-21                     |
|                                                             |                          | RUN HOURS                             | 45 mins                       |
|                                                             |                          |                                       |                               |