

SG-545-250

|                                                                        |                                                          |                                                 |                                                 |
|------------------------------------------------------------------------|----------------------------------------------------------|-------------------------------------------------|-------------------------------------------------|
| <b>VARADA ENERGIES PVT LTD. ( AN ISO 9001-2015 CERTIFIED COMPANY )</b> |                                                          |                                                 |                                                 |
|                                                                        |                                                          | <b>ISO- 8528</b>                                |                                                 |
| <b>GENERAL INFORMATION</b>                                             |                                                          |                                                 |                                                 |
| <b>Customer Name</b>                                                   |                                                          | <b>Customer Order No.</b>                       |                                                 |
|                                                                        |                                                          | <b>Test Cell No.</b>                            | 2                                               |
| <b>PRODUCT INFORMATION</b>                                             |                                                          |                                                 |                                                 |
| <b>Model</b>                                                           | VEPL-250-CDP                                             | <b>Genset Serial No.</b>                        | VEPL/2021-22/0047                               |
| <b>Engine Serial No.</b>                                               | M16 19L00020                                             | <b>Alternator Serial No.</b>                    | N211 399246                                     |
| <b>Brand Name</b>                                                      | Ashok Leyland                                            | <b>Alternator Make.</b>                         | STAMFORD                                        |
| <b>Fuel Type</b>                                                       | HSD                                                      | <b>Controller Type</b>                          | SEDMAC                                          |
| <b>Govoner Type</b>                                                    | MECHANICAL                                               | <b>Cooling System Type</b>                      | WATER COOLED                                    |
| <b>TEST CONDITION</b>                                                  |                                                          |                                                 |                                                 |
| <b>Altitude (Meters ASL)</b>                                           | 1000                                                     | <b>Oil Specifications</b>                       | Ley Power 15 W 40 - Synthetic                   |
| <b>Ambient Temp. (C)</b>                                               | 33                                                       | <b>Humidity (%)</b>                             | 47                                              |
| <b>Air Filter Inlet Temp (C)</b>                                       | 38                                                       | <b>Coolant Mix</b>                              | 50 : 50                                         |
| <b>PRODUCT OPTIONS CHECKED</b>                                         |                                                          |                                                 |                                                 |
| <input checked="" type="checkbox"/> Emergency Stop                     | <input type="checkbox"/> Panel Heater                    | <input type="checkbox"/> Low Coolant Warning    | <input type="checkbox"/> High Fuel S/Down       |
| <input checked="" type="checkbox"/> Over Load Protection               | <input checked="" type="checkbox"/> High Water Temp      | <input checked="" type="checkbox"/> LET Warning | <input type="checkbox"/> High Fuel Warning      |
| <input checked="" type="checkbox"/> Over Speed Protection              | <input checked="" type="checkbox"/> Low Lub Oil Pressure | <input type="checkbox"/> Low Fuel S/Down        | <input type="checkbox"/> Parallel Bus PT Module |
| <input checked="" type="checkbox"/> Under Voltage Protection           | <input type="checkbox"/> Low Coolant S/Down              | <input type="checkbox"/> Low Fuel Warning       | <input type="checkbox"/> Earth Fault S/Down     |
| <b>TECHNICAL DATA (Declared)</b>                                       |                                                          |                                                 |                                                 |
| <b>Service Rating</b>                                                  | 250 kVA                                                  | <b>Power Factor</b>                             | 0.8                                             |
| <b>Power Output (kW)</b>                                               | 200                                                      | <b>Rated Output (kW)</b>                        | 200                                             |
| <b>Rated Voltage (V)</b>                                               | 400                                                      | <b>Rated Current (A)</b>                        | 140                                             |
| <b>Frequency (Hz)</b>                                                  | 60                                                       | <b>Speed (RPM)</b>                              | 1800                                            |
| <b>Number of Phases</b>                                                | 3                                                        | <b>Performance Class</b>                        | H                                               |
| <b>TECHNICAL DATA (Measured)</b>                                       |                                                          |                                                 |                                                 |
| <b>Results (No Load)</b>                                               |                                                          |                                                 |                                                 |
| <b>Voltage</b>                                                         | 1 - 2 : 401 Volts                                        | 2 - 3 : 400 Volts                               | 1 - 3 : 403 Volts                               |
| <b>No Load Frequency</b>                                               | 61                                                       | <b>No Load Coolant Temp. (C)</b>                | 75 deg Cen                                      |
| <b>No Load Lube Press</b>                                              | 3.93 Bar                                                 |                                                 |                                                 |
| <b>Result (Full Load)</b>                                              |                                                          |                                                 |                                                 |
| <b>Voltage</b>                                                         | 1 - 2 : 400 Volts                                        | 2 - 3 : 402 Volts                               | 1 - 3 : 400 Volts                               |
| <b>Current</b>                                                         | 1 : 282 Amps                                             | 2 : 279 Amps                                    | 3 : 282 Amps                                    |
| <b>Full Load Frequency</b>                                             | 60 Hz.                                                   | <b>Full Load Coolant Temp. (C)</b>              | 87                                              |
| <b>Full Load Lube Press</b>                                            | 3.78 Bar                                                 | <b>Power Factor</b>                             | 1.0                                             |
| <b>Prime set tested to 110% of Full Load (if required)</b>             | NA                                                       |                                                 |                                                 |
| <b>Tested By</b>                                                       |                                                          |                                                 |                                                 |
|                                                                        | <b>Date- 10.11.2021</b>                                  |                                                 |                                                 |
|                                                                        | <b>RUN HOURS</b>                                         | 60 mins                                         |                                                 |

